

ODE Framework

1

Generated by Doxygen 1.9.8

1 Namespace Index	1
1.1 Package List	1
2 Hierarchical Index	3
2.1 Class Hierarchy	3
3 Class Index	5
3.1 Class List	5
4 File Index	7
4.1 File List	7
5 Namespace Documentation	9
5.1 Package age	9
5.2 Package age.clock	9
5.3 Package age.event	10
5.4 Package age.gui	10
5.5 Package age.log	10
5.6 Package age.port	10
5.7 Package age.port.jogl	11
5.8 Package age.scene	11
5.9 Package age.task	11
6 Class Documentation	13
6.1 age.AGEEException Class Reference	13
6.1.1 Detailed Description	13
6.1.2 Constructor & Destructor Documentation	14
6.1.2.1 AGEEException() [1/4]	14
6.1.2.2 AGEEException() [2/4]	14
6.1.2.3 AGEEException() [3/4]	14
6.1.2.4 AGEEException() [4/4]	14
6.1.3 Member Data Documentation	15
6.1.3.1 serialVersionUID	15
6.2 age.clock.Alarm Class Reference	15
6.2.1 Constructor & Destructor Documentation	15
6.2.1.1 Alarm()	15
6.2.2 Member Function Documentation	15
6.2.2.1 init()	15
6.2.2.2 trigger()	16
6.2.2.3 update()	16
6.2.3 Member Data Documentation	16
6.2.3.1 mark	16
6.2.3.2 nanoperiod	16
6.2.3.3 task	16

6.3 age.event.Button Enum Reference	16
6.3.1 Member Data Documentation	17
6.3.1.1 BTN1	17
6.3.1.2 BTN2	17
6.3.1.3 BTN3	17
6.3.1.4 BTN4	17
6.3.1.5 BTN5	17
6.3.1.6 BTN6	17
6.3.1.7 BTN7	17
6.3.1.8 BTN8	17
6.3.1.9 NONE	17
6.4 age.Client Class Reference	18
6.4.1 Detailed Description	19
6.4.2 Member Function Documentation	19
6.4.2.1 loop()	19
6.4.2.2 main()	19
6.4.2.3 render()	19
6.4.2.4 run()	19
6.4.2.5 setup()	20
6.4.2.6 setupGUI()	20
6.4.2.7 shutdown()	20
6.4.2.8 toggleDesktop()	20
6.4.2.9 toggleSysmenu()	20
6.4.2.10 update()	20
6.4.3 Member Data Documentation	21
6.4.3.1 clock	21
6.4.3.2 events	21
6.4.3.3 port	21
6.4.3.4 running	21
6.4.3.5 sysMenuFrame	21
6.4.3.6 tasks	21
6.4.3.7 widgets	21
6.4.3.8 windowFrame	22
6.5 age.clock.Clock Class Reference	22
6.5.1 Member Function Documentation	22
6.5.1.1 add()	22
6.5.1.2 addFPS()	22
6.5.1.3 init()	22
6.5.1.4 update()	22
6.5.2 Member Data Documentation	23
6.5.2.1 alarms	23
6.6 age.gui.Dock Class Reference	23

6.6.1 Member Function Documentation	23
6.6.1.1 bottom()	23
6.6.1.2 left()	23
6.6.1.3 right()	23
6.6.1.4 set() [1/2]	23
6.6.1.5 set() [2/2]	24
6.6.1.6 top()	24
6.6.2 Member Data Documentation	24
6.6.2.1 bottom	24
6.6.2.2 left	24
6.6.2.3 right	24
6.6.2.4 top	24
6.7 age.event.Event Class Reference	25
6.7.1 Constructor & Destructor Documentation	26
6.7.1.1 Event()	26
6.7.2 Member Function Documentation	26
6.7.2.1 button()	26
6.7.2.2 character()	26
6.7.2.3 clear()	26
6.7.2.4 command()	26
6.7.2.5 count()	26
6.7.2.6 dimension()	26
6.7.2.7 height()	26
6.7.2.8 key()	26
6.7.2.9 keyEvent()	27
6.7.2.10 keyPressed()	27
6.7.2.11 keyReleased()	27
6.7.2.12 keyTyped()	27
6.7.2.13 pointerClicked()	27
6.7.2.14 pointerEntered()	27
6.7.2.15 pointerEvent()	27
6.7.2.16 pointerExited()	28
6.7.2.17 pointerMoved()	28
6.7.2.18 pointerPressed()	28
6.7.2.19 pointerReleased()	28
6.7.2.20 position()	28
6.7.2.21 surfaceCloseRequest()	28
6.7.2.22 surfaceResized()	28
6.7.2.23 taskCommand()	28
6.7.2.24 type()	29
6.7.2.25 width()	29
6.7.2.26 x()	29

6.7.2.27 y()	29
6.7.3 Member Data Documentation	29
6.7.3.1 button	29
6.7.3.2 character	29
6.7.3.3 command	29
6.7.3.4 count	29
6.7.3.5 dimension	29
6.7.3.6 key	29
6.7.3.7 position	30
6.7.3.8 type	30
6.8 age.event.Events Class Reference	30
6.8.1 Member Function Documentation	31
6.8.1.1 alloc()	31
6.8.1.2 assign()	31
6.8.1.3 free()	31
6.8.1.4 handle()	31
6.8.1.5 post()	31
6.8.1.6 postKeyPressed()	31
6.8.1.7 postKeyReleased()	31
6.8.1.8 postKeyTyped()	31
6.8.1.9 postPointerClicked()	32
6.8.1.10 postPointerEntered()	32
6.8.1.11 postPointerExited()	32
6.8.1.12 postPointerMoved()	32
6.8.1.13 postPointerPressed()	32
6.8.1.14 postPointerReleased()	32
6.8.1.15 postSurfaceCloseRequest()	32
6.8.1.16 postSurfaceResized()	33
6.8.1.17 postTaskCommand()	33
6.8.1.18 update()	33
6.8.2 Member Data Documentation	33
6.8.2.1 cache	33
6.8.2.2 handlers	33
6.8.2.3 inbox	33
6.8.2.4 outbox	33
6.9 age.gui.Flag Enum Reference	34
6.9.1 Member Data Documentation	34
6.9.1.1 BOX	34
6.9.1.2 BUTTON	34
6.9.1.3 CANVAS	34
6.9.1.4 FRAME	34
6.9.1.5 HANDLE	34

6.9.1.6 HIDDEN	34
6.9.1.7 HOVERED	34
6.9.1.8 MULTILINE	35
6.9.1.9 TITLE	35
6.10 age.port.Graphics Interface Reference	35
6.10.1 Member Function Documentation	35
6.10.1.1 calcMultitext() [1/2]	35
6.10.1.2 calcMultitext() [2/2]	36
6.10.1.3 color() [1/3]	36
6.10.1.4 color() [2/3]	36
6.10.1.5 color() [3/3]	36
6.10.1.6 mode2D()	36
6.10.1.7 popTransformation()	36
6.10.1.8 pushTransformation()	37
6.10.1.9 rectangle() [1/3]	37
6.10.1.10 rectangle() [2/3]	37
6.10.1.11 rectangle() [3/3]	37
6.10.1.12 text()	37
6.10.1.13 texture()	37
6.10.1.14 translate() [1/2]	38
6.10.1.15 translate() [2/2]	38
6.11 age.event.Handler Interface Reference	38
6.11.1 Member Function Documentation	38
6.11.1.1 handle()	38
6.12 age.gui.Handling Class Reference	38
6.12.1 Constructor & Destructor Documentation	39
6.12.1.1 Handling()	39
6.12.2 Member Function Documentation	39
6.12.2.1 assign()	39
6.12.2.2 buttonClickAction()	39
6.12.2.3 handleKeyboard()	39
6.12.2.4 handlePointer()	40
6.12.2.5 handleSurface()	40
6.12.2.6 hovered()	40
6.12.2.7 pressedFrameToFront()	40
6.12.2.8 startFrameDragAction()	40
6.12.2.9 startFrameSizeAction()	40
6.12.2.10 startScrollHandleAction()	40
6.12.2.11 stopDragAction()	40
6.12.2.12 updateActionState()	41
6.12.2.13 updateDragAction()	41
6.12.3 Member Data Documentation	41

6.12.3.1 action	41
6.12.3.2 dragged	41
6.12.3.3 events	41
6.12.3.4 hovered	41
6.12.3.5 ref	41
6.12.3.6 tmp	41
6.12.3.7 widgets	41
6.13 age.port.jogl.JOGLEventListener Class Reference	42
6.13.1 Member Function Documentation	42
6.13.1.1 assign()	42
6.13.1.2 handleSurfaceCloseRequest()	43
6.13.1.3 keyPressed()	43
6.13.1.4 keyReleased()	43
6.13.1.5 mouseClicked()	43
6.13.1.6 mouseDragged()	43
6.13.1.7 mouseEntered()	43
6.13.1.8 mouseExited()	43
6.13.1.9 mouseMoved()	43
6.13.1.10 mousePressed()	43
6.13.1.11 mouseReleased()	44
6.13.1.12 mouseWheelMoved()	44
6.13.1.13 translateButton()	44
6.13.1.14 translateKey()	44
6.13.1.15 windowDestroyed()	44
6.13.1.16 windowDestroyNotify()	44
6.13.1.17 windowGainedFocus()	44
6.13.1.18 windowLostFocus()	44
6.13.1.19 windowMoved()	44
6.13.1.20 windowRepaint()	45
6.13.1.21 windowResized()	45
6.13.2 Member Data Documentation	45
6.13.2.1 events	45
6.14 age.port.jogl.JOGLGraphics Class Reference	45
6.14.1 Member Function Documentation	46
6.14.1.1 assign()	46
6.14.1.2 calcMultitext() [1/2]	46
6.14.1.3 calcMultitext() [2/2]	46
6.14.1.4 clear()	46
6.14.1.5 color() [1/3]	46
6.14.1.6 color() [2/3]	47
6.14.1.7 color() [3/3]	47
6.14.1.8 init()	47

6.14.1.9 mode2D()	47
6.14.1.10 mode3D()	47
6.14.1.11 popTransformation()	47
6.14.1.12 pushTransformation()	47
6.14.1.13 rectangle() [1/3]	48
6.14.1.14 rectangle() [2/3]	48
6.14.1.15 rectangle() [3/3]	48
6.14.1.16 text()	48
6.14.1.17 texture()	48
6.14.1.18 translate() [1/2]	49
6.14.1.19 translate() [2/2]	49
6.14.2 Member Data Documentation	49
6.14.2.1 drawable	49
6.14.2.2 fonts	49
6.14.2.3 gl	49
6.14.2.4 glu	49
6.14.2.5 textures	49
6.15 age.port.jogl.JOGLPort Class Reference	50
6.15.1 Member Function Documentation	50
6.15.1.1 add()	50
6.15.1.2 assign()	50
6.15.1.3 create()	51
6.15.1.4 fullscreen() [1/2]	51
6.15.1.5 fullscreen() [2/2]	51
6.15.1.6 get()	51
6.15.1.7 height()	51
6.15.1.8 maximized() [1/2]	51
6.15.1.9 maximized() [2/2]	51
6.15.1.10 render()	51
6.15.1.11 size()	52
6.15.1.12 title() [1/2]	52
6.15.1.13 title() [2/2]	52
6.15.1.14 visible() [1/2]	52
6.15.1.15 visible() [2/2]	52
6.15.1.16 width()	52
6.15.2 Member Data Documentation	52
6.15.2.1 eventListener	52
6.15.2.2 renderables	53
6.15.2.3 renderables_ro	53
6.15.2.4 renderListener	53
6.15.2.5 window	53
6.16 age.port.jogl.JOGLRenderListener Class Reference	53

6.16.1 Constructor & Destructor Documentation	54
6.16.1.1 JOGLRenderListener()	54
6.16.2 Member Function Documentation	54
6.16.2.1 display()	54
6.16.2.2 dispose()	54
6.16.2.3 init()	54
6.16.2.4 reshape()	54
6.16.3 Member Data Documentation	54
6.16.3.1 graphics	54
6.16.3.2 port	54
6.17 age.event.Key Enum Reference	55
6.17.1 Member Data Documentation	56
6.17.1.1 _0	56
6.17.1.2 _1	56
6.17.1.3 _2	57
6.17.1.4 _3	57
6.17.1.5 _4	57
6.17.1.6 _5	57
6.17.1.7 _6	57
6.17.1.8 _7	57
6.17.1.9 _8	57
6.17.1.10 _9	57
6.17.1.11 A	57
6.17.1.12 ADD	57
6.17.1.13 ALT	58
6.17.1.14 B	58
6.17.1.15 BACK_SPACE	58
6.17.1.16 C	58
6.17.1.17 CAPS_LOCK	58
6.17.1.18 CONTROL	58
6.17.1.19 D	58
6.17.1.20 DECIMAL	58
6.17.1.21 DELETE	58
6.17.1.22 DIVIDE	58
6.17.1.23 DOWN	59
6.17.1.24 E	59
6.17.1.25 END	59
6.17.1.26 ENTER	59
6.17.1.27 ESCAPE	59
6.17.1.28 F	59
6.17.1.29 F1	59
6.17.1.30 F10	59

6.17.1.31 F11	59
6.17.1.32 F12	59
6.17.1.33 F2	60
6.17.1.34 F3	60
6.17.1.35 F4	60
6.17.1.36 F5	60
6.17.1.37 F6	60
6.17.1.38 F7	60
6.17.1.39 F8	60
6.17.1.40 F9	60
6.17.1.41 G	60
6.17.1.42 H	60
6.17.1.43 I	61
6.17.1.44 INSERT	61
6.17.1.45 J	61
6.17.1.46 K	61
6.17.1.47 L	61
6.17.1.48 LEFT	61
6.17.1.49 M	61
6.17.1.50 MENU	61
6.17.1.51 MINUS	61
6.17.1.52 MULTIPLY	61
6.17.1.53 N	62
6.17.1.54 NONE	62
6.17.1.55 NP_0	62
6.17.1.56 NP_1	62
6.17.1.57 NP_2	62
6.17.1.58 NP_3	62
6.17.1.59 NP_4	62
6.17.1.60 NP_5	62
6.17.1.61 NP_6	62
6.17.1.62 NP_7	62
6.17.1.63 NP_8	63
6.17.1.64 NP_9	63
6.17.1.65 NUM_LOCK	63
6.17.1.66 O	63
6.17.1.67 P	63
6.17.1.68 PAGE_DOWN	63
6.17.1.69 PAGE_UP	63
6.17.1.70 PAUSE	63
6.17.1.71 PLUS	63
6.17.1.72 POS1	63

6.17.1.73 PRINT_SCREEN	64
6.17.1.74 Q	64
6.17.1.75 R	64
6.17.1.76 RIGHT	64
6.17.1.77 S	64
6.17.1.78 SCROLL_LOCK	64
6.17.1.79 SHIFT	64
6.17.1.80 SPACE	64
6.17.1.81 SUBTRACT	64
6.17.1.82 SYSTEM	64
6.17.1.83 T	65
6.17.1.84 TAB	65
6.17.1.85 U	65
6.17.1.86 UP	65
6.17.1.87 V	65
6.17.1.88 W	65
6.17.1.89 X	65
6.17.1.90 Y	65
6.17.1.91 Z	65
6.18 age.log.Level Enum Reference	66
6.18.1 Member Data Documentation	66
6.18.1.1 DEBUG	66
6.18.1.2 ERROR	66
6.18.1.3 INFO	66
6.18.1.4 WARNING	66
6.19 age.log.Log Class Reference	66
6.19.1 Constructor & Destructor Documentation	67
6.19.1.1 Log() [1/2]	67
6.19.1.2 Log() [2/2]	67
6.19.2 Member Function Documentation	67
6.19.2.1 clear()	67
6.19.2.2 configure()	68
6.19.2.3 debug() [1/2]	68
6.19.2.4 debug() [2/2]	68
6.19.2.5 disable()	68
6.19.2.6 enable()	68
6.19.2.7 error() [1/2]	68
6.19.2.8 error() [2/2]	68
6.19.2.9 format() [1/2]	68
6.19.2.10 format() [2/2]	69
6.19.2.11 get()	69
6.19.2.12 info() [1/2]	69

6.19.2.13 info() [2/2]	69
6.19.2.14 log() [1/2]	69
6.19.2.15 log() [2/2]	69
6.19.2.16 trace() [1/2]	69
6.19.2.17 trace() [2/2]	69
6.19.2.18 warn() [1/2]	70
6.19.2.19 warn() [2/2]	70
6.19.2.20 write()	70
6.19.3 Member Data Documentation	70
6.19.3.1 format	70
6.19.3.2 levels	70
6.19.3.3 map	70
6.19.3.4 trace	70
6.20 age.gui.Multiline Class Reference	71
6.20.1 Constructor & Destructor Documentation	72
6.20.1.1 Multiline()	72
6.20.2 Member Function Documentation	72
6.20.2.1 assign()	72
6.20.2.2 buffer()	72
6.20.2.3 count()	72
6.20.2.4 create()	72
6.20.2.5 down()	73
6.20.2.6 line()	73
6.20.2.7 lineHeight()	73
6.20.2.8 offset() [1/2]	73
6.20.2.9 offset() [2/2]	73
6.20.2.10 page()	73
6.20.2.11 rescale()	73
6.20.2.12 text()	73
6.20.2.13 up()	73
6.20.2.14 update()	74
6.20.3 Member Data Documentation	74
6.20.3.1 buffer	74
6.20.3.2 offset	74
6.20.3.3 scroller	74
6.21 age.scene.Node Class Reference	74
6.21.1 Member Function Documentation	74
6.21.1.1 attach() [1/2]	74
6.21.1.2 attach() [2/2]	75
6.21.1.3 children()	75
6.21.1.4 detach()	75
6.21.1.5 parent()	75

6.21.2 Member Data Documentation	75
6.21.2.1 children	75
6.21.2.2 children_ro	75
6.21.2.3 parent	75
6.22 age.port.Port Interface Reference	75
6.22.1 Member Function Documentation	76
6.22.1.1 add()	76
6.22.1.2 assign()	76
6.22.1.3 create()	76
6.22.1.4 fullscreen() [1/2]	76
6.22.1.5 fullscreen() [2/2]	77
6.22.1.6 height()	77
6.22.1.7 maximized() [1/2]	77
6.22.1.8 maximized() [2/2]	77
6.22.1.9 render()	77
6.22.1.10 size()	77
6.22.1.11 title() [1/2]	77
6.22.1.12 title() [2/2]	78
6.22.1.13 visible() [1/2]	78
6.22.1.14 visible() [2/2]	78
6.22.1.15 width()	78
6.23 age.port.Renderable Interface Reference	78
6.23.1 Member Function Documentation	78
6.23.1.1 render()	78
6.24 age.gui.Rendering Class Reference	79
6.24.1 Constructor & Destructor Documentation	79
6.24.1.1 Rendering()	79
6.24.2 Member Function Documentation	79
6.24.2.1 render() [1/2]	79
6.24.2.2 render() [2/2]	80
6.24.2.3 renderBox()	80
6.24.2.4 renderButton()	80
6.24.2.5 renderCanvas()	80
6.24.2.6 renderChildren()	80
6.24.2.7 renderFrame()	80
6.24.2.8 renderHandle()	80
6.24.2.9 renderMultiline()	80
6.24.2.10 renderTitle()	81
6.24.2.11 renderWidget()	81
6.24.3 Member Data Documentation	81
6.24.3.1 widgets	81
6.25 age.scene.Scene Class Reference	81

6.25.1 Member Function Documentation	81
6.25.1.1 root()	81
6.25.2 Member Data Documentation	81
6.25.2.1 root	81
6.26 age.clock.Task Interface Reference	82
6.26.1 Member Function Documentation	82
6.26.1.1 run()	82
6.27 age.task.Task Interface Reference	82
6.27.1 Member Function Documentation	82
6.27.1.1 perform()	82
6.28 age.task.Tasks Class Reference	82
6.28.1 Constructor & Destructor Documentation	83
6.28.1.1 Tasks()	83
6.28.2 Member Function Documentation	83
6.28.2.1 assign() [1/4]	83
6.28.2.2 assign() [2/4]	83
6.28.2.3 assign() [3/4]	83
6.28.2.4 assign() [4/4]	83
6.28.2.5 construct()	84
6.28.2.6 handleEvent()	84
6.28.2.7 perform()	84
6.28.2.8 put()	84
6.28.2.9 shutdown()	84
6.28.2.10 toggleFullscreen()	84
6.28.2.11 update()	84
6.28.3 Member Data Documentation	84
6.28.3.1 client	84
6.28.3.2 inbox	84
6.28.3.3 outbox	85
6.28.3.4 port	85
6.28.3.5 tasks	85
6.29 age.event.Type Enum Reference	85
6.29.1 Member Data Documentation	85
6.29.1.1 KEY_PRESSED	85
6.29.1.2 KEY_RELEASED	85
6.29.1.3 KEY_TYPED	86
6.29.1.4 NONE	86
6.29.1.5 POINTER_CLICKED	86
6.29.1.6 POINTER_ENTERED	86
6.29.1.7 POINTER_EXITED	86
6.29.1.8 POINTER_MOVED	86
6.29.1.9 POINTER_PRESSED	86

6.29.1.10 POINTER_RELEASED	86
6.29.1.11 SURFACE_CLOSE_REQUEST	86
6.29.1.12 SURFACE_RESIZED	86
6.29.1.13 TASK_COMMAND	87
6.30 age.Util Class Reference	87
6.30.1 Detailed Description	87
6.30.2 Member Function Documentation	87
6.30.2.1 readJsonFile()	87
6.30.2.2 readTextFile()	87
6.30.3 Member Data Documentation	88
6.30.3.1 objectMapper	88
6.31 age.gui.VScroller Class Reference	88
6.31.1 Constructor & Destructor Documentation	89
6.31.1.1 VScroller()	89
6.31.2 Member Function Documentation	89
6.31.2.1 assign()	89
6.31.2.2 create()	90
6.31.2.3 handle()	90
6.31.2.4 set()	90
6.31.2.5 value()	90
6.31.3 Member Data Documentation	90
6.31.3.1 bar	90
6.31.3.2 btnDn	90
6.31.3.3 btnUp	90
6.31.3.4 handle	90
6.31.3.5 mark	90
6.31.3.6 page	91
6.31.3.7 size	91
6.31.3.8 uuid	91
6.32 age.gui.Widget Class Reference	91
6.32.1 Constructor & Destructor Documentation	92
6.32.1.1 Widget()	92
6.32.2 Member Function Documentation	92
6.32.2.1 add() [1/2]	92
6.32.2.2 add() [2/2]	93
6.32.2.3 children()	93
6.32.2.4 clear()	93
6.32.2.5 command() [1/2]	93
6.32.2.6 command() [2/2]	93
6.32.2.7 dimension() [1/3]	93
6.32.2.8 dimension() [2/3]	93
6.32.2.9 dimension() [3/3]	93

6.32.2.10 dimensionAdd() [1/2]	93
6.32.2.11 dimensionAdd() [2/2]	94
6.32.2.12 dock() [1/3]	94
6.32.2.13 dock() [2/3]	94
6.32.2.14 dock() [3/3]	94
6.32.2.15 flag()	94
6.32.2.16 flags()	94
6.32.2.17 height()	94
6.32.2.18 image() [1/2]	94
6.32.2.19 image() [2/2]	94
6.32.2.20 match()	95
6.32.2.21 parent()	95
6.32.2.22 parentResized()	95
6.32.2.23 position() [1/3]	95
6.32.2.24 position() [2/3]	95
6.32.2.25 position() [3/3]	95
6.32.2.26 positionAdd() [1/2]	95
6.32.2.27 positionAdd() [2/2]	95
6.32.2.28 remove()	95
6.32.2.29 resized()	96
6.32.2.30 text() [1/2]	96
6.32.2.31 text() [2/2]	96
6.32.2.32 toFront()	96
6.32.2.33 width()	96
6.32.2.34 x()	96
6.32.2.35 y()	96
6.32.3 Member Data Documentation	96
6.32.3.1 children	96
6.32.3.2 children_ro	96
6.32.3.3 command	97
6.32.3.4 dimension	97
6.32.3.5 dock	97
6.32.3.6 flags	97
6.32.3.7 flags_ro	97
6.32.3.8 image	97
6.32.3.9 parent	97
6.32.3.10 position	97
6.32.3.11 text	97
6.33 age.gui.Widgets Class Reference	98
6.33.1 Constructor & Destructor Documentation	98
6.33.1.1 Widgets()	98
6.33.2 Member Function Documentation	98

6.33.2.1 assign() [1/2]	98
6.33.2.2 assign() [2/2]	98
6.33.2.3 root()	98
6.33.3 Member Data Documentation	98
6.33.3.1 handling	98
6.33.3.2 rendering	99
6.33.3.3 root	99
6.34 age.gui.Window Class Reference	99
6.34.1 Constructor & Destructor Documentation	100
6.34.1.1 Window()	100
6.34.2 Member Function Documentation	100
6.34.2.1 construct()	100
6.34.2.2 getPage()	100
6.34.2.3 title() [1/2]	101
6.34.2.4 title() [2/2]	101
6.34.3 Member Data Documentation	101
6.34.3.1 close	101
6.34.3.2 page	101
6.34.3.3 size	101
6.34.3.4 title	101
7 File Documentation	103
7.1 D:/GIT/repos/ODE/age/age/AGEException.java File Reference	103
7.2 D:/GIT/repos/ODE/age/age/Client.java File Reference	103
7.3 D:/GIT/repos/ODE/age/age/clock/Alarm.java File Reference	103
7.4 D:/GIT/repos/ODE/age/age/clock/Clock.java File Reference	104
7.5 D:/GIT/repos/ODE/age/age/clock/Task.java File Reference	104
7.6 D:/GIT/repos/ODE/age/age/task/Task.java File Reference	104
7.7 D:/GIT/repos/ODE/age/age/event/Button.java File Reference	104
7.8 D:/GIT/repos/ODE/age/age/event/Event.java File Reference	105
7.9 D:/GIT/repos/ODE/age/age/event/Events.java File Reference	105
7.10 D:/GIT/repos/ODE/age/age/event/Handler.java File Reference	105
7.11 D:/GIT/repos/ODE/age/age/event/Key.java File Reference	106
7.12 D:/GIT/repos/ODE/age/age/event/Type.java File Reference	106
7.13 D:/GIT/repos/ODE/age/age/gui/Dock.java File Reference	106
7.14 D:/GIT/repos/ODE/age/age/gui/Flag.java File Reference	106
7.15 D:/GIT/repos/ODE/age/age/gui/Handling.java File Reference	107
7.16 D:/GIT/repos/ODE/age/age/gui/Multiline.java File Reference	107
7.17 D:/GIT/repos/ODE/age/age/gui/Rendering.java File Reference	107
7.18 D:/GIT/repos/ODE/age/age/gui/VScroller.java File Reference	107
7.19 D:/GIT/repos/ODE/age/age/gui/Widget.java File Reference	108
7.20 D:/GIT/repos/ODE/age/age/gui/Widgets.java File Reference	108

7.21 D:/GIT/repos/ODE/age/age/gui/Window.java File Reference	108
7.22 D:/GIT/repos/ODE/age/age/log/Level.java File Reference	109
7.23 D:/GIT/repos/ODE/age/age/log/Log.java File Reference	109
7.24 D:/GIT/repos/ODE/age/age/port/Graphics.java File Reference	109
7.25 D:/GIT/repos/ODE/age/age/port/jogl/JOGLEventListener.java File Reference	109
7.26 D:/GIT/repos/ODE/age/age/port/jogl/JOGLGraphics.java File Reference	110
7.27 D:/GIT/repos/ODE/age/age/port/jogl/JOGLPort.java File Reference	110
7.28 D:/GIT/repos/ODE/age/age/port/jogl/JOGLRenderListener.java File Reference	110
7.29 D:/GIT/repos/ODE/age/age/port/Port.java File Reference	111
7.30 D:/GIT/repos/ODE/age/age/port/Renderable.java File Reference	111
7.31 D:/GIT/repos/ODE/age/age/scene/Node.java File Reference	111
7.32 D:/GIT/repos/ODE/age/age/scene/Scene.java File Reference	112
7.33 D:/GIT/repos/ODE/age/age/task/Tasks.java File Reference	112
7.34 D:/GIT/repos/ODE/age/age/Util.java File Reference	112
Index	113

Chapter 1

Namespace Index

1.1 Package List

Here are the packages with brief descriptions (if available):

age	9
age.clock	9
age.event	10
age.gui	10
age.log	10
age.port	10
age.port.jogl	11
age.scene	11
age.task	11

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

age.clock.Alarm	15
age.event.Button	16
age.Client	18
age.clock.Clock	22
age.gui.Dock	23
age.event.Event	25
age.event.Events	30
age.gui.Flag	34
GLEventListener	
age.port.jogl.JOGLRenderListener	53
age.port.Graphics	35
age.port.jogl.JOGLGraphics	45
age.event.Handler	38
age.gui.Handling	38
age.event.Key	55
KeyListener	
age.port.jogl.JOGLEventListener	42
age.log.Level	66
age.log.Log	66
MouseListener	
age.port.jogl.JOGLEventListener	42
age.scene.Node	74
age.port.Port	75
age.port.jogl.JOGLPort	50
age.port.Renderable	78
Renderable	
age.gui.Rendering	79
RuntimeException	
age.AGEEException	13
age.scene.Scene	81
age.clock.Task	82
age.task.Task	82
age.task.Tasks	82
age.event.Type	85
age.Util	87

age.gui.Widget	91
age.gui.Multiline	71
age.gui.VScroller	88
age.gui.Window	99
age.gui.Widgets	98
WindowListener	
age.port.jogl.JOGLEventListener	42

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

age.AGEEException	
Root Exception for AGE	13
age.clock.Alarm	15
age.event.Button	16
age.Client	
The AGE Application Client main class	18
age.clock.Clock	22
age.gui.Dock	23
age.event.Event	25
age.event.Events	30
age.gui.Flag	34
age.port.Graphics	35
age.event.Handler	38
age.gui.Handling	38
age.port.jogl.JOGLEventListener	42
age.port.jogl.JOGLGraphics	45
age.port.jogl.JOGLPort	50
age.port.jogl.JOGLRenderListener	53
age.event.Key	55
age.log.Level	66
age.log.Log	66
age.gui.Multiline	71
age.scene.Node	74
age.port.Port	75
age.port.Renderable	78
age.gui.Rendering	79
age.scene.Scene	81
age.clock.Task	82
age.task.Task	82
age.task.Tasks	82
age.event.Type	85
age.Util	
The AGE Utility class	87
age.gui.VScroller	88
age.gui.Widget	91
age.gui.Widgets	98
age.gui.Window	99

Chapter 4

File Index

4.1 File List

Here is a list of all files with brief descriptions:

D:/GIT/repos/ODE/age/age/ AGEException.java	103
D:/GIT/repos/ODE/age/age/ Client.java	103
D:/GIT/repos/ODE/age/age/ Util.java	112
D:/GIT/repos/ODE/age/age/clock/ Alarm.java	103
D:/GIT/repos/ODE/age/age/clock/ Clock.java	104
D:/GIT/repos/ODE/age/age/clock/ Task.java	104
D:/GIT/repos/ODE/age/age/event/ Button.java	104
D:/GIT/repos/ODE/age/age/event/ Event.java	105
D:/GIT/repos/ODE/age/age/event/ Events.java	105
D:/GIT/repos/ODE/age/age/event/ Handler.java	105
D:/GIT/repos/ODE/age/age/event/ Key.java	106
D:/GIT/repos/ODE/age/age/event/ Type.java	106
D:/GIT/repos/ODE/age/age/gui/ Dock.java	106
D:/GIT/repos/ODE/age/age/gui/ Flag.java	106
D:/GIT/repos/ODE/age/age/gui/ Handling.java	107
D:/GIT/repos/ODE/age/age/gui/ Multiline.java	107
D:/GIT/repos/ODE/age/age/gui/ Rendering.java	107
D:/GIT/repos/ODE/age/age/gui/ VScroller.java	107
D:/GIT/repos/ODE/age/age/gui/ Widget.java	108
D:/GIT/repos/ODE/age/age/gui/ Widgets.java	108
D:/GIT/repos/ODE/age/age/gui/ Window.java	108
D:/GIT/repos/ODE/age/age/log/ Level.java	109
D:/GIT/repos/ODE/age/age/log/ Log.java	109
D:/GIT/repos/ODE/age/age/port/ Graphics.java	109
D:/GIT/repos/ODE/age/age/port/ Port.java	111
D:/GIT/repos/ODE/age/age/port/ Renderable.java	111
D:/GIT/repos/ODE/age/age/port/jogl/ JOGLEventListener.java	109
D:/GIT/repos/ODE/age/age/port/jogl/ JOGLGraphics.java	110
D:/GIT/repos/ODE/age/age/port/jogl/ JOGLPort.java	110
D:/GIT/repos/ODE/age/age/port/jogl/ JOGLRenderListener.java	110
D:/GIT/repos/ODE/age/age/scene/ Node.java	111
D:/GIT/repos/ODE/age/age/scene/ Scene.java	112
D:/GIT/repos/ODE/age/age/task/ Task.java	104
D:/GIT/repos/ODE/age/age/task/ Tasks.java	112

Chapter 5

Namespace Documentation

5.1 Package age

Packages

- package [clock](#)
- package [event](#)
- package [gui](#)
- package [log](#)
- package [port](#)
- package [scene](#)
- package [task](#)

Classes

- class [AGEException](#)
Root Exception for AGE.
- class [Client](#)
The AGE Application Client main class.
- class [Util](#)
The AGE Utility class.

5.2 Package age.clock

Classes

- class [Alarm](#)
- class [Clock](#)
- interface [Task](#)

5.3 Package age.event

Classes

- enum [Button](#)
- class [Event](#)
- class [Events](#)
- interface [Handler](#)
- enum [Key](#)
- enum [Type](#)

5.4 Package age.gui

Classes

- class [Dock](#)
- enum [Flag](#)
- class [Handling](#)
- class [Multiline](#)
- class [Rendering](#)
- class [VScroller](#)
- class [Widget](#)
- class [Widgets](#)
- class [Window](#)

5.5 Package age.log

Classes

- enum [Level](#)
- class [Log](#)

5.6 Package age.port

Packages

- package [jogl](#)

Classes

- interface [Graphics](#)
- interface [Port](#)
- interface [Renderable](#)

5.7 Package age.port.jogl

Classes

- class [JOGLEventListener](#)
- class [JOGLGraphics](#)
- class [JOGLPort](#)
- class [JOGLRenderListener](#)

5.8 Package age.scene

Classes

- class [Node](#)
- class [Scene](#)

5.9 Package age.task

Classes

- interface [Task](#)
- class [Tasks](#)


Chapter 6

Class Documentation

6.1 age.AGEEException Class Reference

Root Exception for AGE.

Inheritance diagram for age.AGEEException:



Public Member Functions

- [AGEEException](#) ()
Default Constructor.
- [AGEEException](#) (Throwable cause)
Constructor.
- [AGEEException](#) (String message)
Constructor.
- [AGEEException](#) (String message, Throwable cause)
Constructor.

Static Private Attributes

- static final long [serialVersionUID](#) = 1L
Default serial version number.

6.1.1 Detailed Description

Root Exception for AGE.

The AGEException is derived from Runtime Exception which means that no throws declarations have to be added to surrounding methods.

Exceptions of local try/catch blocks commonly are re-thrown by that Exception in order to make throws statements unnecessary.

6.1.2 Constructor & Destructor Documentation

6.1.2.1 AGEException() [1/4]

```
age.AGEException.AGEException ( )
```

Default Constructor.

6.1.2.2 AGEException() [2/4]

```
age.AGEException.AGEException (
    Throwable cause )
```

Constructor.

Parameters

<i>cause</i>	an Exception typically to be re-thrown.
--------------	---

6.1.2.3 AGEException() [3/4]

```
age.AGEException.AGEException (
    String message )
```

Constructor.

Parameters

<i>message</i>	A text message that is printed on the stack trace in case the Exception is thrown on application level.
----------------	---

6.1.2.4 AGEException() [4/4]

```
age.AGEException.AGEException (
    String message,
    Throwable cause )
```

Constructor.

Parameters

<i>message</i>	A text message that is printed on the stack trace in case the Exception is thrown on application level.
<i>cause</i>	an Exception typically to be re-thrown.

6.1.3 Member Data Documentation

6.1.3.1 serialVersionUID

```
final long age.AGEEException.serialVersionUID = 1L [static], [private]
```

Default serial version number.

The documentation for this class was generated from the following file:

- D:/GIT/repos/ODE/age/age/[AGEException.java](#)

6.2 age.clock.Alarm Class Reference

Public Member Functions

- void [init](#) (long nanotime)
- void [update](#) (long nanotime)

Package Functions

- [Alarm](#) (long [nanoperiod](#), [Task](#) task)

Private Member Functions

- void [trigger](#) (int count, float dT)

Private Attributes

- long [nanoperiod](#)
- [Task](#) task
- long [mark](#)

6.2.1 Constructor & Destructor Documentation

6.2.1.1 Alarm()

```
age.clock.Alarm.Alarm (
    long nanoperiod,
    Task task ) [package]
```

6.2.2 Member Function Documentation

6.2.2.1 init()

```
void age.clock.Alarm.init (
    long nanotime )
```

6.2.2.2 trigger()

```
void age.clock.Alarm.trigger (
    int count,
    float dT ) [private]
```

6.2.2.3 update()

```
void age.clock.Alarm.update (
    long nanotime )
```

6.2.3 Member Data Documentation

6.2.3.1 mark

```
long age.clock.Alarm.mark [private]
```

6.2.3.2 nanoperiod

```
long age.clock.Alarm.nanoperiod [private]
```

6.2.3.3 task

```
Task age.clock.Alarm.task [private]
```

The documentation for this class was generated from the following file:

- D:/GIT/repos/ODE/age/age/clock/[Alarm.java](#)

6.3 age.event.Button Enum Reference

Public Attributes

- [NONE](#)
- [BTN1](#)
- [BTN2](#)
- [BTN3](#)
- [BTN4](#)
- [BTN5](#)
- [BTN6](#)
- [BTN7](#)
- [BTN8](#)

6.3.1 Member Data Documentation

6.3.1.1 BTN1

`age.event.Button.BTN1`

6.3.1.2 BTN2

`age.event.Button.BTN2`

6.3.1.3 BTN3

`age.event.Button.BTN3`

6.3.1.4 BTN4

`age.event.Button.BTN4`

6.3.1.5 BTN5

`age.event.Button.BTN5`

6.3.1.6 BTN6

`age.event.Button.BTN6`

6.3.1.7 BTN7

`age.event.Button.BTN7`

6.3.1.8 BTN8

`age.event.Button.BTN8`

6.3.1.9 NONE

`age.event.Button.NONE`

The documentation for this enum was generated from the following file:

- <D:/GIT/repos/ODE/age/age/event/Button.java>

6.4 age.Client Class Reference

The AGE Application Client main class.

Public Member Functions

- void `run` ()
Initializes and executes the Client run loop.
- void `shutdown` ()
Sets the internal Client loop run state to false, and therefore stops the client run loop.

Static Public Member Functions

- static void `main` (String[] args)
The static Client main method to create a client instance and launch the application.

Private Member Functions

- void `setup` ()
Initializes the Client application and its parts.
- void `setupGUI` ()
Initializes and sets up the GUI elements.
- void `toggleSystemenu` ()
Private action method to toggle the visibility of the System Menu.
- void `toggleDesktop` ()
Private action method to toggle the visibility of the Desktop and its contents.
- void `loop` ()
The Client loop that maintains the program logic.
- void `render` (int count, long nanoperiod, float dT)
Private scheduler action to update the display contents and render the Client surface.
- void `update` (int count, long nanoperiod, float dT)
Private scheduler action to update the logic of the Client application.

Private Attributes

- Clock `clock` = new Clock()
The schedule clock.
- Events `events` = new Events()
The event system, handling and transforming input events.
- Widgets `widgets` = new Widgets()
The widget system (the GUI)
- Tasks `tasks` = new Tasks()
The task system.
- Port `port` = new JOGLPort()
The port system.
- boolean `running` = false
The run loop running indicator.
- Widget `sysMenuFrame`
- Widget `windowFrame`

6.4.1 Detailed Description

The AGE Application Client main class.

6.4.2 Member Function Documentation

6.4.2.1 loop()

```
void age.Client.loop ( ) [private]
```

The Client loop that maintains the program logic.

6.4.2.2 main()

```
static void age.Client.main (
    String[] args ) [static]
```

The static Client main method to create a client instance and launch the application.

Parameters

<i>args</i>	Program arguments, unused atm.
-------------	--------------------------------

6.4.2.3 render()

```
void age.Client.render (
    int count,
    long nanoperiod,
    float dT ) [private]
```

Private scheduler action to update the display contents and render the Client surface.

Parameters

<i>count</i>	The number of (skipped) schedule frames since last call
<i>nanoperiod</i>	The duration of a schedule frame in nano seconds
<i>dT</i>	The time elapsed since last schedule call, in Seconds.

6.4.2.4 run()

```
void age.Client.run ( )
```

Initializes and executes the Client run loop.

6.4.2.5 setup()

```
void age.Client.setup ( ) [private]
```

Initializes the Client application and its parts.

6.4.2.6 setupGUI()

```
void age.Client.setupGUI ( ) [private]
```

Initializes and sets up the GUI elements.

6.4.2.7 shutdown()

```
void age.Client.shutdown ( )
```

Sets the internal Client loop run state to false, and therefore stops the client run loop.

6.4.2.8 toggleDesktop()

```
void age.Client.toggleDesktop ( ) [private]
```

Private action method to toggle the visibility of the Desktop and its contents.

6.4.2.9 toggleSysmenu()

```
void age.Client.toggleSysmenu ( ) [private]
```

Private action method to toggle the visibility of the System Menu.

6.4.2.10 update()

```
void age.Client.update (
    int count,
    long nanoperiod,
    float dT ) [private]
```

Private scheduler action to update the logic of the Client application.

Parameters

<i>count</i>	The number of (skipped) schedule frames since last call
<i>nanoperiod</i>	The duration of a schedule frame in nano seconds
<i>dT</i>	The time elapsed since last schedule call, in Seconds.

6.4.3 Member Data Documentation

6.4.3.1 clock

```
Clock age.Client.clock = new Clock() [private]
```

The schedule clock.

6.4.3.2 events

```
Events age.Client.events = new Events() [private]
```

The event system, handling and transforming input events.

6.4.3.3 port

```
Port age.Client.port = new JOGLPort() [private]
```

The port system.

Provides and encapsulates the low level machine dependent parts of the Client application.

6.4.3.4 running

```
boolean age.Client.running = false [private]
```

The run loop running indicator.

6.4.3.5 sysMenuFrame

```
Widget age.Client.sysMenuFrame [private]
```

6.4.3.6 tasks

```
Tasks age.Client.tasks = new Tasks() [private]
```

The task system.

Launches named tasks, that can be posted and queued, on a specific run loop phase.

6.4.3.7 widgets

```
Widgets age.Client.widgets = new Widgets() [private]
```

The widget system (the GUI)

6.4.3.8 windowFrame

```
Widget age.Client.windowFrame [private]
```

The documentation for this class was generated from the following file:

- D:/GIT/repos/ODE/age/age/[Client.java](#)

6.5 age.clock.Clock Class Reference

Public Member Functions

- void [add](#) (long nanoperiod, [Task](#) task)
- void [addFPS](#) (int fps, [Task](#) task)
- void [init](#) ()
- void [update](#) ()

Private Attributes

- final List< [Alarm](#) > [alarms](#) = new ArrayList<>()

6.5.1 Member Function Documentation

6.5.1.1 add()

```
void age.clock.Clock.add (  
    long nanoperiod,  
    Task task )
```

6.5.1.2 addFPS()

```
void age.clock.Clock.addFPS (  
    int fps,  
    Task task )
```

6.5.1.3 init()

```
void age.clock.Clock.init ( )
```

6.5.1.4 update()

```
void age.clock.Clock.update ( )
```

6.5.2 Member Data Documentation

6.5.2.1 alarms

```
final List<Alarm> age.clock.Clock.alarms = new ArrayList<>() [private]
```

The documentation for this class was generated from the following file:

- D:/GIT/repos/ODE/age/age/clock/[Clock.java](#)

6.6 age.gui.Dock Class Reference

Public Member Functions

- float [top](#) ()
- float [bottom](#) ()
- float [left](#) ()
- float [right](#) ()
- void [set](#) ([Dock](#) dock)
- void [set](#) (float [left](#), float [right](#), float [top](#), float [bottom](#))

Private Attributes

- float [left](#) = 0
- float [right](#) = 0
- float [top](#) = 0
- float [bottom](#) = 0

6.6.1 Member Function Documentation

6.6.1.1 bottom()

```
float age.gui.Dock.bottom ( )
```

6.6.1.2 left()

```
float age.gui.Dock.left ( )
```

6.6.1.3 right()

```
float age.gui.Dock.right ( )
```

6.6.1.4 set() [1/2]

```
void age.gui.Dock.set (
    Dock dock )
```

6.6.1.5 set() [2/2]

```
void age.gui.Dock.set (
    float left,
    float right,
    float top,
    float bottom )
```

6.6.1.6 top()

```
float age.gui.Dock.top ( )
```

6.6.2 Member Data Documentation

6.6.2.1 bottom

```
float age.gui.Dock.bottom = 0 [private]
```

6.6.2.2 left

```
float age.gui.Dock.left = 0 [private]
```

6.6.2.3 right

```
float age.gui.Dock.right = 0 [private]
```

6.6.2.4 top

```
float age.gui.Dock.top = 0 [private]
```

The documentation for this class was generated from the following file:

- [D:/GIT/repos/ODE/age/age/gui/Dock.java](#)

6.7 age.event.Event Class Reference

Public Member Functions

- void `clear` ()
- `Type` `type` ()
- `Key` `key` ()
- char `character` ()
- `Button` `button` ()
- int `count` ()
- float `x` ()
- float `y` ()
- `Vector2f` `position` ()
- float `width` ()
- float `height` ()
- `Vector2f` `dimension` ()
- String `command` ()
- void `keyPressed` (`Key` `key`, char `character`)
- void `keyReleased` (`Key` `key`, char `character`)
- void `keyTyped` (`Key` `key`, char `character`)
- void `pointerEntered` (float `x`, float `y`)
- void `pointerExited` (float `x`, float `y`)
- void `pointerMoved` (float `x`, float `y`)
- void `pointerPressed` (`Button` `button`, int `count`, float `x`, float `y`)
- void `pointerClicked` (`Button` `button`, int `count`, float `x`, float `y`)
- void `pointerReleased` (`Button` `button`, int `count`, float `x`, float `y`)
- void `surfaceResized` (float `w`, float `h`)
- void `surfaceCloseRequest` ()
- void `taskCommand` (String `command`)

Package Functions

- `Event` ()

Private Member Functions

- void `keyEvent` (`Type` `type`, `Key` `key`, char `character`)
- void `pointerEvent` (`Type` `type`, `Button` `button`, int `count`, float `x`, float `y`)

Private Attributes

- `Type` `type` = `Type.NONE`
- `Key` `key` = `Key.NONE`
- char `character` = `"\0"`
- `Button` `button` = `Button.NONE`
- int `count` = `-1`
- `Vector2f` `position` = `new Vector2f()`
- `Vector2f` `dimension` = `new Vector2f()`
- String `command` = `null`

6.7.1 Constructor & Destructor Documentation

6.7.1.1 Event()

```
age.event.Event.Event ( ) [package]
```

6.7.2 Member Function Documentation

6.7.2.1 button()

```
Button age.event.Event.button ( )
```

6.7.2.2 character()

```
char age.event.Event.character ( )
```

6.7.2.3 clear()

```
void age.event.Event.clear ( )
```

6.7.2.4 command()

```
String age.event.Event.command ( )
```

6.7.2.5 count()

```
int age.event.Event.count ( )
```

6.7.2.6 dimension()

```
Vector2f age.event.Event.dimension ( )
```

6.7.2.7 height()

```
float age.event.Event.height ( )
```

6.7.2.8 key()

```
Key age.event.Event.key ( )
```

6.7.2.9 keyEvent()

```
void age.event.Event.keyEvent (
    Type type,
    Key key,
    char character ) [private]
```

6.7.2.10 keyPressed()

```
void age.event.Event.keyPressed (
    Key key,
    char character )
```

6.7.2.11 keyReleased()

```
void age.event.Event.keyReleased (
    Key key,
    char character )
```

6.7.2.12 keyTyped()

```
void age.event.Event.keyTyped (
    Key key,
    char character )
```

6.7.2.13 pointerClicked()

```
void age.event.Event.pointerClicked (
    Button button,
    int count,
    float x,
    float y )
```

6.7.2.14 pointerEntered()

```
void age.event.Event.pointerEntered (
    float x,
    float y )
```

6.7.2.15 pointerEvent()

```
void age.event.Event.pointerEvent (
    Type type,
    Button button,
    int count,
    float x,
    float y ) [private]
```

6.7.2.16 pointerExited()

```
void age.event.Event.pointerExited (
    float x,
    float y )
```

6.7.2.17 pointerMoved()

```
void age.event.Event.pointerMoved (
    float x,
    float y )
```

6.7.2.18 pointerPressed()

```
void age.event.Event.pointerPressed (
    Button button,
    int count,
    float x,
    float y )
```

6.7.2.19 pointerReleased()

```
void age.event.Event.pointerReleased (
    Button button,
    int count,
    float x,
    float y )
```

6.7.2.20 position()

```
Vector2f age.event.Event.position ( )
```

6.7.2.21 surfaceCloseRequest()

```
void age.event.Event.surfaceCloseRequest ( )
```

6.7.2.22 surfaceResized()

```
void age.event.Event.surfaceResized (
    float w,
    float h )
```

6.7.2.23 taskCommand()

```
void age.event.Event.taskCommand (
    String command )
```


6.7.2.24 type()

```
Type age.event.Event.type ( )
```

6.7.2.25 width()

```
float age.event.Event.width ( )
```

6.7.2.26 x()

```
float age.event.Event.x ( )
```

6.7.2.27 y()

```
float age.event.Event.y ( )
```

6.7.3 Member Data Documentation

6.7.3.1 button

```
Button age.event.Event.button = Button.NONE [private]
```

6.7.3.2 character

```
char age.event.Event.character = '\0' [private]
```

6.7.3.3 command

```
String age.event.Event.command = null [private]
```

6.7.3.4 count

```
int age.event.Event.count = -1 [private]
```

6.7.3.5 dimension

```
Vector2f age.event.Event.dimension = new Vector2f() [private]
```

6.7.3.6 key

```
Key age.event.Event.key = Key.NONE [private]
```

6.7.3.7 position

```
Vector2f age.event.Event.position = new Vector2f() [private]
```

6.7.3.8 type

```
Type age.event.Event.type = Type.NONE [private]
```

The documentation for this class was generated from the following file:

- D:/GIT/repos/ODE/age/age/event/[Event.java](#)

6.8 age.event.Events Class Reference

Public Member Functions

- void [assign](#) (Type type, [Handler](#) handler)
- void [postKeyPressed](#) ([Key](#) key, char character)
- void [postKeyReleased](#) ([Key](#) key, char character)
- void [postKeyTyped](#) ([Key](#) key, char character)
- void [postPointerEntered](#) (float x, float y)
- void [postPointerExited](#) (float x, float y)
- void [postPointerMoved](#) (float x, float y)
- void [postPointerPressed](#) ([Button](#) button, int count, float x, float y)
- void [postPointerReleased](#) ([Button](#) button, int count, float x, float y)
- void [postPointerClicked](#) ([Button](#) button, int count, float x, float y)
- void [postSurfaceResized](#) (float w, float h)
- void [postSurfaceCloseRequest](#) ()
- void [postTaskCommand](#) (String command)
- void [update](#) ()

Private Member Functions

- void [handle](#) ([Event](#) event)
- void [post](#) ([Event](#) event)
- [Event alloc](#) ()
- void [free](#) ([Event](#) event)

Private Attributes

- final Queue< [Event](#) > [cache](#) = new LinkedList<>()
- final List< [Event](#) > [inbox](#) = new ArrayList<>()
- final List< [Event](#) > [outbox](#) = new ArrayList<>()
- final Map< [Type](#), List< [Handler](#) > > [handlers](#) = new EnumMap<>(Type.class)

6.8.1 Member Function Documentation

6.8.1.1 alloc()

```
Event age.event.Events.alloc ( ) [private]
```

6.8.1.2 assign()

```
void age.event.Events.assign (
    Type type,
    Handler handler )
```

6.8.1.3 free()

```
void age.event.Events.free (
    Event event ) [private]
```

6.8.1.4 handle()

```
void age.event.Events.handle (
    Event event ) [private]
```

6.8.1.5 post()

```
void age.event.Events.post (
    Event event ) [private]
```

6.8.1.6 postKeyPressed()

```
void age.event.Events.postKeyPressed (
    Key key,
    char character )
```

6.8.1.7 postKeyReleased()

```
void age.event.Events.postKeyReleased (
    Key key,
    char character )
```

6.8.1.8 postKeyTyped()

```
void age.event.Events.postKeyTyped (
    Key key,
    char character )
```

6.8.1.9 postPointerClicked()

```
void age.event.Events.postPointerClicked (
    Button button,
    int count,
    float x,
    float y )
```

6.8.1.10 postPointerEntered()

```
void age.event.Events.postPointerEntered (
    float x,
    float y )
```

6.8.1.11 postPointerExited()

```
void age.event.Events.postPointerExited (
    float x,
    float y )
```

6.8.1.12 postPointerMoved()

```
void age.event.Events.postPointerMoved (
    float x,
    float y )
```

6.8.1.13 postPointerPressed()

```
void age.event.Events.postPointerPressed (
    Button button,
    int count,
    float x,
    float y )
```

6.8.1.14 postPointerReleased()

```
void age.event.Events.postPointerReleased (
    Button button,
    int count,
    float x,
    float y )
```

6.8.1.15 postSurfaceCloseRequest()

```
void age.event.Events.postSurfaceCloseRequest ( )
```

6.8.1.16 postSurfaceResized()

```
void age.event.Events.postSurfaceResized (
    float w,
    float h )
```

6.8.1.17 postTaskCommand()

```
void age.event.Events.postTaskCommand (
    String command )
```

6.8.1.18 update()

```
void age.event.Events.update ( )
```

6.8.2 Member Data Documentation

6.8.2.1 cache

```
final Queue<Event> age.event.Events.cache = new LinkedList<>() [private]
```

6.8.2.2 handlers

```
final Map<Type, List<Handler> > age.event.Events.handlers = new EnumMap<>(Type.class) [private]
```

6.8.2.3 inbox

```
final List<Event> age.event.Events.inbox = new ArrayList<>() [private]
```

6.8.2.4 outbox

```
final List<Event> age.event.Events.outbox = new ArrayList<>() [private]
```

The documentation for this class was generated from the following file:

- D:/GIT/repos/ODE/age/age/event/[Events.java](#)

6.9 age.gui.Flag Enum Reference

Public Attributes

- [BOX](#)
- [FRAME](#)
- [BUTTON](#)
- [CANVAS](#)
- [TITLE](#)
- [MULTILINE](#)
- [HANDLE](#)
- [HIDDEN](#)
- [HOVERED](#)

6.9.1 Member Data Documentation

6.9.1.1 BOX

`age.gui.Flag.BOX`

6.9.1.2 BUTTON

`age.gui.Flag.BUTTON`

6.9.1.3 CANVAS

`age.gui.Flag.CANVAS`

6.9.1.4 FRAME

`age.gui.Flag.FRAME`

6.9.1.5 HANDLE

`age.gui.Flag.HANDLE`

6.9.1.6 HIDDEN

`age.gui.Flag.HIDDEN`

6.9.1.7 HOVERED

`age.gui.Flag.HOVERED`

6.9.1.8 MULTILINE

```
age.gui.Flag.MULTILINE
```

6.9.1.9 TITLE


```
age.gui.Flag.TITLE
```

The documentation for this enum was generated from the following file:

- [D:/GIT/repos/ODE/age/age/gui/Flag.java](#)

6.10 age.port.Graphics Interface Reference

Inheritance diagram for age.port.Graphics:



Public Member Functions

- void [mode2D](#) ()
- void [pushTransformation](#) ()
- void [popTransformation](#) ()
- void [color](#) (Color4f c)
- void [color](#) (float r, float g, float b)
- void [color](#) (float r, float g, float b, float a)
- void [translate](#) (Vector2f pos)
- void [translate](#) (float x, float y)
- void [rectangle](#) (Vector2f dim, boolean hollow)
- void [rectangle](#) (Vector2f pos, Vector2f dim, boolean hollow)
- void [rectangle](#) (float x, float y, float w, float h, boolean hollow)
- void [text](#) (float x, float y, CharSequence text, String font)
- void [texture](#) (float x, float y, float w, float h, String texture)
- void [calcMultitext](#) (String [text](#), Vector2f dimension, String font, int[] buffer)
- void [calcMultitext](#) (String [text](#), float width, float height, String font, int[] buffer)

6.10.1 Member Function Documentation

6.10.1.1 calcMultitext() [1/2]

```
void age.port.Graphics.calcMultitext (
    String text,
    float width,
    float height,
    String font,
    int[] buffer )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.2 calcMultitext() [2/2]

```
void age.port.Graphics.calcMultitext (
    String text,
    Vector2f dimension,
    String font,
    int[] buffer )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.3 color() [1/3]

```
void age.port.Graphics.color (
    Color4f c )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.4 color() [2/3]

```
void age.port.Graphics.color (
    float r,
    float g,
    float b )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.5 color() [3/3]

```
void age.port.Graphics.color (
    float r,
    float g,
    float b,
    float a )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.6 mode2D()

```
void age.port.Graphics.mode2D ( )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.7 popTransformation()

```
void age.port.Graphics.popTransformation ( )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.8 pushTransformation()

```
void age.port.Graphics.pushTransformation ( )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.9 rectangle() [1/3]

```
void age.port.Graphics.rectangle (
    float x,
    float y,
    float w,
    float h,
    boolean hollow )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.10 rectangle() [2/3]

```
void age.port.Graphics.rectangle (
    Vector2f dim,
    boolean hollow )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.11 rectangle() [3/3]

```
void age.port.Graphics.rectangle (
    Vector2f pos,
    Vector2f dim,
    boolean hollow )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.12 text()

```
void age.port.Graphics.text (
    float x,
    float y,
    CharSequence text,
    String font )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.13 texture()

```
void age.port.Graphics.texture (
    float x,
    float y,
    float w,
    float h,
    String texture )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.14 translate() [1/2]

```
void age.port.Graphics.translate (
    float x,
    float y )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

6.10.1.15 translate() [2/2]

```
void age.port.Graphics.translate (
    Vector2f pos )
```

Implemented in [age.port.jogl.JOGLGraphics](#).

The documentation for this interface was generated from the following file:

- D:/GIT/repos/ODE/age/age/port/[Graphics.java](#)

6.11 age.event.Handler Interface Reference

Public Member Functions

- void [handle](#) ([Event](#) event)

6.11.1 Member Function Documentation

6.11.1.1 handle()

```
void age.event.Handler.handle (
    Event event )
```

The documentation for this interface was generated from the following file:

- D:/GIT/repos/ODE/age/age/event/[Handler.java](#)

6.12 age.gui.Handling Class Reference

Public Member Functions

- [Handling](#) ([Widgets](#) widgets)
- void [assign](#) (Events [events](#))
- void [handleKeyboard](#) (Event e)
- void [handlePointer](#) (Event e)
- void [handleSurface](#) (Event e)

Private Member Functions

- void [pressedFrameToFront](#) (Event e)
- void [buttonClickAction](#) (Event e)
- void [startFrameSizeAction](#) (Event e)
- void [startFrameDragAction](#) (Event e)
- void [startScrollHandleAction](#) (Event e)
- void [updateActionState](#) (Event e, String [action](#))
- void [updateDragAction](#) (Event e)
- void [stopDragAction](#) (Event e)
- [Widget hovered](#) (Vector2f pos, [Widget](#) widget)

Private Attributes

- Events [events](#)
- final [Widgets](#) [widgets](#)
- [Widget hovered](#) = null
- [Widget dragged](#) = null
- String [action](#) = null
- final Vector2f [ref](#) = new Vector2f()
- final Vector2f [tmp](#) = new Vector2f()

6.12.1 Constructor & Destructor Documentation

6.12.1.1 Handling()

```
age.gui.Handling.Handling (
    Widgets widgets )
```

6.12.2 Member Function Documentation

6.12.2.1 assign()

```
void age.gui.Handling.assign (
    Events events )
```

6.12.2.2 buttonClickAction()

```
void age.gui.Handling.buttonClickAction (
    Event e ) [private]
```

6.12.2.3 handleKeyboard()

```
void age.gui.Handling.handleKeyboard (
    Event e )
```

6.12.2.4 handlePointer()

```
void age.gui.Handling.handlePointer (
    Event e )
```

6.12.2.5 handleSurface()

```
void age.gui.Handling.handleSurface (
    Event e )
```

6.12.2.6 hovered()

```
Widget age.gui.Handling.hovered (
    Vector2f pos,
    Widget widget ) [private]
```

6.12.2.7 pressedFrameToFront()

```
void age.gui.Handling.pressedFrameToFront (
    Event e ) [private]
```

6.12.2.8 startFrameDragAction()

```
void age.gui.Handling.startFrameDragAction (
    Event e ) [private]
```

6.12.2.9 startFrameSizeAction()

```
void age.gui.Handling.startFrameSizeAction (
    Event e ) [private]
```

6.12.2.10 startScrollHandleAction()

```
void age.gui.Handling.startScrollHandleAction (
    Event e ) [private]
```

6.12.2.11 stopDragAction()

```
void age.gui.Handling.stopDragAction (
    Event e ) [private]
```

6.12.2.12 updateActionState()

```
void age.gui.Handling.updateActionState (
    Event e,
    String action ) [private]
```

6.12.2.13 updateDragAction()

```
void age.gui.Handling.updateDragAction (
    Event e ) [private]
```

6.12.3 Member Data Documentation

6.12.3.1 action

```
String age.gui.Handling.action = null [private]
```

6.12.3.2 dragged

```
Widget age.gui.Handling.dragged = null [private]
```

6.12.3.3 events

```
Events age.gui.Handling.events [private]
```

6.12.3.4 hovered

```
Widget age.gui.Handling.hovered = null [private]
```

6.12.3.5 ref

```
final Vector2f age.gui.Handling.ref = new Vector2f() [private]
```

6.12.3.6 tmp

```
final Vector2f age.gui.Handling.tmp = new Vector2f() [private]
```

6.12.3.7 widgets


```
final Widgets age.gui.Handling.widgets [private]
```

The documentation for this class was generated from the following file:

- <D:/GIT/repos/ODE/age/age/gui/Handling.java>

6.13 age.port.jogl.JOGLEventListener Class Reference

Inheritance diagram for age.port.jogl.JOGLEventListener:



Public Member Functions

- void [assign](#) (Events [events](#))
- void [mouseClicked](#) (MouseEvent [e](#))
- void [mouseEntered](#) (MouseEvent [e](#))
- void [mouseExited](#) (MouseEvent [e](#))
- void [mousePressed](#) (MouseEvent [e](#))
- void [mouseReleased](#) (MouseEvent [e](#))
- void [mouseMoved](#) (MouseEvent [e](#))
- void [mouseDragged](#) (MouseEvent [e](#))
- void [mouseWheelMoved](#) (MouseEvent [e](#))
- void [keyPressed](#) (KeyEvent [e](#))
- void [keyReleased](#) (KeyEvent [e](#))
- void [windowResized](#) (WindowEvent [e](#))
- void [windowMoved](#) (WindowEvent [e](#))
- void [windowDestroyNotify](#) (WindowEvent [e](#))
- void [windowDestroyed](#) (WindowEvent [e](#))
- void [windowGainedFocus](#) (WindowEvent [e](#))
- void [windowLostFocus](#) (WindowEvent [e](#))
- void [windowRepaint](#) (WindowUpdateEvent [e](#))

Private Member Functions

- void [handleSurfaceCloseRequest](#) (Event [e](#))
- Button [translateButton](#) (short [button](#))
- Key [translateKey](#) (short [key](#))

Private Attributes

- Events [events](#) = null

6.13.1 Member Function Documentation

6.13.1.1 [assign\(\)](#)

```
void age.port.jogl.JOGLEventListener.assign (
    Events events )
```

6.13.1.2 handleSurfaceCloseRequest()

```
void age.port.jogl.JOGLEventListener.handleSurfaceCloseRequest (
    Event e ) [private]
```

6.13.1.3 keyPressed()

```
void age.port.jogl.JOGLEventListener.keyPressed (
    KeyEvent e )
```

6.13.1.4 keyReleased()

```
void age.port.jogl.JOGLEventListener.keyReleased (
    KeyEvent e )
```

6.13.1.5 mouseClicked()

```
void age.port.jogl.JOGLEventListener.mouseClicked (
    MouseEvent e )
```

6.13.1.6 mouseDragged()

```
void age.port.jogl.JOGLEventListener.mouseDragged (
    MouseEvent e )
```

6.13.1.7 mouseEntered()

```
void age.port.jogl.JOGLEventListener.mouseEntered (
    MouseEvent e )
```

6.13.1.8 mouseExited()

```
void age.port.jogl.JOGLEventListener.mouseExited (
    MouseEvent e )
```

6.13.1.9 mouseMoved()

```
void age.port.jogl.JOGLEventListener.mouseMoved (
    MouseEvent e )
```

6.13.1.10 mousePressed()

```
void age.port.jogl.JOGLEventListener.mousePressed (
    MouseEvent e )
```

6.13.1.11 mouseReleased()

```
void age.port.jogl.JOGLEventListener.mouseReleased (
    MouseEvent e )
```

6.13.1.12 mouseWheelMoved()

```
void age.port.jogl.JOGLEventListener.mouseWheelMoved (
    MouseEvent e )
```

6.13.1.13 translateButton()

```
Button age.port.jogl.JOGLEventListener.translateButton (
    short button ) [private]
```

6.13.1.14 translateKey()

```
Key age.port.jogl.JOGLEventListener.translateKey (
    short key ) [private]
```

6.13.1.15 windowDestroyed()

```
void age.port.jogl.JOGLEventListener.windowDestroyed (
    WindowEvent e )
```

6.13.1.16 windowDestroyNotify()

```
void age.port.jogl.JOGLEventListener.windowDestroyNotify (
    WindowEvent e )
```

6.13.1.17 windowGainedFocus()

```
void age.port.jogl.JOGLEventListener.windowGainedFocus (
    WindowEvent e )
```

6.13.1.18 windowLostFocus()

```
void age.port.jogl.JOGLEventListener.windowLostFocus (
    WindowEvent e )
```

6.13.1.19 windowMoved()

```
void age.port.jogl.JOGLEventListener.windowMoved (
    WindowEvent e )
```


6.13.1.20 windowRepaint()

```
void age.port.jogl.JOGLEventListener.windowRepaint (
    WindowUpdateEvent e )
```

6.13.1.21 windowResized()

```
void age.port.jogl.JOGLEventListener.windowResized (
    WindowEvent e )
```

6.13.2 Member Data Documentation

6.13.2.1 events


```
Events age.port.jogl.JOGLEventListener.events = null [private]
```

The documentation for this class was generated from the following file:

- D:/GIT/repos/ODE/age/age/port/jogl/[JOGLEventListener.java](#)

6.14 age.port.jogl.JOGLGraphics Class Reference

Inheritance diagram for age.port.jogl.JOGLGraphics:



Public Member Functions

- void [assign](#) (GLAutoDrawable [drawable](#))
- void [init](#) ()
- void [clear](#) ()
- void [mode2D](#) ()
- void [mode3D](#) (float fovy, float near, float far)
- void [pushTransformation](#) ()
- void [popTransformation](#) ()
- void [translate](#) (Vector2f t)
- void [translate](#) (float x, float y)
- void [color](#) (Color4f c)
- void [color](#) (float r, float g, float b)
- void [color](#) (float r, float g, float b, float a)
- void [rectangle](#) (Vector2f dim, boolean hollow)
- void [rectangle](#) (Vector2f pos, Vector2f dim, boolean hollow)
- void [rectangle](#) (float x, float y, float w, float h, boolean hollow)
- void [text](#) (float x, float y, CharSequence text, String font)
- void [texture](#) (float x, float y, float w, float h, String texture)
- void [calcMultitext](#) (String [text](#), Vector2f dimension, String font, int[] buffer)
- void [calcMultitext](#) (String [text](#), float width, float height, String font, int[] buffer)

Private Attributes

- GLAutoDrawable [drawable](#) = null
- GL2 [gl](#) = null
- GLU [glu](#) = null
- Map< String, Texture > [textures](#) = new HashMap<>()
- Map< String, TextRenderer > [fonts](#) = new HashMap<>()

6.14.1 Member Function Documentation

6.14.1.1 [assign\(\)](#)

```
void age.port.jogl.JOGLGraphics.assign (
    GLAutoDrawable drawable )
```

6.14.1.2 [calcMultitext\(\)](#) [1/2]

```
void age.port.jogl.JOGLGraphics.calcMultitext (
    String text,
    float width,
    float height,
    String font,
    int[] buffer )
```

Implements [age.port.Graphics](#).

6.14.1.3 [calcMultitext\(\)](#) [2/2]

```
void age.port.jogl.JOGLGraphics.calcMultitext (
    String text,
    Vector2f dimension,
    String font,
    int[] buffer )
```

Implements [age.port.Graphics](#).

6.14.1.4 [clear\(\)](#)

```
void age.port.jogl.JOGLGraphics.clear ( )
```

6.14.1.5 [color\(\)](#) [1/3]

```
void age.port.jogl.JOGLGraphics.color (
    Color4f c )
```

Implements [age.port.Graphics](#).

6.14.1.6 color() [2/3]

```
void age.port.jogl.JOGLGraphics.color (
    float r,
    float g,
    float b )
```

Implements [age.port.Graphics](#).

6.14.1.7 color() [3/3]

```
void age.port.jogl.JOGLGraphics.color (
    float r,
    float g,
    float b,
    float a )
```

Implements [age.port.Graphics](#).

6.14.1.8 init()

```
void age.port.jogl.JOGLGraphics.init ( )
```

6.14.1.9 mode2D()

```
void age.port.jogl.JOGLGraphics.mode2D ( )
```

Implements [age.port.Graphics](#).

6.14.1.10 mode3D()

```
void age.port.jogl.JOGLGraphics.mode3D (
    float fovy,
    float near,
    float far )
```

6.14.1.11 popTransformation()

```
void age.port.jogl.JOGLGraphics.popTransformation ( )
```

Implements [age.port.Graphics](#).

6.14.1.12 pushTransformation()

```
void age.port.jogl.JOGLGraphics.pushTransformation ( )
```

Implements [age.port.Graphics](#).

6.14.1.13 rectangle() [1/3]

```
void age.port.jogl.JOGLGraphics.rectangle (
    float x,
    float y,
    float w,
    float h,
    boolean hollow )
```

Implements [age.port.Graphics](#).

6.14.1.14 rectangle() [2/3]

```
void age.port.jogl.JOGLGraphics.rectangle (
    Vector2f dim,
    boolean hollow )
```

Implements [age.port.Graphics](#).

6.14.1.15 rectangle() [3/3]

```
void age.port.jogl.JOGLGraphics.rectangle (
    Vector2f pos,
    Vector2f dim,
    boolean hollow )
```

Implements [age.port.Graphics](#).

6.14.1.16 text()

```
void age.port.jogl.JOGLGraphics.text (
    float x,
    float y,
    CharSequence text,
    String font )
```

Implements [age.port.Graphics](#).

6.14.1.17 texture()

```
void age.port.jogl.JOGLGraphics.texture (
    float x,
    float y,
    float w,
    float h,
    String texture )
```

Implements [age.port.Graphics](#).

6.14.1.18 translate() [1/2]

```
void age.port.jogl.JOGLGraphics.translate (
    float x,
    float y )
```

Implements [age.port.Graphics](#).

6.14.1.19 translate() [2/2]

```
void age.port.jogl.JOGLGraphics.translate (
    Vector2f t )
```

Implements [age.port.Graphics](#).

6.14.2 Member Data Documentation**6.14.2.1 drawable**

```
GLAutoDrawable age.port.jogl.JOGLGraphics.drawable = null [private]
```

6.14.2.2 fonts

```
Map<String, TextRenderer> age.port.jogl.JOGLGraphics.fonts = new HashMap<>() [private]
```

6.14.2.3 gl

```
GL2 age.port.jogl.JOGLGraphics.gl = null [private]
```

6.14.2.4 glu

```
GLU age.port.jogl.JOGLGraphics.glu = null [private]
```

6.14.2.5 textures


```
Map<String, Texture> age.port.jogl.JOGLGraphics.textures = new HashMap<>() [private]
```

The documentation for this class was generated from the following file:

- D:/GIT/repos/ODE/age/age/port/jogl/[JOGLGraphics.java](#)

6.15 age.port.jogl.JOGLPort Class Reference

Inheritance diagram for age.port.jogl.JOGLPort:



Public Member Functions

- void [assign](#) (Events events)
- String [title](#) ()
- void [title](#) (String title)
- boolean [maximized](#) ()
- void [maximized](#) (boolean maximized)
- boolean [fullscreen](#) ()
- void [fullscreen](#) (boolean fullscreen)
- boolean [visible](#) ()
- void [visible](#) (boolean visible)
- float [width](#) ()
- float [height](#) ()
- void [size](#) (float [width](#), float [height](#))
- void [add](#) (Renderable renderable)
- List< [Renderable](#) > [get](#) ()
- void [create](#) ()
- void [render](#) ()

Private Attributes

- GLWindow [window](#) = null
- JOGLEventListener [eventListener](#) = null
- JOGLRenderListener [renderListener](#) = null
- final List< [Renderable](#) > [renderables](#) = new ArrayList<>()
- final List< [Renderable](#) > [renderables_ro](#) = Collections.unmodifiableList([renderables](#))

6.15.1 Member Function Documentation

6.15.1.1 add()

```
void age.port.jogl.JOGLPort.add (
    Renderable renderable )
```

Implements [age.port.Port](#).

6.15.1.2 assign()

```
void age.port.jogl.JOGLPort.assign (
    Events events )
```

Implements [age.port.Port](#).

6.15.1.3 create()

```
void age.port.jogl.JOGLPort.create ( )
```

Implements [age.port.Port](#).

6.15.1.4 fullscreen() [1/2]

```
boolean age.port.jogl.JOGLPort.fullscreen ( )
```

Implements [age.port.Port](#).

6.15.1.5 fullscreen() [2/2]

```
void age.port.jogl.JOGLPort.fullscreen (
    boolean fullscreen )
```

Implements [age.port.Port](#).

6.15.1.6 get()

```
List< Renderable > age.port.jogl.JOGLPort.get ( )
```

6.15.1.7 height()

```
float age.port.jogl.JOGLPort.height ( )
```

Implements [age.port.Port](#).

6.15.1.8 maximized() [1/2]

```
boolean age.port.jogl.JOGLPort.maximized ( )
```

Implements [age.port.Port](#).

6.15.1.9 maximized() [2/2]

```
void age.port.jogl.JOGLPort.maximized (
    boolean maximized )
```

Implements [age.port.Port](#).

6.15.1.10 render()

```
void age.port.jogl.JOGLPort.render ( )
```

Implements [age.port.Port](#).

6.15.1.11 size()

```
void age.port.jogl.JOGLPort.size (
    float width,
    float height )
```

Implements [age.port.Port](#).

6.15.1.12 title() [1/2]

```
String age.port.jogl.JOGLPort.title ( )
```

Implements [age.port.Port](#).

6.15.1.13 title() [2/2]

```
void age.port.jogl.JOGLPort.title (
    String title )
```

Implements [age.port.Port](#).

6.15.1.14 visible() [1/2]

```
boolean age.port.jogl.JOGLPort.visible ( )
```

Implements [age.port.Port](#).

6.15.1.15 visible() [2/2]

```
void age.port.jogl.JOGLPort.visible (
    boolean visible )
```

Implements [age.port.Port](#).

6.15.1.16 width()

```
float age.port.jogl.JOGLPort.width ( )
```

Implements [age.port.Port](#).

6.15.2 Member Data Documentation**6.15.2.1 eventListener**

```
JOGLEventListener age.port.jogl.JOGLPort.eventListener = null [private]
```


6.15.2.2 renderables

```
final List<Renderable> age.port.jogl.JOGLPort.renderables = new ArrayList<>() [private]
```

6.15.2.3 renderables_ro

```
final List<Renderable> age.port.jogl.JOGLPort.renderables_ro = Collections.unmodifiable←  
List(renderables) [private]
```

6.15.2.4 renderListener

```
JOGLRenderListener age.port.jogl.JOGLPort.renderListener = null [private]
```

6.15.2.5 window


```
GLWindow age.port.jogl.JOGLPort.window = null [private]
```

The documentation for this class was generated from the following file:

- D:/GIT/repos/ODE/age/age/port/jogl/[JOGLPort.java](#)

6.16 age.port.jogl.JOGLRenderListener Class Reference

Inheritance diagram for age.port.jogl.JOGLRenderListener:



Public Member Functions

- [JOGLRenderListener](#) ([JOGLPort](#) port)
- void [init](#) (GLAutoDrawable drawable)
- void [reshape](#) (GLAutoDrawable drawable, int x, int y, int width, int height)
- void [display](#) (GLAutoDrawable drawable)
- void [dispose](#) (GLAutoDrawable drawable)

Private Attributes

- final [JOGLPort](#) port
- final [JOGLGraphics](#) graphics

6.16.1 Constructor & Destructor Documentation

6.16.1.1 JOGLRenderListener()

```
age.port.jogl.JOGLRenderListener.JOGLRenderListener (
    JOGLPort port )
```

6.16.2 Member Function Documentation

6.16.2.1 display()

```
void age.port.jogl.JOGLRenderListener.display (
    GLAutoDrawable drawable )
```

6.16.2.2 dispose()

```
void age.port.jogl.JOGLRenderListener.dispose (
    GLAutoDrawable drawable )
```

6.16.2.3 init()

```
void age.port.jogl.JOGLRenderListener.init (
    GLAutoDrawable drawable )
```

6.16.2.4 reshape()

```
void age.port.jogl.JOGLRenderListener.reshape (
    GLAutoDrawable drawable,
    int x,
    int y,
    int width,
    int height )
```

6.16.3 Member Data Documentation

6.16.3.1 graphics

```
final JOGLGraphics age.port.jogl.JOGLRenderListener.graphics [private]
```

6.16.3.2 port

```
final JOGLPort age.port.jogl.JOGLRenderListener.port [private]
```

The documentation for this class was generated from the following file:

- D:/GIT/repos/ODE/age/age/port/jogl/[JOGLRenderListener.java](#)

6.17 age.event.Key Enum Reference

Public Attributes

- [NONE](#)
- [ESCAPE](#)
- [F1](#)
- [F2](#)
- [F3](#)
- [F4](#)
- [F5](#)
- [F6](#)
- [F7](#)
- [F8](#)
- [F9](#)
- [F10](#)
- [F11](#)
- [F12](#)
- [PRINT_SCREEN](#)
- [SCROLL_LOCK](#)
- [PAUSE](#)
- [_1](#)
- [_2](#)
- [_3](#)
- [_4](#)
- [_5](#)
- [_6](#)
- [_7](#)
- [_8](#)
- [_9](#)
- [_0](#)
- [BACK_SPACE](#)
- [TAB](#)
- [ENTER](#)
- [SPACE](#)
- [Q](#)
- [W](#)
- [E](#)
- [R](#)
- [T](#)
- [Z](#)
- [U](#)
- [I](#)
- [O](#)
- [P](#)
- [A](#)
- [S](#)
- [D](#)
- [F](#)
- [G](#)
- [H](#)
- [J](#)
- [K](#)
- [L](#)

- [Y](#)
- [X](#)
- [C](#)
- [V](#)
- [B](#)
- [N](#)
- [M](#)
- [PLUS](#)
- [MINUS](#)
- [CAPS_LOCK](#)
- [SHIFT](#)
- [CONTROL](#)
- [SYSTEM](#)
- [ALT](#)
- [MENU](#)
- [INSERT](#)
- [DELETE](#)
- [POS1](#)
- [END](#)
- [PAGE_UP](#)
- [PAGE_DOWN](#)
- [UP](#)
- [DOWN](#)
- [LEFT](#)
- [RIGHT](#)
- [NUM_LOCK](#)
- [DIVIDE](#)
- [MULTIPLY](#)
- [SUBTRACT](#)
- [ADD](#)
- [DECIMAL](#)
- [NP_7](#)
- [NP_8](#)
- [NP_9](#)
- [NP_4](#)
- [NP_5](#)
- [NP_6](#)
- [NP_1](#)
- [NP_2](#)
- [NP_3](#)
- [NP_0](#)

6.17.1 Member Data Documentation

6.17.1.1 `_0`

`age.event.Key._0`

6.17.1.2 `_1`

`age.event.Key._1`

6.17.1.3 _2

`age.event.Key._2`

6.17.1.4 _3

`age.event.Key._3`

6.17.1.5 _4

`age.event.Key._4`

6.17.1.6 _5

`age.event.Key._5`

6.17.1.7 _6

`age.event.Key._6`

6.17.1.8 _7

`age.event.Key._7`

6.17.1.9 _8

`age.event.Key._8`

6.17.1.10 _9

`age.event.Key._9`

6.17.1.11 A

`age.event.Key.A`

6.17.1.12 ADD

`age.event.Key.ADD`

6.17.1.13 ALT

`age.event.Key.ALT`

6.17.1.14 B

`age.event.Key.B`

6.17.1.15 BACK_SPACE

`age.event.Key.BACK_SPACE`

6.17.1.16 C

`age.event.Key.C`

6.17.1.17 CAPS_LOCK

`age.event.Key.CAPS_LOCK`

6.17.1.18 CONTROL

`age.event.Key.CONTROL`

6.17.1.19 D

`age.event.Key.D`

6.17.1.20 DECIMAL

`age.event.Key.DECIMAL`

6.17.1.21 DELETE

`age.event.Key.DELETE`

6.17.1.22 DIVIDE

`age.event.Key.DIVIDE`

6.17.1.23 DOWN

```
age.event.Key.DOWN
```

6.17.1.24 E

```
age.event.Key.E
```

6.17.1.25 END

```
age.event.Key.END
```

6.17.1.26 ENTER

```
age.event.Key.ENTER
```

6.17.1.27 ESCAPE

```
age.event.Key.ESCAPE
```

6.17.1.28 F

```
age.event.Key.F
```

6.17.1.29 F1

```
age.event.Key.F1
```

6.17.1.30 F10

```
age.event.Key.F10
```

6.17.1.31 F11

```
age.event.Key.F11
```

6.17.1.32 F12

```
age.event.Key.F12
```

6.17.1.33 F2

`age.event.Key.F2`

6.17.1.34 F3

`age.event.Key.F3`

6.17.1.35 F4

`age.event.Key.F4`

6.17.1.36 F5

`age.event.Key.F5`

6.17.1.37 F6

`age.event.Key.F6`

6.17.1.38 F7

`age.event.Key.F7`

6.17.1.39 F8

`age.event.Key.F8`

6.17.1.40 F9

`age.event.Key.F9`

6.17.1.41 G

`age.event.Key.G`

6.17.1.42 H

`age.event.Key.H`

6.17.1.43 I

```
age.event.Key.I
```

6.17.1.44 INSERT

```
age.event.Key.INSERT
```

6.17.1.45 J

```
age.event.Key.J
```

6.17.1.46 K

```
age.event.Key.K
```

6.17.1.47 L

```
age.event.Key.L
```

6.17.1.48 LEFT

```
age.event.Key.LEFT
```

6.17.1.49 M

```
age.event.Key.M
```

6.17.1.50 MENU

```
age.event.Key.MENU
```

6.17.1.51 MINUS

```
age.event.Key.MINUS
```

6.17.1.52 MULTIPLY

```
age.event.Key.MULTIPLY
```

6.17.1.53 N

`age.event.Key.N`

6.17.1.54 NONE

`age.event.Key.NONE`

6.17.1.55 NP_0

`age.event.Key.NP_0`

6.17.1.56 NP_1

`age.event.Key.NP_1`

6.17.1.57 NP_2

`age.event.Key.NP_2`

6.17.1.58 NP_3

`age.event.Key.NP_3`

6.17.1.59 NP_4

`age.event.Key.NP_4`

6.17.1.60 NP_5

`age.event.Key.NP_5`

6.17.1.61 NP_6

`age.event.Key.NP_6`

6.17.1.62 NP_7

`age.event.Key.NP_7`

6.17.1.63 NP_8

```
age.event.Key.NP_8
```

6.17.1.64 NP_9

```
age.event.Key.NP_9
```

6.17.1.65 NUM_LOCK

```
age.event.Key.NUM_LOCK
```

6.17.1.66 O

```
age.event.Key.O
```

6.17.1.67 P

```
age.event.Key.P
```

6.17.1.68 PAGE_DOWN

```
age.event.Key.PAGE_DOWN
```

6.17.1.69 PAGE_UP

```
age.event.Key.PAGE_UP
```

6.17.1.70 PAUSE

```
age.event.Key.PAUSE
```

6.17.1.71 PLUS

```
age.event.Key.PLUS
```

6.17.1.72 POS1

```
age.event.Key.POS1
```

6.17.1.73 PRINT_SCREEN

```
age.event.Key.PRINT_SCREEN
```

6.17.1.74 Q

```
age.event.Key.Q
```

6.17.1.75 R

```
age.event.Key.R
```

6.17.1.76 RIGHT

```
age.event.Key.RIGHT
```

6.17.1.77 S

```
age.event.Key.S
```

6.17.1.78 SCROLL_LOCK

```
age.event.Key.SCROLL_LOCK
```

6.17.1.79 SHIFT

```
age.event.Key.SHIFT
```

6.17.1.80 SPACE

```
age.event.Key.SPACE
```

6.17.1.81 SUBTRACT

```
age.event.Key.SUBTRACT
```

6.17.1.82 SYSTEM

```
age.event.Key.SYSTEM
```

6.17.1.83 T

`age.event.Key.T`

6.17.1.84 TAB

`age.event.Key.TAB`

6.17.1.85 U

`age.event.Key.U`

6.17.1.86 UP

`age.event.Key.UP`

6.17.1.87 V

`age.event.Key.V`

6.17.1.88 W

`age.event.Key.W`

6.17.1.89 X

`age.event.Key.X`

6.17.1.90 Y

`age.event.Key.Y`

6.17.1.91 Z

`age.event.Key.Z`

The documentation for this enum was generated from the following file:

- [D:/GIT/repos/ODE/age/age/event/Key.java](#)

6.18 age.log.Level Enum Reference

Public Attributes

- [ERROR](#)
- [WARNING](#)
- [INFO](#)
- [DEBUG](#)

6.18.1 Member Data Documentation

6.18.1.1 DEBUG

`age.log.Level.DEBUG`

6.18.1.2 ERROR

`age.log.Level.ERROR`

6.18.1.3 INFO

`age.log.Level.INFO`

6.18.1.4 WARNING

`age.log.Level.WARNING`

The documentation for this enum was generated from the following file:

- [D:/GIT/repos/ODE/age/age/log/Level.java](#)

6.19 age.log.Log Class Reference

Public Member Functions

- void [clear](#) ()
- void [enable](#) ([Level](#) ... [levels](#))
- void [disable](#) ([Level](#) ... [levels](#))
- boolean [trace](#) ()
- void [trace](#) (boolean trace)
- String [format](#) ()
- void [format](#) (String format)

Static Public Member Functions

- static void [configure](#) (String path)
- static [Log](#) [get](#) (String instance)
- static void [log](#) ([Level](#) level, String message, Object ... params)
- static void [info](#) (String message, Object ... params)
- static void [warn](#) (String message, Object ... params)
- static void [error](#) (String message, Object ... params)
- static void [debug](#) (String message, Object ... params)
- static void [log](#) (String instance, [Level](#) level, String message, Object ... params)
- static void [info](#) (String instance, String message, Object ... params)
- static void [warn](#) (String instance, String message, Object ... params)
- static void [error](#) (String instance, String message, Object ... params)
- static void [debug](#) (String instance, String message, Object ... params)

Private Member Functions

- [Log](#) ()
- [Log](#) ([Log](#) parent)
- void [write](#) ([Level](#) level, String message, Object ... params)

Private Attributes

- boolean [trace](#) = false
- Set< [Level](#) > [levels](#) = null
- String [format](#) = null

Static Private Attributes

- static final Map< String, [Log](#) > [map](#) = new HashMap<>()

6.19.1 Constructor & Destructor Documentation

6.19.1.1 [Log\(\)](#) [1/2]

```
age.log.Log.Log ( ) [private]
```

6.19.1.2 [Log\(\)](#) [2/2]

```
age.log.Log.Log (
    Log parent ) [private]
```

6.19.2 Member Function Documentation

6.19.2.1 [clear\(\)](#)

```
void age.log.Log.clear ( )
```

6.19.2.2 configure()

```
static void age.log.Log.configure (
    String path ) [static]
```

6.19.2.3 debug() [1/2]

```
static void age.log.Log.debug (
    String instance,
    String message,
    Object ... params ) [static]
```

6.19.2.4 debug() [2/2]

```
static void age.log.Log.debug (
    String message,
    Object ... params ) [static]
```

6.19.2.5 disable()

```
void age.log.Log.disable (
    Level ... levels )
```

6.19.2.6 enable()

```
void age.log.Log.enable (
    Level ... levels )
```

6.19.2.7 error() [1/2]

```
static void age.log.Log.error (
    String instance,
    String message,
    Object ... params ) [static]
```

6.19.2.8 error() [2/2]

```
static void age.log.Log.error (
    String message,
    Object ... params ) [static]
```

6.19.2.9 format() [1/2]

```
String age.log.Log.format ( )
```


6.19.2.10 format() [2/2]

```
void age.log.Log.format (
    String format )
```

6.19.2.11 get()

```
static Log age.log.Log.get (
    String instance ) [static]
```

6.19.2.12 info() [1/2]

```
static void age.log.Log.info (
    String instance,
    String message,
    Object ... params ) [static]
```

6.19.2.13 info() [2/2]

```
static void age.log.Log.info (
    String message,
    Object ... params ) [static]
```

6.19.2.14 log() [1/2]

```
static void age.log.Log.log (
    Level level,
    String message,
    Object ... params ) [static]
```

6.19.2.15 log() [2/2]

```
static void age.log.Log.log (
    String instance,
    Level level,
    String message,
    Object ... params ) [static]
```

6.19.2.16 trace() [1/2]

```
boolean age.log.Log.trace ( )
```

6.19.2.17 trace() [2/2]

```
void age.log.Log.trace (
    boolean trace )
```

6.19.2.18 warn() [1/2]

```
static void age.log.Log.warn (
    String instance,
    String message,
    Object ... params ) [static]
```

6.19.2.19 warn() [2/2]

```
static void age.log.Log.warn (
    String message,
    Object ... params ) [static]
```

6.19.2.20 write()

```
void age.log.Log.write (
    Level level,
    String message,
    Object ... params ) [private]
```

6.19.3 Member Data Documentation

6.19.3.1 format

```
String age.log.Log.format = null [private]
```

6.19.3.2 levels

```
Set<Level> age.log.Log.levels = null [private]
```

6.19.3.3 map

```
final Map<String, Log> age.log.Log.map = new HashMap<>() [static], [private]
```

6.19.3.4 trace


```
boolean age.log.Log.trace = false [private]
```

The documentation for this class was generated from the following file:

- <D:/GIT/repos/ODE/age/age/log/Log.java>

6.20 age.gui.Multiline Class Reference

Inheritance diagram for age.gui.Multiline:



Public Member Functions

- [Multiline](#) ()
- void [assign](#) (Tasks tasks)
- void [text](#) (String text)
- int [offset](#) ()
- void [up](#) ()
- void [down](#) ()
- void [offset](#) (int offset)
- int [count](#) ()
- int [page](#) ()
- int [lineHeight](#) ()
- CharSequence [line](#) (int idx)
- int[] [buffer](#) ()
- void [rescale](#) (float dy)
- void [update](#) ()

Public Member Functions inherited from [age.gui.Widget](#)

- [Widget](#) (Flag ... flags)
- float [x](#) ()
- float [y](#) ()
- float [width](#) ()
- float [height](#) ()
- Vector2f [position](#) ()
- Vector2f [dimension](#) ()
- [Dock](#) [dock](#) ()
- void [dock](#) (Dock dock)
- void [dock](#) (float top, float bottom, float left, float right)
- void [position](#) (Vector2f position)
- void [position](#) (float x, float y)
- void [positionAdd](#) (Vector2f position)
- void [positionAdd](#) (float x, float y)
- void [dimension](#) (Vector2f dimension)
- void [dimension](#) (float width, float height)
- void [dimensionAdd](#) (Vector2f dimension)
- void [dimensionAdd](#) (float width, float height)
- Set< [Flag](#) > [flags](#) ()
- void [flag](#) (Flag ... flags)
- void [clear](#) (Flag ... flags)
- boolean [match](#) (Flag ... flags)
- [Widget](#) [parent](#) ()

- List< [Widget](#) > [children](#) ()
- void [add](#) ([Widget](#) child)
- void [add](#) (int idx, [Widget](#) child)
- void [remove](#) ()
- void [toFront](#) ()
- String [text](#) ()
- String [image](#) ()
- void [image](#) (String image)
- String [command](#) ()
- void [command](#) (String command)

Private Member Functions

- void [create](#) ()

Private Attributes

- int [offset](#)
- int[] [buffer](#) = new int[1024]
- [VScroller](#) [scroller](#)

6.20.1 Constructor & Destructor Documentation

6.20.1.1 Multiline()

```
age.gui.Multiline.Multiline ( )
```

6.20.2 Member Function Documentation

6.20.2.1 assign()

```
void age.gui.Multiline.assign (
    Tasks tasks )
```

6.20.2.2 buffer()

```
int[] age.gui.Multiline.buffer ( )
```

6.20.2.3 count()

```
int age.gui.Multiline.count ( )
```

6.20.2.4 create()

```
void age.gui.Multiline.create ( ) [private]
```

6.20.2.5 down()

```
void age.gui.Multiline.down ( )
```

6.20.2.6 line()

```
CharSequence age.gui.Multiline.line (
    int idx )
```

6.20.2.7 lineHeight()

```
int age.gui.Multiline.lineHeight ( )
```

6.20.2.8 offset() [1/2]

```
int age.gui.Multiline.offset ( )
```

6.20.2.9 offset() [2/2]

```
void age.gui.Multiline.offset (
    int offset )
```

6.20.2.10 page()

```
int age.gui.Multiline.page ( )
```

6.20.2.11 rescale()

```
void age.gui.Multiline.rescale (
    float dy )
```

6.20.2.12 text()

```
void age.gui.Multiline.text (
    String text )
```

Reimplemented from [age.gui.Widget](#).

6.20.2.13 up()

```
void age.gui.Multiline.up ( )
```

6.20.2.14 update()

```
void age.gui.Multiline.update ( )
```

6.20.3 Member Data Documentation

6.20.3.1 buffer

```
int [ ] age.gui.Multiline.buffer = new int[1024] [private]
```

6.20.3.2 offset

```
int age.gui.Multiline.offset [private]
```

6.20.3.3 scroller

```
VScroller age.gui.Multiline.scroller [private]
```

The documentation for this class was generated from the following file:

- [D:/GIT/repos/ODE/age/age/gui/Multiline.java](#)

6.21 age.scene.Node Class Reference

Public Member Functions

- [Node parent](#) ()
- List< [Node](#) > [children](#) ()
- void [attach](#) ([Node](#) node)
- void [attach](#) (int idx, [Node](#) node)
- void [detach](#) ()

Private Attributes

- [Node parent](#)
- final List< [Node](#) > [children](#) = new ArrayList<>(5)
- final List< [Node](#) > [children_ro](#) = Collections.unmodifiableList([children](#))

6.21.1 Member Function Documentation

6.21.1.1 attach() [1/2]

```
void age.scene.Node.attach (
    int idx,
    Node node )
```

6.21.1.2 attach() [2/2]

```
void age.scene.Node.attach (
    Node node )
```

6.21.1.3 children()

```
List< Node > age.scene.Node.children ( )
```

6.21.1.4 detach()

```
void age.scene.Node.detach ( )
```

6.21.1.5 parent()

```
Node age.scene.Node.parent ( )
```

6.21.2 Member Data Documentation

6.21.2.1 children

```
final List<Node> age.scene.Node.children = new ArrayList<>(5) [private]
```

6.21.2.2 children_ro

```
final List<Node> age.scene.Node.children_ro = Collections.unmodifiableList(children) [private]
```

6.21.2.3 parent


```
Node age.scene.Node.parent [private]
```

The documentation for this class was generated from the following file:

- [D:/GIT/repos/ODE/age/age/scene/Node.java](#)

6.22 age.port.Port Interface Reference

Inheritance diagram for age.port.Port:



Public Member Functions

- void [assign](#) (Events events)
- String [title](#) ()
- void [title](#) (String title)
- boolean [maximized](#) ()
- void [maximized](#) (boolean maximized)
- boolean [fullscreen](#) ()
- void [fullscreen](#) (boolean fullscreen)
- boolean [visible](#) ()
- void [visible](#) (boolean visible)
- float [width](#) ()
- float [height](#) ()
- void [size](#) (float [width](#), float [height](#))
- void [add](#) ([Renderable](#) renderable)
- void [create](#) ()
- void [render](#) ()

6.22.1 Member Function Documentation

6.22.1.1 [add\(\)](#)

```
void age.port.Port.add (  
    Renderable renderable )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.2 [assign\(\)](#)

```
void age.port.Port.assign (  
    Events events )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.3 [create\(\)](#)

```
void age.port.Port.create ( )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.4 [fullscreen\(\)](#) [1/2]

```
boolean age.port.Port.fullscreen ( )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.5 fullscreen() [2/2]

```
void age.port.Port.fullscreen (
    boolean fullscreen )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.6 height()

```
float age.port.Port.height ( )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.7 maximized() [1/2]

```
boolean age.port.Port.maximized ( )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.8 maximized() [2/2]

```
void age.port.Port.maximized (
    boolean maximized )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.9 render()

```
void age.port.Port.render ( )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.10 size()

```
void age.port.Port.size (
    float width,
    float height )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.11 title() [1/2]

```
String age.port.Port.title ( )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.12 title() [2/2]

```
void age.port.Port.title (
    String title )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.13 visible() [1/2]

```
boolean age.port.Port.visible ( )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.14 visible() [2/2]

```
void age.port.Port.visible (
    boolean visible )
```

Implemented in [age.port.jogl.JOGLPort](#).

6.22.1.15 width()

```
float age.port.Port.width ( )
```

Implemented in [age.port.jogl.JOGLPort](#).

The documentation for this interface was generated from the following file:

- D:/GIT/repos/ODE/age/age/port/[Port.java](#)

6.23 age.port.Renderable Interface Reference

Public Member Functions

- void [render](#) ([Graphics](#) g)

6.23.1 Member Function Documentation

6.23.1.1 render()


```
void age.port.Renderable.render (
    Graphics g )
```

The documentation for this interface was generated from the following file:

- D:/GIT/repos/ODE/age/age/port/[Renderable.java](#)

6.24 age.gui.Rendering Class Reference

Inheritance diagram for age.gui.Rendering:



Public Member Functions

- [Rendering](#) ([Widgets](#) widgets)
- void [render](#) ([Graphics](#) g)

Private Member Functions

- void [render](#) ([Graphics](#) g, [Widget](#) widget)
- void [renderWidget](#) ([Graphics](#) g, [Widget](#) widget)
- boolean [renderBox](#) ([Graphics](#) g, [Widget](#) widget)
- boolean [renderFrame](#) ([Graphics](#) g, [Widget](#) widget)
- boolean [renderButton](#) ([Graphics](#) g, [Widget](#) widget)
- boolean [renderCanvas](#) ([Graphics](#) g, [Widget](#) widget)
- boolean [renderTitle](#) ([Graphics](#) g, [Widget](#) widget)
- boolean [renderHandle](#) ([Graphics](#) g, [Widget](#) widget)
- boolean [renderMultiline](#) ([Graphics](#) g, [Widget](#) widget)
- void [renderChildren](#) ([Graphics](#) g, List< [Widget](#) > children)

Private Attributes

- final [Widgets](#) widgets

6.24.1 Constructor & Destructor Documentation

6.24.1.1 Rendering()

```
age.gui.Rendering.Rendering (
    Widgets widgets )
```

6.24.2 Member Function Documentation

6.24.2.1 render() [1/2]

```
void age.gui.Rendering.render (
    Graphics g )
```

6.24.2.2 render() [2/2]

```
void age.gui.Rendering.render (
    Graphics g,
    Widget widget ) [private]
```

6.24.2.3 renderBox()

```
boolean age.gui.Rendering.renderBox (
    Graphics g,
    Widget widget ) [private]
```

6.24.2.4 renderButton()

```
boolean age.gui.Rendering.renderButton (
    Graphics g,
    Widget widget ) [private]
```

6.24.2.5 renderCanvas()

```
boolean age.gui.Rendering.renderCanvas (
    Graphics g,
    Widget widget ) [private]
```

6.24.2.6 renderChildren()

```
void age.gui.Rendering.renderChildren (
    Graphics g,
    List< Widget > children ) [private]
```

6.24.2.7 renderFrame()

```
boolean age.gui.Rendering.renderFrame (
    Graphics g,
    Widget widget ) [private]
```

6.24.2.8 renderHandle()

```
boolean age.gui.Rendering.renderHandle (
    Graphics g,
    Widget widget ) [private]
```

6.24.2.9 renderMultiline()

```
boolean age.gui.Rendering.renderMultiline (
    Graphics g,
    Widget widget ) [private]
```

6.24.2.10 renderTitle()

```
boolean age.gui.Rendering.renderTitle (
    Graphics g,
    Widget widget ) [private]
```

6.24.2.11 renderWidget()

```
void age.gui.Rendering.renderWidget (
    Graphics g,
    Widget widget ) [private]
```

6.24.3 Member Data Documentation

6.24.3.1 widgets

```
final Widgets age.gui.Rendering.widgets [private]
```

The documentation for this class was generated from the following file:

- [D:/GIT/repos/ODE/age/age/gui/Rendering.java](#)

6.25 age.scene.Scene Class Reference

Public Member Functions

- [Node root \(\)](#)

Private Attributes

- [Node root](#) = new [Node\(\)](#)

6.25.1 Member Function Documentation

6.25.1.1 root()

```
Node age.scene.Scene.root ( )
```

6.25.2 Member Data Documentation

6.25.2.1 root

```
Node age.scene.Scene.root = new Node() [private]
```

The documentation for this class was generated from the following file:

- [D:/GIT/repos/ODE/age/age/scene/Scene.java](#)

6.26 age.clock.Task Interface Reference

Public Member Functions

- void [run](#) (int count, long nanoperiod, float dT)

6.26.1 Member Function Documentation

6.26.1.1 run()

```
void age.clock.Task.run (
    int count,
    long nanoperiod,
    float dT )
```

The documentation for this interface was generated from the following file:

- D:/GIT/repos/ODE/age/age/clock/[Task.java](#)

6.27 age.task.Task Interface Reference

Public Member Functions

- void [perform](#) ()

6.27.1 Member Function Documentation

6.27.1.1 perform()

```
void age.task.Task.perform ( )
```

The documentation for this interface was generated from the following file:

- D:/GIT/repos/ODE/age/age/task/[Task.java](#)

6.28 age.task.Tasks Class Reference

Public Member Functions

- void [assign](#) (Port [port](#))
- void [assign](#) (Client [client](#))
- void [assign](#) (Events events)
- [Tasks](#) ()
- void [put](#) (String command)
- void [assign](#) (String command, [Task](#) task)
- void [update](#) ()

Private Member Functions

- void `handleEvent` (Event `e`)
- void `construct` ()
- void `perform` (String `command`)
- void `toggleFullscreen` ()
- void `shutdown` ()

Private Attributes

- final List< String > `inbox` = new ArrayList<>()
- final List< String > `outbox` = new ArrayList<>()
- final Map< String, Task > `tasks` = new HashMap<>()
- Port `port`
- Client `client`

6.28.1 Constructor & Destructor Documentation

6.28.1.1 Tasks()

```
age.task.Tasks.Tasks ( )
```

6.28.2 Member Function Documentation

6.28.2.1 assign() [1/4]

```
void age.task.Tasks.assign (
    Client client )
```

6.28.2.2 assign() [2/4]

```
void age.task.Tasks.assign (
    Events events )
```

6.28.2.3 assign() [3/4]

```
void age.task.Tasks.assign (
    Port port )
```

6.28.2.4 assign() [4/4]

```
void age.task.Tasks.assign (
    String command,
    Task task )
```

6.28.2.5 construct()

```
void age.task.Tasks.construct ( ) [private]
```

6.28.2.6 handleEvent()

```
void age.task.Tasks.handleEvent (
    Event e ) [private]
```

6.28.2.7 perform()

```
void age.task.Tasks.perform (
    String command ) [private]
```

6.28.2.8 put()

```
void age.task.Tasks.put (
    String command )
```

6.28.2.9 shutdown()

```
void age.task.Tasks.shutdown ( ) [private]
```

6.28.2.10 toggleFullscreen()

```
void age.task.Tasks.toggleFullscreen ( ) [private]
```

6.28.2.11 update()

```
void age.task.Tasks.update ( )
```

6.28.3 Member Data Documentation

6.28.3.1 client

```
Client age.task.Tasks.client [private]
```

6.28.3.2 inbox

```
final List<String> age.task.Tasks.inbox = new ArrayList<>() [private]
```


6.28.3.3 outbox

```
final List<String> age.task.Tasks.outbox = new ArrayList<>() [private]
```

6.28.3.4 port

```
Port age.task.Tasks.port [private]
```

6.28.3.5 tasks

```
final Map<String, Task> age.task.Tasks.tasks = new HashMap<>() [private]
```

The documentation for this class was generated from the following file:

- [D:/GIT/repos/ODE/age/age/task/Tasks.java](#)

6.29 age.event.Type Enum Reference

Public Attributes

- [NONE](#)
- [KEY_PRESSED](#)
- [KEY_RELEASED](#)
- [KEY_TYPED](#)
- [POINTER_ENTERED](#)
- [POINTER_EXITED](#)
- [POINTER_PRESSED](#)
- [POINTER_RELEASED](#)
- [POINTER_CLICKED](#)
- [POINTER_MOVED](#)
- [SURFACE_RESIZED](#)
- [SURFACE_CLOSE_REQUEST](#)
- [TASK_COMMAND](#)

6.29.1 Member Data Documentation

6.29.1.1 KEY_PRESSED

```
age.event.Type.KEY_PRESSED
```

6.29.1.2 KEY_RELEASED

```
age.event.Type.KEY_RELEASED
```

6.29.1.3 KEY_TYPED

`age.event.Type.KEY_TYPED`

6.29.1.4 NONE

`age.event.Type.NONE`

6.29.1.5 POINTER_CLICKED

`age.event.Type.POINTER_CLICKED`

6.29.1.6 POINTER_ENTERED

`age.event.Type.POINTER_ENTERED`

6.29.1.7 POINTER_EXITED

`age.event.Type.POINTER_EXITED`

6.29.1.8 POINTER_MOVED

`age.event.Type.POINTER_MOVED`

6.29.1.9 POINTER_PRESSED

`age.event.Type.POINTER_PRESSED`

6.29.1.10 POINTER_RELEASED

`age.event.Type.POINTER_RELEASED`

6.29.1.11 SURFACE_CLOSE_REQUEST

`age.event.Type.SURFACE_CLOSE_REQUEST`

6.29.1.12 SURFACE_RESIZED

`age.event.Type.SURFACE_RESIZED`

6.29.1.13 TASK_COMMAND

`age.event.Type.TASK_COMMAND`

The documentation for this enum was generated from the following file:

- [D:/GIT/repos/ODE/age/age/event/Type.java](#)

6.30 age.Util Class Reference

The AGE Utility class.

Static Public Member Functions

- static final String [readTextFile](#) (String path)
Static utility method to load and return text read from a file located by path.
- static final< C > C [readJsonFile](#) (String path, Class< C > cls)

Static Private Attributes

- static final ObjectMapper [objectMapper](#) = new ObjectMapper()

6.30.1 Detailed Description

The AGE Utility class.

6.30.2 Member Function Documentation

6.30.2.1 readJsonFile()

```
static final< C > C age.Util.readJsonFile (
    String path,
    Class< C > cls ) [static]
```

6.30.2.2 readTextFile()

```
static final String age.Util.readTextFile (
    String path ) [static]
```

Static utility method to load and return text read from a file located by path.

Parameters

<i>path</i>	The file path String of the file to be read
-------------	---

Returns

The file contents as a text String

6.30.3 Member Data Documentation**6.30.3.1 objectMapper**


```
final ObjectMapper age.Util.objectMapper = new ObjectMapper() [static], [private]
```

The documentation for this class was generated from the following file:

- <D:/GIT/repos/ODE/age/age/Util.java>

6.31 age.gui.VScroller Class Reference

Inheritance diagram for age.gui.VScroller:

**Public Member Functions**

- [VScroller](#) ()
- void [assign](#) (Tasks tasks, Task taskUp, Task taskDn)
- void [set](#) (int [size](#), int [page](#), int [mark](#))
- void [value](#) (int [mark](#))
- [Widget](#) [handle](#) ()

Public Member Functions inherited from [age.gui.Widget](#)

- [Widget](#) (Flag ... [flags](#))
- float [x](#) ()
- float [y](#) ()
- float [width](#) ()
- float [height](#) ()
- Vector2f [position](#) ()
- Vector2f [dimension](#) ()
- [Dock](#) [dock](#) ()
- void [dock](#) ([Dock](#) dock)
- void [dock](#) (float top, float bottom, float left, float right)
- void [position](#) (Vector2f position)
- void [position](#) (float [x](#), float [y](#))
- void [positionAdd](#) (Vector2f position)
- void [positionAdd](#) (float [x](#), float [y](#))
- void [dimension](#) (Vector2f dimension)

- void [dimension](#) (float [width](#), float [height](#))
- void [dimensionAdd](#) (Vector2f [dimension](#))
- void [dimensionAdd](#) (float [width](#), float [height](#))
- Set< [Flag](#) > [flags](#) ()
- void [flag](#) ([Flag](#) ... [flags](#))
- void [clear](#) ([Flag](#) ... [flags](#))
- boolean [match](#) ([Flag](#) ... [flags](#))
- [Widget](#) [parent](#) ()
- List< [Widget](#) > [children](#) ()
- void [add](#) ([Widget](#) child)
- void [add](#) (int idx, [Widget](#) child)
- void [remove](#) ()
- void [toFront](#) ()
- String [text](#) ()
- void [text](#) (String text)
- String [image](#) ()
- void [image](#) (String image)
- String [command](#) ()
- void [command](#) (String command)

Private Member Functions

- void [create](#) ()

Private Attributes

- [Widget](#) [btnUp](#)
- [Widget](#) [bar](#)
- [Widget](#) [handle](#)
- [Widget](#) [btnDn](#)
- UUID [uuid](#) = UUID.randomUUID()
- int [size](#)
- int [page](#)
- int [mark](#)

6.31.1 Constructor & Destructor Documentation

6.31.1.1 VScroller()

```
age.gui.VScroller.VScroller ( )
```

6.31.2 Member Function Documentation

6.31.2.1 assign()

```
void age.gui.VScroller.assign (
    Tasks tasks,
    Task taskUp,
    Task taskDn )
```

6.31.2.2 create()

```
void age.gui.VScroller.create ( ) [private]
```

6.31.2.3 handle()

```
Widget age.gui.VScroller.handle ( )
```

6.31.2.4 set()

```
void age.gui.VScroller.set (
    int size,
    int page,
    int mark )
```

6.31.2.5 value()

```
void age.gui.VScroller.value (
    int mark )
```

6.31.3 Member Data Documentation

6.31.3.1 bar

```
Widget age.gui.VScroller.bar [private]
```

6.31.3.2 btnDn

```
Widget age.gui.VScroller.btnDn [private]
```

6.31.3.3 btnUp

```
Widget age.gui.VScroller.btnUp [private]
```

6.31.3.4 handle

```
Widget age.gui.VScroller.handle [private]
```

6.31.3.5 mark

```
int age.gui.VScroller.mark [private]
```

6.31.3.6 page

```
int age.gui.VScroller.page [private]
```

6.31.3.7 size

```
int age.gui.VScroller.size [private]
```

6.31.3.8 uuid


```
UUID age.gui.VScroller.uuid = UUID.randomUUID() [private]
```

The documentation for this class was generated from the following file:

- [D:/GIT/repos/ODE/age/age/gui/VScroller.java](#)

6.32 age.gui.Widget Class Reference

Inheritance diagram for age.gui.Widget:



Public Member Functions

- [Widget \(Flag ... flags\)](#)
- float [x](#) ()
- float [y](#) ()
- float [width](#) ()
- float [height](#) ()
- Vector2f [position](#) ()
- Vector2f [dimension](#) ()
- [Dock dock](#) ()
- void [dock](#) ([Dock dock](#))
- void [dock](#) (float top, float bottom, float left, float right)
- void [position](#) (Vector2f position)
- void [position](#) (float [x](#), float [y](#))
- void [positionAdd](#) (Vector2f [position](#))
- void [positionAdd](#) (float [x](#), float [y](#))
- void [dimension](#) (Vector2f dimension)
- void [dimension](#) (float [width](#), float [height](#))
- void [dimensionAdd](#) (Vector2f [dimension](#))
- void [dimensionAdd](#) (float [width](#), float [height](#))
- Set< [Flag](#) > [flags](#) ()
- void [flag](#) (Flag ... flags)

- void `clear` (`Flag ... flags`)
- boolean `match` (`Flag ... flags`)
- `Widget` `parent` ()
- List< `Widget` > `children` ()
- void `add` (`Widget` child)
- void `add` (int idx, `Widget` child)
- void `remove` ()
- void `toFront` ()
- String `text` ()
- void `text` (String text)
- String `image` ()
- void `image` (String image)
- String `command` ()
- void `command` (String command)

Private Member Functions

- void `resized` (float dx, float dy)
- void `parentResized` (float dx, float dy)

Private Attributes

- final Set< `Flag` > `flags` = EnumSet.noneOf(`Flag.class`)
- final Set< `Flag` > `flags_ro` = Collections.unmodifiableSet(`flags`)
- final Vector2f `position` = new Vector2f()
- final Vector2f `dimension` = new Vector2f()
- final `Dock` `dock` = new `Dock`()
- `Widget` `parent` = null
- final List< `Widget` > `children` = new ArrayList<>(10)
- final List< `Widget` > `children_ro` = Collections.unmodifiableList(`children`)
- String `text` = null
- String `image` = null
- String `command` = null

6.32.1 Constructor & Destructor Documentation

6.32.1.1 `Widget()`

```
age.gui.Widget.Widget (
    Flag ... flags )
```

6.32.2 Member Function Documentation

6.32.2.1 `add()` [1/2]

```
void age.gui.Widget.add (
    int idx,
    Widget child )
```


6.32.2.2 add() [2/2]

```
void age.gui.Widget.add (
    Widget child )
```

6.32.2.3 children()

```
List< Widget > age.gui.Widget.children ( )
```

6.32.2.4 clear()

```
void age.gui.Widget.clear (
    Flag ... flags )
```

6.32.2.5 command() [1/2]

```
String age.gui.Widget.command ( )
```

6.32.2.6 command() [2/2]

```
void age.gui.Widget.command (
    String command )
```

6.32.2.7 dimension() [1/3]

```
Vector2f age.gui.Widget.dimension ( )
```

6.32.2.8 dimension() [2/3]

```
void age.gui.Widget.dimension (
    float width,
    float height )
```

6.32.2.9 dimension() [3/3]

```
void age.gui.Widget.dimension (
    Vector2f dimension )
```

6.32.2.10 dimensionAdd() [1/2]

```
void age.gui.Widget.dimensionAdd (
    float width,
    float height )
```

6.32.2.11 dimensionAdd() [2/2]

```
void age.gui.Widget.dimensionAdd (
    Vector2f dimension )
```

6.32.2.12 dock() [1/3]

```
Dock age.gui.Widget.dock ( )
```

6.32.2.13 dock() [2/3]

```
void age.gui.Widget.dock (
    Dock dock )
```

6.32.2.14 dock() [3/3]

```
void age.gui.Widget.dock (
    float top,
    float bottom,
    float left,
    float right )
```

6.32.2.15 flag()

```
void age.gui.Widget.flag (
    Flag ... flags )
```

6.32.2.16 flags()

```
Set< Flag > age.gui.Widget.flags ( )
```

6.32.2.17 height()

```
float age.gui.Widget.height ( )
```

6.32.2.18 image() [1/2]

```
String age.gui.Widget.image ( )
```

6.32.2.19 image() [2/2]

```
void age.gui.Widget.image (
    String image )
```

6.32.2.20 match()

```
boolean age.gui.Widget.match (
    Flag ... flags )
```

6.32.2.21 parent()

```
Widget age.gui.Widget.parent ( )
```

6.32.2.22 parentResized()

```
void age.gui.Widget.parentResized (
    float dx,
    float dy ) [private]
```

6.32.2.23 position() [1/3]

```
Vector2f age.gui.Widget.position ( )
```

6.32.2.24 position() [2/3]

```
void age.gui.Widget.position (
    float x,
    float y )
```

6.32.2.25 position() [3/3]

```
void age.gui.Widget.position (
    Vector2f position )
```

6.32.2.26 positionAdd() [1/2]

```
void age.gui.Widget.positionAdd (
    float x,
    float y )
```

6.32.2.27 positionAdd() [2/2]

```
void age.gui.Widget.positionAdd (
    Vector2f position )
```

6.32.2.28 remove()

```
void age.gui.Widget.remove ( )
```

6.32.2.29 resized()

```
void age.gui.Widget.resized (
    float dx,
    float dy ) [private]
```

6.32.2.30 text() [1/2]

```
String age.gui.Widget.text ( )
```

6.32.2.31 text() [2/2]

```
void age.gui.Widget.text (
    String text )
```

Reimplemented in [age.gui.Multiline](#).

6.32.2.32 toFront()

```
void age.gui.Widget.toFront ( )
```

6.32.2.33 width()

```
float age.gui.Widget.width ( )
```

6.32.2.34 x()

```
float age.gui.Widget.x ( )
```

6.32.2.35 y()

```
float age.gui.Widget.y ( )
```

6.32.3 Member Data Documentation

6.32.3.1 children

```
final List<Widget> age.gui.Widget.children = new ArrayList<>(10) [private]
```

6.32.3.2 children_ro

```
final List<Widget> age.gui.Widget.children_ro = Collections.unmodifiableList(children) [private]
```

6.32.3.3 command

```
String age.gui.Widget.command = null [private]
```

6.32.3.4 dimension

```
final Vector2f age.gui.Widget.dimension = new Vector2f() [private]
```

6.32.3.5 dock

```
final Dock age.gui.Widget.dock = new Dock() [private]
```

6.32.3.6 flags

```
final Set<Flag> age.gui.Widget.flags = EnumSet.noneOf(Flag.class) [private]
```

6.32.3.7 flags_ro

```
final Set<Flag> age.gui.Widget.flags_ro = Collections.unmodifiableSet(flags) [private]
```

6.32.3.8 image

```
String age.gui.Widget.image = null [private]
```

6.32.3.9 parent

```
Widget age.gui.Widget.parent = null [private]
```

6.32.3.10 position

```
final Vector2f age.gui.Widget.position = new Vector2f() [private]
```

6.32.3.11 text

```
String age.gui.Widget.text = null [private]
```

The documentation for this class was generated from the following file:

- [D:/GIT/repos/ODE/age/age/gui/Widget.java](#)

6.33 age.gui.Widgets Class Reference

Public Member Functions

- [Widgets](#) ()
- void [assign](#) (Port port)
- void [assign](#) (Events events)
- [Widget root](#) ()

Private Attributes

- [Widget root](#) = new [Widget](#)()
- [Handling handling](#) = new [Handling](#)(this)
- [Rendering rendering](#) = new [Rendering](#)(this)

6.33.1 Constructor & Destructor Documentation

6.33.1.1 Widgets()

```
age.gui.Widgets.Widgets ( )
```

6.33.2 Member Function Documentation

6.33.2.1 assign() [1/2]

```
void age.gui.Widgets.assign (
    Events events )
```

6.33.2.2 assign() [2/2]

```
void age.gui.Widgets.assign (
    Port port )
```

6.33.2.3 root()

```
Widget age.gui.Widgets.root ( )
```

6.33.3 Member Data Documentation

6.33.3.1 handling

```
Handling age.gui.Widgets.handling = new Handling(this) [private]
```

6.33.3.2 rendering

```
Rendering age.gui.Widgets.rendering = new Rendering(this) [private]
```

6.33.3.3 root


```
Widget age.gui.Widgets.root = new Widget() [private]
```

The documentation for this class was generated from the following file:

- [D:/GIT/repos/ODE/age/age/gui/Widgets.java](#)

6.34 age.gui.Window Class Reference

Inheritance diagram for age.gui.Window:



Public Member Functions

- [Window](#) (Flag ... flags)
- String [title](#) ()
- void [title](#) (String title)
- [Widget](#) [getPage](#) ()

Public Member Functions inherited from [age.gui.Widget](#)

- [Widget](#) (Flag ... flags)
- float [x](#) ()
- float [y](#) ()
- float [width](#) ()
- float [height](#) ()
- Vector2f [position](#) ()
- Vector2f [dimension](#) ()
- [Dock](#) [dock](#) ()
- void [dock](#) ([Dock](#) dock)
- void [dock](#) (float top, float bottom, float left, float right)
- void [position](#) (Vector2f position)
- void [position](#) (float x, float y)
- void [positionAdd](#) (Vector2f position)
- void [positionAdd](#) (float x, float y)
- void [dimension](#) (Vector2f dimension)
- void [dimension](#) (float width, float height)
- void [dimensionAdd](#) (Vector2f dimension)

- void `dimensionAdd` (float `width`, float `height`)
- Set< `Flag` > `flags` ()
- void `flag` (`Flag` ... `flags`)
- void `clear` (`Flag` ... `flags`)
- boolean `match` (`Flag` ... `flags`)
- `Widget` `parent` ()
- List< `Widget` > `children` ()
- void `add` (`Widget` child)
- void `add` (int idx, `Widget` child)
- void `remove` ()
- void `toFront` ()
- String `text` ()
- void `text` (String text)
- String `image` ()
- void `image` (String image)
- String `command` ()
- void `command` (String command)

Private Member Functions

- void `construct` ()

Private Attributes

- `Widget` `title` = new `Widget`()
- `Widget` `size` = new `Widget`()
- `Widget` `close` = new `Widget`()
- `Widget` `page` = new `Widget`()

6.34.1 Constructor & Destructor Documentation

6.34.1.1 Window()

```
age.gui.Window.Window (
    Flag ... flags )
```

6.34.2 Member Function Documentation

6.34.2.1 construct()

```
void age.gui.Window.construct ( ) [private]
```

6.34.2.2 getPage()

```
Widget age.gui.Window.getPage ( )
```


6.34.2.3 title() [1/2]

```
String age.gui.Window.title ( )
```

6.34.2.4 title() [2/2]

```
void age.gui.Window.title (
    String title )
```

6.34.3 Member Data Documentation

6.34.3.1 close

```
Widget age.gui.Window.close = new Widget() [private]
```

6.34.3.2 page

```
Widget age.gui.Window.page = new Widget() [private]
```

6.34.3.3 size

```
Widget age.gui.Window.size = new Widget() [private]
```

6.34.3.4 title

```
Widget age.gui.Window.title = new Widget() [private]
```

The documentation for this class was generated from the following file:

- [D:/GIT/repos/ODE/age/age/gui/Window.java](#)

Chapter 7

File Documentation

7.1 D:/GIT/repos/ODE/age/age/AGEException.java File Reference

Classes

- class [age.AGEException](#)
Root Exception for AGE.

Packages

- package [age](#)

7.2 D:/GIT/repos/ODE/age/age/Client.java File Reference

```
import age.port.Port;
```

Classes

- class [age.Client](#)
The AGE Application Client main class.

Packages

- package [age](#)

7.3 D:/GIT/repos/ODE/age/age/clock/Alarm.java File Reference

Classes

- class [age.clock.Alarm](#)

Packages

- package [age.clock](#)

7.4 D:/GIT/repos/ODE/age/age/clock/Clock.java File Reference

```
import java.util.ArrayList;
```

Classes

- class [age.clock.Clock](#)

Packages

- package [age.clock](#)

7.5 D:/GIT/repos/ODE/age/age/clock/Task.java File Reference

Classes

- interface [age.clock.Task](#)

Packages

- package [age.clock](#)

7.6 D:/GIT/repos/ODE/age/age/task/Task.java File Reference

Classes

- interface [age.task.Task](#)

Packages

- package [age.task](#)

7.7 D:/GIT/repos/ODE/age/age/event/Button.java File Reference

Classes

- enum [age.event.Button](#)

Packages

- package [age.event](#)

7.8 D:/GIT/repos/ODE/age/age/event/Event.java File Reference

```
import javax.vecmath.Vector2f;
```

Classes

- class [age.event.Event](#)

Packages

- package [age.event](#)

7.9 D:/GIT/repos/ODE/age/age/event/Events.java File Reference

```
import java.util.ArrayList;
```

Classes

- class [age.event.Events](#)

Packages

- package [age.event](#)

7.10 D:/GIT/repos/ODE/age/age/event/Handler.java File Reference

Classes

- interface [age.event.Handler](#)

Packages

- package [age.event](#)

7.11 D:/GIT/repos/ODE/age/age/event/Key.java File Reference

Classes

- enum [age.event.Key](#)

Packages

- package [age.event](#)

7.12 D:/GIT/repos/ODE/age/age/event/Type.java File Reference

Classes

- enum [age.event.Type](#)

Packages

- package [age.event](#)

7.13 D:/GIT/repos/ODE/age/age/gui/Dock.java File Reference

Classes

- class [age.gui.Dock](#)

Packages

- package [age.gui](#)

7.14 D:/GIT/repos/ODE/age/age/gui/Flag.java File Reference

Classes

- enum [age.gui.Flag](#)

Packages

- package [age.gui](#)

7.15 D:/GIT/repos/ODE/age/age/gui/Handling.java File Reference

```
import java.util.ArrayList;
```

Classes

- class [age.gui.Handling](#)

Packages

- package [age.gui](#)

7.16 D:/GIT/repos/ODE/age/age/gui/Multiline.java File Reference

```
import age.task.Tasks;
```

Classes

- class [age.gui.Multiline](#)

Packages

- package [age.gui](#)

7.17 D:/GIT/repos/ODE/age/age/gui/Rendering.java File Reference

```
import java.util.List;
```

Classes

- class [age.gui.Rendering](#)

Packages

- package [age.gui](#)

7.18 D:/GIT/repos/ODE/age/age/gui/VScroller.java File Reference

```
import java.util.UUID;
```

Classes

- class [age.gui.VScroller](#)

Packages

- package [age.gui](#)

7.19 D:/GIT/repos/ODE/age/age/gui/Widget.java File Reference

```
import java.util.ArrayList;
```

Classes

- class [age.gui.Widget](#)

Packages

- package [age.gui](#)

7.20 D:/GIT/repos/ODE/age/age/gui/Widgets.java File Reference

```
import age.event.Events;
```

Classes

- class [age.gui.Widgets](#)

Packages

- package [age.gui](#)

7.21 D:/GIT/repos/ODE/age/age/gui/Window.java File Reference

Classes

- class [age.gui.Window](#)

Packages

- package [age.gui](#)

7.22 D:/GIT/repos/ODE/age/age/log/Level.java File Reference

Classes

- enum [age.log.Level](#)

Packages

- package [age.log](#)

7.23 D:/GIT/repos/ODE/age/age/log/Log.java File Reference

```
import java.io.File;
```

Classes

- class [age.log.Log](#)

Packages

- package [age.log](#)

7.24 D:/GIT/repos/ODE/age/age/port/Graphics.java File Reference

```
import javax.vecmath.Color4f;
```

Classes

- interface [age.port.Graphics](#)

Packages

- package [age.port](#)

7.25 D:/GIT/repos/ODE/age/age/port/jogl/JOGLEventListener.java File Reference

```
import com.jogamp.newt.Window;
```

Classes

- class [age.port.jogl.JOGLEventListener](#)

Packages

- package [age.port.jogl](#)

7.26 D:/GIT/repos/ODE/age/age/port/jogl/JOGLGraphics.java File Reference

```
import com.jogamp.opengl.GL2;
```

Classes

- class [age.port.jogl.JOGLGraphics](#)

Packages

- package [age.port.jogl](#)

7.27 D:/GIT/repos/ODE/age/age/port/jogl/JOGLPort.java File Reference

```
import java.util.ArrayList;
```

Classes

- class [age.port.jogl.JOGLPort](#)

Packages

- package [age.port.jogl](#)

7.28 D:/GIT/repos/ODE/age/age/port/jogl/JOGLRenderListener.java File Reference

```
import com.jogamp.opengl.GLAutoDrawable;
```

Classes

- class [age.port.jogl.JOGLRenderListener](#)

Packages

- package [age.port.jogl](#)

7.29 D:/GIT/repos/ODE/age/age/port/Port.java File Reference

```
import age.event.Events;
```

Classes

- interface [age.port.Port](#)

Packages

- package [age.port](#)

7.30 D:/GIT/repos/ODE/age/age/port/Renderable.java File Reference

Classes

- interface [age.port.Renderable](#)

Packages

- package [age.port](#)

7.31 D:/GIT/repos/ODE/age/age/scene/Node.java File Reference

```
import java.util.ArrayList;
```

Classes

- class [age.scene.Node](#)

Packages

- package [age.scene](#)

7.32 D:/GIT/repos/ODE/age/age/scene/Scene.java File Reference

Classes

- class [age.scene.Scene](#)

Packages

- package [age.scene](#)

7.33 D:/GIT/repos/ODE/age/age/task/Tasks.java File Reference

```
import java.util.ArrayList;
```

Classes

- class [age.task.Tasks](#)

Packages

- package [age.task](#)

7.34 D:/GIT/repos/ODE/age/age/Util.java File Reference

```
import java.io.BufferedReader;
```

Classes

- class [age.Util](#)
The AGE Utility class.

Packages

- package [age](#)

Index

- [_0](#)
 - [age.event.Key](#), [56](#)
 - [_1](#)
 - [age.event.Key](#), [56](#)
 - [_2](#)
 - [age.event.Key](#), [56](#)
 - [_3](#)
 - [age.event.Key](#), [57](#)
 - [_4](#)
 - [age.event.Key](#), [57](#)
 - [_5](#)
 - [age.event.Key](#), [57](#)
 - [_6](#)
 - [age.event.Key](#), [57](#)
 - [_7](#)
 - [age.event.Key](#), [57](#)
 - [_8](#)
 - [age.event.Key](#), [57](#)
 - [_9](#)
 - [age.event.Key](#), [57](#)
- [A](#)
 - [age.event.Key](#), [57](#)
- [action](#)
 - [age.gui.Handling](#), [41](#)
- [ADD](#)
 - [age.event.Key](#), [57](#)
- [add](#)
 - [age.clock.Clock](#), [22](#)
 - [age.gui.Widget](#), [92](#)
 - [age.port.jogl.JOGLPort](#), [50](#)
 - [age.port.Port](#), [76](#)
- [addFPS](#)
 - [age.clock.Clock](#), [22](#)
- [age](#), [9](#)
- [age.AGEEException](#), [13](#)
 - [AGEEException](#), [14](#)
 - [serialVersionUID](#), [15](#)
- [age.Client](#), [18](#)
 - [clock](#), [21](#)
 - [events](#), [21](#)
 - [loop](#), [19](#)
 - [main](#), [19](#)
 - [port](#), [21](#)
 - [render](#), [19](#)
 - [run](#), [19](#)
 - [running](#), [21](#)
 - [setup](#), [19](#)
 - [setupGUI](#), [20](#)
 - [shutdown](#), [20](#)
 - [sysMenuFrame](#), [21](#)
 - [tasks](#), [21](#)
 - [toggleDesktop](#), [20](#)
 - [toggleSysmenu](#), [20](#)
 - [update](#), [20](#)
 - [widgets](#), [21](#)
 - [windowFrame](#), [21](#)
- [age.clock](#), [9](#)
- [age.clock.Alarm](#), [15](#)
 - [Alarm](#), [15](#)
 - [init](#), [15](#)
 - [mark](#), [16](#)
 - [nanoperiod](#), [16](#)
 - [task](#), [16](#)
 - [trigger](#), [15](#)
 - [update](#), [16](#)
- [age.clock.Clock](#), [22](#)
 - [add](#), [22](#)
 - [addFPS](#), [22](#)
 - [alarms](#), [23](#)
 - [init](#), [22](#)
 - [update](#), [22](#)
- [age.clock.Task](#), [82](#)
 - [run](#), [82](#)
- [age.event](#), [10](#)
- [age.event.Button](#), [16](#)
 - [BTN1](#), [17](#)
 - [BTN2](#), [17](#)
 - [BTN3](#), [17](#)
 - [BTN4](#), [17](#)
 - [BTN5](#), [17](#)
 - [BTN6](#), [17](#)
 - [BTN7](#), [17](#)
 - [BTN8](#), [17](#)
 - [NONE](#), [17](#)
- [age.event.Event](#), [25](#)
 - [button](#), [26](#), [29](#)
 - [character](#), [26](#), [29](#)
 - [clear](#), [26](#)
 - [command](#), [26](#), [29](#)
 - [count](#), [26](#), [29](#)
 - [dimension](#), [26](#), [29](#)
 - [Event](#), [26](#)
 - [height](#), [26](#)
 - [key](#), [26](#), [29](#)
 - [keyEvent](#), [26](#)
 - [keyPressed](#), [27](#)
 - [keyReleased](#), [27](#)
 - [keyTyped](#), [27](#)

- pointerClicked, [27](#)
- pointerEntered, [27](#)
- pointerEvent, [27](#)
- pointerExited, [27](#)
- pointerMoved, [28](#)
- pointerPressed, [28](#)
- pointerReleased, [28](#)
- position, [28](#), [29](#)
- surfaceCloseRequest, [28](#)
- surfaceResized, [28](#)
- taskCommand, [28](#)
- type, [28](#), [30](#)
- width, [29](#)
- x, [29](#)
- y, [29](#)
- age.event.Events, [30](#)
 - alloc, [31](#)
 - assign, [31](#)
 - cache, [33](#)
 - free, [31](#)
 - handle, [31](#)
 - handlers, [33](#)
 - inbox, [33](#)
 - outbox, [33](#)
 - post, [31](#)
 - postKeyPressed, [31](#)
 - postKeyReleased, [31](#)
 - postKeyTyped, [31](#)
 - postPointerClicked, [31](#)
 - postPointerEntered, [32](#)
 - postPointerExited, [32](#)
 - postPointerMoved, [32](#)
 - postPointerPressed, [32](#)
 - postPointerReleased, [32](#)
 - postSurfaceCloseRequest, [32](#)
 - postSurfaceResized, [32](#)
 - postTaskCommand, [33](#)
 - update, [33](#)
- age.event.Handler, [38](#)
 - handle, [38](#)
- age.event.Key, [55](#)
 - _0, [56](#)
 - _1, [56](#)
 - _2, [56](#)
 - _3, [57](#)
 - _4, [57](#)
 - _5, [57](#)
 - _6, [57](#)
 - _7, [57](#)
 - _8, [57](#)
 - _9, [57](#)
 - A, [57](#)
 - ADD, [57](#)
 - ALT, [57](#)
 - B, [58](#)
 - BACK_SPACE, [58](#)
 - C, [58](#)
 - CAPS_LOCK, [58](#)
 - CONTROL, [58](#)
 - D, [58](#)
 - DECIMAL, [58](#)
 - DELETE, [58](#)
 - DIVIDE, [58](#)
 - DOWN, [58](#)
 - E, [59](#)
 - END, [59](#)
 - ENTER, [59](#)
 - ESCAPE, [59](#)
 - F, [59](#)
 - F1, [59](#)
 - F10, [59](#)
 - F11, [59](#)
 - F12, [59](#)
 - F2, [59](#)
 - F3, [60](#)
 - F4, [60](#)
 - F5, [60](#)
 - F6, [60](#)
 - F7, [60](#)
 - F8, [60](#)
 - F9, [60](#)
 - G, [60](#)
 - H, [60](#)
 - I, [60](#)
 - INSERT, [61](#)
 - J, [61](#)
 - K, [61](#)
 - L, [61](#)
 - LEFT, [61](#)
 - M, [61](#)
 - MENU, [61](#)
 - MINUS, [61](#)
 - MULTIPLY, [61](#)
 - N, [61](#)
 - NONE, [62](#)
 - NP_0, [62](#)
 - NP_1, [62](#)
 - NP_2, [62](#)
 - NP_3, [62](#)
 - NP_4, [62](#)
 - NP_5, [62](#)
 - NP_6, [62](#)
 - NP_7, [62](#)
 - NP_8, [62](#)
 - NP_9, [63](#)
 - NUM_LOCK, [63](#)
 - O, [63](#)
 - P, [63](#)
 - PAGE_DOWN, [63](#)
 - PAGE_UP, [63](#)
 - PAUSE, [63](#)
 - PLUS, [63](#)
 - POS1, [63](#)
 - PRINT_SCREEN, [63](#)
 - Q, [64](#)
 - R, [64](#)

- RIGHT, 64
- S, 64
- SCROLL_LOCK, 64
- SHIFT, 64
- SPACE, 64
- SUBTRACT, 64
- SYSTEM, 64
- T, 64
- TAB, 65
- U, 65
- UP, 65
- V, 65
- W, 65
- X, 65
- Y, 65
- Z, 65
- age.event.Type, 85
 - KEY_PRESSED, 85
 - KEY_RELEASED, 85
 - KEY_TYPED, 85
 - NONE, 86
 - POINTER_CLICKED, 86
 - POINTER_ENTERED, 86
 - POINTER_EXITED, 86
 - POINTER_MOVED, 86
 - POINTER_PRESSED, 86
 - POINTER_RELEASED, 86
 - SURFACE_CLOSE_REQUEST, 86
 - SURFACE_RESIZED, 86
 - TASK_COMMAND, 86
- age.gui, 10
- age.gui.Dock, 23
 - bottom, 23, 24
 - left, 23, 24
 - right, 23, 24
 - set, 23
 - top, 24
- age.gui.Flag, 34
 - BOX, 34
 - BUTTON, 34
 - CANVAS, 34
 - FRAME, 34
 - HANDLE, 34
 - HIDDEN, 34
 - HOVERED, 34
 - MULTILINE, 34
 - TITLE, 35
- age.gui.Handling, 38
 - action, 41
 - assign, 39
 - buttonClickAction, 39
 - dragged, 41
 - events, 41
 - handleKeyboard, 39
 - handlePointer, 39
 - handleSurface, 40
 - Handling, 39
 - hovered, 40, 41
 - pressedFrameToFront, 40
 - ref, 41
 - startFrameDragAction, 40
 - startFrameSizeAction, 40
 - startScrollHandleAction, 40
 - stopDragAction, 40
 - tmp, 41
 - updateActionState, 40
 - updateDragAction, 41
 - widgets, 41
- age.gui.Multiline, 71
 - assign, 72
 - buffer, 72, 74
 - count, 72
 - create, 72
 - down, 72
 - line, 73
 - lineHeight, 73
 - Multiline, 72
 - offset, 73, 74
 - page, 73
 - rescale, 73
 - scroller, 74
 - text, 73
 - up, 73
 - update, 73
- age.gui.Rendering, 79
 - render, 79
 - renderBox, 80
 - renderButton, 80
 - renderCanvas, 80
 - renderChildren, 80
 - renderFrame, 80
 - renderHandle, 80
 - Rendering, 79
 - renderMultiline, 80
 - renderTitle, 80
 - renderWidget, 81
 - widgets, 81
- age.gui.VScroller, 88
 - assign, 89
 - bar, 90
 - btnDn, 90
 - btnUp, 90
 - create, 89
 - handle, 90
 - mark, 90
 - page, 90
 - set, 90
 - size, 91
 - uuid, 91
 - value, 90
 - VScroller, 89
- age.gui.Widget, 91
 - add, 92
 - children, 93, 96
 - children_ro, 96
 - clear, 93

- command, [93](#), [96](#)
- dimension, [93](#), [97](#)
- dimensionAdd, [93](#)
- dock, [94](#), [97](#)
- flag, [94](#)
- flags, [94](#), [97](#)
- flags_ro, [97](#)
- height, [94](#)
- image, [94](#), [97](#)
- match, [94](#)
- parent, [95](#), [97](#)
- parentResized, [95](#)
- position, [95](#), [97](#)
- positionAdd, [95](#)
- remove, [95](#)
- resized, [95](#)
- text, [96](#), [97](#)
- toFront, [96](#)
- Widget, [92](#)
- width, [96](#)
- x, [96](#)
- y, [96](#)
- age.gui.Widgets, [98](#)
 - assign, [98](#)
 - handling, [98](#)
 - rendering, [98](#)
 - root, [98](#), [99](#)
 - Widgets, [98](#)
- age.gui.Window, [99](#)
 - close, [101](#)
 - construct, [100](#)
 - getPage, [100](#)
 - page, [101](#)
 - size, [101](#)
 - title, [100](#), [101](#)
 - Window, [100](#)
- age.log, [10](#)
- age.log.Level, [66](#)
 - DEBUG, [66](#)
 - ERROR, [66](#)
 - INFO, [66](#)
 - WARNING, [66](#)
- age.log.Log, [66](#)
 - clear, [67](#)
 - configure, [67](#)
 - debug, [68](#)
 - disable, [68](#)
 - enable, [68](#)
 - error, [68](#)
 - format, [68](#), [70](#)
 - get, [69](#)
 - info, [69](#)
 - levels, [70](#)
 - Log, [67](#)
 - log, [69](#)
 - map, [70](#)
 - trace, [69](#), [70](#)
 - warn, [69](#), [70](#)
 - write, [70](#)
- age.port, [10](#)
- age.port.Graphics, [35](#)
 - calcMultitext, [35](#)
 - color, [36](#)
 - mode2D, [36](#)
 - popTransformation, [36](#)
 - pushTransformation, [36](#)
 - rectangle, [37](#)
 - text, [37](#)
 - texture, [37](#)
 - translate, [37](#), [38](#)
- age.port.jogl, [11](#)
- age.port.jogl.JOGLEventListener, [42](#)
 - assign, [42](#)
 - events, [45](#)
 - handleSurfaceCloseRequest, [42](#)
 - keyPressed, [43](#)
 - keyReleased, [43](#)
 - mouseClicked, [43](#)
 - mouseDragged, [43](#)
 - mouseEntered, [43](#)
 - mouseExited, [43](#)
 - mouseMoved, [43](#)
 - mousePressed, [43](#)
 - mouseReleased, [43](#)
 - mouseWheelMoved, [44](#)
 - translateButton, [44](#)
 - translateKey, [44](#)
 - windowDestroyed, [44](#)
 - windowDestroyNotify, [44](#)
 - windowGainedFocus, [44](#)
 - windowLostFocus, [44](#)
 - windowMoved, [44](#)
 - windowRepaint, [44](#)
 - windowResized, [45](#)
- age.port.jogl.JOGLGraphics, [45](#)
 - assign, [46](#)
 - calcMultitext, [46](#)
 - clear, [46](#)
 - color, [46](#), [47](#)
 - drawable, [49](#)
 - fonts, [49](#)
 - gl, [49](#)
 - glu, [49](#)
 - init, [47](#)
 - mode2D, [47](#)
 - mode3D, [47](#)
 - popTransformation, [47](#)
 - pushTransformation, [47](#)
 - rectangle, [47](#), [48](#)
 - text, [48](#)
 - texture, [48](#)
 - textures, [49](#)
 - translate, [48](#), [49](#)
- age.port.jogl.JOGLPort, [50](#)
 - add, [50](#)
 - assign, [50](#)

- create, 50
- eventListener, 52
- fullscreen, 51
- get, 51
- height, 51
- maximized, 51
- render, 51
- renderables, 52
- renderables_ro, 53
- renderListener, 53
- size, 51
- title, 52
- visible, 52
- width, 52
- window, 53
- age.port.jogl.JOGLRenderListener, 53
 - display, 54
 - dispose, 54
 - graphics, 54
 - init, 54
 - JOGLRenderListener, 54
 - port, 54
 - reshape, 54
- age.port.Port, 75
 - add, 76
 - assign, 76
 - create, 76
 - fullscreen, 76
 - height, 77
 - maximized, 77
 - render, 77
 - size, 77
 - title, 77
 - visible, 78
 - width, 78
- age.port.Renderable, 78
 - render, 78
- age.scene, 11
- age.scene.Node, 74
 - attach, 74
 - children, 75
 - children_ro, 75
 - detach, 75
 - parent, 75
- age.scene.Scene, 81
 - root, 81
- age.task, 11
- age.task.Task, 82
 - perform, 82
- age.task.Tasks, 82
 - assign, 83
 - client, 84
 - construct, 83
 - handleEvent, 84
 - inbox, 84
 - outbox, 84
 - perform, 84
 - port, 85
 - put, 84
 - shutdown, 84
 - Tasks, 83
 - tasks, 85
 - toggleFullscreen, 84
 - update, 84
- age.Util, 87
 - objectMapper, 88
 - readJsonFile, 87
 - readTextFile, 87
- AGEException
 - age.AGEException, 14
- Alarm
 - age.clock.Alarm, 15
- alarms
 - age.clock.Clock, 23
- alloc
 - age.event.Events, 31
- ALT
 - age.event.Key, 57
- assign
 - age.event.Events, 31
 - age.gui.Handling, 39
 - age.gui.Multiline, 72
 - age.gui.VScroller, 89
 - age.gui.Widgets, 98
 - age.port.jogl.JOGLEventListener, 42
 - age.port.jogl.JOGLGraphics, 46
 - age.port.jogl.JOGLPort, 50
 - age.port.Port, 76
 - age.task.Tasks, 83
- attach
 - age.scene.Node, 74
- B
 - age.event.Key, 58
- BACK_SPACE
 - age.event.Key, 58
- bar
 - age.gui.VScroller, 90
- bottom
 - age.gui.Dock, 23, 24
- BOX
 - age.gui.Flag, 34
- BTN1
 - age.event.Button, 17
- BTN2
 - age.event.Button, 17
- BTN3
 - age.event.Button, 17
- BTN4
 - age.event.Button, 17
- BTN5
 - age.event.Button, 17
- BTN6
 - age.event.Button, 17
- BTN7
 - age.event.Button, 17
- BTN8

- age.event.Button, 17
- btnDn
 - age.gui.VScroller, 90
- btnUp
 - age.gui.VScroller, 90
- buffer
 - age.gui.Multiline, 72, 74
- BUTTON
 - age.gui.Flag, 34
- button
 - age.event.Event, 26, 29
- buttonClickAction
 - age.gui.Handling, 39
- C
 - age.event.Key, 58
- cache
 - age.event.Events, 33
- calcMultitext
 - age.port.Graphics, 35
 - age.port.jogl.JOGLGraphics, 46
- CANVAS
 - age.gui.Flag, 34
- CAPS_LOCK
 - age.event.Key, 58
- character
 - age.event.Event, 26, 29
- children
 - age.gui.Widget, 93, 96
 - age.scene.Node, 75
- children_ro
 - age.gui.Widget, 96
 - age.scene.Node, 75
- clear
 - age.event.Event, 26
 - age.gui.Widget, 93
 - age.log.Log, 67
 - age.port.jogl.JOGLGraphics, 46
- client
 - age.task.Tasks, 84
- clock
 - age.Client, 21
- close
 - age.gui.Window, 101
- color
 - age.port.Graphics, 36
 - age.port.jogl.JOGLGraphics, 46, 47
- command
 - age.event.Event, 26, 29
 - age.gui.Widget, 93, 96
- configure
 - age.log.Log, 67
- construct
 - age.gui.Window, 100
 - age.task.Tasks, 83
- CONTROL
 - age.event.Key, 58
- count
 - age.event.Event, 26, 29
- age.gui.Multiline, 72
- create
 - age.gui.Multiline, 72
 - age.gui.VScroller, 89
 - age.port.jogl.JOGLPort, 50
 - age.port.Port, 76
- D
 - age.event.Key, 58
- D:/GIT/repos/ODE/age/age/AGEException.java, 103
- D:/GIT/repos/ODE/age/age/Client.java, 103
- D:/GIT/repos/ODE/age/age/clock/Alarm.java, 103
- D:/GIT/repos/ODE/age/age/clock/Clock.java, 104
- D:/GIT/repos/ODE/age/age/clock/Task.java, 104
- D:/GIT/repos/ODE/age/age/event/Button.java, 104
- D:/GIT/repos/ODE/age/age/event/Event.java, 105
- D:/GIT/repos/ODE/age/age/event/Events.java, 105
- D:/GIT/repos/ODE/age/age/event/Handler.java, 105
- D:/GIT/repos/ODE/age/age/event/Key.java, 106
- D:/GIT/repos/ODE/age/age/event/Type.java, 106
- D:/GIT/repos/ODE/age/age/gui/Dock.java, 106
- D:/GIT/repos/ODE/age/age/gui/Flag.java, 106
- D:/GIT/repos/ODE/age/age/gui/Handling.java, 107
- D:/GIT/repos/ODE/age/age/gui/Multiline.java, 107
- D:/GIT/repos/ODE/age/age/gui/Rendering.java, 107
- D:/GIT/repos/ODE/age/age/gui/VScroller.java, 107
- D:/GIT/repos/ODE/age/age/gui/Widget.java, 108
- D:/GIT/repos/ODE/age/age/gui/Widgets.java, 108
- D:/GIT/repos/ODE/age/age/gui/Window.java, 108
- D:/GIT/repos/ODE/age/age/log/Level.java, 109
- D:/GIT/repos/ODE/age/age/log/Log.java, 109
- D:/GIT/repos/ODE/age/age/port/Graphics.java, 109
- D:/GIT/repos/ODE/age/age/port/jogl/JOGLEventListener.java, 109
- D:/GIT/repos/ODE/age/age/port/jogl/JOGLGraphics.java, 110
- D:/GIT/repos/ODE/age/age/port/jogl/JOGLPort.java, 110
- D:/GIT/repos/ODE/age/age/port/jogl/JOGLRenderListener.java, 110
- D:/GIT/repos/ODE/age/age/port/Port.java, 111
- D:/GIT/repos/ODE/age/age/port/Renderable.java, 111
- D:/GIT/repos/ODE/age/age/scene/Node.java, 111
- D:/GIT/repos/ODE/age/age/scene/Scene.java, 112
- D:/GIT/repos/ODE/age/age/task/Task.java, 104
- D:/GIT/repos/ODE/age/age/task/Tasks.java, 112
- D:/GIT/repos/ODE/age/age/Util.java, 112
- DEBUG
 - age.log.Level, 66
- debug
 - age.log.Log, 68
- DECIMAL
 - age.event.Key, 58
- DELETE
 - age.event.Key, 58
- detach
 - age.scene.Node, 75
- dimension
 - age.event.Event, 26, 29

- age.gui.Widget, [93](#), [97](#)
- dimensionAdd
 - age.gui.Widget, [93](#)
- disable
 - age.log.Log, [68](#)
- display
 - age.port.jogl.JOGLRenderListener, [54](#)
- dispose
 - age.port.jogl.JOGLRenderListener, [54](#)
- DIVIDE
 - age.event.Key, [58](#)
- dock
 - age.gui.Widget, [94](#), [97](#)
- DOWN
 - age.event.Key, [58](#)
- down
 - age.gui.Multiline, [72](#)
- dragged
 - age.gui.Handling, [41](#)
- drawable
 - age.port.jogl.JOGLGraphics, [49](#)
- E
 - age.event.Key, [59](#)
- enable
 - age.log.Log, [68](#)
- END
 - age.event.Key, [59](#)
- ENTER
 - age.event.Key, [59](#)
- ERROR
 - age.log.Level, [66](#)
- error
 - age.log.Log, [68](#)
- ESCAPE
 - age.event.Key, [59](#)
- Event
 - age.event.Event, [26](#)
- eventListener
 - age.port.jogl.JOGLPort, [52](#)
- events
 - age.Client, [21](#)
 - age.gui.Handling, [41](#)
 - age.port.jogl.JOGLEventListener, [45](#)
- F
 - age.event.Key, [59](#)
- F1
 - age.event.Key, [59](#)
- F10
 - age.event.Key, [59](#)
- F11
 - age.event.Key, [59](#)
- F12
 - age.event.Key, [59](#)
- F2
 - age.event.Key, [59](#)
- F3
 - age.event.Key, [60](#)

- F4
 - age.event.Key, [60](#)
- F5
 - age.event.Key, [60](#)
- F6
 - age.event.Key, [60](#)
- F7
 - age.event.Key, [60](#)
- F8
 - age.event.Key, [60](#)
- F9
 - age.event.Key, [60](#)
- flag
 - age.gui.Widget, [94](#)
- flags
 - age.gui.Widget, [94](#), [97](#)
- flags_ro
 - age.gui.Widget, [97](#)
- fonts
 - age.port.jogl.JOGLGraphics, [49](#)
- format
 - age.log.Log, [68](#), [70](#)
- FRAME
 - age.gui.Flag, [34](#)
- free
 - age.event.Events, [31](#)
- fullscreen
 - age.port.jogl.JOGLPort, [51](#)
 - age.port.Port, [76](#)
- G
 - age.event.Key, [60](#)
- get
 - age.log.Log, [69](#)
 - age.port.jogl.JOGLPort, [51](#)
- getPage
 - age.gui.Window, [100](#)
- gl
 - age.port.jogl.JOGLGraphics, [49](#)
- glu
 - age.port.jogl.JOGLGraphics, [49](#)
- graphics
 - age.port.jogl.JOGLRenderListener, [54](#)
- H
 - age.event.Key, [60](#)
- HANDLE
 - age.gui.Flag, [34](#)
- handle
 - age.event.Events, [31](#)
 - age.event.Handler, [38](#)
 - age.gui.VScroller, [90](#)
- handleEvent
 - age.task.Tasks, [84](#)
- handleKeyboard
 - age.gui.Handling, [39](#)
- handlePointer
 - age.gui.Handling, [39](#)
- handlers

- age.event.Events, 33
- handleSurface
 - age.gui.Handling, 40
- handleSurfaceCloseRequest
 - age.port.jogl.JOGLEventListener, 42
- Handling
 - age.gui.Handling, 39
- handling
 - age.gui.Widgets, 98
- height
 - age.event.Event, 26
 - age.gui.Widget, 94
 - age.port.jogl.JOGLPort, 51
 - age.port.Port, 77
- HIDDEN
 - age.gui.Flag, 34
- HOVERED
 - age.gui.Flag, 34
- hovered
 - age.gui.Handling, 40, 41
- I
 - age.event.Key, 60
- image
 - age.gui.Widget, 94, 97
- inbox
 - age.event.Events, 33
 - age.task.Tasks, 84
- INFO
 - age.log.Level, 66
- info
 - age.log.Log, 69
- init
 - age.clock.Alarm, 15
 - age.clock.Clock, 22
 - age.port.jogl.JOGLGraphics, 47
 - age.port.jogl.JOGLRenderListener, 54
- INSERT
 - age.event.Key, 61
- J
 - age.event.Key, 61
- JOGLRenderListener
 - age.port.jogl.JOGLRenderListener, 54
- K
 - age.event.Key, 61
- key
 - age.event.Event, 26, 29
- KEY_PRESSED
 - age.event.Type, 85
- KEY_RELEASED
 - age.event.Type, 85
- KEY_TYPED
 - age.event.Type, 85
- keyEvent
 - age.event.Event, 26
- keyPressed
 - age.event.Event, 27
- age.port.jogl.JOGLEventListener, 43
- keyReleased
 - age.event.Event, 27
 - age.port.jogl.JOGLEventListener, 43
- keyTyped
 - age.event.Event, 27
- L
 - age.event.Key, 61
- LEFT
 - age.event.Key, 61
- left
 - age.gui.Dock, 23, 24
- levels
 - age.log.Log, 70
- line
 - age.gui.Multiline, 73
- lineHeight
 - age.gui.Multiline, 73
- Log
 - age.log.Log, 67
- log
 - age.log.Log, 69
- loop
 - age.Client, 19
- M
 - age.event.Key, 61
- main
 - age.Client, 19
- map
 - age.log.Log, 70
- mark
 - age.clock.Alarm, 16
 - age.gui.VScroller, 90
- match
 - age.gui.Widget, 94
- maximized
 - age.port.jogl.JOGLPort, 51
 - age.port.Port, 77
- MENU
 - age.event.Key, 61
- MINUS
 - age.event.Key, 61
- mode2D
 - age.port.Graphics, 36
 - age.port.jogl.JOGLGraphics, 47
- mode3D
 - age.port.jogl.JOGLGraphics, 47
- mouseClicked
 - age.port.jogl.JOGLEventListener, 43
- mouseDragged
 - age.port.jogl.JOGLEventListener, 43
- mouseEntered
 - age.port.jogl.JOGLEventListener, 43
- mouseExited
 - age.port.jogl.JOGLEventListener, 43
- mouseMoved
 - age.port.jogl.JOGLEventListener, 43

- mousePressed
 - age.port.jogl.JOGLEventListener, 43
- mouseReleased
 - age.port.jogl.JOGLEventListener, 43
- mouseWheelMoved
 - age.port.jogl.JOGLEventListener, 44
- MULTILINE
 - age.gui.Flag, 34
- Multiline
 - age.gui.Multiline, 72
- MULTIPLY
 - age.event.Key, 61
- N
 - age.event.Key, 61
- nanoperiod
 - age.clock.Alarm, 16
- NONE
 - age.event.Button, 17
 - age.event.Key, 62
 - age.event.Type, 86
- NP_0
 - age.event.Key, 62
- NP_1
 - age.event.Key, 62
- NP_2
 - age.event.Key, 62
- NP_3
 - age.event.Key, 62
- NP_4
 - age.event.Key, 62
- NP_5
 - age.event.Key, 62
- NP_6
 - age.event.Key, 62
- NP_7
 - age.event.Key, 62
- NP_8
 - age.event.Key, 62
- NP_9
 - age.event.Key, 63
- NUM_LOCK
 - age.event.Key, 63
- O
 - age.event.Key, 63
- objectMapper
 - age.Util, 88
- offset
 - age.gui.Multiline, 73, 74
- outbox
 - age.event.Events, 33
 - age.task.Tasks, 84
- P
 - age.event.Key, 63
- page
 - age.gui.Multiline, 73
 - age.gui.VScroller, 90
- age.gui.Window, 101
- PAGE_DOWN
 - age.event.Key, 63
- PAGE_UP
 - age.event.Key, 63
- parent
 - age.gui.Widget, 95, 97
 - age.scene.Node, 75
- parentResized
 - age.gui.Widget, 95
- PAUSE
 - age.event.Key, 63
- perform
 - age.task.Task, 82
 - age.task.Tasks, 84
- PLUS
 - age.event.Key, 63
- POINTER_CLICKED
 - age.event.Type, 86
- POINTER_ENTERED
 - age.event.Type, 86
- POINTER_EXITED
 - age.event.Type, 86
- POINTER_MOVED
 - age.event.Type, 86
- POINTER_PRESSED
 - age.event.Type, 86
- POINTER_RELEASED
 - age.event.Type, 86
- pointerClicked
 - age.event.Event, 27
- pointerEntered
 - age.event.Event, 27
- pointerEvent
 - age.event.Event, 27
- pointerExited
 - age.event.Event, 27
- pointerMoved
 - age.event.Event, 28
- pointerPressed
 - age.event.Event, 28
- pointerReleased
 - age.event.Event, 28
- popTransformation
 - age.port.Graphics, 36
 - age.port.jogl.JOGLGraphics, 47
- port
 - age.Client, 21
 - age.port.jogl.JOGLRenderListener, 54
 - age.task.Tasks, 85
- POS1
 - age.event.Key, 63
- position
 - age.event.Event, 28, 29
 - age.gui.Widget, 95, 97
- positionAdd
 - age.gui.Widget, 95
- post

- age.event.Events, 31
- postKeyPressed
 - age.event.Events, 31
- postKeyReleased
 - age.event.Events, 31
- postKeyTyped
 - age.event.Events, 31
- postPointerClicked
 - age.event.Events, 31
- postPointerEntered
 - age.event.Events, 32
- postPointerExited
 - age.event.Events, 32
- postPointerMoved
 - age.event.Events, 32
- postPointerPressed
 - age.event.Events, 32
- postPointerReleased
 - age.event.Events, 32
- postSurfaceCloseRequest
 - age.event.Events, 32
- postSurfaceResized
 - age.event.Events, 32
- postTaskCommand
 - age.event.Events, 33
- pressedFrameToFront
 - age.gui.Handling, 40
- PRINT_SCREEN
 - age.event.Key, 63
- pushTransformation
 - age.port.Graphics, 36
 - age.port.jogl.JOGLGraphics, 47
- put
 - age.task.Tasks, 84
- Q
 - age.event.Key, 64
- R
 - age.event.Key, 64
- readJsonFile
 - age.Util, 87
- readTextFile
 - age.Util, 87
- rectangle
 - age.port.Graphics, 37
 - age.port.jogl.JOGLGraphics, 47, 48
- ref
 - age.gui.Handling, 41
- remove
 - age.gui.Widget, 95
- render
 - age.Client, 19
 - age.gui.Rendering, 79
 - age.port.jogl.JOGLPort, 51
 - age.port.Port, 77
 - age.port.Renderable, 78
- renderables
 - age.port.jogl.JOGLPort, 52
- renderables_ro
 - age.port.jogl.JOGLPort, 53
- renderBox
 - age.gui.Rendering, 80
- renderButton
 - age.gui.Rendering, 80
- renderCanvas
 - age.gui.Rendering, 80
- renderChildren
 - age.gui.Rendering, 80
- renderFrame
 - age.gui.Rendering, 80
- renderHandle
 - age.gui.Rendering, 80
- Rendering
 - age.gui.Rendering, 79
- rendering
 - age.gui.Widgets, 98
- renderListener
 - age.port.jogl.JOGLPort, 53
- renderMultiline
 - age.gui.Rendering, 80
- renderTitle
 - age.gui.Rendering, 80
- renderWidget
 - age.gui.Rendering, 81
- rescale
 - age.gui.Multiline, 73
- reshape
 - age.port.jogl.JOGLRenderListener, 54
- resized
 - age.gui.Widget, 95
- RIGHT
 - age.event.Key, 64
- right
 - age.gui.Dock, 23, 24
- root
 - age.gui.Widgets, 98, 99
 - age.scene.Scene, 81
- run
 - age.Client, 19
 - age.clock.Task, 82
- running
 - age.Client, 21
- S
 - age.event.Key, 64
- SCROLL_LOCK
 - age.event.Key, 64
- scroller
 - age.gui.Multiline, 74
- serialVersionUID
 - age.AGEEException, 15
- set
 - age.gui.Dock, 23
 - age.gui.VScroller, 90
- setup
 - age.Client, 19
- setupGUI

- age.Client, 20
- SHIFT
 - age.event.Key, 64
- shutdown
 - age.Client, 20
 - age.task.Tasks, 84
- size
 - age.gui.VScroller, 91
 - age.gui.Window, 101
 - age.port.jogl.JOGLPort, 51
 - age.port.Port, 77
- SPACE
 - age.event.Key, 64
- startFrameDragAction
 - age.gui.Handling, 40
- startFrameSizeAction
 - age.gui.Handling, 40
- startScrollHandleAction
 - age.gui.Handling, 40
- stopDragAction
 - age.gui.Handling, 40
- SUBTRACT
 - age.event.Key, 64
- SURFACE_CLOSE_REQUEST
 - age.event.Type, 86
- SURFACE_RESIZED
 - age.event.Type, 86
- surfaceCloseRequest
 - age.event.Event, 28
- surfaceResized
 - age.event.Event, 28
- sysMenuFrame
 - age.Client, 21
- SYSTEM
 - age.event.Key, 64
- T
 - age.event.Key, 64
- TAB
 - age.event.Key, 65
- task
 - age.clock.Alarm, 16
- TASK_COMMAND
 - age.event.Type, 86
- taskCommand
 - age.event.Event, 28
- Tasks
 - age.task.Tasks, 83
- tasks
 - age.Client, 21
 - age.task.Tasks, 85
- text
 - age.gui.Multiline, 73
 - age.gui.Widget, 96, 97
 - age.port.Graphics, 37
 - age.port.jogl.JOGLGraphics, 48
- texture
 - age.port.Graphics, 37
 - age.port.jogl.JOGLGraphics, 48
- textures
 - age.port.jogl.JOGLGraphics, 49
- TITLE
 - age.gui.Flag, 35
- title
 - age.gui.Window, 100, 101
 - age.port.jogl.JOGLPort, 52
 - age.port.Port, 77
- tmp
 - age.gui.Handling, 41
- toFront
 - age.gui.Widget, 96
- toggleDesktop
 - age.Client, 20
- toggleFullscreen
 - age.task.Tasks, 84
- toggleSysmenu
 - age.Client, 20
- top
 - age.gui.Dock, 24
- trace
 - age.log.Log, 69, 70
- translate
 - age.port.Graphics, 37, 38
 - age.port.jogl.JOGLGraphics, 48, 49
- translateButton
 - age.port.jogl.JOGLEventListener, 44
- translateKey
 - age.port.jogl.JOGLEventListener, 44
- trigger
 - age.clock.Alarm, 15
- type
 - age.event.Event, 28, 30
- U
 - age.event.Key, 65
- UP
 - age.event.Key, 65
- up
 - age.gui.Multiline, 73
- update
 - age.Client, 20
 - age.clock.Alarm, 16
 - age.clock.Clock, 22
 - age.event.Events, 33
 - age.gui.Multiline, 73
 - age.task.Tasks, 84
- updateActionState
 - age.gui.Handling, 40
- updateDragAction
 - age.gui.Handling, 41
- uuid
 - age.gui.VScroller, 91
- V
 - age.event.Key, 65
- value
 - age.gui.VScroller, 90
- visible

- age.port.jogl.JOGLPort, [52](#)
 - age.port.Port, [78](#)
- VScroller
 - age.gui.VScroller, [89](#)
- W
 - age.event.Key, [65](#)
- warn
 - age.log.Log, [69](#), [70](#)
- WARNING
 - age.log.Level, [66](#)
- Widget
 - age.gui.Widget, [92](#)
- Widgets
 - age.gui.Widgets, [98](#)
- widgets
 - age.Client, [21](#)
 - age.gui.Handling, [41](#)
 - age.gui.Rendering, [81](#)
- width
 - age.event.Event, [29](#)
 - age.gui.Widget, [96](#)
 - age.port.jogl.JOGLPort, [52](#)
 - age.port.Port, [78](#)
- Window
 - age.gui.Window, [100](#)
- window
 - age.port.jogl.JOGLPort, [53](#)
- windowDestroyed
 - age.port.jogl.JOGLEventListener, [44](#)
- windowDestroyNotify
 - age.port.jogl.JOGLEventListener, [44](#)
- windowFrame
 - age.Client, [21](#)
- windowGainedFocus
 - age.port.jogl.JOGLEventListener, [44](#)
- windowLostFocus
 - age.port.jogl.JOGLEventListener, [44](#)
- windowMoved
 - age.port.jogl.JOGLEventListener, [44](#)
- windowRepaint
 - age.port.jogl.JOGLEventListener, [44](#)
- windowResized
 - age.port.jogl.JOGLEventListener, [45](#)
- write
 - age.log.Log, [70](#)
- X
 - age.event.Key, [65](#)
- x
 - age.event.Event, [29](#)
 - age.gui.Widget, [96](#)
- Y
 - age.event.Key, [65](#)
- y
 - age.event.Event, [29](#)
 - age.gui.Widget, [96](#)

Z

- age.event.Key, [65](#)