


HƯỚNG DẪN THỰC HÀNH CHƯƠNG 6 – Thực hành 2



Mục tiêu:

- R-UTC cấp phát DHCP v4,v6 cho máy L12-PC1
- Sử dụng dịch vụ Web với 2 domain utc.edu.vn và utc2.edu.vn
- Sử dụng dịch vụ Mail, gửi mail giữa 2 hòm thư @utc.edu.vn và @utc2.edu.vn

Chia mạng thành các mạng con (Xem chi tiết trong file Bảng quy hoạch)

Không gian IP	Ipv4 Address 116.154.208.0/23	Ipv6 Address 24C1:D8E0::/48	VLAN ID (tên VLAN)
L1-v4 = /24; L1-v6 = /64	116.154.208.0/24	24C1:D8E0:0:1::/64	VLAN 12 (UTC-CLA)
L2-v4 = /25; L2-v6 = /64	116.154.209.0/25	24C1:D8E0:0:2::/64	VLAN 22 (UTC2-CLA)
L3-v4 = /26; L3-v6 = /64	116.154.209.128/26	24C1:D8E0:0:3::/64	VLAN 10 (UTC-SER)
L4-v4 = /27; L4-v6 = /64	116.154.209.192/27	24C1:D8E0:0:4::/64	VLAN 20 (UTC2-SER)
L5-v4 = /28; L5-v6 = /64	116.154.209.224/28	24C1:D8E0:0:5::/64	VLAN 11 (UTC-VIP)
L6-v4 = /29; L6-v6 = /64	116.154.209.240/29	24C1:D8E0:0:6::/64	VLAN 21 (UTC2-VIP)
L7-v4 = /30; L7-v6 = /64	116.154.209.248/30	24C1:D8E0:0:7::/64	Kết nối giữa 2 Router

- Cấu hình địa chỉ IP ở Router R-UTC

Device Name: R-UTC
Custom Device Model: 2811 IOS15
Hostname: R-UTC

Port	Link	VLAN	IP Address	IPv6 Address	MAC Address
FastEthernet0/0	Up	--	116.154.209.225/28	24C1:D8E0:0:5::1/64	0002.1642.1801
FastEthernet0/1	Up	--	116.154.209.129/26	24C1:D8E0:0:3::1/64	0002.1642.1802
FastEthernet1/0	Up	--	116.154.208.1/24	24C1:D8E0:0:1::1/64	0090.2BD3.A601
FastEthernet1/1	Up	--	116.154.209.249/30	24C1:D8E0:0:7::1/64	0090.2BD3.A602
Vlan1	Up	1	<not set>	<not set>	0000.0C6C.EC60

Physical Location: Intercity > Home City > Corporate Office > Main Wiring Closet > Rack > R-UTC

```
en
conf t
hostname R-UTC
enable secret UTC@123
exit
wr mem
conf t
interface fa0/0
ip address 116.154.209.225 255.255.255.240
ipv6 address 24C1:D8E0:0:5::1/64
no shut
ex
```

```
interface fa0/1
ip address 116.154.209.129 255.255.255.192
ipv6 address 24C1:D8E0:0:3::1/64
no shut
ex
interface fa1/0
ip address 116.154.208.1 255.255.255.0
ipv6 address 24C1:D8E0:0:1::1/64
no shut
exit
interface fa1/1
ip address 116.154.209.249 255.255.255.252
ipv6 address 24C1:D8E0:0:7::1/64
speed 100
duplex full
no shut
exit
```

- Cấu hình địa chỉ IP ở Router R-UTC2


Device Name: R-UTC2					
Custom Device Model: 2811 IOS15					
Hostname: R-UTC2					
Port	Link	VLAN	IP Address	IPv6 Address	MAC Address
FastEthernet0/0	Up	--	116.154.209.241/29	24C1:D8E0:0:6::1/64	0002.1728.A501
FastEthernet0/1	Up	--	116.154.209.193/27	24C1:D8E0:0:4::1/64	0002.1728.A502
FastEthernet1/0	Up	--	116.154.209.1/25	24C1:D8E0:0:2::1/64	0090.2B46.3401
FastEthernet1/1	Up	--	116.154.209.250/30	24C1:D8E0:0:7::2/64	0090.2B46.3402
Vlan1	Down	1	<not set>	<not set>	0001.64AA.4CDB
Physical Location: Intercity > Home City > Corporate Office > Main Wiring Closet > Rack > R-UTC2					

```
en
conf t
hostname R-UTC2
enable secret UTC@123
exit
wr mem
conf t
interface fa0/0
ip address 116.154.209.241 255.255.255.248
ipv6 address 24C1:D8E0:0:6::1/64
no shut
```

```
ex
interface fa0/1
ip address 116.154.209.193 255.255.255.224
ipv6 address 24C1:D8E0:0:4::1/64
no shut
ex
interface fa1/0
ip address 116.154.209.1 255.255.255.128
ipv6 address 24C1:D8E0:0:2::1/64
no shut
exit
interface fa1/1
ip address 116.154.209.250 255.255.255.252
ipv6 address 24C1:D8E0:0:7::2/64
speed 100
duplex full
no shut
exit
```

- Cấu hình địa chỉ IP trên các máy Server

Máy L10-Ser1



The screenshot shows a configuration window titled "L10 - Ser1" with a tabbed interface. The "Desktop" tab is selected, displaying the "IP Configuration" section. This section contains two sub-panels: "IP Configuration" and "IPv6 Configuration".

IP Configuration:

- ☐ DHCP
- ☒ Static
- IPv4 Address: 116.154.209.131
- Subnet Mask: 255.255.255.192
- Default Gateway: 116.154.209.129
- DNS Server: 116.154.209.131

IPv6 Configuration:

- ☐ Automatic
- ☒ Static
- IPv6 Address: 24C1:D8E0:0:3::3 / 64
- Link Local Address: FE80::2E0:B0FF:FEE8:6440
- Default Gateway: 24C1:D8E0:0:3::1
- DNS Server: 24C1:D8E0:0:3::3

Máy L10-Ser2

L10 - Ser2

Physical Config Services Desktop Programming Attributes

IP Configuration X

IP Configuration

☐ DHCP ☒ Static

IPv4 Address 116.154.209.133

Subnet Mask 255.255.255.192

Default Gateway 116.154.209.129

DNS Server 116.154.209.131

IPv6 Configuration

☐ Automatic ☒ Static


IPv6 Address 24C1:D8E0:0:3::5 / 64

Link Local Address FE80::2D0:58FF:FE5D:4B04

Default Gateway 24C1:D8E0:0:3::1

DNS Server 24C1:D8E0:0:3::3

Máy L20-Ser1



Tương tự với các máy L11-Lap1, L22-PC1, L21-Lap1

Cấu hình trên Switch

- Tại Switch Sw-UTC-A1

```
en
```

```
conf t
```

```
hostname SW-UTC-A1
```

```
enable secret UTC@123
```

```
exit
```

```
wri mem
```

```
en
conf t
vlan 10
name UTC-Ser
end
conf t
vlan 11
name UTC-VIP
end
conf t
vlan 12
name UTC-Cla
end
conf t
int range Fa 0/11, Fa 0/2, Fa 0/12
switchport mode access
switchport access vlan 10
end
conf t
```

```
int range Fa 0/4, Fa 0/1
switchport mode access
switchport access vlan 11
end
conf t
int Fa 0/3
switchport mode access
switchport access vlan 12
end
show vlan brief
```

- Tại Switch Sw-UTC-A2

```
en
conf t
hostname SW-UTC-A2
enable secret UTC@123
exit
wri mem
en
conf t
```

```
vlan 10
name UTC-Ser
end
conf t
vlan 11
name UTC-VIP
end
conf t
vlan 12
name UTC-Cla
end
conf t
int Fa 0/1
switchport mode access
switchport access vlan 12
end
show vlan brief
```

- Tại Switch Sw-UTC2

```
en
```

```
conf t
hostname SW-UTC2
enable secret UTC@123
exit
wri mem
en
conf t
vlan 20
name UTC-Ser
end
conf t
vlan 21
name UTC-VIP
end
conf t
vlan 22
name UTC-Cla
end
conf t
```

```
int range Fa 0/11, Fa 0/2
switchport mode access
switchport access vlan 20
end

conf t
int range Fa 0/10, Fa 0/1
switchport mode access
switchport access vlan 21
end

conf t
int range Fa 0/12, Fa 0/3
switchport mode access
switchport access vlan 22
end

show vlan brief
```

- Cấu hình DHCP trên Router

```
conf t
ip dhcp pool UTC-DHCPv4-pool
network 116.154.208.0 255.255.255.0
```

```
default-router 116.154.208.1
dns-server 116.154.209.131
ex
ip dhcp excluded-address 116.154.208.1 116.154.208.60
ip dhcp pool UTC-DHCPv6-pool
dns-server
ex
interface fa 0/1
ipv6 nd other-config-flag
ipv6 dhcp server UTC-DHCPv6-pool
show ip dhcp pool
```

Cấu hình Trunk

- Tại Switch Sw-UTC-A1

```
en
conf t
int G 0/1
switchport mode trunk
switchport trunk allowed vlan 10,11,12
end
```

- Tại Switch Sw-UTC-A2

```
en
conf t
int G 0/1
switchport mode trunk
switchport trunk allowed vlan 10,11,12
end
```

- Cấu hình định tuyến trên R-UTC

```
en
ip route 0.0.0.0 0.0.0.0 116.154.209.250
```

- Cấu hình định tuyến trên R-UTC2

```
en
ip route 116.154.209.128 255.255.255.192 116.154.209.249
ip route 116.154.209.224 255.255.255.240 116.154.209.249
ip route 116.154.208.0 255.255.255.0 116.154.209.249
```

Cấu hình DNS trên Server L10-Ser1

L10 - Ser1

Physical Config **Services** Desktop Programming Attributes

SERVICES

- HTTP
- DHCP
- DHCPv6
- TFTP
- DNS**
- SYSLOG
- AAA
- NTP
- EMAIL
- FTP
- IoT
- VM Management
- Radius EAP

DNS

DNS Service ☒ On ☐ Off

Resource Records

Name Type **A Record** ▼

Address

No.	Name	Type	Detail
0	mail.utc.edu.vn	A Record	116.154.209.133
1	mail.utc2.edu.vn	A Record	116.154.209.195
2	utc.edu.vn	A Record	116.154.209.133
3	utc2.edu.vn	A Record	116.154.209.195
4	www.mail.utc.edu.vn	A Record	116.154.209.133
5	www.mail.utc2.edu.vn	A Record	116.154.209.195
6	www.utc.edu.vn	A Record	116.154.209.133
7	www.utc2.edu.vn	A Record	116.154.209.195

Cấu hình HTTP, Email

Trên Server L10-Ser2

L10 - Ser2

PhysicalConfigServicesDesktopProgrammingAttributes

SERVICES

HTTP

DHCP

DHCPv6

TFTP

DNS

SYSLOG

AAA

NTP

EMAIL

FTP

IoT

VM Management

Radius EAP

HTTP

☒ On

☐ Off

HTTPS

☒ On

☐ Off

File Manager

	File Name	Edit	Delete
1	copyrights.html	(edit)	(delete)
2	cscoptlogo177x111.jpg		(delete)
3	helloworld.html	(edit)	(delete)
4	image.html	(edit)	(delete)
5	index.html	(edit)	(delete)
6	utc-index.html	(edit)	(delete)

L10 - Ser2

PhysicalConfigServicesDesktopProgrammingAttributes

SERVICES

HTTP


DHCP

DHCPv6


File Name:


utc-index.html

<h1> UTC - THE WAY TO SUCCESS </h1>



Trên server L20-Ser1





Cấu hình configure mail trên 1 máy PC dùng mail @utc.edu.vn (Các máy khác cấu hình tương tự)

Trên máy L11-Lap1

The image shows a screenshot of a software application window titled "L11 - Lap1". The window has a menu bar with "Physical", "Config", "Desktop", "Programming", and "Attributes". The "Desktop" tab is selected. A "Configure Mail" dialog box is open, featuring a blue title bar with a close button (X). The dialog is organized into three sections: "User Information", "Server Information", and "Logon Information".

Section	Field	Value
User Information	Your Name:	vip1
	Email Address	vip1@utc.edu.vn
Server Information	Incoming Mail Server	mail.utc.edu.vn
	Outgoing Mail Server	mail.utc.edu.vn
Logon Information	User Name:	vip1
	Password:	•••

Cấu hình configure mail trên 1 máy PC dùng mail @utc2.edu.vn (Các máy khác cấu hình tương tự)

Trên máy L21-Lap1

L21 - Lap1

Physical Config **Desktop** Programming Attributes

Configure Mail X

User Information

Your Name: vip2

Email Address: vip2@utc2.edu.vn

Server Information

Incoming Mail Server: mail.utc2.edu.vn

Outgoing Mail Server: mail.utc2.edu.vn

Logon Information

User Name: vip2

Password: ●●●

Kiểm tra gửi mail giữa các địa chỉ khác nhau

