

# LTE EMM and ECM States

January 23, 2013

(Last Updated: September 20, 2013)

**NMC Consulting Group (tech@netmanias.com)**

[www.netmanias.com](http://www.netmanias.com)

[www.nmcgroups.com](http://www.nmcgroups.com)

## About NMC Consulting Group

NMC Consulting Group is an advanced and professional network consulting company, specializing in IP network areas (e.g., FTTH, Metro Ethernet and IP/MPLS), service areas (e.g., IPTV, IMS and CDN), and wireless network areas (e.g., Mobile WiMAX, LTE and Wi-Fi) since 2002.

Copyright © 2002-2013 NMC Consulting Group. All rights reserved.



# Type of EMM Procedures

- **EMM Common Procedure:** Procedures which can always be initiated whilst a NAS signalling connection exists
- **EMM Specific Procedure:** Procedures related to user mobility (Registration and Location Update)
- **EMM Connection Management Procedure:** Procedures related to establishing a NAS signalling connection

## Types of EMM Procedures


Type	EMM Procedures	Initiator	The initiator will:
<b>EMM Common Procedure</b>	<b>GUTI Allocation</b>	Network	Allocate a GUTI and provide a new TAI list to a UE.
	<b>Authentication</b>	Network	Through EPS-AKA procedure, perform mutual authentication between user and network, and agree on a key $K_{ASME}$ .
	<b>Security Mode Control</b>	Network	Initialize NAS signalling security between UE and MME with EPS NAS keys and EPS security algorithms.
	<b>Identification</b>	Network	Request a UE for IMSI or IMEI.
	<b>EMM Information</b>	Network	Support network identity and time zone (NITZ). Network optionally sends network name and time information to a UE.
<b>EMM Specific Procedure</b>	<b>Attach</b>	UE	Attach IMSI in network, and establish an EMM context and a default bearer.
	<b>Detach</b>	UE or Network	Detach the IMSI in the network, to release an EMM context and all bearers.
	<b>Tracking Area Update</b>	UE	At normal TAU, have the network update the registration of the actual TA of a UE. At periodic TAU, periodically notify the availability of the UE.
<b>EMM Connection Management Procedure</b>	<b>Service Request</b>	UE	Establish a secure connection to network, and request resource reservation for sending data.
	<b>Paging</b>	Network	Request a NAS signalling connection establishment, and prompt UE to re-attach .
	<b>Transport of NAS Message</b>	UE or Network	

# EMM/ECM/RRC State



Layer	State	Entity	Description
EMM	EMM-Deregistered	UE, MME	UE is not attached to any LTE network and no EMM context has been established in the UE and MME. The MME does not know the current location of the UE, but may have tracking area (TA) information last reported by the UE.
	EMM-Registered	UE, MME	UE has been attached to the LTE network and an IP address has been assigned to the UE. An EMM Context has been established and a default EPS bearer context has been activated in the UE and MME. The MME knows the current location of UE with an accuracy of a cell or, at least, a tracking area.
ECM	ECM-Idle	UE, MME	No NAS signalling connection (ECM connection) is established yet. The UE has not been assigned physical resources, i.e. radio resources (SRB/DRB) and network resources (S1 bearer/S1 signalling connection) yet.
	ECM-Connected	UE, MME	A NAS signalling connection (ECM connection) is established. The UE has been assigned physical resources, i.e. radio resources (SRB/DRB) and network resources (S1 bearer/S1 signalling connection). The ECM connection consists of an RRC connection and an S1 signalling connection.
RRC	RRC-Idle	UE, eNB	No RRC is established yet.
	RRC-Connected	UE, eNB	An RRC connection has been established.

# EMM State Transition



Case	State	User Experience (Example)
A	EMM-Deregistered + ECM-Idle + RRC-Idle	<ul style="list-style-type: none"><li>When a UE is switched on for the first time after subscription</li><li>When a UE is switched on after staying turned off for a long time</li><li>No UE context in the UE and MME.</li></ul>
B	EMM-Deregistered + ECM-Idle + RRC-Idle	<ul style="list-style-type: none"><li>When a UE is switched on within a certain period of time after being turned off</li><li>When ECM connection is lost during communication due to radio link failure</li><li>Some UE context from the last attach can still be stored in the UE and MME (e.g., to avoid running an AKA procedure during every Attach procedure).</li></ul>
C	EMM-Registered + ECM-Connected + RRC-Connected	<ul style="list-style-type: none"><li>When a UE is attached to network (an MME) and is using services (e.g., Internet, VoD, Live TV ..)</li><li>The mobility of a UE is handled by a handover procedure.</li></ul>
D	EMM-Registered + ECM-Idle + RRC-Idle	<ul style="list-style-type: none"><li>When a UE is attached to network (an MME), but not using any service</li><li>The mobility of a UE is handled by a cell reselection procedure.</li></ul>

# EMM Features (1) – UE Location Information


UE Location Information Set in Each EPS Entity

Case	State	UE	eNB	S-GW	P-GW	MME	HSS	PCR	SPR
A	EMM-Deregistered + ECM-Idle + RRC-Idle	-	-	-	-	-	-	-	-
B	EMM-Deregistered + ECM-Idle + RRC-Idle	Last Visited TAI	-	-	-	TAI of Last TAU	MME ID	-	-
C	EMM-Registered + ECM-Connected + RRC-Connected	ECGI, TAI	ECGI, TAI	ECGI, TAI of Last TAU	ECGI, TAI of Last TAU	ECGI, TAI of Last TAU	MME ID	ECGI	-
D	EMM-Registered + ECM-Idle + RRC-Idle	-	-	TAI of Last TAU	TAI of Last TAU	TAI of Last TAU	MME ID	TAI of Last TAU	-


# EMM Features (2) – EPS Bearer and NAS Signalling Connection Information

EPS Bearer and NAS Signalling Connection Information

Case	State	EPS Bearer			NAS Signalling Connection (= ECM Connection)		S11 Signalling Conn. (MME – SGW)	S5 Signalling Conn. (SGW – PGW)
		Radio Bearer (UE – eNB)	S1 Bearer (eNB – SGW)	S5 Bearer (SGW – PGW)	RRC Conn. (UE – eNB)	S1 Conn. (eNB – MME)		
A	EMM-Deregistered + ECM-Idle + RRC-Idle	-	-	-	-	-	-	-
B	EMM-Deregistered + ECM-Idle + RRC-Idle	-	-	-	Established	Established	-	-
C	EMM-Registered + ECM-Connected + RRC-Connected	Established	Established	Established	Established	Established	Established	Established
D	EMM-Registered + ECM-Idle + RRC-Idle	-	-	Established	-	-	Established	Established



State C (EMM-Registered + ECM-Connected + RRC-Connected)



State D (EMM-Registered + ECM-Idle + RRC-Idle)

# EMM Features (3) – Mobility Information

## Features Related to User Mobility

Case	State	Mobility	Tracking Area Update	Paging
A	EMM-Deregistered + ECM-Idle + RRC-Idle	<ul style="list-style-type: none"><li>• PLMN/Cell Selection</li></ul>	-	-
B	EMM-Deregistered + ECM-Idle + RRC-Idle	<ul style="list-style-type: none"><li>• PLMN/Cell Selection</li></ul>	-	-
C	EMM-Registered + ECM-Connected + RRC-Connected	<ul style="list-style-type: none"><li>• Handover:<ul style="list-style-type: none"><li>- Intra-eNB handover</li><li>- X2 Handover</li><li>- S1 Handover</li></ul></li></ul>	<ul style="list-style-type: none"><li>• TAU when TA is changed</li></ul>	-
D	EMM-Registered + ECM-Idle + RRC-Idle	<ul style="list-style-type: none"><li>• Cell Reselection</li></ul>	<ul style="list-style-type: none"><li>• TAU when TA is changed</li><li>• Periodic TAU</li></ul>	<ul style="list-style-type: none"><li>• Paging Control</li></ul>

## EMM Features (4) – UE ID Information

### UE IDs Set in Each EPS Entity

Case	State	UE	eNB	S-GW	P-GW	MME	HSS	PCR	SPR
<b>A</b>	EMM-Deregistered + ECM-Idle + RRC-Idle	IMSI	-	-	-	-	IMSI	-	IMSI
<b>B</b>	EMM-Deregistered + ECM-Idle + RRC-Idle	IMSI, GUTI	-	-	-	IMSI, GUTI	IMSI	-	IMSI
<b>C</b>	EMM-Registered + ECM-Connected + RRC-Connected	IMSI, GUTI, UE IP addr., C-RNTI	C-RNTI, eNB/MME UE S1AP ID, Old/New eNB UE X2AP ID	IMSI	IMSI, UE IP addr.	IMSI, GUTI, UE IP addr., eNB/MME UE S1AP ID	IMSI	IMSI, UE IP addr.	IMSI
<b>D</b>	EMM-Registered + ECM-Idle + RRC-Idle	IMSI, GUTI, UE IP addr.	-	IMSI	IMSI, UE IP addr.	IMSI, GUTI, UE IP addr.	IMSI	IMSI, UE IP addr.	IMSI



## EPS Entity Information Set in State A

**State A: EMM-Deregistered + ECM-Idle + RRC-Idle**

[illegible]

## EPS Entity Information Set in State B

### State B: EMM-Deregistered + ECM-Connected + RRC-Connected

[illegible]

# EPS Entity Information Set in State C

**State C: EMM-Registered + ECM-Connected + RRC-Connected**

UE	eNB	S-GW	P-GW	MME	HSS	PCRF	SPR
IMSI	-	IMSI	IMSI	IMSI	IMSI	IMSI	IMSI
LTE K	-	-	-	-	LTE K	-	-
APN in Use	-	-	APN in Use	APN in Use	Default APN	APN in Use	-
-	-	-	-	EPS QoS Subscribed Profile	EPS QoS Subscribed Profile	-	-
-	-	-	PCC Rule	-	-	PCC Rule	Access Profile
GUTI	-	-	-	GUTI	-	-	-
TAI	TAI	TAI of Last TAU	TAI of Last TAU	TAI of Last TAU	-	TAI of Last TAU	-
NAS Security Context	-	-	-	NAS Security Context	-	-	-
-	-	-	-	-	MME ID	-	-
TAL List	-	-	-	TAI List	-	-	-
UE IP address	-	-	UE IP address	UE IP address	-	UE IP address	-
C-RNTI	C-RNTI	-	-	-	-	-	-
ECGI	ECGI	ECGI	ECGI	ECGI	-	ECGI	-
AS Security Context	AS Security Context	-	-	-	-	-	-
-	Used UE-AMBR (UL/DL)	-	-	Used UE-AMBR (UL/DL)	-	-	-
Used APN-AMBR (UL)	-	-	Used APN-AMBR (UL/DL)	Used APN-AMBR (UL/DL)	-	-	-
EPS Bearer ID	EPS Bearer ID	EPS Bearer ID	EPS Bearer ID	EPS Bearer ID	-	-	-
DRB ID	DRB ID	-	-	-	-	-	-
-	E-RAB ID	-	-	E-RAB ID	-	-	-
-	S1-TEID (DL/UL)	S1-TEID (DL/UL)	-	S1-TEID (DL/UL)	-	-	-
-		S5-TEID (DL/UL)	S5-TEID (DL/UL)	S5-TEID (DL/UL)	-	-	-
TFT(UL)	-	-	TFT(UL/DL)	-	-	-	-
QCI	QCI	QCI	QCI	QCI	-	-	-
-	ARP	ARP	ARP	ARP	-	-	-
-	eNB UE S1AP ID	-	-	eNB UE S1AP ID	-	-	-
-	MME UE S1AP ID	-	-	MME UE S1AP ID	-	-	-
-	eNB UE X2AP ID	-	-	-	-	-	-

# EPS Entity Information Set in State D

## State D: EMM-Registered + ECM-Idle + RRC-Idle

UE	eNB	S-GW	P-GW	MME	HSS	PCRF	SPR
IMSI	-	IMSI	IMSI	IMSI	IMSI	IMSI	IMSI
LTE K	-	-	-	-	LTE K	-	-
APN in Use	-	-	APN in Use	APN in Use	Default APN	APN in Use	-
-	-	-	-	EPS QoS Subscribed Profile	EPS QoS Subscribed Profile	-	-
-	-	-	PCC Rule	-	-	PCC Rule	Access Profile
GUTI	-	-	-	GUTI	-	-	-
TAI	TAI	TAI of Last TAU	TAI of Last TAU	TAI of Last TAU	-	TAI of Last TAU	-
NAS Security Context	-	-	-	NAS Security Context	-	-	-
-	-	-	-	-	MME ID	-	-
TAL List	-	-	-	TAI List	-	-	-
UE IP address	-	-	UE IP address	UE IP address	-	UE IP address	-
C-RNTI	C-RNTI	-	-	-	-	-	-
ECGI	ECGI	ECGI	ECGI	ECGI	-	ECGI	-
AS Security Context	AS Security Context	-	-	-	-	-	-
-	Used UE-AMBR (UL/DL)	-	-	Used UE-AMBR (UL/DL)	-	-	-
Used APN-AMBR (UL)	-	-	Used APN-AMBR (UL/DL)	Used APN-AMBR (UL/DL)	-	-	-
EPS Bearer ID	EPS Bearer ID	EPS Bearer ID	EPS Bearer ID	EPS Bearer ID	-	-	-
DRB ID	DRB ID	-	-	-	-	-	-
-	E-RAB ID	-	-	E-RAB ID	-	-	-
-	S1-TEID (DL/UL)	S1-TEID (DL/UL)	-	S1-TEID (DL/UL)	-	-	-
-	-	S5-TEID (DL/UL)	S5-TEID (DL/UL)	S5-TEID (DL/UL)	-	-	-
TFT(UL)	-	-	TFT(UL/DL)	-	-	-	-
QCI	QCI	QCI	QCI	QCI	-	-	-
-	ARP	ARP	ARP	ARP	-	-	-
-	eNB UE S1AP ID	-	-	eNB UE S1AP ID	-	-	-
-	MME UE S1AP ID	-	-	MME UE S1AP ID	-	-	-
-	eNB UE X2AP ID	-	-	-	-	-	-

## References and Abbreviations

- [1] 3GPP TS 24.301, “Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3”.
- [2] Netmanias Technical Document, “LTE Network Architecture”, December 2012,  
<http://www.netmanias.com/bbs/view.php?id=techdocs&no=52>
- [3] Netmanias Technical Document, “LTE Security II”, August 2012 ,  
<http://www.netmanias.com/bbs/view.php?id=techdocs&no=66>
- [4] NMC Consulting Group Confidential Internal Report, “E2E LTE Network Design”, August 2010.

### Abbreviations

AMBR	: Aggregated Maximum Bit Rate	MBR	: Maximum Bit Rate
APN	: Access Point Name	MME	: Mobility Management Entity
ARP	: Allocation and Retention Priority	NAS	: Non Access Stratum
AS	: Access Stratum	PCC	: Policy and Charging Control
C-RNTI	: Cell Radio Network Temporary Identifier	PCRF	: Policy and Charging Rule Function
DRB	: Data Radio Bearer	PDCP	: Packet Data Convergence Protocol
ECGI	: E-UTRAN Cell Global Identifier	P-GW	: Packet Data Network Gateway
ECM	: EPS Connection Management	PLMN	: Public Land Mobile Network
EMM	: EPS Mobility Management	QCI	: QoS Class Identifier
eNB	: Evolved Node B	RLC	: Radio Link Control
EPS	: Evolved Packet System	RRC	: Radio Resource Control
E-RAB	: E-UTRAN Radio Access Bearer	S1AP	: S1 Application Protocol
ESM	: EPS Session Management	S-GW	: Serving Gateway
E-UTRAN	: Evolved Universal Terrestrial Radio Access Network	SPR	: Subscriber Profile Repository
GBR	: Guaranteed Bit Rate	TAI	: Tracking Area identity
GUTI	: Globally Unique Temporary Identifier	TAU	: Tracking Area Update
HSS	: Home Subscriber Server	TFT	: Traffic Flow Template
IMSI	: Serving Gateway	UE	: User Equipment
LTE	: Subscriber Profile Repository	X2AP	: X2 Application Protocol
MAC	: Medium Access Control		

# Netmanias LTE Technical Documents

Visit <http://www.netmanias.com> to view and download more technical documents.

Index	Topic	Document title	Document presented here
1	Network Architecture	LTE Network Architecture: Basic	
2	Identification	LTE Identification I: UE and ME Identifier	
3		LTE Identification II: NE and Location Identifier	
4		LTE Identification III: EPS Session/Bearer Identifier	
5	Security	LTE Security I: LTE Security Concept and LTE Authentication	
6		LTE Security II: NAS and AS Security	
7	QoS	LTE QoS: SDF and EPS Bearer QoS	
8	EMM	<b>LTE EMM and ECM States</b>	<b>O</b>
9		LTE EMM: User Experience based EMM Scenario and Eleven EMM Cases	
10		LTE EMM Procedure: 1. Initial Attach (Part 1) – Case of Initial Attach	
11		LTE EMM Procedure: 1. Initial Attach (Part 2) – Call Flow of Initial Attach	
12		LTE EMM Procedure: 2. Detach	
13		LTE EMM Procedure: 3. S1 Release	
14		LTE EMM Procedure: 4. Service Request	
15		LTE EMM Procedure: 5. Periodic TAU	
16		LTE EMM Procedure: 6. Handover without TAU (Part 1) – Overview of LTE Handover	
17		LTE EMM Procedure: 6. Handover without TAU (Part 2) – X2 Handover	
18		LTE EMM Procedure: 6. Handover without TAU (Part 3) – S1 Handover	
19		LTE EMM Procedure: 7. Cell Reselection without TAU	
20		LTE EMM Procedure: 8/9. Handover/Cell Reselection with TAU	
21		LTE EMM Procedure: 10/11. Toward Another City	
22	PCC	LTE Policy and Charging Control (PCC)	
23	Charging	LTE Charging I: Offline	
24		LTE Charging II: Online (TBD)	
25	IP Address Allocation	LTE: IP Address Allocation Schemes I: Basic	
26		LTE: IP Address Allocation Schemes II: A Case for Two Cities	

# Netmanias Research and Consulting Scope

		99	00	01	02	03	04	05	06	07	08	09	10	11	12	13
Services	eMBMS/Mobile IPTV															
	CDN/Mobile CDN															
	Transparent Caching															
	BSS/OSS															
	Cable TPS															
	Voice/Video Quality															
	IMS															
	Policy Control/PCRF															
	IPTV/TPS															
Mobile Network	LTE															
	Mobile WiMAX															
	Carrier WiFi															
	LTE Backaul															
Wireline Network	Data Center Migration															
	Carrier Ethernet															
	FTTH															
	Data Center															
	Metro Ethernet															
	MPLS															
	IP Routing															

Visit <http://www.netmanias.com> to view and download more technical documents.