

# Recurrent neurons (p.381)

phunc20

January 28, 2021

## Abstract

Personally, I found the equations on p.381 were not to the point, at least not enough for me to grasp the exact meaning and shapes of the input and output of a layer of recurrent neurons. Every time I re-read these paragraphs, I cannot recall the understanding I reached at the previous reading. Thus, I decided to make a note here to try to change the situation, hoping to make things clearer.

## 1 A Single Recurrent Neuron

The output of a single recurrent neuron of a single input instance  $x_{(t)}$  equals

$$y_{(t)} = \phi\left(\langle x_{(t)}, w_x \rangle + y_{(t-1)}w_y + b\right),$$

where

- $x_{(t)}, w_x \in \mathbb{R}^k$  ( $k$  can be any positive integer the user consider suitable)
- $\langle \cdot, \cdot \rangle$  denotes the inner product in  $\mathbb{R}^k$
- $y_{(t-1)} \in \mathbb{R}$  is the output of the previous time step
- $w_y, b$  are both in  $\mathbb{R}$

## 2 A Layer of Recurrent Neurons

To illustrate, let's take Figure 14-2 for example, in which we have a layer of **5** recurrent neurons. So, the output of this particular layer equals

$$\begin{pmatrix} y_{(t),1} \\ y_{(t),2} \\ y_{(t),3} \\ y_{(t),4} \\ y_{(t),5} \end{pmatrix} = \phi \begin{pmatrix} \langle x_{(t)}, w_{x,1} \rangle + \langle y_{(t-1)}, w_{y,1} \rangle + b_1 \\ \langle x_{(t)}, w_{x,2} \rangle + \langle y_{(t-1)}, w_{y,2} \rangle + b_2 \\ \langle x_{(t)}, w_{x,3} \rangle + \langle y_{(t-1)}, w_{y,3} \rangle + b_3 \\ \langle x_{(t)}, w_{x,4} \rangle + \langle y_{(t-1)}, w_{y,4} \rangle + b_4 \\ \langle x_{(t)}, w_{x,5} \rangle + \langle y_{(t-1)}, w_{y,5} \rangle + b_5 \end{pmatrix}, \text{ i.e.}$$

$$y_{(t)} = \phi \left( W_x^T x_{(t)} + W_y^T y_{(t-1)} + b \right),$$

where

- $y_{(t),j} \in \mathbb{R}$  for all  $j = 1, 2, 3, 4, 5$
- $x_{(t)} \in \mathbb{R}^k$  as before, and  $y_{(t-1)} \in \mathbb{R}^l$ , where  $l = \#(\text{recurrent neurons})$ , i.e. number of recurrent neurons in the layer, here, in particular,  $l = 5$
- $w_{x,j} \in \mathbb{R}^k, w_{y,j} \in \mathbb{R}^l, b_j \in \mathbb{R}$  are the weights and bias associated with the  $j$ -th neuron (for all  $j = 1, 2, 3, 4, 5$ )
- We define

$$W_x^T = \begin{pmatrix} - & w_{x,1}^T & - \\ - & w_{x,2}^T & - \\ - & w_{x,3}^T & - \\ - & w_{x,4}^T & - \\ - & w_{x,5}^T & - \end{pmatrix}$$

or equivalently

$$W_x = \begin{pmatrix} | & | & | & | & | \\ w_{x,1} & w_{x,2} & w_{x,3} & w_{x,4} & w_{x,5} \\ | & | & | & | & | \end{pmatrix}.$$

- We define similarly

$$W_y^T = \begin{pmatrix} -w_{y,1}^T & - \\ -w_{y,2}^T & - \\ -w_{y,3}^T & - \\ -w_{y,4}^T & - \\ -w_{y,5}^T & - \end{pmatrix}$$

or equivalently

$$W_y = \begin{pmatrix} | & | & | & | & | \\ w_{y,1} & w_{y,2} & w_{y,3} & w_{y,4} & w_{y,5} \\ | & | & | & | & | \end{pmatrix}.$$

- It is understood that

$$b = \begin{pmatrix} b_1 \\ b_2 \\ b_3 \\ b_4 \\ b_5 \end{pmatrix}$$

### 3 A Layer of Recurrent Neurons on A Batch of Instances

Like in the case of a fully connected neural network, we can have an expression (using matrices) for an entire batch of input instances, say,  $m$  instances

$$Y_{(t)} = \phi \left( X_{(t)} W_x + Y_{(t-1)} W_y + b \right)$$

where

- $\text{shape}(X_{(t)}) = (m, k)$
- $\text{shape}(W_x) = (k, l)$
- $\text{shape}(Y_{(t-1)}) = (m, l)$
- $\text{shape}(W_y) = (l, l)$
- $\text{shape}(b) = (1, l)$