

MOONPO DEVELOPMENT LIMITED

Sample Evaluation Report

SER NO	102469	REV	0
FINAL SER FILE		REMARKS	

SUBMISSION SECTION

P/N:	812-21725-00-01	DESCRIPTION	BAG SHRINK 0.03 170x250 PP CAT A
VENDOR CODE	1W130D	SUPPLIER	WINKONG INDUSTRIE LTD
MFG PN	812-21725-00-01	MANUFACTURER	WINKONG INDUSTRIE LTD
CUSTOMER PN		MODEL	JENGA MINI
SAMPLE QTY(pcs)	5	DOMAIN	VN
SUBMITTED BY	YUNA	TOOLINGPART	N
DATE	2026-07-24	PLC REV	00
REASON	NewPart	MOLD NO	
		CAVITY	

REPORT SECTION

RESULT	FULL APPROVAL
--------	---------------

.	本SER使用的法規要求請參考PN為XXX-XXXXX-XX-XX的最新版本CS
.	Material meets Rohs 2.0 and REACH Requirement

SUMMARY	1. Type of Bag: SHRINK BAG
	2. Material: POF
	3. Finishing: With 2-hole needle
	4. Size: 170x250mm ± 5mm
	5. Thickness: 0.03mm

PREPARED	CLKuang;2026-07-24	PROJECT APPROVED	GZXie;2026-07-29
REVIEWED	XLHe;2026-07-29	SUPPORT APPROVED	RomanLaw;2026-07-29

此文件以电子文件确认, 故不会在文件上签名确认,
此乃电子文件在公司网页上是唯一受控的文件, 打印出来的不被视为受控文件。

Engineering Evaluation Data She

PART#	812-21725-00-01				PART# Rev(Plastic Only)	00					
A:GENERAL DATA											
No.	Description	Specification	Actual	Result	Remarks						
1	Material	POF	POF	A							
2	Type of Bag	SHRINK BAG	SHRINK BAG	A							
3	Finishing	With 2-hole needle	With 2-hole needle	A							
4	Thickness	0.03mm	0.03mm	A							
B:SPECIAL DATA											
Code(Dimension)		1	2	3	4	5	6	7	8	9	10
Parameter(Other)		L	W								
Specification	SPEC.	250	170								
	Tolerance+/-	5	5								
	Unit	mm	mm								
	TestCondition /Equipment	Ruler	Ruler								
Measuring data	Sample 1	253.00	171.00								
	Sample 2	253.00	170.50								
	Sample 3	252.00	171.00								
	Sample 4	255.00	170.00								
	Sample 5	254.00	171.00								
	Sample 6										
	Sample 7										
	Sample 8										
	Sample 9										
	Sample 10										
Average		253.40	170.70	#DIV/0!	#DIV/0!	#DIV/0!	#DIV/0!	#DIV/0!	#DIV/0!	#DIV/0!	#DIV/0!
Result		A	A								
Max Acc. Range											
C:OVERALL RESULT											
Overall Result		A									

REMARK :

1. Type of result :

A = Accepted. Within specification.

FA = Functional Accepted. Out specification, "Max. Acceptable Range" needed to be specified to indicate the functional acceptable range. IQC please follow this range for incoming inspection.

R = Rejected.Out specification.

Evaluated By : CLKuang

Date: 2026/7/27

ENG0019b

812-21725-00-01

