## Phu Nguyen

Module 06 Lab - Regression and Classification Models**Objective:** To understand the difference between regression and classification and to build your first linear models for both tasks.**In this lab, you will write the code to train and evaluate the models.**

Part 1: Regression vs. ClassificationThis is the most fundamental distinction between types of supervised learning problems.* **Regression:** The goal is to predict a **continuous numerical value**. * *Examples:* Predicting the price of a house, the temperature tomorrow, or the stock price.* **Classification:** The goal is to predict a **discrete category or class label**. * *Examples:* Predicting if an email is spam or not spam, if a flower is a setosa, versicolor, or virginica, or if a customer will churn or not.**In this lab, we will tackle one of each.**

Part 2: Linear Regression**Concept:** Linear Regression is used to predict a continuous value. It works by finding the best-fitting straight line through the data points. The model learns a "slope" (coefficient) for each feature and an "intercept".* **Problem:** We will predict the `Fare` of a Titanic passenger based on their `Age` and `Pclass`.

```
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
from sklearn.metrics import mean_squared_error

# Load and prepare the data
df = pd.read_csv('https://raw.githubusercontent.com/datasciencedojo/datasets/master/titanic.csv')

# For simplicity, we'll drop rows with missing age
df.dropna(subset=['Age'], inplace=True)

# Define features and target
features = ['Age', 'Pclass']
target_reg = 'Fare'

X_reg = df[features]
y_reg = df[target_reg]

# Split the data
X_train_reg, X_test_reg, y_train_reg, y_test_reg = train_test_split(X_reg, y_reg, test_size=0.2, random_state=42)
```

Task 1: Train and Evaluate a Linear Regression Model**Your Task:**1. Create an instance of the `LinearRegression` model.2. Train the model using the training data (`X_train_reg`, `y_train_reg`).3. Make predictions on the test data.4. Evaluate the model using `mean_squared_error`. This metric tells us the average of the squared differences between the predicted and actual values.

```
# 1. Create the model instance
lr_model = LinearRegression()

# 2. Train the model
lr_model.fit(X_train_reg, y_train_reg)

# 3. Make predictions
y_pred_reg = lr_model.predict(X_test_reg)

# 4. Evaluate the model
import numpy as np
mse = mean_squared_error(y_test_reg, y_pred_reg)
print(f"Mean Squared Error for Fare Prediction: {mse:.2f}")
print(f"The square root of this is {np.sqrt(mse):.2f}, meaning our model is off by about ${np.sqrt(mse):.0f} on average.")
```

```
Mean Squared Error for Fare Prediction: 3364.92
The square root of this is 58.01, meaning our model is off by about $58 on average.
```

Part 3: Logistic Regression**Concept:** Despite its name, Logistic Regression is a **classification** algorithm. It works by calculating the probability that a given input belongs to a certain class. It's one of the most widely used and interpretable classification models.* **Problem:** We will predict whether a passenger `Survived` based on their `Age`, `Pclass`, and `Sex`.

```
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score

# Prepare data for classification
# We need to encode 'Sex' column
df['Sex'] = df['Sex'].map({'male': 0, 'female': 1})

# Define features and target
features_cls = ['Age', 'Pclass', 'Sex']
target_cls = 'Survived'

X_cls = df[features_cls]
y_cls = df[target_cls]

# Split the data
X_train_cls, X_test_cls, y_train_cls, y_test_cls = train_test_split(X_cls, y_cls, test_size=0.2, random_state=42)
```

Task 2: Train and Evaluate a Logistic Regression Model**Your Task:**1. Create an instance of the `LogisticRegression` model.2. Train the model using the classification training data.3. Make predictions on the test data.4. Evaluate the model using `accuracy_score`.

```
# 1. Create the model instance
log_model = LogisticRegression()

# 2. Train the model
log_model.fit(X_train_cls, y_train_cls)

# 3. Make predictions
y_pred_cls = log_model.predict(X_test_cls)

# 4. Evaluate the model
accuracy = accuracy_score(y_test_cls, y_pred_cls)
print(f"Accuracy for Survival Prediction: {accuracy:.2%}")
```

```
Accuracy for Survival Prediction: 74.83%
```

📝 Knowledge Check**Instructions:** Answer the following questions in this markdown cell.1. **In your own words, what is the key difference between a regression problem and a classification problem?**2. **The `LinearRegression` model has an attribute called `.coef_`. After you train the model, print `lr_model.coef_`. What do these numbers represent?**3. **Why did we use `mean_squared_error` to evaluate the regression model but `accuracy_score` for the classification model?** Why wouldn't accuracy be a good metric for the fare prediction task?**1. Regression predicts a continuous number, like a fare price. Classification predicts a category, like survived or not survived. 2. The .coef_ numbers show how much the predicted Fare changes when a feature goes up by 1, while the other feature stays the same. The first number is for Age and the second is for Pclass. Pclass is negative, so a higher class number means a lower fare. 3.Fare is a number that can be anything, so predictions are almost never exactly right. MSE tells us how far off we are on average.**

**Survived is just 0 or 1, so a prediction is either right or wrong, and accuracy just counts how many we got right.**