

Introduction to Algorithms

Lecture 16 Computational Complexity

Xue Chen

xuechen1989@ustc.edu.cn

2024 spring in




Outline

- 1 Introduction
- 2 Undecidable Languages
- 3 Class P of polynomial time algorithms
- 4 Class NP of non-deterministic algorithms
- 5 NP-complete
- 6 More NPC and reductions
- 7 More about Approximation Algorithms

Overview

- 1 We have discussed various methods to design **efficient algorithms**
- 2 Many problems do **not have efficient algorithms**, e.g.




(a) HALTING PROBLEM

Satisfiability $\in NP$

$$(x_1 \vee \neg x_2 \vee x_3) \wedge$$
$$(x_1 \wedge (\neg x_1 \vee x_2) \wedge x_3)$$


(b) SATISFIABILITY



(c) GO GAME PROBLEM

Overview

- 1 We have discussed various methods to design **efficient algorithms**
- 2 Many problems do **not have efficient algorithms**, e.g.



(d) HALTING PROBLEM

Satisfiability $\in NP$

$$(x_1 \vee \neg x_2 \vee x_3) \wedge$$
$$(x_1 \wedge (\neg x_1 \vee x_2) \wedge x_3)$$

(e) SATISFIABILITY



(f) GO GAME PROBLEM


Computational Complexity

Study computational efficiency of problems:

- 1 Can computers solve it?
- 2 How long? Does it have efficient (poly-time) algorithms?

History

- 1 Turing defined the math model of modern computer around 1936




— called Turing Machine

- 2 Basically, Turing Machine is **an automaton with a memory tape**

History

- 1 Turing defined the math model of modern computer around 1936




— called Turing Machine

- 2 Basically, Turing Machine is **an automaton with a memory tape**
- 3 Turing-Church Theorem/Thesis: Any physical computation can be simulated by a Turing machine (with poly-time overhead)

History

- 1 Turing defined the math model of modern computer around 1936



— called Turing Machine

- 2 Basically, Turing Machine is **an automaton with a memory tape**
- 3 Turing-Church Theorem/Thesis: Any physical computation can be simulated by a Turing machine (with poly-time overhead)
- 4 ☺ Turing machine is **simple enough** to argue the limitation of modern computers

Turing Machines

An informal introduction:

- 1 Consider it as a **low-level** programming language — even lower than assembly language
- 2 A fixed number (say ≤ 100) of instructions
- 3 Its description has a fixed number of lines/instructions
- 4 Its input is all $\{0, 1\}$ -strings, i.e., $\{0, 1\}^*$
- 5 Its output is $\{0, 1\}$
- 6 Unbound memory space — different from automata

An Assembly Language Program

```
;
; Program to multiply a number by the constant 6
;
        .ORIG      x3050
        LD         R1, SIX
        LD         R2, NUMBER
        AND        R3, R3, #0           ; Clear R3. It will
                                         ; contain the product.
; The inner loop
;
AGAIN    ADD        R3, R3, R2
        ADD        R1, R1, #-1
        BRp        AGAIN               ; R1 keeps track of
                                         ; the iteration.
;
        HALT
;
NUMBER   .BLKW      1
SIX      .FILL      x0006
;
        .END
```


Math Models

Binary Encoding of Problems — Languages

- 1 Only consider **decision problems** for now: For an instance/input I , the output is either 1 (means **YES**) or 0 (means **NO**)
 - 2 Fix a decision problem Q , encode the instance I as a binary string $enc(I)$ in $\{0, 1\}^*$
 - 3 Define the language of Q as $L_Q = \{enc(I) : Q(I) = 1\}$
- Example 1 **PRIME**: For a binary number $t \in \{0, 1\}^*$, output 1 iff it is a prime. $L_{\text{PRIME}} = \left\{ t_0 \cdots t_n \in \{0, 1\}^* \mid \sum_{i=0}^n t_i \cdot 2^i \text{ is a prime} \right\} = \{10, 11, 101, 111, 1011, 1101, \dots\}$

Math Models

Binary Encoding of Problems — Languages

- 1 Only consider **decision problems** for now: For an instance/input I , the output is either 1 (means **YES**) or 0 (means **NO**)
 - 2 Fix a decision problem Q , encode the instance I as a binary string $enc(I)$ in $\{0, 1\}^*$
 - 3 Define the language of Q as $L_Q = \{enc(I) : Q(I) = 1\}$
- Example 1 **PRIME**: For a binary number $t \in \{0, 1\}^*$, output 1 iff it is a prime. $L_{\text{PRIME}} = \left\{ t_0 \cdots t_n \in \{0, 1\}^* \mid \sum_{i=0}^n t_i \cdot 2^i \text{ is a prime} \right\} = \{10, 11, 101, 111, 1011, 1101, \dots\}$
 - Example 2 **CONNECTIVITY**: For a graph G , output 1 iff G is a connected. $L_{\text{CONN}} = \left\{ T \in \{0, 1\}^* \mid T \text{ presents a connected graph} \right\}$

Overview

Why do we need Turing Machines and binary encodings?

Overview

Why do we need Turing Machines and binary encodings?


- 1 Use simple descriptions to prove that **computers can not solve some problems** (called undecidable) despite running time



Overview


Why do we need Turing Machines and binary encodings?

- 1 Use simple descriptions to prove that **computers can not solve some problems** (called undecidable) despite running time



- 2 Use their binary encodings and executions on simple models to prove that **some problem is the hardest in a class** (called complete) like SAT problems in NP and LP in P

Computational Classes



Undecidable languages

Halting Problem

Outline

- 1 Introduction
- 2 Undecidable Languages
- 3 Class P of polynomial time algorithms
- 4 Class NP of non-deterministic algorithms
- 5 NP-complete
- 6 More NPC and reductions
- 7 More about Approximation Algorithms

Introduction

Main Question

Where is the **limit of computation**? — Are there problems/languages that can not be solved by computers (called undecidable)?

Yes — in fact, many problems

Introduction

Main Question

Where is the **limit of computation**? — Are there problems/languages that can not be solved by computers (called undecidable)?

Yes — in fact, many problems

- ① **Halting Problem**: Given a program M and input x , will M halt on input x within a finite number of steps?

Introduction

Main Question

Where is the **limit of computation**? — Are there problems/languages that can not be solved by computers (called undecidable)?

Yes — in fact, many problems

- 1 **Halting Problem**: Given a program M and input x , will M halt on input x within a finite number of steps?
- 2 **EMPTY**: Given a program M , will it ever output **YES**?

Introduction

Main Question

Where is the **limit of computation**? — Are there problems/languages that can not be solved by computers (called undecidable)?


Yes — in fact, many problems

- 1 **Halting Problem**: Given a program M and input x , will M halt on input x within a finite number of steps?
- 2 **EMPTY**: Given a program M , will it ever output **YES**?
- 3 **ALL**: Given a program M , will it accept any input?
- 4 **EQ**: Given two programs M_1 and M_2 , are they equivalent?

Road Map

To show they are undecidable,

- ① Show Language **UC** is undecidable — the hardness of **UC** is the cornerstone of undecidable theory
- ② Reduce **UC** to **Halting** and other problems



— if a computer solves any other prob, then it solves **UC**, which is impossible from (1)

1st Undecidable Language

Definition

- 1 Sort all programs from 1 to ∞ : M_1, M_2, \dots
- 2 Sort all inputs in $\{0, 1\}^*$ from 1 to ∞ : I_1, I_2, \dots
- 3 For each $\alpha \in \{0, 1\}^*$, consider the natural number corresponding to it

1st Undecidable Language

Definition

- 1 Sort all programs from 1 to ∞ : M_1, M_2, \dots
- 2 Sort all inputs in $\{0, 1\}^*$ from 1 to ∞ : I_1, I_2, \dots
- 3 For each $\alpha \in \{0, 1\}^*$, consider the natural number corresponding to it
- 4 Define $UC(\alpha) = 0$ only if $M_\alpha(I_\alpha) = 1$; o.w. $UC(\alpha) = 1$ when $M_\alpha(I_\alpha) = 0$ or never halts

Theorem 1

UC is undecidable

Halting Problem

Definition

Given a program M and input x , output 1 to indicate that M halts on input x within a finite number of steps

Halting Problem

Definition

Given a program M and input x , output 1 to indicate that M halts on input x within a finite number of steps

- 1 Reduce UC to Halting — direction is very important!
- 2 Halting is decidable \Rightarrow UC is decidable

Halting Problem

Definition

Given a program M and input x , output 1 to indicate that M halts on input x within a finite number of steps

- 1 Reduce UC to Halting — direction is very important!
- 2 Halting is decidable \Rightarrow UC is decidable
- 3 Since THM1, this is impossible. So Halting is undecidable.

EMPTY Problem

Definition

Given a program M , output 1 if $M(x) = 1$ for any $x \in \{0, 1\}^*$.

EMPTY Problem

Definition

Given a program M , output 1 if $M(x) = 1$ for any $x \in \{0, 1\}^*$.

- ① We leave the rest problems in homework
- ② One more question: Is this language decidable or not?

Given a program M , an input x , and t , output 1 if M accepts x in t steps.

EMPTY Problem

Definition

Given a program M , output 1 if $M(x) = 1$ for any $x \in \{0, 1\}^*$.

- ① We leave the rest problems in homework
- ② One more question: Is this language decidable or not?

Given a program M , an input x , and t , output 1 if M accepts x in t steps.

- ③ Next: What is the limit of **efficient computation**?

Outline

- 1 Introduction
- 2 Undecidable Languages
- 3 Class P of polynomial time algorithms
- 4 Class NP of non-deterministic algorithms
- 5 NP-complete
- 6 More NPC and reductions
- 7 More about Approximation Algorithms

Intro

Definition

P is the class of all problems with a (deterministic) polynomial time algorithm — same as $P :=$ class of poly-time algorithms

Consider P captures efficient computation

Definition

P is the class of all problems with a (deterministic) polynomial time algorithm — same as $P :=$ class of poly-time algorithms

Consider P captures efficient computation

- 1 Good News: Definition P is very robust — poly-time reductions keeps the total running in P

Definition

P is the class of all problems with a (deterministic) polynomial time algorithm — same as $P :=$ class of poly-time algorithms

Consider P captures efficient computation

- 1 Good News: Definition P is very robust — poly-time reductions keeps the total running in P
- 2 Issue 1: How about randomized poly-time algorithms? Most researchers believe $\text{Class}(\text{randomized poly-time algorithms}) = P$ 😊
- 3 Issue 2: Definition P is too strict — the algorithm runs in poly-time for **all inputs**. Average-case complexity 😊

Definition

P is the class of all problems with a (deterministic) polynomial time algorithm — same as $P :=$ class of poly-time algorithms

Consider P captures efficient computation

- 1 Good News: Definition P is very robust — poly-time reductions keeps the total running in P
- 2 Issue 1: How about randomized poly-time algorithms? Most researchers believe $\text{Class}(\text{randomized poly-time algorithms}) = P$ 😊
- 3 Issue 2: Definition P is too strict — the algorithm runs in poly-time for **all inputs**. Average-case complexity 😊
- 4 Issue 3: Lack of precision, is n^{10} efficient? 😞
- 5 Issue 4: How about quantum algorithms? Not sure whether general quantum computers are realizable 😞

Relation between Languages

Given two problems A and B , how to compare their hardness?


- 1 Prime is **equivalent** to composite
- 2 How to compare connectivity and set cover?

Relation between Languages

Given two problems A and B , how to compare their hardness?

- 1 Prime is **equivalent** to composite
- 2 How to compare connectivity and set cover?

Poly Time Reduction (a.k.a. Cook/Karp Reduction)



$A \leq_p B$: poly-time reduction from A to B

Requirements:

- 1 Reduction time is polynomial
- 2 Map **Yes** instance to **Yes** instance and **No** instance to **No** — the most technical part

— for now, $A \leq_p B$ means that B is harder than A ; essentially,
 $B \in P \Rightarrow A \in P$

Complete problems

Complete Problems of a class

A problem P is complete in the class \mathcal{C} only if (1) $P \in \mathcal{C}$; (2) any problem $Q \in \mathcal{C}$ has a reduction $Q \leq_p P$

— informally, P is the “hardest” problem in \mathcal{C}

- 1 If there is a poly-time algorithm of P , then every problem in \mathcal{C} has poly-time algorithms


Complete problems

Complete Problems of a class

A problem P is complete in the class \mathcal{C} only if (1) $P \in \mathcal{C}$; (2) any problem $Q \in \mathcal{C}$ has a reduction $Q \leq_p P$

— informally, P is the “hardest” problem in \mathcal{C}

- 1 If there is a poly-time algorithm of P , then every problem in \mathcal{C} has poly-time algorithms
- 2 Example 1: Linear programming is complete in P



- 3 Another P-complete problem: Given a program M , input x , and string S , determine $M(x) = 1$ in $|S|$ steps or not

Outline

- 1 Introduction
- 2 Undecidable Languages
- 3 Class P of polynomial time algorithms
- 4 Class NP of non-deterministic algorithms
- 5 NP-complete
- 6 More NPC and reductions
- 7 More about Approximation Algorithms

Background

There are many problems not in P:

Example

Given a program M , input x , and number N , determine $M(x) = 1$ in N steps or not

- 1 This problem is exponential-time complete.
- 2 Question: What's difference between the P-complete problem —
Given M , x , and string S , determine $M(x) = 1$ in $|S|$ steps or not?


Background

There are many problems not in P:

Example

Given a program M , input x , and number N , determine $M(x) = 1$ in N steps or not

- 1 This problem is exponential-time complete.
- 2 Question: What's difference between the P-complete problem —
Given M , x , and string S , determine $M(x) = 1$ in $|S|$ steps or not?
- 3 However, this problem is not very interesting
- 4 The most interesting class **probably not** in P is NP



What is NP?

The original definition is by **non-deterministic** Turing machine. We will consider the **modern interpretation**:

Definition of NP

A language/problem L is in NP only if \exists an algorithm, called verifier, V such that

- ① For any $x \in L$, \exists a proof y s.t. $V(x, y) = 1$ in $\text{poly}(|x|)$ time — completeness
 - ② For any $x \notin L$, for any proof y , $V(x, y) = 0$ in $\text{poly}(|x|)$ time — soundness
-
- ① $V(x, \cdot)$ is a non-deterministic algorithm but $V(x, y)$ is deterministic

What is NP?

The original definition is by **non-deterministic** Turing machine. We will consider the **modern interpretation**:


Definition of NP

A language/problem L is in NP only if \exists an algorithm, called verifier, V such that

- ① For any $x \in L$, \exists a proof y s.t. $V(x, y) = 1$ in $\text{poly}(|x|)$ time — completeness
 - ② For any $x \notin L$, for any proof y , $V(x, y) = 0$ in $\text{poly}(|x|)$ time — soundness
-
- ① $V(x, \cdot)$ is a non-deterministic algorithm but $V(x, y)$ is deterministic
 - ② In Case 1, y depends on x
 - ③ $|y| = \text{poly}(n)$ because V runs in poly-time
 - ④ Example 1: $L_{\text{CLIQUE}} = \left\{ (G, k) : \exists \text{ a clique of size } k \text{ in } G \right\}$


Example 1: Clique

- 1 y is a subset of k vertices in G
- 2 $V((G, k), y)$ checks all pairs in y are connected in G




Example 1: Clique

- 1 y is a subset of k vertices in G
- 2 $V((G, k), y)$ checks all pairs in y are connected in G
- 3 Completeness: If $(G, k) \in L_{\text{CLIQUE}}$ — \exists a k -clique in G , y encodes that subset



Example 1: Clique

- ① y is a subset of k vertices in G
- ② $V((G, k), y)$ checks all pairs in y are connected in G
- ③ Completeness: If $(G, k) \in L_{\text{CLIQUE}}$ — \exists a k -clique in G , y encodes that subset
- ④ Soundness: If $(G, k) \notin L_{\text{CLIQUE}}$ — \forall k -subset in G , V rejects it since it is not a clique



Example 2: SAT problem

- 1 Description: each instance Φ has n Boolean variables x_1, \dots, x_n and m clauses C_1, \dots, C_m
- 2 $L_{\text{SAT}} = \left\{ \Phi \text{ is satisfiable} : \exists \sigma \in \{T, F\}^n \text{ s.t. } C_1(\sigma) = C_2(\sigma) = \dots = C_m(\sigma) = T \right\}$

$$\begin{aligned} C_1: & x_1 \vee x_2 \vee \bar{x}_4 \vee \bar{x}_n \\ C_2: & \bar{x}_3 \vee \bar{x}_{n-2} \vee \bar{x}_{n-1} \vee x_n \\ C_3: & x_5 \\ C_4: & x_6 \vee x_7 \\ & \vdots \\ C_m: & x_1 \vee x_2 \vee x_3 \vee \dots \vee x_n \end{aligned}$$

Example 2: SAT problem

- 1 Description: each instance Φ has n Boolean variables x_1, \dots, x_n and m clauses C_1, \dots, C_m
- 2 $L_{\text{SAT}} = \left\{ \Phi \text{ is satisfiable} : \exists \sigma \in \{T, F\}^n \text{ s.t. } C_1(\sigma) = C_2(\sigma) = \dots = C_m(\sigma) = T \right\}$
- 3 y is a string $\in \{T, F\}^n$ as the assignment on x
- 4 V verifies $C_1(y) = C_2(y) = \dots = C_m(y) = T$

$$\begin{aligned} C_1: & x_1 \vee x_2 \vee \bar{x}_4 \vee \bar{x}_n \\ C_2: & \bar{x}_3 \vee \bar{x}_{n-2} \vee \bar{x}_{n-1} \vee x_n \\ C_3: & x_5 \\ C_4: & x_6 \vee x_7 \\ & \vdots \\ C_m: & x_1 \vee x_2 \vee x_3 \vee \dots \vee x_n \end{aligned}$$

Example 2: SAT problem

- 1 Description: each instance Φ has n Boolean variables x_1, \dots, x_n and m clauses C_1, \dots, C_m
- 2 $L_{\text{SAT}} = \left\{ \Phi \text{ is satisfiable} : \exists \sigma \in \{T, F\}^n \text{ s.t. } C_1(\sigma) = C_2(\sigma) = \dots = C_m(\sigma) = T \right\}$
- 3 y is a string $\in \{T, F\}^n$ as the assignment on x
- 4 V verifies $C_1(y) = C_2(y) = \dots = C_m(y) = T$
- 5 Equivalent to define Φ as a CNF $C_1 \wedge C_2 \wedge C_3 \wedge \dots \wedge C_m$

$$\begin{aligned} C_1: & x_1 \vee x_2 \vee \bar{x}_4 \vee \bar{x}_n \\ C_2: & \bar{x}_3 \vee \bar{x}_{n-2} \vee \bar{x}_{n-1} \vee x_n \\ C_3: & x_5 \\ C_4: & x_6 \vee x_7 \\ & \vdots \\ C_m: & x_1 \vee x_2 \vee x_3 \vee \dots \vee x_n \end{aligned}$$

P vs NP

NP captures many interesting problems and is probably $\not\subseteq P$

① $P \subseteq NP$: Why?

P vs NP

NP captures many interesting problems and is probably $\not\subseteq P$

- 1 $P \subseteq NP$: Why?
- 2 We believe $P \neq NP$: Intuitively, one can verify a proof \nRightarrow One can generate that proof
— one million dollar problem

P vs NP


NP captures many interesting problems and is probably $\not\subseteq P$

- 1 $P \subseteq NP$: Why?
- 2 We believe $P \neq NP$: Intuitively, one can verify a proof \nRightarrow One can generate that proof — one million dollar problem
- 3 Next: How to prove $P \neq NP$ formally?
Find a problem and prove it does not have poly-time algorithms

P vs NP

NP captures many interesting problems and is probably $\not\subseteq P$

- 1 $P \subseteq NP$: Why?
- 2 We believe $P \neq NP$: Intuitively, one can verify a proof \nRightarrow One can generate that proof — one million dollar problem
- 3 Next: How to prove $P \neq NP$ formally?
Find a problem and prove it does not have poly-time algorithms



- 4 Which problem? — NP-complete

Outline

- 1 Introduction
- 2 Undecidable Languages
- 3 Class P of polynomial time algorithms
- 4 Class NP of non-deterministic algorithms
- 5 NP-complete
- 6 More NPC and reductions
- 7 More about Approximation Algorithms

NP-complete

NP-complete: "Hardest" problems in NP under poly-time reduction

Definition

A problem L is NP-complete iff (1) $L \in \text{NP}$; (2) for any $Q \in \text{NP}$, $Q \leq_p L$.

NP-complete

NP-complete: "Hardest" problems in NP under poly-time reduction

Definition

A problem L is NP-complete iff (1) $L \in \text{NP}$; (2) for any $Q \in \text{NP}$, $Q \leq_p L$.

- ① THM 34.4 in **CLRS**: $P \neq \text{NP} \Leftrightarrow \forall \text{ NP-complete problem } L \notin P$
- ② A concrete plan to show $P \neq \text{NP}$: (1) Find an NP-complete problem L ; (2) Prove that L does not admit poly-time algorithms

NP-complete

NP-complete: "Hardest" problems in NP under poly-time reduction

Definition

A problem L is NP-complete iff (1) $L \in \text{NP}$; (2) for any $Q \in \text{NP}$, $Q \leq_p L$.

- 1 THM 34.4 in **CLRS**: $P \neq \text{NP} \Leftrightarrow \forall \text{ NP-complete problem } L \notin P$
- 2 A concrete plan to show $P \neq \text{NP}$: (1) Find an NP-complete problem L ; (2) Prove that L does not admit poly-time algorithms
- 3 Good news: A long list of natural NP-complete problems: Clique, SAT, independent set, ...
- 4 Bad news: Extremely difficult to show: a problem *does not* have poly-time algorithms

NP-complete

NP-complete: "Hardest" problems in NP under poly-time reduction

Definition

A problem L is NP-complete iff (1) $L \in \text{NP}$; (2) for any $Q \in \text{NP}$, $Q \leq_p L$.


- 1 THM 34.4 in **CLRS**: $P \neq \text{NP} \Leftrightarrow \forall \text{ NP-complete problem } L \notin P$
- 2 A concrete plan to show $P \neq \text{NP}$: (1) Find an NP-complete problem L ; (2) Prove that L does not admit poly-time algorithms
- 3 Good news: A long list of natural NP-complete problems: Clique, SAT, independent set, ...
- 4 Bad news: Extremely difficult to show: a problem *does not* have poly-time algorithms
- 5 Since $P \neq \text{NP}$ is very plausible, another way: problem Q is NP-complete means $Q \notin \text{Ps.t.}$ Q does not have a poly-time algorithm

More about NP

- 1 If we can not design poly-time algorithms for Q , showing Q is NP-complete gives an excuse

More about NP


- 1 If we can not design poly-time algorithms for Q , showing Q is NP-complete gives an excuse
- 2 Do not feel frustrated for $P \neq NP$ — that's a good news for cryptography



In fact, cryptography assumptions are much stronger than $P \neq NP$

More about NP

- 1 If we can not design poly-time algorithms for Q , showing Q is NP-complete gives an excuse
- 2 Do not feel frustrated for $P \neq NP$ — that's a good news for cryptography



In fact, cryptography assumptions are much stronger than $P \neq NP$


- 3 Surprisingly, very few hard problems are presumably not NP-complete: graph isomorphism, factoring, . . . ;

NP-complete

Next question: How to show a problem is NP-complete?

Recall definition

A problem L is NP-complete iff (1) $L \in \text{NP}$; (2) for any $Q \in \text{NP}$, $Q \leq_p L$.




NP-complete

Next question: How to show a problem is NP-complete?

Recall definition

A problem L is NP-complete iff (1) $L \in \text{NP}$; (2) for any $Q \in \text{NP}$, $Q \leq_p L$.

(1) is easy. But (2) is **challenging** — Enough to show $R \leq_R Q$ for some $R \in \text{NP-complete}$.



NP-complete


Next question: How to show a problem is NP-complete?

Recall definition

A problem L is NP-complete iff (1) $L \in \text{NP}$; (2) for any $Q \in \text{NP}$, $Q \leq_p L$.

(1) is easy. But (2) is **challenging** — Enough to show $R \leq_R Q$ for some $R \in \text{NP-complete}$.

- 1 But which problem shall we begin with?
- 2 Roadmap of NPC problems





CIRCUIT-SAT

Description

$L_{\text{CIRCUIT-SAT}} = \{C : C \text{ is satisfiable}\}$ where circuit C is a DAG with AND \wedge , OR \vee , NOT \neg gates and n input variables x_1, \dots, x_n

Input variables



CIRCUIT-SAT (II)

Theorem 34.7


$L_{\text{CIRCUIT-SAT}}$ is NP-complete.

CIRCUIT-SAT (II)

Theorem 34.7

$L_{\text{CIRCUIT-SAT}}$ is NP-complete.

① Lemma 34.5 in CLRS: $L_{\text{CIRCUIT-SAT}}$ is in NP




$A \leq_p B$: poly-time reduction from A to B

CIRCUIT-SAT (II)

Theorem 34.7

$L_{\text{CIRCUIT-SAT}}$ is NP-complete.

- ① Lemma 34.5 in CLRS: $L_{\text{CIRCUIT-SAT}}$ is in NP





$A \leq_p B$: poly-time reduction from A to B

- ② Lemma 34.6 in CLRS: $\forall Q \in \text{NP}$, $Q \leq_p L_{\text{CIRCUIT-SAT}}$ — roughly, fix V and x then treat proof y as Boolean variables such that execution on the hardware level is a circuit


- 1 To show $Q \leq_p L_{\text{CIRCUIT-SAT}}$, consider Q 's verifier V such that $Q(x) = 1$ iff $\exists y$ s.t. $V(x, y) = 1$.
- 2 Our goal is to show a reduction that given V and x , outputs a circuit $C_{V,x}(y)$ s.t. $C_{V,x}(y) = V(x, y)$

- 1 To show $Q \leq_p L_{\text{CIRCUIT-SAT}}$, consider Q 's verifier V such that $Q(x) = 1$ iff $\exists y$ s.t. $V(x, y) = 1$.
- 2 Our goal is to show a reduction that given V and x , outputs a circuit $C_{V,x}(y)$ s.t. $C_{V,x}(y) = V(x, y)$
- 3 In one sentence, $C_{V,x}(y)$ is the circuit computing $V(I, y)$ in hardware level






- 1 Because the time and memory space of V is $\text{poly}(n)$, its size is $\text{poly}(n)$




- ① Because the time and memory space of V is $\text{poly}(n)$, its size is $\text{poly}(n)$
- ② We can compute $C_{V,x}(y)$ in $\text{poly}(n)$ time




- 1 Because the time and memory space of V is $\text{poly}(n)$, its size is $\text{poly}(n)$
 - 2 We can compute $C_{V,x}(y)$ in $\text{poly}(n)$ time
 - 3 Because $C_{V,x}(y) = V(x, y)$ for any $y, x \in L_Q$ iff $C_{V,x}$ is satisfiable
- ☺

Road Map



- 1 CIRCUIT-SAT is the 1st non-trivial NP-complete problem

Road Map



- 1 CIRCUI-T-SAT is the 1st non-trivial NP-complete problem
- 2 Next show SAT is NP-complete:

Each instance Φ has n Boolean variables x_1, \dots, x_n and m clauses C_1, \dots, C_m such that $L_{\text{SAT}} = \{\Phi : \exists \sigma \in \{T, F\}^n \text{ s.t. } C_1(\sigma) = C_2(\sigma) = \dots = C_m(\sigma) = T\}$

SAT Problem

Theorem 34.9 in CLRS

SAT is NP-complete

SAT Problem

Theorem 34.9 in CLRS

SAT is NP-complete

- 1 SAT is in NP



SAT Problem

Theorem 34.9 in CLRS

SAT is NP-complete

- 1 SAT is in NP
- 2 Reduce CIRCUIT-SAT \rightarrow SAT

Input variables



$$C_1: x_1 \vee x_2 \vee \bar{x}_4 \vee \bar{x}_n$$

$$C_2: \bar{x}_3 \vee \bar{x}_{n-2} \vee \bar{x}_{n-1} \vee x_n$$

$$C_3: x_5$$


$$C_4: x_6 \vee x_7$$

⋮

$$C_m: x_1 \vee x_2 \vee x_6 \vee \dots \vee x_n$$

Basic Idea

- ① Assign a Boolean variable to each gate to denote its evaluation:



- ② Question: How to make sure $x_4 = \overline{x_3}$ and $x_5 = x_1 \vee x_2$?
- ③ Completeness & Soundness: $\exists x$ s.t. $C(x) = \text{True} \iff \exists \sigma$ s.t. all clauses in $\Phi(\sigma)$ are true

3-SAT

Definition: Each instance Φ has n Boolean variables x_1, \dots, x_n and m clauses C_1, \dots, C_m of width 3 such that

$$L_{3\text{SAT}} = \{\Phi : \exists \sigma \in \{T, F\}^n \text{ s.t. } C_1(\sigma) = C_2(\sigma) = \dots = C_m(\sigma) = T\}$$

Theorem 34.10 in CLRS

3SAT (CNF) is NP-complete.

3-SAT

Definition: Each instance Φ has n Boolean variables x_1, \dots, x_n and m clauses C_1, \dots, C_m of width 3 such that

$$L_{3SAT} = \{\Phi : \exists \sigma \in \{T, F\}^n \text{ s.t. } C_1(\sigma) = C_2(\sigma) = \dots = C_m(\sigma) = T\}$$

Theorem 34.10 in CLRS

3SAT (CNF) is NP-complete.


Proof Sketch:

- 1 3SAT is in NP
- 2 Reduce SAT to 3SAT

Outline

- 1 Introduction
- 2 Undecidable Languages
- 3 Class P of polynomial time algorithms
- 4 Class NP of non-deterministic algorithms
- 5 NP-complete
- 6 More NPC and reductions
- 7 More about Approximation Algorithms


Overview



To show a problem Q is NP-complete

- 1 Easy part: $Q \in \text{NP}$
- 2 Tricky part: Reduce a NP-complete problem (known ones like CIRCUI-T-SAT, SAT, 3SAT) to Q

Clique




G with a clique of 7 vertices

Theorem 34.11 in CLRS

$L_{\text{CLIQUE}} := \{(G, k) : \exists \text{ a } k\text{-clique in } G\}$ is NP-complete.

Clique



G with a clique of 7 vertices

Theorem 34.11 in CLRS

$L_{\text{CLIQUE}} := \{(G, k) : \exists \text{ a } k\text{-clique in } G\}$ is NP-complete.

Proof Sketch:

- 1 It is in NP.
- 2 Reduce 3SAT to CLIQUE.

Discussion

- 1 Gadgets are the key in reductions — more gadgets next!
- 2 We only discussed decision problem so far: Given (G, k) , output YES to indicate \exists a k -clique in G .

Discussion


- 1 Gadgets are the key in reductions — more gadgets next!
- 2 We only discussed decision problem so far: Given (G, k) , output YES to indicate \exists a k -clique in G .
- 3 How about optimization problem: Given G , find the largest clique in G ?
- 4 Question: Is the optimization problem NP-complete?

Discussion

- 1 Gadgets are the key in reductions — more gadgets next!
- 2 We only discussed decision problem so far: Given (G, k) , output **YES** to indicate \exists a k -clique in G .
- 3 How about **optimization** problem: Given G , find **the largest clique** in G ?
- 4 Question: Is the optimization problem NP-complete?
— While it is harder than the decision problem, can not prove it is in NP




Discussion

- 1 Gadgets are the key in reductions — more gadgets next!
- 2 We only discussed decision problem so far: Given (G, k) , output YES to indicate \exists a k -clique in G .
- 3 How about optimization problem: Given G , find the largest clique in G ?
- 4 Question: Is the optimization problem NP-complete?
— While it is harder than the decision problem, can not prove it is in NP 
- 5 Definition: For a problem P , if $Q \leq_p P$ for any $Q \in \text{NP}$, call P NP-hard
- 6 Examples of NP-hard: Largest clique in G ; find an assignment to maximize # clauses for 3SAT

Set Cover

A **vertex cover** of $G = (V, E)$ is a subset $S \subseteq V$ such that every edge has at least one endpoint in S




Theorem 34.12 in **CLRS**

$L_{\text{Vertex-Cover}} = \{(G, k) : G \text{ has a vertex cover of size } k\}$ is NP-complete

Set Cover

A **vertex cover** of $G = (V, E)$ is a subset $S \subseteq V$ such that every edge has at least one endpoint in S



Theorem 34.12 in **CLRS**

$L_{\text{Vertex-Cover}} = \{(G, k) : G \text{ has a vertex cover of size } k\}$ is NP-complete

- 1 $L_{\text{Vertex-Cover}}$ is in NP
- 2 Reduce **CLIQUE** to Vertex-Cover

Subset Sum

Theorem 34.15 in CLRS

$L_{\text{Subset-Sum}} = \left\{ \langle S = (s_1, \dots, s_n), t \rangle : \exists S' \subseteq S \text{ with summation} = t \right\}$ is NP-complete

- 1 $L_{\text{Subset-Sum}}$ is in NP
- 2 Reduce 3SAT to Subset-Sum

Reduction


$$C_1 = x_1 \vee \overline{x_2} \vee \overline{x_3}, C_2 = \overline{x_1} \vee \overline{x_2} \vee \overline{x_3}, C_3 = \overline{x_1} \vee \overline{x_2} \vee x_3, C_4 = x_1 \vee x_2 \vee x_3$$

		x_1	x_2	x_3	C_1	C_2	C_3	C_4
v_1	=	1	0	0	1	0	0	1
v'_1	=	1	0	0	0	1	1	0
v_2	=	0	1	0	0	0	0	1
v'_2	=	0	1	0	1	1	1	0
v_3	=	0	0	1	0	0	1	1
v'_3	=	0	0	1	1	1	0	0
s_1	=	0	0	0	1	0	0	0
s'_1	=	0	0	0	2	0	0	0
s_2	=	0	0	0	0	1	0	0
s'_2	=	0	0	0	0	2	0	0
s_3	=	0	0	0	0	0	1	0
s'_3	=	0	0	0	0	0	2	0
s_4	=	0	0	0	0	0	0	1
s'_4	=	0	0	0	0	0	0	2
t	=	1	1	1	4	4	4	4

More NP-hard Problems

Max Independent Set

Given a graph G , it is NP-hard to find the maximal independent set.



Which problem shall we reduce from?

Max Cut

Theorem

Given a graph G , it is NP-hard to find a max cut.


Reduction from Max Independent Set:

Max Cut

Theorem

Given a graph G , it is NP-hard to find a max cut.

Reduction from Max Independent Set: Given $G = (V, E)$ from MIS, construct $G' = (V', E')$ for Max Cut:




$$V' = x \cup V \cup \{u_e, v_e : \forall e \in E\}$$

$$E' = \{(x, v) : \forall v \in V\} \cup \{e\text{-gadget} : \forall e \in E\}$$


where $(u, v)\text{-gadget} := (x, u_e), (x, v_e), (u, u_e), (v, v_e), (u_e, v_e)$

Analysis




- 1 \Rightarrow If $I \subset V$ is independent of size k , define a cut $S := I$ then for each (u, v) -gadget, add u_e to S if $v \in S$ or add v_e to S if $u \in S$
- 2 OBS: cut S is $|I| + 4 \cdot |E|$

Analysis



- 1 \Rightarrow If $I \subset V$ is independent of size k , define a cut $S := I$ then for each (u, v) -gadget, add u_e to S if $v \in S$ or add v_e to S if $u \in S$
- 2 OBS: cut S is $|I| + 4 \cdot |E|$
- 3 \Leftarrow Given cut $S \subset V'$ of $k + 4 \cdot |E|$ edges, assume $x \notin S$
- 4 Consider $I := S \cap V$ — suppose $\exists m(I)$ edges inside I s.t. it is not independent

Analysis



- ① \Rightarrow If $I \subset V$ is independent of size k , define a cut $S := I$ then for each (u, v) -gadget, add u_e to S if $v \in S$ or add v_e to S if $u \in S$
- ② OBS: cut S is $|I| + 4 \cdot |E|$
- ③ \Leftarrow Given cut $S \subset V'$ of $k + 4 \cdot |E|$ edges, assume $x \notin S$
- ④ Consider $I := S \cap V$ — suppose $\exists m(I)$ edges inside I s.t. it is not independent
- ⑤ For a gadget of $e = (u, v)$, if both u and $v \in I$, S cuts at most 3 edges in this gadget. Otherwise, S cuts 4 edges.
- ⑥ $E(S, S') \leq |I| + 4 \cdot |E| - |m(I)| \Rightarrow$ deleting one point in each $m(I)$ provides an independent set of size $|I| - |m(I)| \geq k$

2-SAT

2-SAT

- 1 n Boolean variables $x_1, \dots, x_n \in \{T, F\}$ and m clauses of **width 2** like $x_1 \vee \overline{x_2}, \overline{x_3} \vee \overline{x_4}, x_2 \vee x_3, \dots$
- 2 Find an assignment to satisfy all clauses.

Different from 3-SAT, 2-SAT is in P; however, MAX-2-SAT is NP-hard

- 1 Why 2-SAT \in P?

2-SAT

2-SAT

- 1 n Boolean variables $x_1, \dots, x_n \in \{T, F\}$ and m clauses of **width 2** like $x_1 \vee \overline{x_2}, \overline{x_3} \vee \overline{x_4}, x_2 \vee x_3, \dots$
- 2 Find an assignment to satisfy all clauses.

Different from 3-SAT, 2-SAT is in P; however, MAX-2-SAT is NP-hard

- 1 Why 2-SAT \in P?
- 2 $x_1 \vee \overline{x_2}$ implies $x_1 = F \Rightarrow x_2 = F$ and $x_2 = T \Rightarrow x_1 = T$
- 3 Construct a directed graph on $2n$ vertices and draw the above $2m$ relations

2-SAT

2-SAT

- 1 n Boolean variables $x_1, \dots, x_n \in \{T, F\}$ and m clauses of **width 2** like $x_1 \vee \overline{x_2}$, $\overline{x_3} \vee \overline{x_4}$, $x_2 \vee x_3, \dots$
- 2 Find an assignment to satisfy all clauses.

Different from 3-SAT, 2-SAT is in P; however, MAX-2-SAT is NP-hard

- 1 Why 2-SAT \in P?
- 2 $x_1 \vee \overline{x_2}$ implies $x_1 = F \Rightarrow x_2 = F$ and $x_2 = T \Rightarrow x_1 = T$
- 3 Construct a directed graph on $2n$ vertices and draw the above $2m$ relations
- 4 If \exists a cycle contains $x_i = T$ and $x_i = F$, no solution
- 5 Otherwise, assign a variable to T and repeat it

Max-2-SAT

Max-2-SAT

- 1 n Boolean variables $x_1, \dots, x_n \in \{T, F\}$ and m clauses of **width 2** like $x_1 \vee \overline{x_2}, \overline{x_3} \vee \overline{x_4}, x_2 \vee x_3, \dots$
- 2 Find an assignment to **maximize # good clauses**

Reduction from 3-SAT:

Max-2-SAT

Max-2-SAT

- 1 n Boolean variables $x_1, \dots, x_n \in \{T, F\}$ and m clauses of **width 2** like $x_1 \vee \overline{x_2}, \overline{x_3} \vee \overline{x_4}, x_2 \vee x_3, \dots$
- 2 Find an assignment to **maximize # good clauses**

Reduction from 3-SAT:

- 1 For each clause $C = x \vee y \vee z$ in 3-SAT, consider 10 clauses in 2-SAT with an extra variable w_C
- 2 $x, y, z, w_C, \overline{x} \vee \overline{y}, \overline{x} \vee \overline{z}, \overline{y} \vee \overline{z}, x \vee \overline{w_C}, y \vee \overline{w_C}, z \vee \overline{w_C}$

Max-2-SAT

Max-2-SAT

- 1 n Boolean variables $x_1, \dots, x_n \in \{T, F\}$ and m clauses of **width 2** like $x_1 \vee \overline{x_2}, \overline{x_3} \vee \overline{x_4}, x_2 \vee x_3, \dots$
- 2 Find an assignment to **maximize # good clauses**

Reduction from 3-SAT:

- 1 For each clause $C = x \vee y \vee z$ in 3-SAT, consider 10 clauses in 2-SAT with an extra variable w_C
- 2 $x, y, z, w_C, \overline{x} \vee \overline{y}, \overline{x} \vee \overline{z}, \overline{y} \vee \overline{z}, x \vee \overline{w_C}, y \vee \overline{w_C}, z \vee \overline{w_C}$
- 3 $C(\sigma) = \text{True} \Rightarrow 7$ of them are satisfied with some w_C ; otherwise at most 6
- 4 Claim: 3-SAT is satisfiable $\Leftrightarrow \text{value(2-SAT)} = 7m$

Discussion

- 1 There are poly-time algorithms for special cases of Vertex-Cover and Subset-Sum
- 2 Example 1: Vertex-Cover of bipartite graphs is in P
- 3 Example 2: Subset-Sum of small integers is in P

Discussion

- 1 There are poly-time algorithms for **special cases** of **Vertex-Cover** and **Subset-Sum**
- 2 Example 1: Vertex-Cover of **bipartite graphs** is in P
- 3 Example 2: Subset-Sum of **small integers** is in P
- 4 There are various ways to design the reductions!

Discussion


- 1 There are poly-time algorithms for special cases of Vertex-Cover and Subset-Sum
- 2 Example 1: Vertex-Cover of bipartite graphs is in P
- 3 Example 2: Subset-Sum of small integers is in P
- 4 There are various ways to design the reductions!
- 5 Most important thing: The direction is from a known NP-complete problem to this problem!

Outline

- 1 Introduction
- 2 Undecidable Languages
- 3 Class P of polynomial time algorithms
- 4 Class NP of non-deterministic algorithms
- 5 NP-complete
- 6 More NPC and reductions
- 7 More about Approximation Algorithms

Introduction

Many interesting problems, like finding the smallest **Vertex-Cover** in G , are NP-hard




Question

In both theory and practice, what can we do for NP-hard problems?

Introduction

Many interesting problems, like finding the smallest **Vertex-Cover** in G , are NP-hard




Question

In both theory and practice, what can we do for NP-hard problems?

- 1 Exhaustive Search (for SAT problems)
- 2 Local search heuristics (like evolution)

Introduction

Many interesting problems, like finding the smallest **Vertex-Cover** in G , are NP-hard



Question

In both theory and practice, what can we do for NP-hard problems?

- 1 Exhaustive Search (for SAT problems)
- 2 Local search heuristics (like evolution)
- 3 Approximation Algorithms

Approximation Algorithms

For an optimization problem like **MAX-2-SAT**, it may take exponential time to find the optimal solution whose value is **OPT**

Key Insight

Design a trade-off between time and accuracy

Approximation Algorithms

For an optimization problem like **MAX-2-SAT**, it may take exponential time to find the optimal solution whose value is **OPT**

Key Insight

Design a trade-off between time and accuracy

- 1 This is an important idea in CS: in big data algorithms, design trade-offs between space and accuracy

Approximation Algorithms

For an optimization problem like **MAX-2-SAT**, it may take exponential time to find the optimal solution whose value is **OPT**

Key Insight

Design a trade-off between time and accuracy

- 1 This is an important idea in CS: in big data algorithms, design trade-offs between space and accuracy
- 2 What do we mean accuracy?

Approximation Algorithms

For an optimization problem like **MAX-2-SAT**, it may take exponential time to find the optimal solution whose value is **OPT**

Key Insight

Design a trade-off between time and accuracy

- 1 This is an important idea in CS: in big data algorithms, design trade-offs between space and accuracy
- 2 What do we mean accuracy?
- 3 Suppose our algorithm finds a solution with value **ANS**
- 4 Define **ANS/OPT** as the approximation ratio — > 1 for minimizations and < 1 for maximizations

Vertex-Cover

Given G , find a vertex-cover with a minimum size

Theorem 35.1 in [CLRS](#)

There are poly-time algorithms that guarantee a 2-approximation

Vertex-Cover

Given G , find a vertex-cover with a minimum size

Theorem 35.1 in CLRS

There are poly-time algorithms that guarantee a 2-approximation


Recall that for Set-Cover, the approximation algorithm is $\ln n$.

Traveling Salesman Problem — Hamilton Cycle


Description: Given a weighted graph $G = (V, E)$, find a sequence $\vec{u} = (u_0, \dots, u_n)$ of V s.t. (1) $u_0 = u_n$ and each vertex appears once; (2) the total weight $\sum_{i=1}^k c(u_{i-1}, u_i)$ is minimum.

Traveling Salesman Problem — Hamilton Cycle

Description: Given a weighted graph $G = (V, E)$, find a sequence $\vec{u} = (u_0, \dots, u_n)$ of V s.t. (1) $u_0 = u_n$ and each vertex appears once; (2) the total weight $\sum_{i=1}^k c(u_{i-1}, u_i)$ is minimum.



Input
(assume Euclidean distances)




An Optimal Tour: 14.715

THM 35.2 in CLRS

If $c(\cdot, \cdot)$ satisfies **the triangle inequality**, there are poly-time algorithms with ≤ 2 -approximation ratios

Traveling Salesman Problem — Hamilton Cycle

Description: Given a weighted graph $G = (V, E)$, find a sequence $\vec{u} = (u_0, \dots, u_n)$ of V s.t. (1) $u_0 = u_n$ and each vertex appears once; (2) the total weight $\sum_{i=1}^k c(u_{i-1}, u_i)$ is minimum.




THM 35.2 in CLRS


If $c(\cdot, \cdot)$ satisfies **the triangle inequality**, there are poly-time algorithms with ≤ 2 -approximation ratios

Remark: The triangle inequality is necessary, otherwise no constant approx unless $P=NP$ — Section 35.2.2 in CLRS

2-Approx of TSP




Step 1: MST



Step 2: Preorder Traversal Full Walk W


a b c b h b a d e f e g e d a




Step 3: Hamiltonian Cycle H : 19.074

- ① Step 1: Find a MST T of G
- ② Step 2: Find the preorder walk W of T
- ③ Step 3: Output the Hamilton cycle H of W

2-Approx of TSP




Step 1: MST



Step 2: Preorder Traversal Full Walk W

a b c b h b a d e f e g e d a




Step 3: Hamiltonian Cycle H : 19.074

- ① Step 1: Find a MST T of G
- ② Step 2: Find the preorder walk W of T
- ③ Step 3: Output the Hamilton cycle H of W
- ④ Analysis: $c(H) \leq c(W) = 2c(T)$ and $c(T) \leq c(H^*)$ for the optimal solution

1.5-Approx of TSP


Christofides Algorithm — short-cut via the Eulerian Tour



1 Find a MST T

1.5-Approx of TSP


Christofides Algorithm — short-cut via the Eulerian Tour



- 1 Find a MST T
- 2 $M := \text{min-cost matching of odd degree nodes in } T$
- 3 Find the Eulerian tour E on $T \cup M$
- 4 Output the Hamilton cycle H of E

1.5-Approx of TSP

Christofides Algorithm — short-cut via the Eulerian Tour



- 1 Find a MST T
- 2 $M := \text{min-cost matching of odd degree nodes in } T$
- 3 Find the Eulerian tour E on $T \cup M$
- 4 Output the Hamilton cycle H of E
- 5 Analysis: $c(H) \leq c(M) + c(T)$ and $c(M) \leq c(H^*)/2$

Approximating MIS

Here is a **strange** claim about approximating max-independent-set

Claim

For some $\alpha < 1$, if \exists an α -approximation algorithm in P for MIS, then $\sqrt{\alpha}$ -approximating MIS is also in P.

- 1 Reduction: Given a graph $G = (V, E)$, consider its 2-fold OR-power $H = (V^2, E_H)$ s.t.

$$(u_1, u_2) \sim (v_1, v_2) \text{ iff } u_1 \sim v_1 \text{ or } u_2 \sim v_2$$

Approximating MIS

Here is a **strange** claim about approximating max-independent-set

Claim

For some $\alpha < 1$, if \exists an α -approximation algorithm in P for MIS, then $\sqrt{\alpha}$ -approximating MIS is also in P.

- 1 Reduction: Given a graph $G = (V, E)$, consider its 2-fold OR-power $H = (V^2, E_H)$ s.t.

$$(u_1, u_2) \sim (v_1, v_2) \text{ iff } u_1 \sim v_1 \text{ or } u_2 \sim v_2$$

- 2 Let S be an independent set of H and $S_1 := \{u_1 | \exists u_2 \text{ s.t. } (u_1, u_2) \in S\}$ and vice versa for S_2
- 3 OBS: $S_1 \times S_2$ is also independent

Approximating MIS

Here is a **strange** claim about approximating max-independent-set

Claim

For some $\alpha < 1$, if \exists an α -approximation algorithm in P for MIS, then $\sqrt{\alpha}$ -approximating MIS is also in P.

- 1 Reduction: Given a graph $G = (V, E)$, consider its 2-fold OR-power $H = (V^2, E_H)$ s.t.

$$(u_1, u_2) \sim (v_1, v_2) \text{ iff } u_1 \sim v_1 \text{ or } u_2 \sim v_2$$

- 2 Let S be an independent set of H and $S_1 := \{u_1 | \exists u_2 \text{ s.t. } (u_1, u_2) \in S\}$ and vice versa for S_2
- 3 OBS: $S_1 \times S_2$ is also independent
- 4 Next, how to finish the proof?

Approximating MIS

In fact, we could consider k -fold OR-power for any k !

Claim

For some $\alpha < 1$, if there is an α -approximation algorithm in P for MIS, then $\alpha^{1/k}$ -approximating MIS is also in P for any k .

- 1 If there is a 0.001-approximation, setting $k = 800$, we obtain a 0.99-approximation.
- 2 How shall we interpret this result?

Approximating MIS

In fact, we could consider k -fold OR-power for any k !

Claim

For some $\alpha < 1$, if there is an α -approximation algorithm in P for MIS, then $\alpha^{1/k}$ -approximating MIS is also in P for any k .

- 1 If there is a 0.001-approximation, setting $k = 800$, we obtain a 0.99-approximation.
- 2 How shall we interpret this result?
- 3 Researchers believe this is saying no constant-approximation for MIS unless $\text{NP}=\text{P}$
- 4 In fact, we can show: No $n^{0.999}$ -approximation for MIS unless $\text{NP}=\text{P}$

Approximating MIS

In fact, we could consider k -fold OR-power for any k !

Claim

For some $\alpha < 1$, if there is an α -approximation algorithm in P for MIS, then $\alpha^{1/k}$ -approximating MIS is also in P for any k .

- 1 If there is a 0.001-approximation, setting $k = 800$, we obtain a 0.99-approximation.
- 2 How shall we interpret this result?
- 3 Researchers believe this is saying no constant-approximation for MIS unless $\text{NP}=\text{P}$
- 4 In fact, we can show: No $n^{0.999}$ -approximation for MIS unless $\text{NP}=\text{P}$
- 5 3 steps: NP-hard to distinguish \exists an independent set of size $n/10$ or $\text{MIS} \leq 0.99 \cdot n/10$; then apply $O(\log n)$ -fold OR-power; finally, sparsify the product to $n^{O(1)}$ size

Summary

- 1 Undecidable problem: **Halting**, **Accepting**, **Rejecting**, ...
- 2 Many problems can not be solved in poly-time (at least we believe so) — NP captures the most interesting class



Summary

- 1 Undecidable problem: **Halting**, **Accepting**, **Rejecting**, ...
- 2 Many problems can not be solved in poly-time (at least we believe so) — NP captures the most interesting class
- 3 Complete problems stand for the hardest problem in a class like linear programming in P
- 4 A great notion is NP-complete: $P \neq NP \Leftrightarrow \forall \text{ NP-complete problem } Q, Q \notin P$

Summary


- 1 Undecidable problem: **Halting**, **Accepting**, **Rejecting**, ...
- 2 Many problems can not be solved in poly-time (at least we believe so) — NP captures the most interesting class
- 3 Complete problems stand for the hardest problem in a class like linear programming in P
- 4 A great notion is NP-complete: $P \neq NP \Leftrightarrow \forall \text{ NP-complete problem } Q, Q \notin P$
- 5 Many natural problems are NP-complete: SAT, CLIQUE, SUBSET-SUM, Vertex-Cover, ...
- 6 There are many ways to cure NP-complete 😊

For this course



- 1 As a science, CS is much more than coding — creations, good definitions, rigorous analyses, ...

For this course





- 1 As a science, CS is much more than coding — creations, good definitions, rigorous analyses, ...
- 2 Design and analysis of algorithms are the backbone of programs

运用之妙
存乎一心

60/100

岳飞

For this course



- 1 As a science, CS is much more than coding — creations, good definitions, rigorous analyses, ...
- 2 Design and analysis of algorithms are the backbone of programs

运用之妙
存乎一心

- 3 Hope you enjoy this course and learn something (at least) ☺

Questions?