

# Introduction to Algorithms

## Lecture 11 Minimum Spanning Trees

Xue Chen

xuechen1989@ustc.edu.cn

2024 spring in




# Outline

- 1 Introduction
- 2 Basic Properties
- 3 Prim's Algorithm
- 4 Kruskal's Algorithm
- 5 Data Structures for Disjoint Sets

# Overview

Spanning trees are fundamental objects in graph theory




- 1 Connectivity: DFS/BFS trees
- 2 Single Source Shortest Paths Tree
- 3 Today: **Minimum Spanning Trees**
- 4 More: trees for cut, ...

# Problem Description

## Minimum Spanning Tree (MST)

Give a undirected & weighted graph  $G$ , define the weight of a tree  $T$  to be the sum of all weights on its edges. The goal is to find a Tree with minimum weight.




- 1 Network Design: Traffic, electrical, ...
- 2 Algorithm Design: traveling salesman prob, Steiner tree, ...

# Outline

- 1 Introduction
- 2 Basic Properties**
- 3 Prim's Algorithm
- 4 Kruskal's Algorithm
- 5 Data Structures for Disjoint Sets


# Basic Properties of Trees

- 1 Remove a cycle edge can **not** disconnect a graph
- 2 A tree on  $n$  nodes has  $n - 1$  edges
- 3 Any **connected** graph  $G = (V, E)$  with  $|E| = |V| - 1$  is a tree
- 4 A connected graph is a tree iff  $\exists$  a **unique** path between any two nodes




# Cut Property

- ① True or False: If  $\exists$  a unique edge  $e$  with the lightest weight,  $e$  is in any MST.



# Cut Property


- 1 True or False: If  $\exists$  a unique edge  $e$  with the lightest weight,  $e$  in any MST.
- 2 Question: So  $(h, g)$  is always in MST, how about 2nd lightest edges  $(i, c)$  and  $(g, f)$ ?





# Cut Property

- 1 True or False: If  $\exists$  a unique edge  $e$  with the lightest weight,  $e$  is in any MST.
- 2 Question: So  $(h, g)$  is always in MST, how about 2nd lightest edges  $(i, c)$  and  $(g, f)$ ?



## Greedy method in Theorem 23.1 of CLRS


Let  $A$  be a subset of edges that is included in some MST.

Pick any cut  $(S, \bar{S})$  such that no edge in  $A$  crosses it.

Then for any lightest edge  $e$  on  $(S, \bar{S})$ ,  $\exists$  a MST that contains  $e$ .

# Cut Property

- 1 True or False: If  $\exists$  a unique edge  $e$  with the lightest weight,  $e$  is in any MST.
- 2 Question: So  $(h, g)$  is always in MST, how about 2nd lightest edges  $(i, c)$  and  $(g, f)$ ?



Greedy method in Theorem 23.1 of **CLRS**

Let  $A$  be a subset of edges that is included in some MST.

Pick any cut  $(S, \bar{S})$  such that no edge in  $A$  crosses it.

Then for any lightest edge  $e$  on  $(S, \bar{S})$ ,  $\exists$  a MST that contains  $e$ .

## Two Algorithms from opposite directions

$$\text{Cut}(S, \overline{S}) := \{(u, v) : u \in S, v \notin S\}$$

Greedy method in Theorem 23.1 of **CLRS**

Let **A** be a subset of edges that is included in some MST.

Pick any cut **(S,  $\overline{S}$ )** such that no edge in A cross it.

Then for any lightest edge  $e$  on  $(S, \overline{S})$ ,  $\exists$  a MST that contains  $e$ .

- 1 Prim's algorithm: Maintain  $S$  by adding vertices and finding the lightest edge on  $E \cap (S, \overline{S})$

## Two Algorithms from opposite directions

$$\text{Cut}(S, \overline{S}) := \{(u, v) : u \in S, v \notin S\}$$

Greedy method in Theorem 23.1 of CLRS

Let  $A$  be a subset of edges that is included in some MST.

Pick any cut  $(S, \overline{S})$  such that no edge in  $A$  cross it.

Then for any lightest edge  $e$  on  $(S, \overline{S})$ ,  $\exists$  a MST that contains  $e$ .

- 1 Prim's algorithm: Maintain  $S$  by adding vertices and finding the lightest edge on  $E \cap (S, \overline{S})$
- 2 Kruskal's Algorithm: Add edge  $e$  by verifying whether  $A \cup e$  has a cycle or not.

# Outline

- 1 Introduction
- 2 Basic Properties
- 3 Prim's Algorithm**
- 4 Kruskal's Algorithm
- 5 Data Structures for Disjoint Sets

# Overview


Based on the cut property, consider a greedy method to grow a tree  $S$ :

- 1 Start from  $S = \{\text{root}\}$  and add a neighbor with the lightest **crossing edge to**  $S$  every time

# Overview

Based on the cut property, consider a greedy method to grow a tree  $S$ :


- 1 Start from  $S = \{\text{root}\}$  and add a neighbor with the lightest **crossing edge** to  $S$  every time



# Overview

Based on the cut property, consider a greedy method to grow a tree  $S$ :

- 1 Start from  $S = \{\text{root}\}$  and add a neighbor with the lightest **crossing edge** to  $S$  every time






# Overview

Based on the cut property, consider a greedy method to grow a tree  $S$ :

- 1 Start from  $S = \{\text{root}\}$  and add a neighbor with the lightest **crossing edge** to  $S$  every time
- 2 Use a heap to maintain the lightest cross edge to  $v$  for every  $v \notin S$



- ①  $u.key := \min_{v \in S} w(u, v)$  for  $u \notin S$
- ②  $u.\pi$  denotes its argmin (as its father)
- ③  $Q$  maintains  $\overline{S}$  according to  $u.key$

MST-PRIM( $G, w, r$ )

```
1  for each  $u \in G.V$ 
2       $u.key = \infty$ 
3       $u.\pi = \text{NIL}$ 
4   $r.key = 0$ 
5   $Q = G.V$ 
6  while  $Q \neq \emptyset$ 
7       $u = \text{EXTRACT-MIN}(Q)$ 
8      for each  $v \in G.Adj[u]$ 
9          if  $v \in Q$  and  $w(u, v) < v.key$ 
10              $v.\pi = u$ 
11              $v.key = w(u, v)$ 
```

- ①  $u.key := \min_{v \in S} w(u, v)$  for  $u \notin S$
- ②  $u.\pi$  denotes its argmin (as its father)
- ③  $Q$  maintains  $\bar{S}$  according to  $u.key$

MST-PRIM( $G, w, r$ )

```
1  for each  $u \in G.V$ 
2       $u.key = \infty$ 
3       $u.\pi = \text{NIL}$ 
4   $r.key = 0$ 
5   $Q = G.V$ 
6  while  $Q \neq \emptyset$ 
7       $u = \text{EXTRACT-MIN}(Q)$ 
8      for each  $v \in G.Adj[u]$ 
9          if  $v \in Q$  and  $w(u, v) < v.key$ 
10              $v.\pi = u$ 
11              $v.key = w(u, v)$ 
```

## Time Complexity

$O(m \log n)$ : Each vertex will be extracted once; so every edge will make **at most one** change in the heap

# Outline

- 1 Introduction
- 2 Basic Properties
- 3 Prim's Algorithm
- 4 Kruskal's Algorithm**
- 5 Data Structures for Disjoint Sets

# Overview


An alternate greedy approach:

- 1 Maintain a set of edges  $A$  (the same one in THM 23.1 in [CLRS](#))
- 2 Try every edge  $e$  from the lightest to the heaviest: If  $A + \{e\}$  does not constitute a cycle,  $A = A + \{e\}$

# Overview

An alternate greedy approach:

- 1 Maintain a set of edges  $A$  (the same one in THM 23.1 in [CLRS](#))
- 2 Try every edge  $e$  from the lightest to the heaviest: If  $A + \{e\}$  does not constitute a cycle,  $A = A + \{e\}$



# Description

MST-KRUSKAL( $G, w$ )

```
1   $A = \emptyset$ 
2  for each vertex  $v \in G.V$ 
3      MAKE-SET( $v$ )
4  sort the edges of  $G.E$  into nondecreasing order by weight  $w$ 
5  for each edge  $(u, v) \in G.E$ , taken in nondecreasing order by weight
6      if  $\text{FIND-SET}(u) \neq \text{FIND-SET}(v)$ 
7           $A = A \cup \{(u, v)\}$ 
8          UNION( $u, v$ )
9  return  $A$ 
```

Example: Pseudo-code from CLRS

## Time Complexity

$\text{SORT}(m \text{ edges}) + n \times \text{UNION} + m \times \text{FIND-SET}$

Next: Disjoint sets supports UNION and FIND-SET in almost **constant time**: RADIX-SORT + Disjoint sets is faster than  $O(m \log n)$

# Outline

- 1 Introduction
- 2 Basic Properties
- 3 Prim's Algorithm
- 4 Kruskal's Algorithm
- 5 Data Structures for Disjoint Sets**



# Introduction

A data structure for disjoint sets: For a fixed ground set, support 3 operations

- 1 MAKE-SET( $x$ ): create a new set  $\{x\}$  for element  $x$
- 2 FIND-SET( $x$ ): Find the **representative element** of  $x$ 's set

# Introduction


A data structure for disjoint sets: For a fixed ground set, support 3 operations

- 1 MAKE-SET( $x$ ): create a new set  $\{x\}$  for element  $x$
- 2 FIND-SET( $x$ ): Find the **representative element** of  $x$ 's set
- 3 UNION( $x, y$ ): Unites two disjoint sets, which contain  $x$  and  $y$  separately, into one set

# Introduction

A data structure for disjoint sets: For a fixed ground set, support 3 operations


- 1 MAKE-SET( $x$ ): create a new set  $\{x\}$  for element  $x$
- 2 FIND-SET( $x$ ): Find the **representative element** of  $x$ 's set
- 3 UNION( $x, y$ ): Unites two disjoint sets, which contain  $x$  and  $y$  separately, into one set



## Applications

Maintenance of connected components in graphs and maps, equivalence relation, least-common ancestors problem, ...

# Implementation



Maintain those **sets as trees**


① Root is **the unique representation**

② Question:

How to implement MAKE-SET and FIND-SET?

How about UNION operation?

# Implementation



Maintain those **sets as trees**

① Root is **the unique representation**


② Question:

How to implement MAKE-SET and FIND-SET?

How about UNION operation?

③ Recall: **height** is the most important parameter for time complexity

# Implementation



Maintain those **sets as trees**


① Root is **the unique representation**

② Question:

How to implement MAKE-SET and FIND-SET?

How about UNION operation?


③ Recall: **height** is the most important parameter for time complexity




## Rank of elements

To maintain heights, define a **rank** for each element:

After  $\text{makeset}(A), \text{makeset}(B), \dots, \text{makeset}(G)$ :




After  $\text{union}(A, D), \text{union}(B, E), \text{union}(C, F)$ :




# Rank of elements

To maintain heights, define a **rank** for each element:

After `makeset(A), makeset(B), ..., makeset(G)`:



After `union(A, D), union(B, E), union(C, F)`:




## UNION( $x, y$ )


- 1 Let  $r_x$  and  $r_y$  be their representatives
- 2 If  $rank(r_x) > rank(r_y)$ :  $\pi(r_y) = r_x$
- 3 Else:  $\pi(r_x) = r_y$  and Update  $rank(r_y)$  to  $\max\{rank(r_y), rank(r_x) + 1\}$




After  $\text{makeset}(A), \text{makeset}(B), \dots, \text{makeset}(G)$ :




After  $\text{union}(A, D), \text{union}(B, E), \text{union}(C, F)$ :



After  $\text{union}(C, G), \text{union}(E, A)$ :



After  $\text{union}(B, G)$ :



# Basic Properties

- ① For any non-root  $x$ ,  $rank(\pi(x)) > rank(x)$ 
  - Question: Is it always true  $rank(\pi(x)) = rank(x) + 1$ ?

# Basic Properties

- ① For any non-root  $x$ ,  $rank(\pi(x)) > rank(x)$ 
  - Question: Is it always true  $rank(\pi(x)) = rank(x) + 1$ ?
- ② Any tree with root-rank  $k$  has at least  $2^k$  nodes
  - proof by induction

# Basic Properties

- ① For any non-root  $x$ ,  $rank(\pi(x)) > rank(x)$ 
  - Question: Is it always true  $rank(\pi(x)) = rank(x) + 1$ ?
- ② Any tree with root-rank  $k$  has at least  $2^k$  nodes
  - proof by induction
- ③ If there are  $n$  elements in all trees, at most  $n/2^k$  nodes of rank  $k$ 
  - implies all trees have height  $\leq \log n$

# Basic Properties

- ① For any non-root  $x$ ,  $rank(\pi(x)) > rank(x)$ 
    - Question: Is it always true  $rank(\pi(x)) = rank(x) + 1$ ?
  - ② Any tree with root-rank  $k$  has at least  $2^k$  nodes
    - proof by induction
  - ③ If there are  $n$  elements in all trees, at most  $n/2^k$  nodes of rank  $k$ 
    - implies all trees have height  $\leq \log n$
- ☹ But this only implies  $O(\log n)$  time for FIND-SET!

# Basic Properties

- ① For any non-root  $x$ ,  $rank(\pi(x)) > rank(x)$ 
    - Question: Is it always true  $rank(\pi(x)) = rank(x) + 1$ ?
  - ② Any tree with root-rank  $k$  has at least  $2^k$  nodes
    - proof by induction
  - ③ If there are  $n$  elements in all trees, at most  $n/2^k$  nodes of rank  $k$ 
    - implies all trees have height  $\leq \log n$
- ☹ But this only implies  $O(\log n)$  time for FIND-SET!

A Small trick improves time significantly

**Path compression:** In FIND-SET, set  $\pi(x)$  to be the root for all  $x$  on the path

# Formal Description

---

**function** FIND-SET( $x$ )

**if**  $\pi(x) \neq x$  **then**

$\pi(x) = \text{FIND-SET}(\pi(x))$

**return**  $\pi(x)$

//  $x$  is not a root

// Path Compression Trick

**procedure** MAKE-SET( $x$ )

$\pi(x) = x$  and  $\text{rank}(x) = 0$

**procedure** UNION-SET( $x, y$ )

$r_x = \text{FIND-SET}(x)$  and  $r_y = \text{FIND-SET}(y)$




**if**  $\text{rank}(r_x) > \text{rank}(r_y)$  **then**

$\pi(r_y) = r_x$

**else**

$\pi(r_x) = r_y$  and  $\text{rank}(r_y) = \max\{\text{rank}(r_y), \text{rank}(r_x) + 1\}$

---



Find(I) followed by Find(k)



# Amortized Analysis

Let  $\log^* n$  be number of log operations that bring  $n$  down to 1,  
e.g.,  $\log^* 1000 = 4$  and  $\log^* 2^{65536} = 5$

## THM: Running time of Disjoint Sets

Amortized time of  $m$  FIND-SET operations is  $O(m + n) \cdot \log^* n$ .

# Amortized Analysis

Let  $\log^* n$  be number of log operations that bring  $n$  down to 1,  
e.g.,  $\log^* 1000 = 4$  and  $\log^* 2^{65536} = 5$

## THM: Running time of Disjoint Sets

Amortized time of  $m$  FIND-SET operations is  $O(m + n) \cdot \log^* n$ .

- 1 Consider those ranks— path compression does not affect their ranks
- 2 Divide all ranks into  $\log^* n + O(1)$  intervals:

$\leftarrow \log^* n \text{ intervals} \rightarrow$

$$\{1\}, \{2\}, \{3, 4\}, \{5, 6, \dots, 16\}, \{17, \dots, 2^{16} = 65536\}, \{65537, \dots\}, \dots$$

$\leq \frac{n}{2} \text{ nodes}, \leq \frac{n}{4}, \dots, \leq \frac{n}{32} + \dots + \frac{n}{2^{16}} \text{ nodes}, \dots$

# Amortized Analysis

Let  $\log^* n$  be number of log operations that bring  $n$  down to 1, e.g.,  $\log^* 1000 = 4$  and  $\log^* 2^{65536} = 5$

## THM: Running time of Disjoint Sets

Amortized time of  $m$  FIND-SET operations is  $O(m + n) \cdot \log^* n$ .

- 1 Consider those ranks— path compression does not affect their ranks
- 2 Divide all ranks into  $\log^* n + O(1)$  intervals:


$\{1\}, \{2\}, \{3, 4\}, \{5, 6, \dots, 16\}, \{17, \dots, 2^{16} = 65536\}, \{65537, \dots, 3, \dots$   
 $\leq \frac{n}{2} \text{ nodes}, \leq \frac{n}{4}, \dots, \leq \frac{n}{32} + \dots + \frac{n}{2^{16}} \text{ nodes}, \dots$

*(Handwritten note:  $\log^* n$  intervals with arrows pointing to the sequence of sets)*

- 3 Amortized analysis with accounting method: For each  $x$  whose rank  $\in [k + 1, \dots, 2^k]$ , assign a budget  $2^k$  — total budget  $= n \cdot \log^* n$
- 4 Next:  $m \cdot \log^* n + \text{budgets}$  bounds time of  $m \times$  FIND-SET


1 Consider FIND-SET of length  $\ell$ :  $x_\ell \rightarrow x_{\ell-1} \rightarrow \cdots \rightarrow x_1 \rightarrow x_0$

- 1 Consider FIND-SET of length  $\ell$ :  $x_\ell \rightarrow x_{\ell-1} \rightarrow \dots \rightarrow x_1 \rightarrow x_0$
- 2 Fix  $i \in [\ell]$ : FIND-SET never changes  $\text{rank}(x_i)$ ; but  $\text{rank}(\pi(x_i))$  becomes larger




- 3 To bound amortized-time(FIND-SET), our focus is on  $[\text{rank}(x_i), \text{rank}(\pi(x_i))]$  vs intervals of ranks

- 1 Consider FIND-SET of length  $\ell$ :  $x_\ell \rightarrow x_{\ell-1} \rightarrow \dots \rightarrow x_1 \rightarrow x_0$
- 2 Fix  $i \in [\ell]$ : FIND-SET never changes  $\text{rank}(x_i)$ ; but  $\text{rank}(\pi(x_i))$  becomes larger



- 3 To bound amortized-time(FIND-SET), our focus is on  $[\text{rank}(x_i), \text{rank}(\pi(x_i))]$  vs intervals of ranks
- 4 OBS: Once  $[\text{rank}(x_i), \text{rank}(\pi(x_i))]$  crossed an interval, it keeps crossing those intervals in the future — this part is at most  $\log^* n$

- 1 Consider FIND-SET of length  $\ell$ :  $x_\ell \rightarrow x_{\ell-1} \rightarrow \dots \rightarrow x_1 \rightarrow x_0$
- 2 Fix  $i \in [\ell]$ : FIND-SET never changes  $\text{rank}(x_i)$ ; but  $\text{rank}(\pi(x_i))$  becomes larger



- 3 To bound amortized-time(FIND-SET), our focus is on  $[\text{rank}(x_i), \text{rank}(\pi(x_i))]$  vs intervals of ranks
- 4 OBS: Once  $[\text{rank}(x_i), \text{rank}(\pi(x_i))]$  crossed an interval, it keeps crossing those intervals in the future — this part is at most  $\log^* n$
- 5 O.w. pay the cost by the budget of  $x_i$  — If  $\text{rank}(x_i) \in [k+1, \dots, 2^k]$ , after  $x_i$  paid  $\leq 2^k$  times,  $\text{rank}(\pi(x_i))$  falls into above case and  $x_i$  stops paying

# Summary

- 1 Two algorithms implements the greedy idea
- 2 Prim's ALG runs in  $O(m \log n)$  via heaps (faster by Fibonacci-heap)
- 3 Kruskal's ALG runs in  $O(m \log^* n)$  after sorting



# Summary

- 1 Two algorithms implements the greedy idea
- 2 Prim's ALG runs in  $O(m \log n)$  via heaps (faster by Fibonacci-heap)
- 3 Kruskal's ALG runs in  $O(m \log^* n)$  after sorting
- 4 For disjoint sets, a small change makes a big difference: from  $O(\log n)$  to 5!



# Questions?