

# Introduction to Algorithms: Lecture 4

Xue Chen

xuechen1989@ustc.edu.cn

2025 spring in



# HW & Experiment

- 1 HW 2 & Experiment 1 are out
- 2 Office hours of Week 4 and Week 5 are in classroom 3A103

# Outline

- 1 Introduction
- 2 Hash
- 3 Heap and Heapsort

# Data Structure


A data structure is a specific way to organize data such that these data can be used efficiently.

# Data Structure

A data structure is a specific way to organize data such that these data can be used efficiently.

1 Many models: logical, mathematical, . . . ,

## 1.21 JSP Example 2 – Logical Data Structure





NOTE: Logical data structure diagram of transaction file

- If sales report is required (no reference to purchases) which shows totals for both cash and credit sales as shown above.
- Every record will no longer be processed and the purchases will be ignored.

# Data Structure

A data structure is a specific way to organize data such that these data can be used efficiently.

- 1 Many models: logical, **mathematical**, ... ,





- 2 Different types: Linear (queues, stacks, linked lists, ... ),  
**Non-Linear (trees, graphs, ... )**

# Data Structure

A data structure is a specific way to organize data such that these data can be used efficiently.


- 1 Many models: logical, **mathematical**, ... ,



- 2 Different types: Linear (queues, stacks, linked lists, ... ),  
**Non-Linear (trees, graphs, ... )**
- 3 Other properties: static vs **dynamic**, homogenous, ...

# Overview

This course considers data structures as a way to represent finite dynamic sets (of various elements).




The goal is



# Overview

This course considers data structures as a way to represent finite dynamic sets (of various elements).



The goal is

- 1 Maintain it efficiently
- 2 Answer queries like (1) who is the oldest kid? (2) How many kids born in August 2015? ...

## Overview (II)

Each element has a **unique ID/pointer** (like “Alice”) and a **key value**  $k \in \mathbb{Z}$  with a **total order** (like “dob: 15/04/31”).

### Standard Operations on dynamic sets

## Overview (II)

Each element has a **unique ID/pointer** (like “Alice”) and a **key value**  $k \in \mathbb{Z}$  with a **total order** (like “dob: 15/04/31”).

### Standard Operations on dynamic sets

- 1 SEARCH( $S, k$ ): Return a pointer  $x$  to an element in  $S$  with value  $k$  or NIL
- 2 INSERT( $S, x$ ): Insert the element pointed by  $x$  to  $S$
- 3 DELETE( $S, x$ ): Delete element pointed by  $x$  from  $S$

## Overview (II)

Each element has a **unique ID/pointer** (like “Alice”) and a **key value**  $k \in \mathbb{Z}$  with a **total order** (like “dob: 15/04/31”).

### Standard Operations on dynamic sets

- 1 SEARCH( $S, k$ ): Return a pointer  $x$  to an element in  $S$  with value  $k$  or NIL
- 2 INSERT( $S, x$ ): Insert the element pointed by  $x$  to  $S$
- 3 DELETE( $S, x$ ): Delete element pointed by  $x$  from  $S$
- 4 MINIMUM( $S$ ): Return a point to element in  $S$  with the smallest key
- 5 SUCCESSOR( $S, x$ ): Given  $x$ , return the next element after  $x$  in  $S$

## Overview (II)

Each element has a **unique ID/pointer** (like “Alice”) and a **key value**  $k \in \mathbb{Z}$  with a **total order** (like “dob: 15/04/31”).

### Standard Operations on dynamic sets

- 1 SEARCH( $S, k$ ): Return a pointer  $x$  to an element in  $S$  with value  $k$  or NIL
- 2 INSERT( $S, x$ ): Insert the element pointed by  $x$  to  $S$
- 3 DELETE( $S, x$ ): Delete element pointed by  $x$  from  $S$
- 4 MINIMUM( $S$ ): Return a point to element in  $S$  with the smallest key
- 5 SUCCESSOR( $S, x$ ): Given  $x$ , return the next element after  $x$  in  $S$
- 6 UNION( $S, T$ ): Unites the two dynamic sets  $S$  and  $T$
- 7 COUNT( $S, k_1, k_2$ ): Given a total order and an interval  $[k_1, k_2]$ , return the number of elements in  $S$  with a key value  $k$  in  $[k_1, k_2]$ .

# Outline

- 1 Introduction
- 2 Hash
- 3 Heap and Heapsort

# Introduction

Hash maintains a **dynamic set  $S$**  of keys for the dictionary problem

## Example

Maintain all students information — enroll, graduate, search by id and name, ...

Student Information		
Student's Name: _____	Nickname: _____	
Birthday: _____	Allergies: _____	
Primary Address: _____	Home Phone: _____	
Parent/Guardian Name: _____	Day Phone: _____	E-mail: _____
Parent/Guardian Name: _____	Day Phone: _____	E-mail: _____
Who is the best person to contact during the day? _____		

# Description

$x.key$  denotes the **unique key** of each element  $x$  — for convenience, only consider one key in  $\mathbb{Z}$ .


- 1 SEARCH( $k$ ): Find  $x$  in  $S$  with  $x.key = k$
- 2 DELETE( $x$ ): Delete  $x$  in  $S$
- 3 INSERT( $x$ ): Insert  $x$  in  $S$



# Description

$x.key$  denotes the **unique key** of each element  $x$  — for convenience, only consider one key in  $\mathbb{Z}$ .

- 1 SEARCH( $k$ ): Find  $x$  in  $S$  with  $x.key = k$
- 2 DELETE( $x$ ): Delete  $x$  in  $S$
- 3 INSERT( $x$ ): Insert  $x$  in  $S$



# Notations

- 1  $U$ : the domain of keys
- 2  $S$ : the dynamic set in  $U$
- 3  $m$ : the max elements in  $S$

Think  $|U| = 10^9$  and  $m = 10^3$  or  $10^6$

# Notations

- ①  $U$ : the domain of keys
- ②  $S$ : the dynamic set in  $U$
- ③  $m$ : the max elements in  $S$

Think  $|U| = 10^9$  and  $m = 10^3$  or  $10^6$

## Questions

- (1) If we only want to support SEARCH, INSERT, DELETE in  $O(1)$  time, what shall we do?
- (2) If we only have  $O(m)$  storage-space, what shall we do?

# Notations

- ①  $U$ : the domain of keys
- ②  $S$ : the dynamic set in  $U$
- ③  $m$ : the max elements in  $S$

Think  $|U| = 10^9$  and  $m = 10^3$  or  $10^6$

## Questions

- (1) If we only want to support SEARCH, INSERT, DELETE in  $O(1)$  time, what shall we do?
- (2) If we only have  $O(m)$  storage-space, what shall we do?

- ① Solution 1: Maintain  $T : U \rightarrow \text{node}$  s.t.  $T[x.\text{key}] = x$  for any  $x$

# Notations

- ①  $U$ : the domain of keys
- ②  $S$ : the dynamic set in  $U$
- ③  $m$ : the max elements in  $S$

Think  $|U| = 10^9$  and  $m = 10^3$  or  $10^6$

## Questions

- (1) If we only want to support SEARCH, INSERT, DELETE in  $O(1)$  time, what shall we do?
- (2) If we only have  $O(m)$  storage-space, what shall we do?

- ① Solution 1: Maintain  $T : U \rightarrow \text{node}$  s.t.  $T[x.\text{key}] = x$  for any  $x$
- ② Solution 2: Maintain an array or a chain.

# Hash

Hash tries to get the best parts of both —  $O(1)$  time and  $O(m)$  space.

# Hash

Hash tries to get the best parts of both —  $O(1)$  time and  $O(m)$  space.

## Solution


- 1 Prepare a hash function  $f : U \rightarrow [m]$   
like  $f_{a,b}(x) = (a \cdot x.key + b) \bmod m$
- 2 Maintain a truth table  $T : [m] \rightarrow \text{node}$

# Hash

Hash tries to get the best parts of both —  $O(1)$  time and  $O(m)$  space.

## Solution

- 1 Prepare a hash function  $f : U \rightarrow [m]$   
like  $f_{a,b}(x) = (a \cdot x.\text{key} + b) \bmod m$
- 2 Maintain a truth table  $T : [m] \rightarrow \text{node}$



Assume no collision, how to support SEARCH, INSERT, DELETE?



# Handle Collisions (I)

Collisions are unavoidable unless  $|S| \leq \sqrt{m}$

— birthday paradox.

## Theorem

*For a perfectly random hash  $h$ ,*

$$Pr_h [h(x_1), \dots, h(x_k) \text{ have no collision}] \leq e^{-\binom{k}{2}/m}.$$

# Handle Collisions (I)


Collisions are unavoidable unless  $|S| \leq \sqrt{m}$

— birthday paradox.

## Theorem

For a perfectly random hash  $h$ ,

$$\Pr_h [h(x_1), \dots, h(x_k) \text{ have no collision}] \leq e^{-\binom{k}{2}/m}.$$



For each node  $x$ , introduce  $x.left$  and  $x.right$  to maintain the chain


## Solution 1

Maintain a chain for each position in  $T$

# Collisions 2

## Solution 2

Put  $x$  into the next empty box in  $T$  — open-addressing method



## Solution 3: Power of 2-choice

### A surprising powerful idea

Prepare multiple hash functions, say  $h_1$  and  $h_2$ , and put  $x$  into  $h_1(x)$  or  $h_2(x)$

- 1 Multiple choices hash
- 2 Always-Go-Left Hash
- 3 Cuckoo Hash: When  $n < m/2$ , at most one ball in every bin.

# Summary

As a warm-up, Hash is the most fundamental data structure in CS

- 1 Collisions are **unavoidable** unless the table is huge.

# Summary

As a warm-up, Hash is the most fundamental data structure in CS

- 1 Collisions are **unavoidable** unless the table is huge.
- 2 Solution 1, maintaining chains in  $T$ , is more time-efficient but waste  $\Omega(1)$ -frac of space.
- 3 Solution 2, open-addressing method, is more space efficient but slower.

# Summary

As a warm-up, Hash is the most fundamental data structure in CS

- 1 Collisions are **unavoidable** unless the table is huge.
- 2 Solution 1, maintaining chains in  $T$ , is more time-efficient but waste  $\Omega(1)$ -frac of space.
- 3 Solution 2, open-addressing method, is more space efficient but slower.
- 4 Solution 3, multiple choices hash and cuckoo hash.

# Summary

As a warm-up, Hash is the most fundamental data structure in CS

- 1 Collisions are **unavoidable** unless the table is huge.
- 2 Solution 1, maintaining chains in  $T$ , is more time-efficient but waste  $\Omega(1)$ -frac of space.
- 3 Solution 2, open-addressing method, is more space efficient but slower.
- 4 Solution 3, multiple choices hash and cuckoo hash.
- 5 More: memory-hierarchy hash, ...




# Outline

- 1 Introduction
- 2 Hash
- 3 Heap and Heapsort

# Introduction


A heap is a nearly complete binary tree that supports **MAXIMUM**, INSERT, DELETE of a set with **ordered keys** in time  $O(\log n)$ .



## Main Property

# Introduction

A heap is a nearly complete binary tree that supports **MAXIMUM**, INSERT, DELETE of a set with **ordered keys** in time  $O(\log n)$ .




## Main Property

- 1 For any node  $v$  (not root),  $\text{parent}[v].\text{key} \geq v.\text{key}$   
 $\Rightarrow$  the maximal key value is at the root, called max-heap.
- 2 **Nearly-complete & Almost-balanced**: Most nodes (except  $\leq 1$  node) have either 2 children (called  $v.\text{left}$  and  $v.\text{right}$ ) or 0.

# Introduction

A heap is a nearly complete binary tree that supports **MAXIMUM**, INSERT, DELETE of a set with **ordered keys** in time  $O(\log n)$ .




## Main Property

- 1 For any node  $v$  (not root), **parent[v].key  $\geq$  v.key**  
 $\Rightarrow$  the maximal key value is at the root, called max-heap.
- 2 **Nearly-complete & Almost-balanced**: Most nodes (except  $\leq 1$  node) have either 2 children (called  $v.left$  and  $v.right$ ) or 0.


Remarks: (1) Only consider one dynamic set and  $n :=$  its size. (2) Neglect corner cases in these slides.

# Details

Two ways to view the heap because it is **nearly complete**.




(a)



(b)

## Details

Two ways to view the heap because it is **nearly complete**.



Implement it as an array

For each node with label  $i$ ,

$Key(i) :$   $A[i]$

$Parent(i) :$   $[i/2]$

$Left(i) :$   $2i$

$Right(i) :$   $2i + 1.$

Remark:  $Left(i) = \emptyset$  if  $2i > n$  and vice versa for  $Right(i)$ .

# Maintaining the heap

## Operations

The binary heap supports the following operations in  $O(\log n)$  time except BUILD-MAX-HEAP in  $O(n)$  time:

- 1 HEAP-MAXIMUM( $A$ ): *return*  $A[1]$

# Maintaining the heap

## Operations

The binary heap supports the following operations in  $O(\log n)$  time except BUILD-MAX-HEAP in  $O(n)$  time:

- 1 HEAP-MAXIMUM( $A$ ): *return*  $A[1]$
- 2 MAX-HEAPIFY( $A, i$ ): Decrease the value of  $A[i]$  and adjust
- 3 HEAP-EXTRACT-MAX( $A$ ): Remove the largest element (root) in  $A$
- 4 HEAP-INCREASE-KEY( $A, i$ ): Increase the value of  $A[i]$  and adjust



# Maintaining the heap

## Operations

The binary heap supports the following operations in  $O(\log n)$  time except BUILD-MAX-HEAP in  $O(n)$  time:


- 1 HEAP-MAXIMUM( $A$ ): *return*  $A[1]$
- 2 MAX-HEAPIFY( $A, i$ ): Decrease the value of  $A[i]$  and adjust
- 3 HEAP-EXTRACT-MAX( $A$ ): Remove the largest element (root) in  $A$
- 4 HEAP-INCREASE-KEY( $A, i$ ): Increase the value of  $A[i]$  and adjust
- 5 MAX-HEAP-INSERT( $A, k$ ): Insert a new element with key value  $k$
- 6 BUILD-MAX-HEAP( $A$ ): Build array  $A$  as a heap.

# Maintaining the heap

## Operations

The binary heap supports the following operations in  $O(\log n)$  time except BUILD-MAX-HEAP in  $O(n)$  time:


- 1  $\text{HEAP-MAXIMUM}(A)$ : return  $A[1]$
- 2  $\text{MAX-HEAPIFY}(A, i)$ : Decrease the value of  $A[i]$  and adjust
- 3  $\text{HEAP-EXTRACT-MAX}(A)$ : Remove the largest element (root) in  $A$
- 4  $\text{HEAP-INCREASE-KEY}(A, i)$ : Increase the value of  $A[i]$  and adjust
- 5  $\text{MAX-HEAP-INSERT}(A, k)$ : Insert a new element with key value  $k$
- 6  $\text{BUILD-MAX-HEAP}(A)$ : Build array  $A$  as a heap.



Key property: the height  $h$  is  $\leq \lceil \log_2 n \rceil + 1$ .

# MAX-HEAPIFY


Task: After decreasing  $A[i]$ , maintain  $A$  as a heap.



**Example:** Adjust  $A[2]$  to maintain the properties of a heap

# MAX-HEAPIFY

Task: After decreasing  $A[i]$ , maintain  $A$  as a heap.



**Example:** Adjust  $A[2]$  to maintain the properties of a heap


Recall two main properties: (1)  $A[i] \geq A[2i] \ \& \ A[2i + 1]$  (2) a nearly complete binary tree

---

```
procedure MAX-HEAPIFY( $A, i$ )  
  while  $A[i] \leq A[2i]$  or  $A[i] \leq A[2i + 1]$  do  
     $largest = \arg \max\{A[2i], A[2i + 1]\}$   
    Exchange  $A[i]$  with  $A[largest]$   
     $i = largest$ 
```

---

# Example run of MAX-HEAPIFY



**Example:** Adjust  $A[2]$  to maintain the properties of a heap

# BUILD-MAX-HEAP

Task: Input  $A[1], \dots, A[n]$ , adjust them to make it a heap.

# BUILD-MAX-HEAP

Task: Input  $A[1], \dots, A[n]$ , adjust them to make it a heap.

---

```
procedure BUILD-MAX-HEAP( $A$ )  
  for  $i = \lfloor n/2 \rfloor, \dots, 1$  do  
    MAX-HEAPIFY( $A, i$ )
```

---

# BUILD-MAX-HEAP

Task: Input  $A[1], \dots, A[n]$ , adjust them to make it a heap.

---

```
procedure BUILD-MAX-HEAP( $A$ )  
  for  $i = \lfloor n/2 \rfloor, \dots, 1$  do  
    MAX-HEAPIFY( $A, i$ )
```

---


## Remarks

- 1 The loop  $i$  has to go from  $\lfloor n/2 \rfloor$  to 1. Otherwise it violates 1st property.
- 2 Question: Running time?



# Running time of BUILD-MAX-HEAP

While the total height is  $\log_2 n$ , only 1 node (root) will have  $\log_2 n$  exchanges possibly; only 2 nodes will have  $\log_2 n - 1$  exchanges possibly, ...



$$1 \cdot \log_2 n + 2 \cdot (\log_2 n - 1) + \dots + n/4 \cdot 1 = O(n).$$

# HEAP-EXTRACT-MAX

Task: Remove  $A[1]$  from  $A$  — decrease  $n$  and maintain  $A$  as a heap

# HEAP-EXTRACT-MAX

Task: Remove  $A[1]$  from  $A$  — decrease  $n$  and maintain  $A$  as a heap

---

---

**procedure** HEAP-EXTRACT-MAX( $A$ )

$\text{max} = A[1]$

$A[1] = A[n]$

$n = n - 1$

    MAX-HEAPIFY( $A, 1$ )

    Return max

---

# HEAP-EXTRACT-MAX

Task: Remove  $A[1]$  from  $A$  — decrease  $n$  and maintain  $A$  as a heap

---

---

**procedure** HEAP-EXTRACT-MAX( $A$ )

$\text{max} = A[1]$

$A[1] = A[n]$

$n = n - 1$

    MAX-HEAPIFY( $A, 1$ )

    Return  $\text{max}$

---

## Question

Use BUILD-MAX-HEAP and HEAP-EXTRACT-MAX to design a sort algorithm?

# HEAP-INCREASE-KEY

Task: After increasing  $A[i]$ , maintain  $A$  as a heap

# HEAP-INCREASE-KEY

Task: After increasing  $A[i]$ , maintain  $A$  as a heap

---

**procedure** HEAP-INCREASE-KEY( $A, i, key$ )

$A[i] = key$

**while**  $i > 1$  and  $A[\text{parent}(i)] < A[i]$  **do**

        Exchange  $A[i]$  with  $A[\text{parent}(i)]$

$i = \text{Parent}(i)$

---

# HEAP-INCREASE-KEY

Task: After increasing  $A[i]$ , maintain  $A$  as a heap

---

**procedure** HEAP-INCREASE-KEY( $A, i, key$ )

$A[i] = key$

**while**  $i > 1$  and  $A[\text{parent}(i)] < A[i]$  **do**

        Exchange  $A[i]$  with  $A[\text{parent}(i)]$

$i = \text{Parent}(i)$

---

## Question

How to delete an arbitrary element?

# MAX-HEAP-INSERT

Task: Insert a new element with value *key*

---

---

**procedure** HEAP-INCREASE-KEY(*A*, *key*)

$n = n + 1$

    HEAP-INCREASE-KEY(*A*, *n*, *key*)

---



# Summary of Heap

- 1 Heap is a priority queue that keeps the largest element as the root
- 2 An almost complete binary tree

# Summary of Heap

- ① Heap is a priority queue that keeps the largest element as the root
- ② An almost complete binary tree
- ③ Easy to implement and works well in practice
- ④ Support many operations in  $O(\log_2 n)$ -time

# Summary of Heap

- 1 Heap is a priority queue that keeps the largest element as the root
- 2 An almost complete binary tree
- 3 Easy to implement and works well in practice
- 4 Support many operations in  $O(\log_2 n)$ -time
- 5 While heap does not support SEARCH(KEY), one could combine it with Hash
- 6 But neither of them could find the  $k$ th largest in  $o(n)$  time.


# Extensions

Support UNION in  $o(n)$  time

## Binomial heap and Fibonacci Heap

Basic idea: Allow each node to have more children.

While they are **faster and more powerful**, complicated to implement.



# Questions?