

ARUS UX/UI Fix Instructions for Replit

Upload this file and tell Replit: "Apply every fix in this file exactly as specified."

CONTEXT

You are fixing UX/UI issues in the ARUS maritime crew management frontend. Users: vessel officers on tablets at sea, shore-based fleet managers, admins on desktop. Devices: tablet (primary vessel use), mobile phone, desktop browser, Electron desktop app. Stack: React + TypeScript, shadcn/ui, TanStack Query, date-fns, Recharts, Tailwind CSS, wouter routing. Do NOT change any API endpoints, schema types in @shared, or test files.

SECTION 1: NAVIGATION & INFORMATION ARCHITECTURE

Fix 1.1 — `client/src/pages/home.tsx`

Replace the right-click-only dock hint with a touch-compatible long-press handler and a visible pin icon on each `CategoryCard`.

Step A: Add a long-press hook at the top of the file (before the `CategoryCard` component):

```
function useLongPress(callback: () => void, ms = 500) {
  const timerRef = React.useRef<ReturnType<typeof setTimeout> | null>(null);
  const start = () => { timerRef.current = setTimeout(callback, ms); };
  const stop = () => { if (timerRef.current) clearTimeout(timerRef.current); };
  return { onMouseDown: start, onMouseUp: stop, onMouseLeave: stop, onTouchStart:
}
```

Step B: In the `CategoryCard` component, add a visible Pin button overlay that appears on hover/focus, alongside the existing `ContextMenu`:

```
import { Pin } from "lucide-react";
```

```
// Inside the CategoryCard div, add this button as the last child of the icon con
```

```

<button
  onClick={(e) => { e.preventDefault(); e.stopPropagation(); onAddToDock(hubItem)
  className={cn(
    "absolute -top-1 -right-1 w-6 h-6 rounded-full flex items-center justify-cent
    "bg-background border shadow-sm transition-opacity",
    "opacity-0 group-hover:opacity-100 focus:opacity-100",
    isInDock ? "text-primary" : "text-muted-foreground"
  )}
  aria-label={isInDock ? "Already in dock" : "Pin to dock"}
  title={isInDock ? "Already in dock" : "Pin to dock"}
  disabled={isInDock}
>
  <Pin className="h-3 w-3" />
</button>

```

Make the parent icon container `relative` by adding `relative` to its `className`.

Step C: Add a first-visit dock onboarding tooltip. Add this state at the top of `HomePage` :

```

const [showDockHint, setShowDockHint] = React.useState(() => {
  return !localStorage.getItem("arus-dock-hint-seen");
});

```

Replace the existing empty-dock hint div with:

```

{dockItems.length === 0 && showDockHint && (
  <div className="fixed bottom-4 left-1/2 -translate-x-1/2 z-50">
    <div className="flex items-center gap-2 px-4 py-2 bg-popover border rounded-f
      <Pin className="h-4 w-4" />
      <span>Hover a category and tap the pin icon to add it here for quick access
    <button
      onClick={() => { setShowDockHint(false); localStorage.setItem("arus-dock-
        className="ml-1 text-foreground/60 hover:text-foreground"
        aria-label="Dismiss tip"
      >
        <X className="h-3 w-3" />
      </button>
    </div>
  </div>
)}

```

Step D: Add a "Recent" row above the category grid. Add this state and effect in `HomePage` :

```

const [recentHrefs, setRecentHrefs] = React.useState<string[]>(() => {
  try { return JSON.parse(localStorage.getItem("arus-recent-items") || "[]"); } c

```

```

});

// Expose a function to record visits (call this from navigation events if possib
// or simply show the last dock items as recents as a first pass):
const recentItems = React.useMemo(() => {
  const allItems = getAllNavigationItems();
  const hubItems = navigationCategories.map(cat => ({
    name: cat.name, href: cat.hubRoute, icon: cat.icon, description: cat.descript
  }));
  return recentHrefs
    .map(href => [...allItems, ...hubItems].find(i => i.href === href))
    .filter((i): i is NavigationItem => !!i)
    .slice(0, 3);
}, [recentHrefs]);

```

Above the category grid in JSX, add:

```

{recentItems.length > 0 && (
  <div className="mb-6 w-full">
    <p className="text-xs text-muted-foreground mb-2 font-medium uppercase tracki
    <div className="flex gap-3 flex-wrap">
      {recentItems.map(item => {
        const Icon = item.icon;
        return (
          <Link key={item.href} href={item.href}>
            <div className="flex items-center gap-2 px-3 py-2 rounded-xl border b
              <Icon className="h-4 w-4 text-primary" />
              <span className="text-sm font-medium">{item.name}</span>
            </div>
          </Link>
        );
      })}
    </div>
  </div>
)}

```

Fix 1.2 — All hub page files (operations-hub, fleet-hub, maintenance-hub, etc.)

Add a breadcrumb bar at the top of each hub so users can navigate back. In each hub file, add this import and component above the `IconGridLayout`:

```

import { ChevronRight, Home } from "lucide-react";

```

```
import { Link } from "wouter";

// Add above the return statement's IconGridLayout:
// (Replace "Operations" with the hub's actual title in each file)
<nav className="flex items-center gap-1 px-4 py-2 text-sm text-muted-foreground b
  <Link href="/">
    <span className="flex items-center gap-1 hover:text-foreground cursor-pointer
      <Home className="h-3 w-3" />
      <span>Home</span>
    </span>
  </Link>
  <ChevronRight className="h-3 w-3" />
  <span className="text-foreground font-medium">Operations</span>
</nav>
```

Apply to: operations-hub.tsx, fleet-hub.tsx, maintenance-hub.tsx, logistics-hub.tsx, logs-hub.tsx, system-hub.tsx. Change the hub name label in each file accordingly.

Fix 1.3 — Create `client/src/components/BottomNav.tsx` (new file)

```
import { Link, useLocation } from "wouter";
import { Home, Activity, Users, FileText, Settings } from "lucide-react";
import { cn } from "@/lib/utils";

const NAV_ITEMS = [
  { href: "/", label: "Home", icon: Home },
  { href: "/operations", label: "Operations", icon: Activity },
  { href: "/crew", label: "Crew", icon: Users },
  { href: "/logs", label: "Logs", icon: FileText },
  { href: "/system", label: "System", icon: Settings },
];

export function BottomNav() {
  const [location] = useLocation();

  return (
    <nav className="fixed bottom-0 left-0 right-0 z-50 bg-background/90 backdrop-
      <div className="flex items-center justify-around h-14 px-2">
        {NAV_ITEMS.map(({ href, label, icon: Icon }) => {
          const active = location === href || (href !== "/" && location.startsWithWit
          return (
            <Link key={href} href={href}>
              <div className={cn(
                "flex flex-col items-center gap-0.5 px-3 py-1 rounded-lg transiti
```

```

        active ? "text-primary" : "text-muted-foreground"
      )}>
        <Icon className={cn("h-5 w-5", active && "fill-primary/20")} />
        <span className="text-[10px] font-medium">{label}</span>
      </div>
    </Link>
  );
}
</div>
</nav>
);
}

```

Then in the root layout or App component, add `<BottomNav />` at the bottom, and add `pb-14 md:pb-0` to the main content wrapper so content isn't hidden behind it.

Fix 1.4 — `client/src/pages/home.tsx` — move dock above bottom nav on mobile

Change the Dock component's container className from:

```
"fixed bottom-4 left-1/2 -translate-x-1/2 z-50"
```

to:

```
"fixed bottom-16 left-1/2 -translate-x-1/2 z-50 md:bottom-4"
```

Apply the same change to the dock hint/onboarding tip container.

SECTION 2: FORMS & DATA ENTRY

Fix 2.1 — `client/src/components/HoursOfRestGrid.tsx` — touch support for grid

Add touch-to-paint support. At the top of the component, after the hook destructuring, add:

```

const gridRef = React.useRef<HTMLDivElement>(null);

const handleTouchMove = React.useCallback((e: React.TouchEvent) => {
  e.preventDefault();
  const touch = e.touches[0];
  const el = document.elementFromPoint(touch.clientX, touch.clientY) as HTMLElement;
  if (el?.dataset?.cellRow && el?.dataset?.cellHour) {

```

```

        onDrag(Number(el.dataset.cellRow), Number(el.dataset.cellHour));
    }
}, [onDrag]);

```

On every grid cell div that has `onMouseDown` and `onMouseEnter`, add:

- `data-cell-row={actualIndex}`
- `data-cell-hour={h}`
- `onTouchStart={(e) => { e.preventDefault(); startDrag(actualIndex, h); }}`

On the grid container div (the one with `data-testid="rest-hours-grid"`), add:

```

ref={gridRef}
onTouchMove={handleTouchMove}
style={{ touchAction: "none" }}

```

Fix 2.2 — `client/src/components/HoursOfRestGrid.tsx` — auto-switch to mobile view

Add this effect inside the component, after the hook destructuring:

```

React.useEffect(() => {
    const checkMobile = () => {
        if (window.innerWidth < 768 && viewMode === "month") {
            setViewMode("mobile");
        }
    };
    checkMobile();
    window.addEventListener("resize", checkMobile);
    return () => window.removeEventListener("resize", checkMobile);
}, []); // eslint-disable-line react-hooks/exhaustive-deps

```

Fix 2.3 — `client/src/components/HoursOfRestGrid.tsx` — add sticky grid legend

Immediately before the grid container div (the one with `data-testid="rest-hours-grid"`), add:

```

<div className="flex flex-wrap items-center gap-4 mb-3 p-2 bg-muted/30 rounded-lg"
  <span className="flex items-center gap-1.5">
    <span className="w-4 h-4 rounded bg-emerald-200 dark:bg-emerald-800 border bo

```

```

    REST
  </span>
  <span className="flex items-center gap-1.5">
    <span className="w-4 h-4 rounded bg-rose-200 dark:bg-rose-800 border border-r
    WORK
  </span>
  <span className="flex items-center gap-1.5">
    <span className="w-4 h-4 rounded border-2 border-indigo-400 bg-transparent" /
    Night hours (20:00-06:00)
  </span>
  <span className="text-muted-foreground">· Click or drag to toggle · Touch and d
</div>

```

Fix 2.4 — client/src/components/HoursOfRestGrid.tsx — save toast + beforeunload guard

Add these effects inside the component:

```

// beforeunload guard
React.useEffect(() => {
  const handler = (e: BeforeUnloadEvent) => {
    if (saveStatus === "unsaved") {
      e.preventDefault();
      e.returnValue = "";
    }
  };
  window.addEventListener("beforeunload", handler);
  return () => window.removeEventListener("beforeunload", handler);
}, [saveStatus]);

```

In the upload/save success handler (wherever `saveStatus` transitions to "saved"), add a toast call. Find where `saveStatus` is set to "saved" in `useHoursOfRestData` and ensure the component calls:

```

const { toast } = useToast();
// After save success:
toast({
  title: "Rest hours saved",
  description: `Saved for ${selectedCrewMember?.name ?? "crew member"} — ${meta.m
});

```

Add `import { useToast } from "@/hooks/use-toast";` at the top of the file.

Fix 2.5 — `client/src/components/HoursOfRestGrid.tsx` — undo/redo tooltip with step count

Replace the undo and redo buttons with:

```
<TooltipProvider>
  <Tooltip>
    <TooltipTrigger asChild>
      <Button variant="outline" size="sm" onClick={undo}
        disabled={historyIndex <= 0} data-testid="button-undo">
        <Undo className="w-4 h-4" />
      </Button>
    </TooltipTrigger>
    <TooltipContent>
      {historyIndex <= 0
        ? "Nothing to undo"
        : `Undo (${historyIndex} step${historyIndex !== 1 ? "s" : ""} available)`
      }
    </TooltipContent>
  </Tooltip>
</TooltipProvider>

<TooltipProvider>
  <Tooltip>
    <TooltipTrigger asChild>
      <Button variant="outline" size="sm" onClick={redo}
        disabled={historyIndex >= history.length - 1} data-testid="button-redo">
        <Redo className="w-4 h-4" />
      </Button>
    </TooltipTrigger>
    <TooltipContent>
      {historyIndex >= history.length - 1
        ? "Nothing to redo"
        : `Redo (${history.length - 1 - historyIndex} step${history.length - 1 -
        </TooltipContent>
      }
    </Tooltip>
  </TooltipProvider>
```

```
Add import { Tooltip, TooltipContent, TooltipProvider, TooltipTrigger } from
"@/components/ui/tooltip";
```

Fix 2.6 — `client/src/components/HoursOfRestGrid.tsx` — Clear All confirmation dialog

Replace the clear all button with:

```
import { AlertDialog, AlertDialogAction, AlertDialogCancel, AlertDialogContent, A

<AlertDialog>
  <AlertDialogTrigger asChild>
    <Button variant="outline" size="sm"
      className="border-slate-300 text-slate-700 hover:bg-slate-50 dark:text-slat
      data-testid="button-clear-all">
      Clear All
    </Button>
  </AlertDialogTrigger>
  <AlertDialogContent>
    <AlertDialogHeader>
      <AlertDialogTitle>Clear all rest hours?</AlertDialogTitle>
      <AlertDialogDescription>
        This will clear all rest hours for{" "}
        <strong>{selectedCrewMember?.name ?? "this crew member"}</strong> in{" "}
        <strong>{meta.month} {meta.year}</strong>.
        This can be undone using the Undo button immediately after.
      </AlertDialogDescription>
    </AlertDialogHeader>
    <AlertDialogFooter>
      <AlertDialogCancel>Cancel</AlertDialogCancel>
      <AlertDialogAction onClick={clearAll} className="bg-destructive hover:bg-de
        Clear All Hours
      </AlertDialogAction>
    </AlertDialogFooter>
  </AlertDialogContent>
</AlertDialog>
```

Fix 2.7 — client/src/components/HoursOfRestGrid.tsx — Save button visual hierarchy

Change the Save to Database button className from its current outline style to:

```
className="bg-blue-600 hover:bg-blue-700 text-white shadow-md hover:shadow-lg tra
```

Change variant to `variant="default"`. This makes it visually dominant over the utility buttons.

Fix 2.8 — `client/src/components/HoursOfRestGrid.tsx` — mobile view timeline touch

In the mobile view's timeline bar section, add touch handlers to the hour buttons:

```
// On each hour button inside the mobile timeline bar:
onTouchStart={(e) => { e.preventDefault(); startDrag(ri, h); }}
onTouchEnd={() => {}}
```

Add `style={{ touchAction: "none" }}` to the mobile timeline bar container div.

Fix 2.9 — `client/src/components/CrewScheduler.tsx` — fix responsive grids

Change all fixed column grids in this file:

```
// Skill assignment grid — before:
<div className="grid grid-cols-4 gap-4">
// After:
<div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-4 gap-4">

// Port call form grid — before:
<div className="grid grid-cols-1 md:grid-cols-2 gap-4">
// This one is fine, leave it.

// Any grid-cols-3 found in this file — before:
<div className="grid grid-cols-3 gap-4">
// After:
<div className="grid grid-cols-1 sm:grid-cols-3 gap-4">
```

Fix 2.10 — `client/src/components/CrewManagement.tsx` — fix responsive grids

```
// Crew name/rank grid — before:
<div className="grid grid-cols-2 gap-4">
// After:
<div className="grid grid-cols-1 sm:grid-cols-2 gap-4">

// Max hours / min rest / vessel grid — before:
<div className="grid grid-cols-3 gap-4">
// After:
<div className="grid grid-cols-1 sm:grid-cols-3 gap-4">
```

Fix 2.11 — client/src/components/CrewScheduler.tsx — shift template duration auto-calculation

In the shift template form, make `durationH` computed from start and end. Find the `durationH` `FormField` and replace it with a read-only display:

```
// Replace the durationH FormField with:
<FormItem>
  <FormLabel>Duration</FormLabel>
  <div className="flex h-10 items-center px-3 rounded-md border bg-muted text-sm
    {(() => {
      const start = p.shiftForm.watch("start");
      const end = p.shiftForm.watch("end");
      if (!start || !end) return "-";
      const [sh, sm] = start.split(":").map(Number);
      const [eh, em] = end.split(":").map(Number);
      let mins = (eh * 60 + em) - (sh * 60 + sm);
      if (mins < 0) mins += 24 * 60; // cross-midnight
      const hrs = (mins / 60).toFixed(1);
      return `${hrs}h${mins < 0 || (eh < sh) ? " (next day)" : ""}`;
    })()}
  </div>
  <p className="text-xs text-muted-foreground">Calculated from start and end time
</FormItem>
```

Also add a `useEffect` in the form that updates `durationH` whenever start or end changes:

```
React.useEffect(() => {
  const start = p.shiftForm.getValues("start");
  const end = p.shiftForm.getValues("end");
  if (start && end) {
    const [sh, sm] = start.split(":").map(Number);
    const [eh, em] = end.split(":").map(Number);
    let mins = (eh * 60 + em) - (sh * 60 + sm);
    if (mins < 0) mins += 24 * 60;
    p.shiftForm.setValue("durationH", mins / 60);
  }
}, [p.shiftForm.watch("start"), p.shiftForm.watch("end")]);
```

Fix 2.12 — client/src/components/CrewScheduler.tsx — port call / drydock date validation

In `handleAddPortCall` , add at the top:

```
if (p.newPortCall.start && p.newPortCall.end && new Date(p.newPortCall.end) <= new Date(p.newPortCall.start)) {
  toast({ title: "Invalid dates", description: "End time must be after start time" });
  return;
}
```

In `handleAddDrydock` , add at the top:

```
if (p.newDrydock.start && p.newDrydock.end && new Date(p.newDrydock.end) <= new Date(p.newDrydock.start)) {
  toast({ title: "Invalid dates", description: "End time must be after start time" });
  return;
}
```

Below each pair of datetime inputs, add a timezone label:

```
<p className="text-xs text-muted-foreground col-span-2">All times in vessel local time</p>
```

Fix 2.13 — `client/src/components/CrewScheduler.tsx` — sliders: add number input alongside

For each Slider in the Advanced Preferences section, add an editable number input next to it. Replace each slider block pattern with:

```
// Example for fairness — repeat for night_over and pref_off:
<div>
  <div className="flex justify-between items-center mb-2">
    <Label className="text-sm">Fairness</Label>
    <input
      type="number"
      min={0} max={100}
      value={p.preferences.weights.fairness}
      onChange={(e) => p.setPreferences({ ...p.preferences, weights: { ...p.preferences.weights, fairness: e.target.value } })}
      className="w-16 h-7 text-sm text-center border rounded-md bg-background"
    />
  </div>
  <Slider
    value={p.preferences.weights.fairness}
    onValueChange={(val) => p.setPreferences({ ...p.preferences, weights: { ...p.preferences.weights, fairness: val } })}
    min={0} max={100} step={1}
    data-testid="slider-fairness"
  />
</div>
```

```
<p className="text-xs text-muted-foreground mt-1">Balance workload across crew</p>
</div>
```

Fix 2.14 — `client/src/components/CrewNotificationSettingsTab.tsx` — keep sub-toggles visible when master is off

When `emailAlertsEnabled` is false, the sub-toggles currently disappear entirely. Change the conditional rendering from:

```
{localSettings?.emailAlertsEnabled && (
  <>
    <Separator />
    <div className="space-y-4">...</div>
  </>
)}
```

To:

```
<>
  <Separator />
  <div className={cn("space-y-4 transition-opacity", !localSettings?.emailAlertsE
    <h4 className="text-sm font-medium text-muted-foreground">Alert Types</h4>
    { /* ... all three switch rows unchanged ... */ }
  </div>
  { !localSettings?.emailAlertsEnabled && (
    <p className="text-xs text-muted-foreground mt-1">
      Enable the master switch above to configure individual alert types.
    </p>
  ) }
</>
```

Add `import { cn } from "@lib/utils";` if not already imported.

SECTION 3: COMPLIANCE & SAFETY-CRITICAL SCREENS

Fix 3.1 — `client/src/components/HoursOfRest.tsx` — calendar cell click for violation detail

Make each calendar cell interactive. Replace the existing day cell div with:

```

const [selectedDayDetail, setSelectedDayDetail] = React.useState<typeof calendarG

// Cell:
<button
  key={dayData.day}
  onClick={() => setSelectedDayDetail(selectedDayDetail?.day === dayData.day ? nu
  className={cn(
    "p-2 text-center text-xs border rounded transition-all",
    dayData.compliant
      ? "bg-green-100 border-green-300 text-green-800 dark:bg-green-900/30 dark:b
      : "bg-red-100 border-red-300 text-red-800 dark:bg-red-900/30 dark:border-re
    selectedDayDetail?.day === dayData.day && "ring-2 ring-primary"
  )}
  title={` ${dayData.date}: ${dayData.restHours}h rest – tap for details`}
  data-testid={`calendar-day-${dayData.day}`}
  aria-label={` ${dayData.date}: ${dayData.restHours} hours rest, ${dayData.compli
>
  <div className="font-semibold">{dayData.day}</div>
  <div>{dayData.restHours}h</div>
</button>

```

After the calendar grid, add the detail panel:

```

{selectedDayDetail && (
  <div className="mt-3 p-3 border rounded-lg bg-muted/50 text-sm space-y-1" data-
    <p className="font-semibold">{selectedDayDetail.date}</p>
    <div className="flex items-center gap-2">
      {selectedDayDetail.restHours >= 10
        ? <CheckCircle2 className="h-4 w-4 text-green-500" />
        : <AlertTriangle className="h-4 w-4 text-red-500" />}
      <span>Rest recorded: <strong>{selectedDayDetail.restHours}h</strong> (minim
    </div>
    <p className="text-xs text-muted-foreground">
      7-day cumulative and block-split rules require the full Hours of Rest grid.
    </p>
  </div>
)}

```

Add necessary imports: `CheckCircle2`, `AlertTriangle` from `lucide-react`, `cn` from `@/lib/utils`.

Fix 3.2 — `client/src/components/CrewScheduler.tsx` — STCW compliance projected disclaimer

Find the STCW compliance summary section (the one with "STCW Compliance Summary" heading) and add immediately above it:

```
<div className="mb-3 p-3 bg-amber-50 dark:bg-amber-950 border border-amber-200 da
  <AlertTriangle className="h-4 w-4 mt-0.5 flex-shrink-0" />
  <span>
    <strong>Projected only.</strong> This compliance check is based on the propos
    and does not account for pre-existing logged hours of rest. Verify against ac
    Hours of Rest records before Port State Control inspection.
  </span>
</div>
```

Fix 3.3 — `client/src/components/CrewScheduler.tsx` — STCW compliance table overflow

Wrap the raw compliance table in a scroll container:

```
// Before:
<table className="w-full text-sm border-collapse ..." >
// After — wrap with:
<div className="overflow-x-auto rounded-lg border">
  <table className="w-full text-sm border-collapse ..." >
  </table>
</div>
```

Fix 3.4 — `client/src/components/crew/FatigueRiskBadge.tsx` — popover affordance + methodology

Step A: Add click affordance to the badge. Change the badge to include a `ChevronDown` icon:

```
// In the badge JSX, after the existing label span, add:
<ChevronDown className="h-2.5 w-2.5 opacity-60" />
```

Add `ChevronDown` to the `lucide-react` import.

Step B: In `FatigueDetailsContent`, add thresholds and methodology note after the score Progress bar:

```
<div className="text-xs text-muted-foreground space-y-1 pt-1">
```

```

<p className="font-medium">Score thresholds</p>
<p>Low: 0-39 · Medium: 40-59 · High: 60-79 · Critical: 80+</p>
<p className="pt-1">
  Score is based on sleep debt, consecutive night shifts, night work ratio,
  and weekly work hours over the last {lookbackDays ?? 14} days.
</p>
<p className="pt-1 italic">
  Operational aid only. Consult your SMS for fatigue management procedures.
</p>
</div>

```

Add this block just before the closing `</div>` of the `FatigueDetailsContent` component, after the last `<Separator />`.

Note: `lookbackDays` is not in scope inside `FatigueDetailsContent`. Either pass it as a prop: `function FatigueDetailsContent({ data, crewName, lookbackDays = 14 }: ...) and update the call site to pass it, or hardcode the default value 14 inline.`

Fix 3.5 — `client/src/components/CertificationExpiryAlerts.tsx` — add “Mark as Renewed” action

In the `CertRow` component, after the existing Acknowledge button, add a “Renewed” state. Add a “Mark as Renewed” button when cert IS acknowledged but not yet resolved:

```

// After the existing !cert.alertAcknowledged button block, add:
{cert.alertAcknowledged && (
  <Button
    variant="ghost"
    size="sm"
    className="ml-4 text-green-600 hover:text-green-700 hover:bg-green-50"
    onClick={() => onMarkRenewed?.(cert)}
    data-testid={`button-renewed-${cert.id}`}
  >
    <Check className="h-3 w-3 mr-1" />Mark as Renewed
  </Button>
)}

```

Update `CertRow` props to include `onMarkRenewed?: (cert: ExpiringCertification) => void`. Wire this up in `CertificationExpiryAlertBanner` — for now it can call a `console.log` placeholder if the mutation doesn’t exist yet:

```

const handleMarkRenewed = (cert: ExpiringCertification) => {
  // TODO: implement renewCertMutation when API endpoint is available

```



```
toast({ title: "Marked as renewed", description: `${cert.cert} for ${cert.crewM
};
```

Pass `onMarkRenewed={handleMarkRenewed}` to each `CertRow`.

Fix 3.6 — `client/src/components/DocumentExpiryAlerts.tsx` — same “Mark as Renewed”

Apply the identical pattern as Fix 3.5 to `DocumentRow` and `DocumentExpiryAlertBanner`.
Use `onMarkRenewed?: (doc: ExpiringDocument) => void` on `DocumentRow`.

Fix 3.7 — `client/src/components/HoursOfRest.tsx` — add 7-day rule disclaimer

Add this note directly in the `CardDescription` of the calendar card:

```
<CardDescription>
  Daily rest hours visualization (
    <span className="text-green-700 dark:text-green-400 font-medium">green = compli
    <span className="text-red-700 dark:text-red-400 font-medium">red = violation &l
  )
  <span className="block mt-1 text-amber-600 dark:text-amber-400 text-xs">
    This calendar reflects the 24h minimum rest rule only.
    The 77h/7-day rule and rest-block-split rules require the full Hours of Rest
  </span>
</CardDescription>
```

SECTION 4: MOBILE RESPONSIVENESS

Fix 4.1 — All files with `grid-cols-3` or `grid-cols-4` — add responsive breakpoints

Search every file in `client/src/components/` and `client/src/pages/` for these patterns and apply the replacements below. Do NOT change grids that are inside data tables or intentionally fixed-width UI (like the `HoursOfRestGrid` hour columns).

```
"grid grid-cols-3" → "grid grid-cols-1 sm:grid-cols-3"
"grid grid-cols-4" → "grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-4"
"grid-cols-3 gap-4" → "grid-cols-1 sm:grid-cols-3 gap-4"
"grid-cols-4 gap-4" → "grid-cols-1 sm:grid-cols-2 lg:grid-cols-4 gap-4"
```

Affected files include at minimum:

- CrewManagement.tsx
 - CrewScheduler.tsx
 - HoursOfRestGrid.tsx (summary stats grid only, NOT the hour columns)
 - logs-compliance-hub.tsx
 - desktop-setup.tsx
-

Fix 4.2 — client/src/components/HoursOfRestGrid.tsx — mobile view paint mode

In the mobile view's day cards, on the timeline bar container, add:

```
style={{ touchAction: "none" }}
onTouchMove={ (e) => {
  e.preventDefault();
  const touch = e.touches[0];
  const el = document.elementFromPoint(touch.clientX, touch.clientY) as HTMLEleme
  if (el?.dataset?.mobileHour && el?.dataset?.mobileRow) {
    onDrag(Number(el.dataset.mobileRow), Number(el.dataset.mobileHour));
  }
}}
```

On each hour button inside the mobile timeline, add:

```
data-mobile-row={ri}
data-mobile-hour={h}
onTouchStart={ (e) => { e.preventDefault(); startDrag(ri, h); }}
```

Fix 4.3 — client/src/components/CrewScheduler.tsx — STCW results table mobile

The compliance results table is a raw HTML table. Wrap it:

```
// Before:
<div className="overflow-x-auto">
  <table className="w-full text-sm ...">
// This may already be wrapped — if not, add the wrapper.
// Also add a note above the table on mobile:
```

Add above the table:

```
<p className="text-xs text-muted-foreground mb-2 sm:hidden">
  Scroll horizontally to see full compliance data →
</p>
```

Fix 4.4 — `client/src/components/crew/STCWComplianceWidget.tsx` — mobile scroll hint

The vessel breakdown ScrollArea may overflow on mobile. Add a scroll hint:

```
// Above the ScrollArea:
<p className="text-xs text-muted-foreground mb-1 sm:hidden">Tap a vessel to expand</p>
```

Fix 4.5 — `client/src/pages/home.tsx` — dock positioning fix for mobile

The dock sits at `bottom-4` which conflicts with iOS Safari's gesture area and the new BottomNav. Change all dock and hint containers:

```
// Fixed dock container className - change:
"fixed bottom-4 left-1/2 -translate-x-1/2 z-50"
// To:
"fixed bottom-16 left-1/2 -translate-x-1/2 z-50 md:bottom-4"

// Same for the onboarding hint container.
```

Fix 4.6 — Global — add `pb-safe` padding for iOS home bar

In the root layout or App.tsx, add bottom padding to account for iOS safe area:

```
// On the main content wrapper element, add to className:
"pb-safe"
// And in global CSS (index.css or globals.css), add:
.pb-safe {
  padding-bottom: env(safe-area-inset-bottom, 0px);
}
```

SECTION 5: VISUAL CONSISTENCY FIXES

Fix 5.1 — `client/src/components/crew/FatigueRiskBadge.tsx` — badge is interactive, make it obvious

The badge opens a popover but looks like a static label. Add a subtle ring on focus and ensure the badge has `tabIndex={0}` so keyboard users can access it:

```
// On the Badge component used as PopoverTrigger, add:
tabIndex={0}
className={cn(
  "gap-1.5 cursor-pointer transition-all",
  "hover:ring-2 hover:ring-offset-1 hover:ring-primary/50",
  "focus:ring-2 focus:ring-offset-1 focus:ring-primary",
  config.bgColor, config.color, config.borderColor,
  className
)}
aria-haspopup="true"
aria-label={`Fatigue risk: ${config.label}${showScore ? ` (score: ${fatigueData.s`
```

Fix 5.2 — `client/src/components/CertificationExpiryAlerts.tsx` — fix flex/inline-flex conflict

```
// Find:
<span className="flex items-center gap-1 inline-flex">
// Replace with:
<span className="inline-flex items-center gap-1">
```

Fix 5.3 — Dark mode hardcoded colors audit

In the following files, replace hardcoded color classes that don't respond to dark mode:

In `client/src/pages/not-found.tsx`:

```
// Before:
"min-h-screen w-full flex items-center justify-center bg-gray-50"
"text-2xl font-bold text-gray-900"
"text-sm text-gray-600"
// After:
"min-h-screen w-full flex items-center justify-center bg-background"
```

```
"text-2xl font-bold text-foreground"
"text-sm text-muted-foreground"
```

In `client/src/components/CrewScheduler.tsx`, find raw HTML table cells with `text-gray-600`:

```
// Before: className="text-gray-600"
// After:  className="text-muted-foreground"
```

Find `bg-gray-50 dark:bg-gray-800` pattern in the crew member list:

```
// Before: className="... hover:bg-gray-50 dark:hover:bg-gray-800 ..."
// After:  className="... hover:bg-muted/50 ..."
```

Find `bg-gray-50` in compliance table rows:

```
// Before: className="p-3 bg-gray-50"
// After:  className="p-3 bg-muted/50"
```

Fix 5.4 — `client/src/components/HoursOfRestGrid.tsx` — checkmark emoji to icon

```
// Before:
<span className="text-lg">✓</span>
// After:
<CheckCircle2 className="h-4 w-4 text-emerald-600 dark:text-emerald-400 inline" /
```

Ensure `CheckCircle2` is imported from `lucide-react`.

SECTION 6: ACCESSIBILITY

Fix 6.1 — `client/src/components/HoursOfRestGrid.tsx` — grid cell ARIA

On every grid cell div in the main grid, add:

```
role="checkbox"
aria-checked={isRest}
aria-label={` ${isRest ? "Rest" : "Work"} at ${String(h).padStart(2, "0")}:00${isN
onKeyDown={ (e) => {
  if (e.key === " " || e.key === "Enter") {
```

```
e.preventDefault();
startDrag(actualIndex, h);
}
}}
tabIndex={0}
```

Fix 6.2 — `client/src/components/CrewScheduler.tsx` — STCW table header scope

Add `scope="col"` to every `<th>` in the raw STCW compliance table:

```
<th scope="col" className="border border-gray-300 dark:border-gray-600 px-2 py-1
<th scope="col" className="border border-gray-300 dark:border-gray-600 px-2 py-1
<th scope="col" className="border border-gray-300 dark:border-gray-600 px-2 py-1
<th scope="col" className="border border-gray-300 dark:border-gray-600 px-2 py-1
<th scope="col" className="border border-gray-300 dark:border-gray-600 px-2 py-1
<th scope="col" className="border border-gray-300 dark:border-gray-600 px-2 py-1
```

Fix 6.3 — `client/src/components/HoursOfRest.tsx` — calendar cell ARIA

Each calendar day button already has an `aria-label` from Fix 3.1 above. Also add to the calendar grid container:

```
role="grid"
aria-label="Monthly rest hours calendar"
```

Add to each day-of-week header div:

```
role="columnheader"
```

SECTION 7: SCHEDULING UX

Fix 7.1 — `client/src/components/CrewScheduler.tsx` — crew list expand

The crew status tab hard-caps at 6 members with "and N more" but no way to expand. Replace the slice and the "more" text with a collapsible:

```
import { Collapsible, CollapsibleContent, CollapsibleTrigger } from "@/components
```

```

const [showAllCrew, setShowAllCrew] = React.useState(false);
const visibleCrew = showAllCrew ? p.crew : p.crew.slice(0, 6);

// Replace the slice + "and N more" div with:
{visibleCrew.map((member: Crew) => (
  // ... existing member div unchanged ...
))}
{p.crew.length > 6 && (
  <button
    onClick={() => setShowAllCrew(!showAllCrew)}
    className="w-full text-center text-sm text-primary hover:underline py-2"
  >
    {showAllCrew ? "Show less" : `Show all ${p.crew.length} crew members`}
  </button>
)}

```

Fix 7.2 — Remove duplicate skill assignment entry point in

`client/src/components/CrewManagement.tsx`

The "Add Skills" card on the Crew Members tab (TabsContent value="crew") is a duplicate of the "Assign Skills" tab. Remove the entire second Card (the one with CardTitle "Add Skills") from the `value="crew"` TabsContent. The Skills assignment functionality is fully covered by the `value="assign"` tab.

Keep the first Card (Add Crew Member) in the crew tab. Keep the crew roster Card in the crew tab. Remove only the "Add Skills to crew members" Card from the crew tab.

VALIDATION CHECKLIST

After applying all fixes, verify:

- Dock pin icon appears on hover on desktop category cards
- Long-press or pin button works on touch devices (test in browser mobile emulation)
- Bottom nav renders on screens < 768px and is hidden on desktop
- Bottom nav does not overlap dock or content
- HoR grid auto-switches to mobile view on < 768px screens
- Grid cells respond to touch drag (test in mobile emulation)

- Clear All shows confirmation dialog before clearing
 - STCW validation checkbox defaults to checked
 - STCW compliance table shows projected disclaimer
 - Calendar cells are tappable and show detail panel
 - Undo/redo buttons show step count in tooltip
 - Save button is visually dominant (filled, not outline)
 - All grid-cols-3/4 forms are readable at 375px width
 - Fatigue badge has ChevronDown icon and is keyboard focusable
 - Sub-toggles in notification settings remain visible (greyed) when master switch is off
 - Shift template duration auto-calculates from start/end times
 - Port call form validates end > start
 - No "and N more" dead ends in crew list — show all button works
 - Dark mode: not-found page, scheduler table, crew list use semantic colors
-

DO NOT CHANGE

- Any file in @shared/
- Any API endpoint URLs or query keys (except the fatigue query key fix from previous prompt)
- Any routing configuration files
- Any test files
- The HoursOfRestGrid hour column widths (hourW constant) — these are intentional
- Any authentication or permission logic