Swimming against a superfluid flow: Self-propulsion via vortex-antivortex shedding in a quantum fluid of light Supplemental material

Myrann Baker-Rasooli,[1] Tangui Aladjidi,[1] Tiago D. Ferreira,[2] Alberto Bramati,[1,3] Mathias Albert,[4,3] Pierre-Élie Larré,[5,*] and Quentin Glorieux[1,3,†]

[1] *Sorbonne Université, ENS Paris, Collège de France, Université PSL, CNRS, Laboratoire Kastler Brossel, F-75005 Paris, France*
[2] *Universidade do Porto and INESC TEC, Centre of Applied Photonics, Rua do Campo Alegre, Porto, Portugal*
[3] *Institut Universitaire de France (IUF)*
[4] *Université Côte d'Azur, CNRS, INPHYNI, France*
[5] *Université Paris-Saclay, CNRS, LPTMS, 91405, Orsay, France*

CROSS-PHASE MODULATION

In our experiment, the full system is described by two coupled NLS equations for the optical fields $E(\mathbf{r}_\perp, z)$ and $E_\mathrm{i}(\mathbf{r}_\perp, z)$ of the superfluid and impurity beams, respectively:

$$i\partial_z E = \left(-\frac{\nabla_\perp^2}{2k_0} - k_0 n_2 |E|^2\right) E + g_\mathrm{XPM} |E_\mathrm{i}|^2 E, \quad (1)$$

$$i\partial_z E_\mathrm{i} = \left(-\frac{\nabla_\perp^2}{2k_\mathrm{i}} - k_\mathrm{i} n_{2,\mathrm{i}} |E_\mathrm{i}|^2\right) E_\mathrm{i} + g_\mathrm{XPM} |E|^2 E_\mathrm{i}. \quad (2)$$

In these equations, g_XPM denotes the cross-phase-modulation (XPM) coupling constant, and $n_{2,\mathrm{i}} > 0$ describes self-focusing for the impurity beam at k_i. When the paraxial diffraction is compensated by the self-focusing nonlinearity, the impurity beam acquires a bright-soliton-like spatial shape in the $\mathbf{r}_\perp$ plane, resulting in a nondeformable impurity potential $V(\mathbf{r}_\perp, z) = g_\mathrm{XPM} |E_\mathrm{i}(\mathbf{r}_\perp, z)|^2$ along z for the superfluid of light.

EXPERIMENTAL SETUP

As shown in Fig. 1, we create a superfluid of light by propagating a 780 nm laser beam through a $L = 20$ cm-long ^{87}Rb-vapor cell heated to 150 °C, which acts as a nonlinear medium. The beam is slightly detuned from the rubidium D2 line (~ -8 GHz) to have a substantial optical nonlinearity. An optical impurity is introduced by overlapping an auxiliary beam with the beam creating the superfluid, along the z axis at the center of the cell. This impurity beam has a waist $\sigma \simeq 7.5\xi$ of the order of a few healing lengths $\xi \simeq 50$ μm, much smaller than the overall transverse size $\sim 100\xi$ of the superfluid. To make the impurity act as a transverse potential barrier for the superfluid, the 795 nm impurity beam is tuned close to the D1 line with a positive detuning ($\sim +2$ GHz), leading to a relative linear-refractive-index change via optical pumping. The transverse-flow velocity past this potential barrier is optically controlled by only adjusting the superfluid-beam angle $\mathbf{k}_\perp$ with a piezo-mirror, while the impurity beam is on-axis.




FIG. 1. **Experimental setup.** A 780 nm laser beam is sent into a 20 cm-long rubidium-vapor cell to generate the superfluid of light. An optical impurity is produced with a 795 nm, narrower laser beam, overlapping with the superfluid beam. It is tuned close to the D1 line with a positive detuning ($\sim +2$ GHz), leading to a relative linear-refractive-index change via optical pumping. The output plane of the nonlinear medium is then imaged on a camera. The relative angle between the laser beams is set by a piezo-mirror, which adjusts the fluid-beam angle at the input. A reference beam, different from the initial fluid beam, is recombined with the main beam before the camera to enable phase measurement. The side of the cell is also imaged with a microscope placed on a translation stage, and the measured fluorescence is sent to another camera.

Using a dual-imaging system, we simultaneously measure the fluorescence of the beams from the side and record the amplitude and phase of the superfluid of light at the exit of the rubidium cell. These are recorded using an off-axis interferometer. The side of the cell is imaged with a microscope located on a translation stage, and the measured fluorescence is sent to an other camera, making it possible to reconstruct, as a function of the propagation time z, the impurity-beam trajectory.

SUPERFLUID VELOCITY

From the superfluid-phase map $\phi = \phi(\mathbf{r}_\perp)$, we reconstruct the total velocity field of the flow, $\mathbf{v}(\mathbf{r}_\perp) = \nabla_\perp \phi(\mathbf{r}_\perp)/k_0$.




FIG. 2. **From the phase to the velocity of the superfluid.** The total velocity, reconstructed from the combination of each gradient component calculated using the 1D unwrapped-phase method.

To compute the velocity map, we must first perform a 2D unwrapping of the phase. However, because we work with discretized data arrays, phase singularities (i.e., 2π windings) create numerical discontinuities that prevent an accurate reconstruction [1]. To circumvent this issue, the phase is unwrapped separately along each axis, yielding ϕ'_x and ϕ'_y. The total velocity field is then obtained by combining the gradient components computed from these two independently unwrapped phase profiles, as illustrated in Fig. 2.

SOUND VELOCITY

When entering the rubidium cell, the fluid beam undergoes a sudden increase in energy as a function of the propagation time z, due to the presence of the impurity potential. This energy is typically redistributed into counterpropagating sound waves with velocities $\pm c_s$ in the transverse $\mathbf{r}_\perp$-plane, a process analogous to quench dynamics in weakly interacting quantum gases. We measure the speed of sound c_s in the superfluid by analyzing the transverse separation of these waves at final time $z = L$. Specifically, half their transverse separation, r_s, is related to c_s by the simple relation $r_s = c_s L$.

This measurement is performed in the density difference $\rho - \rho_0$, where ρ is the superfluid density with the impurity, and ρ_0 is the density without it. Typical images are shown in Fig. 3 (top panels). We then perform an azimuthal average of this density difference, centered on the impurity, which is shown as a function of the radial position in the bottom panel. From the position r_s of the sound wave (corresponding to the density dip and indicated by the red vertical line), we extract the speed of sound c_s from $r_s = c_s L$. Since this measurement is performed at the exit of the hot vapor and the camera collects light cumulatively, the procedure does not provide the instantaneous speed of sound but rather its value averaged over the entire propagation, taking into account light absorption through the medium.




FIG. 3. **Measuring the speed of sound.** Top: The fluid density without the impurity, ρ_0, is subtracted from the fluid density with the impurity, ρ, revealing the formation of an acoustic perturbation (blue annulus) expanding with velocity c_s in the transverse plane. Bottom: This speed of sound is deduced from the location $r_s = c_s L$ of the acoustic dip (vertical dotted line) in the averaged $\rho - \rho_0$ at final propagation time $z = L$.

VORTEX-SHEDDING FREQUENCY

We assume that the shedding of vortex-antivortex pairs occurs periodically and consider that each new pair detected by the camera is produced at the exit of the cell, supposing it forms instantaneously. Fig. 4 provides a schematic view of the vortex pairs periodically emitted along the rubidium cell as the Mach number of the flow, β, is increased from the critical value $\beta_1 = \beta_c$ required for nucleation of the first pair. Each time the camera detects the ith pair at $\beta = \beta_i$ ($i \geqslant 1$), the time elapsed since the observation of the $(i-1)$th pair at $\beta = \beta_{i-1}$ is necessarily $\Delta z_i = L/i$. From the data $\{\beta_i, \Delta z_i\}$ we infer the vortex-shedding frequency $1/\Delta z$ as a function of the flow Mach number β, which exhibits a linear trend very consistent with previous cold-atom experiments [2] [see Fig. 2(c) of the main text].

COUNTERFLOW IMPURITY MOTION: THEORY

The studied system is composed of two components: a 2D ($\mathbf{r}_\perp = x\hat{\mathbf{x}} + y\hat{\mathbf{y}}$) superfluid of light flowing in the positive-x direction with incoming density ρ_0 and velocity v_0; and an optical impurity embedded within the vapor, modeled as a repulsive, localized potential $V(\mathbf{r}_\perp - X\hat{\mathbf{x}})$ with maximum amplitude V_0, characteristic radius σ, and time-dependent




FIG. 4. **Periodic vortex shedding along the cell.** For each emission event $i \geqslant 1$ at the output of the cell, the shedding frequency $1/\Delta z$ is inferred by dividing the Rb cell into i segments. The first (second, third) pair at $\beta = \beta_1 = \beta_c$ (β_2, β_3) is in blue (red, green).

center-of-mass position $X(z)$ along the incoming stream. This is illustrated in Fig. 5, which also schematically shows one of the vortex-antivortex pairs responsible for propelling the impurity upstream. The notations are the ones used in the main text.

The superfluid is described by an electric field with a slowly varying envelope $E(\mathbf{r}_\perp, z)$ obeying the NLS equation [Eq. (1) in the main text]. Its Hamiltonian, in the absence of the impurity, is given by

$$H_\mathrm{f} = \alpha \int d^2\mathbf{r}_\perp \left(\frac{|\nabla_\perp E|^2}{2k_0} - \frac{k_0 n_2 \rho^2}{2} \right), \tag{3}$$

where the first, mass term originates from paraxial diffraction (k_0 is the propagation constant of the laser beam creating the superfluid), and the last, interaction term is due to the Kerr nonlinearity of the vapor ($n_2\rho$ is the Kerr shift




FIG. 5. **Schematic of the system.** A superflow (blue) impinges upon a mobile impurity (gray), which self-propels upstream by vortex-antivortex shedding downstream.

in the local refractive index of the vapor, with $n_2 < 0$ and $\rho = |E|^2$ the superfluid density). The constant α ensures that H_f has the correct units of a wave number in the language of superfluids of light [see discussion after (16)]. Here, we focus solely on the motion of the impurity's center of mass, disregarding any temporal change to its shape. Therefore, the impurity can be modeled as a point particle whose dynamics, in the absence of the superfluid, is obtained from the kinetic Hamiltonian

$$H_\mathrm{i} = \frac{P^2}{2k_\mathrm{i}}. \tag{4}$$

In this equation, $P(z)$ denotes the momentum of the impurity's center of mass, and k_i is its mass. Finally, the fluid and the impurity interact via the standard Hamiltonian

$$H_\mathrm{f,i} = \alpha \int d^2\mathbf{r}_\perp \; V(\mathbf{r}_\perp - X\hat{\mathbf{x}})\rho, \tag{5}$$

where α is the same normalization constant as in (3). The equations of motion obtained from the full Hamiltonian, $H = H_\mathrm{f} + H_\mathrm{i} + H_\mathrm{f,i}$, are $\partial_z(\sqrt{\alpha}E) = \delta H/\delta(i\sqrt{\alpha}E^*)$ (and its complex conjugate), $\dot{X} \equiv dX/dz = \partial_P H$, and $\dot{P} = -\partial_X H$, which leads to the coupled dynamical equations

$$i\partial_z E = \left[-\frac{\nabla_\perp^2}{2k_0} + V(\mathbf{r}_\perp - X\hat{\mathbf{x}}) - k_0 n_2 \rho \right] E, \tag{6}$$

$$k_\mathrm{i}\ddot{X} = F = \alpha \int d^2\mathbf{r}_\perp \; \partial_x V(\mathbf{r}_\perp - X\hat{\mathbf{x}})\rho. \tag{7}$$

Equation (6) is nothing but Eq. (1) of the main text, and (7) is Newton's second law of motion for the impurity's center of mass, where the force F coincides with the drag force exerted by the superfluid on the impurity (see, e.g., Ref. [3]). This final equation for the impurity's trajectory along the incoming stream, $X = X(z)$, is highly nonlinear but can be approximately solved under certain simplifying physical hypotheses, as detailed below. In the following, we analyze a single cycle of vortex-antivortex shedding. The full trajectory is then obtained by using the final center-of-mass position and velocity in each cycle as the initial conditions for the next.

The core object in (7) is the drag force experienced by the impurity, F, which we evaluate in the following way:

$$F = -\alpha \int d^2\mathbf{r}_\perp \; V(\mathbf{r}_\perp)\partial_x \rho(\mathbf{r}_\perp + X\hat{\mathbf{x}}, z) \tag{8}$$

$$\approx -\alpha \ell V_0 (\rho_\mathrm{down} - \rho_\mathrm{up}). \tag{9}$$

Equation (8) is obtained from a straightforward change of variables and integration by parts. Approximation (9) assumes a top-hat potential of large spatial extent [i.e., $V(\mathbf{r}_\perp) = V_0$ for $r_\perp < \sigma$ with σ large, and zero otherwise], and weak density gradients in the direction perpendicular to the collimated incoming flux. Thus, the 2D force can be safely approximated [4] by the difference in density between the downstream ($x = X + \sigma$) and upstream

($x = X - \sigma$) poles of the impurity, weighted by an effective fluid-impurity cross-section ℓ. Then, to evaluate $\rho_{\rm up}$ and $\rho_{\rm down}$, we use the Madelung equation for the superfluid's velocity field $\mathbf{v} = \nabla_\perp \arg(E)/k_0$, which is the real part of the NLS equation (6) (see, e.g., Ref. [5]). The dispersionless limit for this equation is appropriate in the configuration of our experiment, where σ is larger than the healing length $\xi = 1/(2k_0^2|n_2|\rho_0)^{1/2}$. In addition, we assume that the velocity field surrounding the impurity does not vary significantly over one cycle of vortex emission. Therefore, the densities $\rho_{\rm up}$ and $\rho_{\rm down}$ can be evaluated in terms of the velocities $\mathbf{v}_{\rm up}$ and $\mathbf{v}_{\rm down}$, respectively, from the Bernoulli-type law

$$\frac{k_0 \mathbf{v}_{\rm up,down}^2}{2} - k_0 n_2 \rho_{\rm up,down} = \frac{k_0 v_0^2}{2} - k_0 n_2 \rho_0. \tag{10}$$

Upstream, we roughly approximate the velocity of the flow to its asymptotic value:

$$\mathbf{v}_{\rm up} \approx v_0 \hat{\mathbf{x}}. \tag{11}$$

Downstream, the emitted vortex-antivortex pair superimposes on the background flow, which results in a total velocity $\mathbf{v}_{\rm down} \approx v_0\hat{\mathbf{x}} + \mathbf{v}_{\rm v}$. A point-vortex model, which can be obtained from the 2D Hamiltonian (3) [6], makes it possible to evaluate $\mathbf{v}_{\rm v}$ in the form (see, e.g., Ref. [7])

$$\mathbf{v}_{\rm v} = \sum_{\nu=\pm1} \frac{\Gamma_\nu}{2\pi}\left(-\frac{y-y_\nu}{|\mathbf{r}_\perp - \mathbf{r}_\nu|^2}\hat{\mathbf{x}} + \frac{x-x_\nu}{|\mathbf{r}_\perp - \mathbf{r}_\nu|^2}\hat{\mathbf{y}}\right), \tag{12}$$

where $\Gamma_\nu = 2\pi\nu/k_0$ is the circulation of the flow velocity around the vortex with charge $\nu = \pm 1$ and position $\mathbf{r}_\nu = x_\nu\hat{\mathbf{x}} + y_\nu\hat{\mathbf{y}}$, where $x_\nu = x_{-\nu} = x_0$ and $y_\nu = -\nu\sigma$ (see Fig. 5). This leads to, at the center of the pair for simplicity ($x = x_0$ and $y = 0$),

$$\mathbf{v}_{\rm down} \approx \left(v_0 - \frac{2}{k_0\sigma}\right)\hat{\mathbf{x}}. \tag{13}$$

Insertion of Eqs. (11) and (13) into (10) yields

$$\rho_{\rm up} \approx \rho_0, \tag{14}$$

$$\rho_{\rm down} \approx \rho_0 + \Delta\rho, \quad \Delta\rho = 2\sqrt{2}\rho_0\frac{\xi}{\sigma}\left(\beta - \sqrt{2}\frac{\xi}{\sigma}\right), \tag{15}$$

where $\beta = v_0/c_{\rm s}$ is the Mach number of the incoming flow, $c_{\rm s} = (|n_2|\rho_0)^{1/2}$ being the speed of sound far from the impurity.

When the expressions for the upstream and downstream densities from Eqs. (14) and (15) are substituted into the drag force (9), Newton's law (7) for the motion of the impurity's center of mass along the incoming stream integrates easily to give

$$X(z) \approx Az^2 + \dot{X}_0 z + X_0, \quad A = -\frac{\alpha\ell V_0 \Delta\rho}{k_{\rm i}}. \tag{16}$$

In these equations, X_0 and $\dot{X}_0$ are the initial position and velocity, respectively, of the impurity for the cycle in question (for the very first cycle, both X_0 and $\dot{X}_0$ are zero). The acceleration A, given by the second of Eqs. (16), depends on several key quantities, starting with the normalization constant α introduced in (3). This constant incorporates the microscopic parameters of the laser and medium used to produce the superfluid of light. Because we do not derive its exact form here, we treat it as a fitting parameter to match the parabolic model (16) to the measured trajectory (with X_0 and $\dot{X}_0$ extracted from data). Given that $\alpha \simeq 3\ {\rm V}^{-2}$ is found to be of a nonextreme order of magnitude, we are confident that the remaining dependencies in the formula for A are sufficient to explain its underlying physics. These remaining factors include the effective fluid-impurity cross-section ℓ, which we estimate as the impurity diameter $2\sigma \simeq 15\xi$ plus twice a vortex diameter for a top-hat beam and to the beam waist for a Gaussian beam, the impurity's amplitude $V_0 \simeq 7.9\ {\rm m}^{-1}$, and, most importantly, the downstream density variation $\Delta\rho$, whose expression in terms of the impurity's radius σ and the Mach number β is provided in (15). From the latter dependence, we deduce that the acceleration A is negative, i.e. the impurity is propelled upstream, if

$$\beta > \sqrt{2}\frac{\xi}{\sigma}. \tag{17}$$

This condition is met at a sufficiently high flow velocity compared to the speed of sound, or for a sufficiently wide impurity compared to the healing length. In our experiment, $\sqrt{2}\xi/\sigma \simeq 0.19$ ($\sigma \simeq 7.5\xi$), which is below the critical Mach number for vortex nucleation that we measure, $\beta_{\rm c} \simeq 0.35$. Therefore, constraint (17) is satisfied in our setup ($\beta \gtrsim \beta_{\rm c}$), quantitatively conditioning upstream motion of the impurity. Interestingly, this is associated with the formation of a density hump downstream, $\Delta\rho > 0$, most certainly due to the clockwise (for $y > 0$) and anticlockwise ($y < 0$) vorticity windings (see Fig. 5), which together drag light intensity to the rear of the impurity. This density hump acts as a repulsive potential for the impurity, which then moves upstream to minimize its energy. It is worth noting that this model is intentionally simplified: it focuses on the local density difference associated with a single point-vortex pair in a homogeneous fluid, forgetting about the complex transient gradients in the wake that may momentarily modify the sign of the full density imbalance $\Delta\rho$. However, even a transient $\Delta\rho > 0$ (here associated with vortices) appears sufficient to kick the impurity upstream. Furthermore, while the upstream motion of the impurity is a cumulative effect of sequential pair emissions, we argue that our single-pair approach remains robust: the influence of older vortices decays rapidly with distance as they are swept downstream, ensuring the force is dominated by the most recently nucleated pair.

Counterflow motion of the impurity is explained by the shedding of vortices downstream, once the Mach number β exceeds the critical value $\beta_{\rm c} \simeq 0.35$. When β is further increased, other excitations are stimulated in the superfluid, such as *sound waves* upstream. As evidenced in the main text, this occurs for β approaching unity, surely for




FIG. 6. **Sound and vortex contributions to the total drag.** The force F_s is the contribution from the sound waves emitted upstream for $\beta \gtrsim 1$ [Eq. (18)], and F_v is the one from the vortex pairs emitted downstream [Eqs. (9), (14), and (15)]. Both forces are plotted in arbitrary units against the impurity's radius σ in units of the healing length. The shaded area corresponds to the regime where self-propulsion against the flow is possible at sonic velocities, characterized by a total drag force $F_\mathrm{v} + F_\mathrm{s} < 0$.

$\beta \gtrsim 1$, i.e., when the flow velocity v_0 exceeds the speed of sound c_s. In this velocity regime, the work imparted by this sonic radiation manifests as a positive drag force F_s, opposite to the negative vortex force $F \equiv F_\mathrm{v}$ estimated in Eqs. (9), (14), and (15). For a Gaussian potential $V(\mathbf{r}_\perp) = V_0 \exp[-\mathbf{r}_\perp^2/(2\sigma^2)]$, the dependence of F_s on β and σ can be easily estimated provided V_0 is smaller than the inverse nonlinear length, $1/z_\mathrm{NL}$. We find [8]

$$F_\mathrm{s} \propto \frac{\bar\beta^2}{\beta}\frac{\sigma^4}{\xi^4} e^{-\bar\beta^2\sigma^2/\xi^2}\Big[I_0(\bar\beta^2\sigma^2/\xi^2) - I_1(\bar\beta^2\sigma^2/\xi^2)\Big], \quad (18)$$

where $\bar\beta = [2(\beta^2-1)]^{1/2}$ and I_n is the modified Bessel function of the first kind. Assuming vortices still contribute to the drag at these sonic velocities and for such an impurity, motion against the incoming stream is only possible when the sound contribution F_s is not large enough to overcome the vortex contribution F_v, specifically when $F_\mathrm{s} < -F_\mathrm{v}$ (see Fig. 6). This situation contrasts with the experiment by Michel *et al.* [4], where the impurity strength V_0 was too small compared to $1/z_\mathrm{NL}$ to generate vortices, resulting in a single positive force F_s due to upstream radiation of sound waves, and then downstream motion of the mobile impurity.

HELMHOLTZ DECOMPOSITION

In the main text, we analyze separately the "comp"ressible (divergent) and "inc"ompressible (rotational) components of the density-weighted velocity field, defined as

$$\mathbf{u}(\mathbf{r}_\perp) = \sqrt{\rho(\mathbf{r}_\perp)}\mathbf{v}(\mathbf{r}_\perp). \quad (19)$$

These two contributions appear in the following Helmholtz decomposition:

$$\mathbf{u}(\mathbf{r}_\perp) = \mathbf{u}^\mathrm{comp}(\mathbf{r}_\perp) + \mathbf{u}^\mathrm{inc}(\mathbf{r}_\perp), \quad (20)$$
$$\mathbf{u}^\mathrm{comp}(\mathbf{r}_\perp) = \nabla_\perp \Phi(\mathbf{r}_\perp), \quad (21)$$
$$\mathbf{u}^\mathrm{inc}(\mathbf{r}_\perp) = \nabla_\perp \times \mathbf{A}(\mathbf{r}_\perp), \quad (22)$$

where Φ and $\mathbf{A}$ are scalar and vector potentials, respectively. In practice, the incompressible velocity is obtained by subtracting the compressible component from the total density-weighted velocity, $\mathbf{u}^\mathrm{inc} = \mathbf{u} - \mathbf{u}^\mathrm{comp}$, with $\mathbf{u}^\mathrm{comp}$ obtained from its Fourier components:

$$\mathbf{u}^\mathrm{comp}(\mathbf{r}_\perp) = \mathrm{FT}^{-1}[i\mathbf{k}_\perp U_\Phi(\mathbf{k}_\perp)](\mathbf{r}_\perp), \quad (23)$$
$$U_\Phi(\mathbf{k}_\perp) = -i\frac{\mathbf{k}_\perp}{k_\perp^2}\cdot \mathrm{FT}[\mathbf{u}(\mathbf{r}_\perp)](\mathbf{k}_\perp). \quad (24)$$

NET MOMENTUM OF THE FLOW

To determine the contribution of vortices to the net momentum of the fluid, we make use of the Helmholtz decomposition described above, which separates the incompressible component, associated with vortices, from the compressible component, associated with sound waves, of the density-weighted velocity $\mathbf{u}$. Figure 7(a) shows the norm of the incompressible (top panels) and compressible (bottom) contributions for $\beta = 1.1$. As explained above, the incompressible field is obtained by subtracting the compressible contribution from the total density-weighted velocity. The left and right panels display the velocity fields in the laboratory and fluid frames, respectively. The change of reference frame is performed by subtracting the phase of the fluid in the absence of the impurity, using the same value of β. In the fluid frame, we observe that the vortex contribution is predominantly directed towards the negative-x direction, in contrast to the compressible part, which exhibits contributions in all directions.

To quantitatively show that this behavior is directly related to the upstream displacement of the impurity, as observed in Fig. 7(b), we measure the total net momentum along the x axis, defined as

$$p = \int d^2\mathbf{r}_\perp \; u_x(\mathbf{r}_\perp), \quad u_x(\mathbf{r}_\perp) = \sqrt{\rho(\mathbf{r}_\perp)}v_x(\mathbf{r}_\perp). \quad (25)$$

We denote by p_0 the net momentum of the fluid in the absence of the impurity, and by p its counterpart in the presence of the impurity. It is worth noting that we use (25) as a proxy, the actual, physical momentum being rigorously defined as the integral of the current density ρv_x.

In the laboratory frame, and without the impurity, we observe a linear increase of the net momentum, as shown in Fig. 7(c) by the gray dots. This behavior changes in the presence of the impurity: a clear bifurcation appears once $\beta = \beta_\mathrm{c} \simeq 0.35$, i.e., when the first vortex-antivortex pair is emitted. By subtracting p_0 from p, we place ourselves in the reference frame of the fluid and separate the




FIG. 7. **Contributions to the net momentum of the fluid.** **a** – Norm of the density-weighted velocity map at $\beta = 1.1$ for the incompressible (top) and compressible (bottom) components, shown in the laboratory (left) and fluid (right) reference frames, respectively. The associated streamlines are displayed on each image. **b** – Final impurity position measured at the exit of the cell for different values of the Mach number β. **c** – Total net momentum against β in the laboratory frame, with (p) and without (p_0) the impurity, shown by the green and gray dots, respectively. **d** – Fluid-frame net momentum for the total (green), incompressible (orange), and compressible (blue) components of the density-weighted velocity.

vortex and acoustic contributions to the total momentum. The different components of the momentum are shown in Fig. 7(d). The green squares, orange triangles, and blue triangles correspond to the total, incompressible, and compressible contributions, respectively. These values show a clear negative trend, with the dominant contribution to the total momentum coming from the vortices, while the compressible component remains almost negligible. For $\beta > 0.8$, as discussed in the main text, additional phenomena appear, such as radiation of sound waves ahead of the impurity. At this point, the balance between the compressible and incompressible components starts to change, since vortex emission has ceased.

* pierre-elie.larre@universite-paris-saclay.fr
† quentin.glorieux@sorbonne-universite.fr

[1] Q. Glorieux, C. Piekarski, Q. Schibler, T. Aladjidi, and M. Baker-Rasooli, Paraxial fluids of light, Adv. At. Mol. Opt. Phys. **74**, 157 (2025).
[2] W. J. Kwon, S. W. Seo, and Y.-il Shin, Periodic shedding of vortex dipoles from a moving penetrable obstacle in a Bose-Einstein condensate, Phys. Rev. A **92**, 033613 (2015).
[3] N. Pavloff, Breakdown of superfluidity of an atom laser past an obstacle, Phys. Rev. A **66**, 013610 (2002).
[4] C. Michel, O. Boughdad, M. Albert, P.-É. Larré, and M. Bellec, Superfluid motion and drag-force cancellation in a fluid of light, Nat. Commun. **9**, 2108 (2018).
[5] L. P. Pitaevskii and S. Stringari, *Bose-Einstein Condensation and Superfluidity* (Oxford University Press, Oxford, 2016).
[6] J. Skipp, J. Laurie, and S. Nazarenko, Hamiltonian derivation of the point vortex model from the two-dimensional nonlinear Schrödinger equation, Phys. Rev. E **107**, 025107 (2023).
[7] J. Dalibard, *Fluides quantiques de basse dimension et transition de Kosterlitz-Thouless*, Lectures of the Chair Atomes et Rayonnement at Collège de France, Paris, 2016-2017.
[8] T. D. Ferreira, V. Rocha, D. Silva, A. Guerreiro, and N. A. Silva, Towards the experimental observation of turbulent regimes and the associated energy cascades with paraxial fluids of light, New J. Phys. **24**, 113050 (2022).