Function Keys Mappings

Function		shift (⇧)	control (^)	^⇧	meta (⌥)	⌥⇧	^⌥	^⌥⇧
Key		S	C	C-S	M	M-S	C-M	C-M-S
F1	Prefix: (help)	Prefix: (help)	unassigned	unassigned	unassigned ➢ F6	unassigned ➢C-M-p	unassigned ➢C-M-p	unassigned ➢C-M-p
F2	(bm-next) pel-use-bm = t	(bm-next) pel-use-bm = t	unassigned	unassigned	unassigned ➢ F7	unassigned ➢C-M-p	unassigned ➢C-M-p	unassigned ➢C-M-p
F3	(kmacro-start-macro-or-insert-counter ARG)	(kmacro-start-macro-or-insert-counter ARG)	unassigned	unassigned	unassigned ➢ F8	unassigned ➢C-M-p	unassigned ➢C-M-p	unassigned ➢C-M-p
F4	(kmacro-end-or-call-macro ARG &optional NO-REPEAT)	(kmacro-end-or-call-macro ARG &optional NO-REPEAT)	unassigned	unassigned	unassigned ➢ F9	unassigned ➢C-M-p	unassigned ➢C-M-p	unassigned ➢C-M-p
F5	(repeat REPEAT-ARG)	(repeat REPEAT-ARG) and mark	(centi-assign)	unassigned	(pel-scroll-up &optional N)	(pel-scroll-up-other &optional N)	unassigned ➢ ~	unassigned ➢ ~
F6	Prefix: pel:f6	Prefix: pel:f6	unassigned	unassigned	(pel-scroll-down &optional N)	(pel-scroll-down-other &optional N)	unassigned ➢ ~	unassigned ➢ ~
F7	• Prefix: pel-∑wnd • pel-∑narrate pel-use-hydra= t, pel-use-applescript=t	unassigned as <f19>	unassigned	unassigned	unassigned	unassigned	unassigned ➢ ~	unassigned ➢ ~
F8	Prefix: projectile (activated by F11 F8 pel-use-projectile=t)	unassigned	unassigned	unassigned	unassigned	unassigned	unassigned ➢ ~	unassigned ➢ ~
F9	unassigned	unassigned	unassigned	unassigned	unassigned	(pel-show-init-time)	unassigned ➢ ~	unassigned ➢ ~
F10	(menu-bar-open &optional FRAME)	(menu-bar-open &optional FRAME)	(buffer-menu-open)	(buffer-menu-open)	(toggle-frame-maximized)	(toggle-frame-maximized)	unassigned ➢ ~	unassigned ➢ ~
F11	Prefix: pel:	Prefix: pel:	unassigned	unassigned	unassigned	(pel-scroll-up &optional N)	unassigned ➢ ~	unassigned ➢ ~
F12	PEL Mode sensitive prefix	Prefix: mode sensitive	unassigned	unassigned	PEL Mode sensitive prefix Same as F12: helps typing sequences with Meta keys.	(pel-scroll-down &optional N)	unassigned ➢ ~	unassigned ➢ ~

Special Legend for the above table

The colour and symbols used in the above table follow the standard legend described in ➢**Legend** with the additional conventions listed here.	
unassigned	The key is not assigned by PEL.
unassigned	The key does not do anything in terminal mode.
unassigned ➢	When pressing this key in terminal mode the action corresponds to the key identified after the ➢ symbol.
(toggle-frame-maximized)	In terminal mode the command toggle-frame-maximized is executed, but has no effect.
PEL Mode sensitive prefix	PEL provides mode sensitive keys that are globally accessible via the `<f11> SPACE` key sequence prefix. For example, when editing a buffer using the emacs-lisp-mode major mode, the `<f12>` prefix gives access to commands that are specific to Emacs Lisp. If you want to access the same commands while editing a buffer that use another major-mode, you can then type `<f11> SPACE l` prefix to get to the same list of commands. PEL provides a set of mode sensitive key binding sets for several major modes, but not for all of them. As time evolves the number of major modes supported will grow.