Emacs Support for Chibi Scheme 🚧

Description	Keystroke	Function	Note
Chibi Scheme Programming Language Support See also: • ∑ **File/Directory Variables**	🚧 **Chibi Scheme** is an implementation of Scheme, used for embedding in other programs and provide scripting. PEL support for Chibi Scheme is preliminary. More work is required to identify Chibi specific support. 🔲 PEL activates Chibi Scheme support when the **pel-use-chibi** user-option is turned on (**t**). PEL provide extra support for the Chibi Scheme programming language. Most support is provided by Emacs support for **ℙ𝓁 - Scheme** . • The Chibi programming language is a Scheme implementation. The Chibi Scheme files use the same extension as Scheme: .ss.		

Open this PDF file.
See also: ∑ **Help/Info**
	`<f11> SPC C-s C-i <f1>`
	
	`<f12> <f1>`
		(pel-help-pdf &optional OPEN-WEB-PAGE)	Open the **ℙ𝓁 - Chibi** local PDF. If the prefix argument (like **C-u** or **M--**) is used, then it opens the remote GitHub hosted raw PDF instead. If the **pel-flip-help-pdf-arg** user-option is set it's the other way around.

∑ **Customize** PEL Chibi Scheme support	`<f11> SPC C-s C-i <f2>`
	
	`<f12> <f2>`
		(pel-customize-pel &optional OTHER-WINDOW)	Customize PEL Chibi support.
			• If OTHER-WINDOW is non-nil (use **C-u**), display in another window.

∑ **Customize** Emacs Chibi Scheme support	`<f11> SPC C-s C-i <f3>`
	
	`<f12> <f3>`
		(pel-customize-library &optional OTHER-WINDOW)	Customize Emacs Scheme support: scheme, geiser, quack, lispy.
			• If OTHER-WINDOW is non-nil (use **C-u**), display in another window.

	Use the following commands to interact with the Chibi Scheme REPL.		

Open the Chibi REPL	`<f11> z r C-i`
	
	`<f12> z`
		(pel-chibi-repl &optional N)	Run the Chibi Scheme REPL in window specified by N.
			• By default use the other window. If a numeric argument is specified, its value correspond to the direction of a numeric keypad:
			      8
			   4 6
			      2
			That is:
			• 8: up
			• 4: left
			• 6: right
			• 2: down
			• 0 and 5 identify the current window.

Erase the content of REPL	`<f12> C-l`	**(pel-clear-scheme-repl-buffer)**	Erase content of the Chibi Scheme REPL running under Emacs.