Keys with Super modifier keys (⌘ on macOS)

macOS Key	Mac OS Terminal	Emacs in Terminal mode	Emacs in Graphics mode

Special key: Clear	The Apple keyboards with numeric keypad have a Clear key. That key is located at the top left of the numeric keypad at the position where the numlock key is often located in other keyboards.
	
	Over the years Apple manufactured keyboards with this key with different labels: **clear** and ⌧ are the most often seen labels. See **here** and **here**.
	
	    Names: **Clear, CLR, CLS**
	    Symbol: ⌧
	    Mac symbol: ⌧
	    Key Code: **0x47**
	
	The documented purpose of the Clear key is to clear the selected content but is application dependent. For instance:
	• Inside spreadsheet programs (like macOS Numbers and Excel) it clears the content of currently selected cells. It also clears the content of currently selected text.
	• Inside macOS Finder it selects the file with the name alphabetically sorted last.
	• Inside macOS Terminal.app it can be configured to act as a Numlock key in the Profiles keyboard list.
	• I have not yet found a way to map it in iTerm2. I posted a question in StackExchange AskDifferent while I continue the investigation.
	    • It is possible to map specific keys of the numeric keypad but the Clear key registers as Numlock right away.		

Clear			
• **macOS Keyboard Shortcuts** • **Terminal Keyboard Shortcuts**	This table list the macOS specific key and their meaning as well as the bindings and availability inside Emacs running in terminal (TTY) mode and in graphics mode. The keys marked **macOS key** are reserved to macOS and are user configurable in macOS System Preferences. See also: **macOS Fct Keys**		
⌘-F1			macOS key
⌘-F2			macOS key
⌘-F3			macOS key
⌘-F4			macOS key
⌘-F5			macOS key
⌘-F6			macOS key
⌘-F7			macOS key
⌘-F8			macOS key
⌘-F9			macOS key
⌘-F10			macOS key
⌘-F11			macOS key
⌘-F12			macOS key
⌘-<home>	Scroll to top		*undefined*
⌘-<end>	Scroll to bottom		*undefined*
⌘-<pgUp>	Page up		*undefined*
⌘-<pgDn>	Page down		*undefined*
⌘-<up>			(**windmove-up** &optional ARG)
⌘-<down>			(**windmove-down** &optional ARG)
⌘-<right>			(**windmove-right** &optional ARG)
⌘-<left>			(**windmove-left** &optional ARG)
⌘-<tab>	Previous application menu		macOS key
⌘-<backspace>			*undefined*
⌘-<del>			*undefined*
⌘-<ret>	Mark line & send return		*undefined*
⌘-S-<ret>	Send return without marking		*undefined*
⌘-<space>			macOS key
⌘-`	next window		macOS key
⌘-1			*undefined*
⌘-2			*undefined*
⌘-3			*undefined*
⌘-4			*undefined*
⌘-5			*undefined*
⌘-6			*undefined*
⌘-7			*undefined*
⌘-8			*undefined*
⌘-9			*undefined*
⌘-0	Restore default font size		*undefined*
⌘--	make font smaller		(***center-line** &optional NLINES*)
⌘-=			*undefined*
⌘-~	previous window		(**ns-prev-frame**)
⌘-!			*undefined*
⌘-@			*undefined*
⌘-#	macOS full screen snapshot		macOS full screen snapshot

macOS Key	Mac OS Terminal	Emacs in Terminal mode	Emacs in Graphics mode
⌘-$	macOS partial screen capture		macOS partial screen capture
⌘-%	Open macOS screen capture menu		macOS pops-up the screen capture menu which can be used to take screen shots in several ways. The menu looks like this:
⌘-^			emacs kill all?? No help registers.
⌘-&			(kill-current-buffer)
⌘-*			*undefined*
⌘-(			*undefined*
⌘-)			*undefined*
⌘-_			*undefined*
⌘-+	make font bigger		*undefined*
⌘-[			*undefined*
⌘-]			*undefined*
⌘-\			*undefined*
⌘-{			*undefined*
⌘-}			*undefined*
⌘-|	Show all tabs or exit tab overview		(**shell-command-on-region** START END COMMAND &optional OUTPUT-BUFFER REPLACE ERROR-BUFFER DISPLAY-ERROR-BUFFER REGION-NONCONTIGUOUS-P)
⌘-;			*undefined*
⌘-'			(**next-multiframe-window**)
⌘-:			(ispell)
⌘-"			*undefined*
⌘-,	Open terminal preferences		(customize)
⌘-.	Break (similar to C-c)	(**keyboard-quit**)	*undefined*
⌘-/			*undefined*
⌘-<			*undefined*
⌘->			*undefined*
⌘-?			(**info** &optional FILE-OR-NODE BUFFER)
⌘-<space>			**macOS key: Spotlight Search**
⌘-a	Select all		(**mark-whole-buffer**)
⌘-b			*undefined*
⌘-c	Copy	Can be used to copy marked text area	(**ns-copy-including-secondary**)
⌘-d	Split window into 2 panes		(**isearch-repeat-backward**)
⌘-e	Find using selected text		(**isearch-yank-kill**)
⌘-f	Find		(**isearch-forward** &optional REGEXP-P NO-RECURSIVE-EDIT)
⌘-g	Find Next		(**isearch-repeat-forward**)
⌘-h			(**ns-do-hide-emacs**)
⌘-i	Show/hide inspector		*undefined*
⌘-j	Jump to the selected text		(**exchange-point-and-mark** &optional ARG)
⌘-k	Clear to start		(**kill-current-buffer**)
⌘-l	Clear to previous mark		(**goto-line** LINE &optional BUFFER)
⌘-m			(**iconify-frame** &optional FRAME)
⌘-n	New Window		(**make-frame** &optional PARAMETERS)
⌘-o			(**ns-open-file-using-panel**)
⌘-p	print		(**ns-print-buffer**)
⌘-q			(**save-buffers-kill-emacs** &optional ARG)
⌘-r	Toggle "Allow Mouse Reporting" option		*undefined*
⌘-s	Export text as		(**save-buffer** &optional ARG)
⌘-t	New tab		(**ns-popup-font-panel** &optional FRAME)
⌘-u	Mark		(**revert-buffer** &optional IGNORE-AUTO NOCONFIRM PRESERVE-MODES)
⌘-v	Paste	(**xterm-paste**)	(**yank** &optional ARG)
⌘-w	Close tab - prompt if process is running		(**delete-frame** &optional FRAME FORCE)
⌘-x	Cut		(**kill-region** BEG END &optional REGION)
⌘-y			(**ns-paste-secondary**)
⌘-z			(**undo** &optional ARG)
⌘-A	Select between marks		*Same as lowercase*
⌘-B			*undefined*

macOS Key	Mac OS Terminal	Emacs in Terminal mode	Emacs in Graphics mode
⌘-C	Show/Hide colours		(**ns-popup-color-panel** &optional FRAME)
⌘-D	Close split pane		(**ido-dired**)
⌘-E			(**edit-abbrevs**)
⌘-F			*Same as lowercase*
⌘-G	Find previous		*Same as lowercase*
⌘-H			(**ns-do-hide-others**)
⌘-I	Edit title		*undefined*
⌘-J			*Same as lowercase*
⌘-K			*Same as lowercase*
⌘-L			(**shell-command** COMMAND &optional OUTPUT-BUFFER ERROR-BUFFER)
⌘-M	Insert bookmark		(**manual-entry** MAN-ARGS)
⌘-N	New command		*Same as lowercase*
⌘-O			*Same as lowercase*
⌘-P			*Same as lowercase*
⌘-Q	Close **all** applications and log out.	Close **all** applications and log out.	Close **all** applications and log out.
⌘-R			*undefined*
⌘-S	Export selected text as		(**ns-write-file-using-panel**)
⌘-T	Show/hide tab bar		*Same as lowercase*
⌘-U	Unmark		*Same as lowercase*
⌘-V	Paste the selection		*Same as lowercase*
⌘-W	Close window - prompt if process is running		*Same as lowercase*
⌘-X			*Same as lowercase*
⌘-Y			*Same as lowercase*
⌘-Z			*Same as lowercase*
⌘-C-<space>	Open the character viewer		*undefined*
⌘-C-?	Open **man** page index for word at point		*undefined*
⌘-C-a			*undefined*
⌘-C-b			*undefined*
⌘-C-c			*undefined*
⌘-C-d			**Not accessible**
⌘-C-e			*undefined*
⌘-C-f	Enter/Exit full screen		*undefined*
⌘-C-g			*undefined*
⌘-C-h			*undefined*
⌘-C-i			*undefined*
⌘-C-j			*undefined*
⌘-C-k			*undefined*
⌘-C-l			*undefined*
⌘-C-m			*undefined*
⌘-C-n	new window with same command		*undefined*
⌘-C-o			*undefined*
⌘-C-p			*undefined*
⌘-C-q			macOS Logout
⌘-C-r			*undefined*
⌘-C-s			*undefined*
⌘-C-t	new tab with same command		*undefined*
⌘-C-u			*undefined*
⌘-C-v	Paste escaped text		*undefined*
⌘-C-w			*undefined*
⌘-C-x			*undefined*
⌘-C-y			*undefined*
⌘-C-z			*undefined*
⌘-C-A			*undefined*
⌘-C-B			*undefined*
⌘-C-C	Copy without background color		*undefined*
⌘-C-D			*undefined*
⌘-C-E			*undefined*
⌘-C-F			*undefined*

macOS Key	Mac OS Terminal	Emacs in Terminal mode	Emacs in Graphics mode
⌘-C-G			*undefined*
⌘-C-H			*undefined*
⌘-C-I			*undefined*
⌘-C-J			*undefined*
⌘-C-K			*undefined*
⌘-C-L			*undefined*
⌘-C-M			*undefined*
⌘-C-N			*undefined*
⌘-C-O			*undefined*
⌘-C-P			*undefined*
⌘-C-Q			*undefined*
⌘-C-R			*undefined*
⌘-C-S			*undefined*
⌘-C-T			*undefined*
⌘-C-U			*undefined*
⌘-C-V	Paste escaped selection		*undefined*
⌘-C-W			*undefined*
⌘-C-X			*undefined*
⌘-C-Y			*undefined*
⌘-C-Z			*undefined*
⌘-⌥-a			**Not accessible**
⌘-⌥-b			*undefined - extended char* (this is similar to binding **s-∫**)
⌘-⌥-c			macOS invert screen colours
⌘-⌥-d			*undefined - extended char* (this is similar to binding **s-∂**)
⌘-⌥-e			*undefined - extended char* (this is similar to binding **s-´**)
⌘-⌥-f			*undefined - extended char* (this is similar to binding **s-ƒ**)
⌘-⌥-g			*undefined - extended char* (this is similar to binding **s-©**)
⌘-⌥-h			**(ns-do-hide-others)** - translated - available
⌘-⌥-i	Edit Background Color		*undefined - extended char*
⌘-⌥-j			*undefined - extended char*
⌘-⌥-k			*undefined - extended char*
⌘-⌥-l	Clear to previous bookmark		*undefined - extended char*
⌘-⌥-m			*undefined - extended char*
⌘-⌥-n			*undefined - extended char*
⌘-⌥-o			*undefined - extended char*
⌘-⌥-p			*undefined - extended char*
⌘-⌥-q			*undefined - extended char*
⌘-⌥-r	Soft reset terminal emulator state		*undefined - extended char*
⌘-⌥-s			*undefined - extended char*
⌘-⌥-t			*undefined - extended char*
⌘-⌥-u	Mark as bookmark		*undefined - extended char*
⌘-⌥-v			*undefined - extended char*
⌘-⌥-w	Close other tabs		*undefined - extended char*
⌘-⌥-x			*undefined - extended char*
⌘-⌥-y			*undefined - extended char*
⌘-⌥-z			*undefined - extended char*
⌘-⌥-A			*undefined*
⌘-⌥-B			*undefined*
⌘-⌥-C	Copy plain text		*undefined*
⌘-⌥-D			***Show/Hide macOS Dock***
⌘-⌥-E			*undefined*
⌘-⌥-F			*undefined*
⌘-⌥-G			*undefined*
⌘-⌥-H			**(ns-do-hide-others)** - translated - available
⌘-⌥-I			*undefined*
⌘-⌥-J			*undefined*
⌘-⌥-K			*undefined*
⌘-⌥-L			***Show/Hide LaunchPad***
⌘-⌥-M	Insert bookmark with name		*undefined*
⌘-⌥-N			*undefined*

macOS Key	Mac OS Terminal	Emacs in Terminal mode	Emacs in Graphics mode
⌘⌥-O	Toggle "Use Option as Meta key" option		*undefined*
⌘⌥-P			*undefined*
⌘⌥-Q			macOS logout other app.
⌘⌥-R			*undefined*
⌘⌥-S			*undefined*
⌘⌥-T			*undefined*
⌘⌥-U			*undefined*
⌘⌥-V			*undefined*
⌘⌥-W	Close all terminal windows not running processes, prompt, for others.		*undefined*
⌘⌥-X			*undefined*
⌘⌥-Y			*undefined*
⌘⌥-Z			*undefined*
⌘⌥-[	Select the previous input source		*undefined*
⌘⌥-]	Select the next input source		*undefined*
C-r	Reverse search command history		
C-<tab>	Next tab		
C-S-<tab>	Previous tab		
⌘⌥-<home>			*undefined*
⌘⌥-<end>			*undefined*
⌘⌥-<pgUp>	Line Up		*undefined*
⌘⌥-<pgDn>	Line Down		*undefined*
⌘⌥-<up>	Jump to previous bookmark		*undefined*
⌘⌥-<down>	Jump to next bookmark		*undefined*
⌘⌥-<right>			*undefined*
⌘⌥-<left>			*undefined*
⌘⌥-<tab>			*undefined*
⌘⌥-<backspace>			*undefined*
⌘⌥-<del>			*undefined*
⌘⌥-<ret>			*undefined*
⌘⌥-<space>			macOS New Smart Folder
⌘⌥-0			*undefined - extended char*
⌘⌥-1			*undefined - extended char*
⌘⌥-2			*undefined - extended char*
⌘⌥-3			*undefined - extended char*
⌘⌥-4			*undefined - extended char*
⌘⌥-5			*undefined - extended char*
⌘⌥-6			*undefined - extended char*
⌘⌥-7			*undefined - extended char*
⌘⌥-8			*undefined - extended char*
⌘⌥-9			*undefined - extended char*
⌘⌥C-<home>			*undefined*
⌘⌥C-<end>			*undefined*
⌘⌥C-<pgUp>			*undefined*
⌘⌥C-<pgDn>			*undefined*
⌘⌥C-<up>			*undefined*
⌘⌥C-<down>			*undefined*
⌘⌥C-<right>			*undefined*
⌘⌥C-<left>			*undefined*
⌘⌥C-<tab>			*undefined*
⌘⌥C-<backspace>			*undefined*
⌘⌥C-<del>			*undefined*
⌘⌥C-<ret>			*undefined*
⌘⌥C-<space>			*undefined*
⌘⌥C--			*undefined*
⌘⌥C-!			*undefined*
⌘⌥C-@			*undefined*
⌘⌥C-#			*undefined*
⌘⌥C-$			*undefined*

macOS Key	Mac OS Terminal	Emacs in Terminal mode	Emacs in Graphics mode
⌘⌥C–%			*undefined*
⌘⌥C–^			*undefined*
⌘⌥C–&			*undefined*
⌘⌥C–*			*undefined*
⌘⌥C–(			*undefined*
⌘⌥C–)			*undefined*
⌘⌥C–_			*undefined*
⌘⌥C–+			*undefined*
⌘⌥C–`			*undefined*
⌘⌥C–0			*undefined*
⌘⌥C–1			*undefined*
⌘⌥C–2			*undefined*
⌘⌥C–3			*undefined*
⌘⌥C–4			*undefined*
⌘⌥C–5			*undefined*
⌘⌥C–6			*undefined*
⌘⌥C–7			*undefined*
⌘⌥C–8			*undefined*
⌘⌥C–9			*undefined*
⌘⌥C––			*undefined*
⌘⌥C–=			*undefined*
⌘⌥C–[			*undefined*
↘ Topic Index			*undefined*
⌘⌥C–\			*undefined*
⌘⌥C–{			*undefined*
⌘⌥C–}			*undefined*
⌘⌥C–|			*undefined*
⌘⌥C–;			*undefined*
⌘⌥C–'			*undefined*
⌘⌥C–:			*undefined*
⌘⌥C–"			*undefined*
⌘⌥C–,			*undefined*
⌘⌥C–.			*undefined*
⌘⌥C–/			*undefined*
⌘⌥C–<			macOS key ???
⌘⌥C–>	**run sysdiagnose**		**macOS key: run sysdiagnose.** ⚠️ This sends information to Apple.
⌘⌥C–?			**Not accessible**
⌘⌥C–a			*undefined*
⌘⌥C–b			*undefined*
⌘⌥C–c			*undefined*
⌘⌥C–d			*undefined*
⌘⌥C–e			*undefined*
⌘⌥C–f			*undefined*
⌘⌥C–g			*undefined*
⌘⌥C–h			*undefined*
⌘⌥C–i			*undefined*
⌘⌥C–j			*undefined*
⌘⌥C–k			*undefined*
⌘⌥C–l			*undefined*
⌘⌥C–m			*undefined*
⌘⌥C–n			*undefined*
⌘⌥C–o			*undefined*
⌘⌥C–p			*undefined*
⌘⌥C–q			*undefined*
⌘⌥C–r	Hard reset terminal emulator state		*undefined*
⌘⌥C–s			*undefined*
⌘⌥C–t			*undefined*
⌘⌥C–u			*undefined*
⌘⌥C–v			*undefined*
⌘⌥C–w			*undefined*

macOS Key	Mac OS Terminal	Emacs in Terminal mode	Emacs in Graphics mode
⌘⌥C-x			*undefined*
⌘⌥C-y			*undefined*
⌘⌥C-z			*undefined*
⌘⌥C-A			*undefined*
⌘⌥C-B			*undefined*
⌘⌥C-C			*undefined*
⌘⌥C-D			*undefined*
⌘⌥C-E			*undefined*
⌘⌥C-F			*undefined*
⌘⌥C-G			*undefined*
⌘⌥C-H			*undefined*
⌘⌥C-I			*undefined*
⌘⌥C-J			*undefined*
⌘⌥C-K			*undefined*
⌘⌥C-L			*undefined*
⌘⌥C-M			*undefined*
⌘⌥C-N			*undefined*
⌘⌥C-O			*undefined*
⌘⌥C-P			*undefined*
⌘⌥C-Q			**Not accessible**
⌘⌥C-R			*undefined*
⌘⌥C-S			*undefined*
⌘⌥C-T			*undefined*
⌘⌥C-U			*undefined*
⌘⌥C-V			*undefined*
⌘⌥C-W			*undefined*
⌘⌥C-X			*undefined*
⌘⌥C-Y			*undefined*
⌘⌥C-Z			*undefined*