## Keys with Super modifier keys (₩ on macOS)

macOS Key	Mac OS Terminal	Emacs Terminal	Emacs Graphics mode
Keyboard Shortcuts in Terminal on Mac	graphics mode.		ir meaning as well as the bindings and availability inside Emacs running in terminal (TTY) mode and in macOS and are user configurable in macOS System Preferences.
<b> Ж-F1</b>			macOS key
			macOS key
<b>%−F2</b>			
<b>%-F3</b>			macOS key
<b>%-F4</b>			macOS key
<b>%-F5</b>			macOS key
<b>%-F6</b>			macOS key
<b>%-F</b> 7			macOS key
<b>%-F8</b>			macOS key
<b>Ж</b> − <b>F</b> 9			macOS key
<b>%-F10</b>			macOS key
<b>%-F11</b>			macOS key
<b>%-F12</b>			macOS key
<b>%</b> - <home></home>	Scroll to top		undefined
	·		
%- <end></end>	Scroll to bottom		undefined
₩- <pgup></pgup>	Page up		undefined
₩- <pgdn></pgdn>	Page down		undefined
<b>%−<up></up></b>			(windmove-up &optional ARG)
%- <down></down>			(windmove-down &optional ARG)
%- <right></right>			(windmove-right &optional ARG)
%- <left></left>			(windmove-left &optional ARG)
%- <tab></tab>	Previous application menu		macOS key
%- <backspace></backspace>			undefined
光- <del></del>			undefined
%- <ret></ret>	Mark line & send return		undefined
			undefined
%-S- <ret></ret>	Send return without marking		
%- <space></space>			macOS key
<b>第</b> _~	next window		macOS key
₩-1			undefined
<b>%−2</b>			undefined
<b>%−3</b>			undefined
₩-4			undefined
<b>%−5</b>			undefined
<b>%−6</b>			undefined
<b>%</b> −7			undefined
<b>%−8</b>			undefined
<b>%</b> −9			undefined
	Destare default fant sins		
<b> 8−0</b>	Restore default font size		undefined
<b>%</b>	make font smaller		(center-line &optional NLINES)
₩-=			undefined
<b>%</b> -~	previous window		(ns-prev-frame)
₩-!			undefined
<b>%</b> −@			undefined
₩-#	macOS full screen snapshot		macOS full screen snapshot
<b>%</b> −\$	macOS partial screen capture		macOS partial screen capture
<b>#-</b> %	Open macOS screen capture menu		macOS pops-up the screen capture menu which can be used to take screen shots in several ways. The menu looks like this:
			Options Capture
₩_^			emacs kill all?? No help registers.
<b>%</b> −&			(kill-current-buffer)
<b>%</b> −*			undefined
<b>%</b> −(			undefined
<b>%</b> −(			undefined
<b>%</b>			undefined

macOS Key	Mac OS Terminal	Emacs Terminal	Emacs Graphics mode
<b>%</b> −+	make font bigger		undefined
<b>%</b> -[			undefined
<b>%</b> −1			undefined
₩_\			undefined
<b>%−</b> {			undefined
₩-}			undefined
<b>%</b> −	Show all tabs or exit tab overview		(shell-command-on-region START END COMMAND & optional OUTPUT-BUFFER REPLACE ERROR-BUFFER DISPLAY-ERROR-BUFFER REGION-NONCONTIGUOUS-P)
<b>%−;</b>			undefined
<b>%</b> −′			(next-multiframe-window)
<b>%−:</b>			(ispell)
₩_"			undefined
₩-,	Open terminal preferences		(customize)
₩	Break (similar to C-c)	(keyboard-quit)	undefined
第-/			undefined
<b>%</b> -<			undefined
₩->			undefined
₩-?			(info &optional FILE-OR-NODE BUFFER)
%- <space></space>			macOS key: Spotlight Search
<b>%−a</b>	Select all		(mark-whole-buffer)
<b>%−b</b>			undefined
<b>Ж−с</b>	Сору	Can be used to copy marked text area	(ns-copy-including-secondary)
<b>%−a</b>	Split window into 2 panes		(isearch-repeat-backward)
<b>Ж−е</b>	Find using selected text		(isearch-yank-kill)
<b>%</b> − <b>f</b>	Find		(isearch-forward &optional REGEXP-P NO-RECURSIVE-EDIT)
<b>%−g</b>	Find Next		(isearch-repeat-forward)
<b>%−h</b>			(ns-do-hide-emacs)
<b>%</b> −i	Show/hide inspector		undefined
<b>Ж-</b> ј	Jump to the selected text		(exchange-point-and-mark &optional ARG)
<b>%−k</b>	Clear to start		(kill-current-buffer)
<b>%</b> −1	Clear to previous mark		(goto-line LINE &optional BUFFER)
<b>%−m</b>			(iconify-frame &optional FRAME)
<b>%−n</b>	New Window		(make-frame &optional PARAMETERS)
<b>%-o</b>			(ns-open-file-using-panel)
<b>%−p</b>	print		(ns-print-buffer)
<b>%−q</b>			(save-buffers-kill-emacs &optional ARG)
<b>%-r</b>	Toggle "Allow Mouse Reporting" option		undefined
<b>%−s</b>	Export text as		(save-buffer &optional ARG)
<b>%−t</b>	New tab		(ns-popup-font-panel &optional FRAME)
₩-u	Mark		(revert-buffer &optional IGNORE-AUTO NOCONFIRM PRESERVE-MODES)
<b>%−v</b>	Paste	(xterm-paste)	(yank &optional ARG)
<b>%−w</b>	Close tab - prompt if process is running		(delete-frame &optional FRAME FORCE)
<b>%−x</b>	Cut		(kill-region BEG END &optional REGION)
<b>%−y</b>			(ns-paste-secondary)
<b>%−z</b>			(undo &optional ARG)
<b>%−A</b>	Select between marks		Same as lowercase
Ж−В			undefined
<b>%−c</b>	Show/Hide colours		(ns-popup-color-panel &optional FRAME)
<b>%−D</b>	Close split pane		(ido-dired)
<b>%−E</b>			(edit-abbrevs)
<b>%−F</b>			Same as lowercase
<b>%</b> − <b>G</b>	Find previous		Same as lowercase
Ж−н	- w ····		(ns-do-hide-others)
<b>%−1</b>	Edit title		undefined
<b>Ж-J</b>			Same as lowercase
Ж−к			Same as lowercase
<b>Ж−L</b>			(shell-command COMMAND &optional OUTPUT-BUFFER ERROR-BUFFER)
Ж-м	Insert bookmark		(manual-entry MAN-ARGS)
<b>ж-и</b>	New command		Same as lowercase

macOS Key	Mac OS Terminal	Emacs Terminal	Emacs Graphics mode
<b>%−o</b>			Same as lowercase
<b>%−P</b>			Same as lowercase
<b>%−Q</b>	Close <b>all</b> applications and log out.	Close all applications and log out.	Close all applications and log out.
<b>%−R</b>			undefined
<b>%−s</b>	Export selected text as		(ns-write-file-using-panel)
<b>%</b> − <b>T</b>	Show/hide tab bar		Same as lowercase
₩-ʊ	Unmark		Same as lowercase
<b>%−v</b>	Paste the selection		Same as lowercase
<b>Ж−W</b>	Close window - prompt if process is running		Same as lowercase
<b>%−x</b>			Same as lowercase
<b>%</b> −¥			Same as lowercase
<b>%−Z</b>	Open the character viewer		Same as lowercase  undefined
<b>%-C-</b> <space> <b>%-C-</b>?</space>	Open the character viewer  Open man page index for		undefined
<b>%-C-</b> a	word at point		undefined
<b>%</b> − <b>C</b> − <b>b</b>			undefined
<b>%-C-c</b>			undefined
<b>%-c-d</b>			Not accessible
<b>ж-с-е</b>			undefined
<b>%-c-f</b>	Enter/Exit full screen		undefined
<b>%−c−g</b>			undefined
Ж- <b>с</b> -h			undefined
<b>%-c-i</b>			undefined
<b>ж-с-</b> ј			undefined
<b>%-c-k</b>			undefined
<b>%-c-1</b>			undefined
<b>%−C−m</b>			undefined
<b>%−c−n</b>	new window with same command		undefined
<b>%−C−o</b>			undefined
<b>Ж-С-р</b>			undefined
<b>%−C−q</b>			macOS Logout
<b>%-C-r %-C-s</b>			undefined undefined
#-c-t	new tab with same command		undefined
<b>%−C−u</b>			undefined
<b>%−c−v</b>	Paste escaped text		undefined
<b>%−c−w</b>			undefined
<b>Ж-с-</b> x			undefined
ж-с- <sub>У</sub>			undefined
<b>%-c-</b> z			undefined
<b>%-c-A</b>			undefined
<b>Ж−С−В</b>			undefined
<b>%-c-c</b>	Copy without background color		undefined
<b>%-c-d</b>			undefined
<b>Ж−С−Е</b>			undefined
<b>%−C−F</b>			undefined
<b>%−c−g</b>			undefined
<b>%-с-н</b>			undefined
<b>%-C-I</b>			undefined
<b>%-C-J</b>			undefined
<b>Ж−С−К</b>			undefined
₩-C-L			undefined
<b>Ж-С-</b> М <b>Ж-С-</b> N			undefined undefined
ж-с-n Ж-с-о			undefined
ж-с-р			undefined
ж-с-р Ж-с-Q			undefined
00-C-Q			

macOS Key	Mac OS Terminal	Emacs Terminal	Emacs Graphics mode
<b>%−C−R</b>			undefined
<b>%-c-s</b>			undefined
<b>Ж-С-т</b>			undefined
<b></b> ₩- <b>c</b> - <b>u</b>			undefined
₩-c-v	Paste escaped selection		undefined
<b>%-c-w</b>			undefined
<b>%-c-x</b>			undefined
<b>%−C−Y</b>			undefined
<b>%-c-z</b>			undefined
%\\_a			Not accessible
# <b>\</b> _ <b>b</b>			undefined - extended char (this is similar to binding s-∫)
%\\_c			macOS invert screen colours
#\\ <b>d</b>			undefined - extended char (this is similar to binding s-∂)
%\Z-e			undefined - extended char (this is similar to binding s- ´)
# <b>\</b> - <b>f</b>			undefined - extended char (this is similar to binding s-f)
<b>%</b> ₹ <b>-</b> g			undefined - extended char (this is similar to binding s-@)
% <b>\~h</b>	<b>-</b>		(ns-do-hide-others) - translated - available
% <b>\</b> -i	Edit Background Color		undefined - extended char
<b>%</b> ₹-j			undefined - extended char
<b>%</b> ₹-k			undefined - extended char
<b>%</b> ₹-1	Clear to previous bookmark		undefined - extended char
<b>%</b> √-m			undefined - extended char
%\\_n			undefined - extended char
<b>o</b> −✓೫			undefined - extended char
<b>q</b> −ブ業			undefined - extended char
<b>p</b> −7%			undefined - extended char
%\\-r	Soft reset terminal		undefined - extended char
<b>第</b> ℃-s	emulator state		undefined - extended char
<b>%</b> ₹-t			undefined - extended char
<b>%</b> \\_ <b>u</b>	Mark as bookmark		undefined - extended char
<b>v</b> −7 %			undefined - extended char
w-✓%	Close other tabs		undefined - extended char
<b>x</b> −7%			undefined - extended char
<b>%</b> √- <b>y</b>			undefined - extended char
%\_z			undefined - extended char
<b>A</b> −7%			undefined
<b>%</b> ₹ <b>-B</b>			undefined
<b>%</b> ₹-c	Copy plain text		undefined
<b>d</b> −√%			undefined
<b>%</b> ∇-E			undefined
<b>%\_F</b>			undefined
<b>%</b> ₹ <b>-G</b>			undefined
<b>H−</b> √ <b>%</b>			(ns-do-hide-others) - translated - available
<b>1−7</b> %			undefined
<b>%</b> ₹ <b>-J</b>			undefined
<b>%</b> ₹- <b>к</b>			undefined
<b>%</b> ₹- <b>L</b>	Invested to the second		undefined
M-√#	Insert bookmark with name		undefined
<b>%</b> ₹ <b>-N</b>			undefined
<b>0−</b> ∑₩	Toggle "Use Option as Meta key" option		undefined
<b>₽</b> \_ <b>P</b>			undefined
<b>9-</b> 7₩			macOS logout other app.
<b>%</b> ∇- <b>R</b>			undefined
<b>%</b> ₹ <b>-s</b>			undefined
<b>17-</b> √%			undefined
₩\ण			undefined
<b>v</b> −7%			undefined

macOS Key	Mac OS Terminal	Emacs Terminal	Emacs Graphics mode
₩ <b>~</b> -₩	Close all terminal windows not running processes, prompt, for others.		undefined
<b>x</b> −7 <b>%</b>			undefined
<b>Y-</b> √%			undefined
<b>%</b> ∇- <b>z</b>			undefined
C-r	Reverse search command history		
C- <tab></tab>	Next tab		
C-S- <tab></tab>	Previous tab		
%\\ <home></home>			undefined
%\\ <end></end>			undefined
%\\_ <pg\up></pg\up>	Line Up		undefined
%\\_ <pgdn></pgdn>	Line Down		undefined
<b>%</b> ∇- <up></up>	Jump to previous bookmark		undefined
%\\\\_ <down></down>	Jump to next bookmark		undefined
%\\- <right></right>			undefined
%\\- <left></left>			undefined
<b>%</b> \\_ <tab></tab>			undefined
%\\- <backspace></backspace>			undefined
%\\- <del></del>			undefined
%\\- <ret></ret>			undefined
%\\\- <space></space>			macOS New Smart Folder
0−√%			undefined - extended char
<b>%</b> ₹-1			undefined - extended char
<b>%</b> ℃ <b>-2</b>			undefined - extended char
<b>%</b> ℃ <b>-3</b>			undefined - extended char
<b>%</b> ₹-4			undefined - extended char
<b>%</b> ℃ <b>-5</b>			undefined - extended char
<b>%</b> ₹ <b>-6</b>			undefined - extended char
<b>%</b> ℃ <b>-7</b>			undefined - extended char
8−7#			undefined - extended char
<b>%</b> ₹-9			undefined - extended char
%√c- <home></home>			undefined
%\\C- <end></end>			undefined
%√C- <pgup></pgup>			undefined
%℃c- <pgdn></pgdn>			undefined
%\\C- <up></up>			undefined
%√c- <down></down>			undefined
%\C- <right></right>			undefined
%\C- <left></left>			undefined
%\\C- <tab></tab>			undefined
%\C- <backspace></backspace>			undefined
%\C- <del></del>			undefined
%\C- <ret></ret>			undefined
%\C- <space></space>			undefined
%℃ <b>c-~</b>			undefined
%√c-!			undefined
%√c-@			undefined
%℃ <b>c</b> -#			undefined
%℃ <b>c</b> -\$			undefined
<b>%</b> ℃ <b>c</b> -%			undefined
<b>%</b> ℃ <b>c</b> -^			undefined
<b>%</b> ℃ <b>c</b> -&			undefined
<b>%</b> ℃ <b>c</b> -*			undefined
%∑c-(			undefined
%√c-)			undefined
%√c			undefined
%√c-+			undefined
%√c-`			undefined
			Total   Tota

macOS Key	Mac OS Terminal	Emacs Terminal	Emacs Graphics mode
%\c-0			undefined
<b>%</b> ℃ <b>c</b> −1			undefined
<b>%</b> ℃c-2			undefined
<b>%</b> ℃ <b>c</b> -3			undefined
<b>%</b> ℃c-4			undefined undefined
#\C-6			undefined
#\\c-7			undefined
<b>%</b> ℃ <b>c-8</b>			undefined
<b>%</b> ℃c-9			undefined
%℃c			undefined
<b>%</b> ℃ <b>c</b> -=			undefined
%√c-[			undefined
<b>%</b> ℃c-]			undefined
%℃c-\			undefined
<b>%</b> \\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			undefined undefined
% Cc-}			undefined
%℃-;			undefined
%\c-'			undefined
%\c-:			undefined
%℃c-"			undefined
<b>%</b> ℃ <b>c</b> -,			undefined
%\c			undefined
<b>%</b> ℃ <b>c</b> -/			undefined
%\C-<	run sysdiagnose		macOS key ???
%℃c->	run sysulagnose		macOS key: run sysdiagnose. 1 This sends information to Apple.
%\\\C-a			Not accessible  undefined
% \C-b			undefined
#\\c-c			undefined
%√c-d			undefined
<b>%</b> ₹ <b>c</b> -e			undefined
%√c-f			undefined
<b>%</b> ℃ <b>c</b> -g			undefined
%√c-h			undefined
%\C-i			undefined
%\c-j			undefined
%\C-k			undefined undefined
% \c-m			undefined
%\\C-n			undefined
<b>%</b> ₹ <b>c-</b> o			undefined
%\C-p			undefined
<b>%</b> ∖c-q			undefined
#\c-r	Hard reset terminal emulator state		undefined
%\\\c-s			undefined
%\c-t			undefined
Ж∖C-u			undefined
<b>%</b> ℃ <b>c-v</b>			undefined
<b>% \</b> C− <b>w</b>			undefined
%℃c-x			undefined
<b>%</b> \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			undefined undefined
ж Сс−z Ж Сс−A			undefined
ж√с-в			undefined
%\c-c			undefined
<b>%</b> ₹ <b>C-</b> D			undefined
% <b>\_C-E</b>			undefined
Ж∖c-ғ			undefined

macOS Key	Mac OS Terminal	Emacs Terminal	Emacs Graphics mode
%√c-g			undefined
Ж∕С-н			undefined
%√c-I			undefined
Ж∠с-т			undefined
Ж√с-к			undefined
%∠c-r			undefined
Ж∕С-м			undefined
Ж√С-И			undefined
%∠c-o			undefined
<b>%</b> ℃ <b>C-P</b>			undefined
%∠c-δ			Not accessible
%℃C-R			undefined
%℃c-s			undefined
<b>%</b> ℃ <b>-T</b>			undefined
<b>%</b> ∇ <b>c</b> − <b>u</b>			undefined
<b>%</b> ℃ <b>c-v</b>			undefined
<b>%</b> ∠c-w			undefined
%√c-x			undefined
<b>%</b> ∠c-x			undefined
%℃c-z			undefined