

# 🚧 Emacs support for the Seed7 Programming Language 🚧

Description	Keystroke	Function	Note
<b>Seed7 Editing</b>  Last updated on: 2025-04-04	PEL supports for the Seed7 programming language is experimental and not yet documented except for what you see here. 📦 The <a href="#">seed7-mode</a> external package is installed when <a href="#">🔧</a> the <b>pel-use-seed7</b> user-option is set to t.  🚧⚠️ I am currently writing seed7-mode and it's in very early state. It supports some rendering (still not complete for the Seed7 files (files with .sd7 and .si7 extensions)).		
<b>Open this PDF file.</b> See also: <a href="#">📖 Help/Info</a>	<a href="#">&lt;f11&gt;</a> <a href="#">SPC 7</a> <a href="#">&lt;f1&gt;</a>	(pel-help-pdf &optional OPEN-WEB-PAGE)	Open the <a href="#">📖 - Seed7</a> local PDF. If the prefix argument (like <b>C-u</b> or <b>M--</b> ) is used, then it opens the remote GitHub hosted raw PDF instead. If the <b>pel-flip-help-pdf-arg</b> user-option is set it's the other way around.
	<a href="#">&lt;f12&gt;</a> <a href="#">&lt;f1&gt;</a>		
<a href="#">🔧</a> <b>Customize</b> PEL Seed7 support	<a href="#">&lt;f11&gt;</a> <a href="#">SPC 7</a> <a href="#">&lt;f2&gt;</a>	(pel-customize-pel &optional OTHER-WINDOW)	Customize PEL Seed7 support. • If OTHER-WINDOW is non-nil (use <b>C-u</b> ), display in another window.
	<a href="#">&lt;f12&gt;</a> <a href="#">&lt;f2&gt;</a>		
<a href="#">🔧</a> <b>Customize</b> Emacs Seed7 support	<a href="#">&lt;f11&gt;</a> <a href="#">SPC 7</a> <a href="#">&lt;f3&gt;</a>	(pel-customize-library &optional OTHER-WINDOW)	Customize Emacs Seed7 support: <a href="#">seed7</a> • If OTHER-WINDOW is non-nil (use <b>C-u</b> ), display in another window.
	<a href="#">&lt;f12&gt;</a> <a href="#">&lt;f3&gt;</a>		
<b>Comments</b>			
<b>Toggle display of comments in buffer or active region</b> See also: <a href="#">📖 Comments</a>	<a href="#">&lt;f11&gt;</a> <a href="#">;</a> <a href="#">;</a>	(hide/show-comments-toggle &optional START END)	Toggle hiding/showing of comments in the active region or whole buffer. • If the region is active then toggle in the region. Otherwise, in the whole buffer. 📦 This requires the <a href="#">hide-comnt.el</a> package (see <a href="#">📖 Comments</a> ). <a href="#">🔧</a> PEL activates it when the <b>pel-use-hide-comnt</b> user option is t.

## Emacs & Seed7 — References

Document	Notes	
The Seed7 Programming Language	<ul style="list-style-type: none"> <li><a href="#">Seed7 @ Wikipedia</a></li> <li><a href="#">Seed7 Home</a></li> <li><a href="#">Seed7 @ Github</a></li> </ul>	
	<ul style="list-style-type: none"> <li><a href="#">Seed7 @ reddit</a></li> <li><a href="#">Seed7 @ Rosetta code</a></li> </ul>	
Presentations	<ul style="list-style-type: none"> <li><a href="#">The Seed7 Programming Language @ Youtube</a></li> <li><a href="#">The Seed7 Programming Langage Presentation at CPP Vienna @ Youtube</a></li> <li><a href="#">Another speech about the Seed7 Programming Language</a></li> </ul>	
	<a href="#">Modern Extensible Languages.</a> Daniel Zingaro, McMaster U. April 11, 2007 (pdf)	
Emacs support <span>🚧</span> not yet written	<ul style="list-style-type: none"> <li><a href="#">seed7-mode @ Github</a></li> </ul>	