

Abbreviations/Expansions

[illegible]

Operation	Keystroke	Function	Note								
Creating Abbreviations	<ul style="list-style-type: none">define an abbreviation<ul style="list-style-type: none">C-x a gC-x a linverse method<ul style="list-style-type: none">C-x a i gC-x a i l<i>explicit</i> define-global-abbrevdefine-mode-abbrev		ff ff ff								
Define an abbreviation	<ul style="list-style-type: none">C-x a g<f11> a g	add-global-abbrev	<ul style="list-style-type: none">.... ff								
Define an abbreviation for the current mode only	<ul style="list-style-type: none">C-x a lC-x a +C-x a C-a<f11> a l	add-mode-abbrev	<ul style="list-style-type: none">... ff								
Define expansion	<ul style="list-style-type: none">C-x a i gC-x a -	inverse-add-global-abbrev	<ul style="list-style-type: none">... ff								
Define expansion for the current mode only	C-x a i l	inverse-add-mode-abbrev	<ul style="list-style-type: none">... ff								
Explicitly define global abbreviation/expansion	<f11> a G	define-global-abbrev	<ul style="list-style-type: none">.								
Explicitly define local abbreviation/expansion	<f11> a L	define-mode-abbrev	<ul style="list-style-type: none">.								
Manual Expansion of Abbreviations											
Define prefix-based abbreviations	M- '	abbrev-prefix-mark	<ul style="list-style-type: none">. EmacWiki Abbrev Prefixes <ul style="list-style-type: none">.. M- ' M- ' M- '								
Expand abbreviation ff	<ul style="list-style-type: none">C-x 'C-x a e<f11> a e<f11> /	expand-abbrev	<ul style="list-style-type: none">..								
Expand abbreviations in region	<f11> a E	expand-region-abbrevs	<ul style="list-style-type: none">... ff								
Undo last expansion	<f11> a u	unexpand-abbrev	<ul style="list-style-type: none">. ff								
Editing Abbreviations in the *Abbrev* buffer.	<ul style="list-style-type: none">.. <table border="1"><thead><tr><th>NAME</th><th>USECOUNT</th><th>EXPANSION</th><th>HOOK</th></tr></thead><tbody><tr><td>.</td><td></td><td></td><td></td></tr></tbody></table>	NAME	USECOUNT	EXPANSION	HOOK	.					ff ff
NAME	USECOUNT	EXPANSION	HOOK								
.											
List & Edit all abbreviation definitions	<f11> a M-l	list-abbrevs	<ul style="list-style-type: none">... ff C-u ff C-c C-c								
Edit abbreviations in *Abbrev* buffer	<ul style="list-style-type: none"><f11> a M-e%-E	edit-abbrevs	<ul style="list-style-type: none">.. ff ff ff C-c C-c								
Abbrevs buffer commands			ff								
Use specified abbreviations	C-c C-c	edit-abbrevs-redefine	ff								
Save abbreviations	C-x C-s	abbrev-edit-save-buffer)	. ff								
Save abbreviations to specified file	C-x C-w	abbrev-edit-save-to-file	ff								
Saving Abbreviations			ff ff								
Write abbreviations in a file	<f11> a s	write-abbrev-file	<ul style="list-style-type: none">.								
Read abbreviations from a file	<f11> a r	read-abbrev-file	<ul style="list-style-type: none">.								
Write abbreviations inside current buffer after point	<f11> a i	insert-abbrevs	<ul style="list-style-type: none">.								
Define abbreviations by reading them from the current buffer	<f11> a X	pel-extract-abbrev-definitions	<ul style="list-style-type: none">.... ff ff ff 								

Operation	Keystroke	Function	Note
Deleting Abbreviations	M-x kill-all-abbrevs		
Delete all abbreviations		kill-all-abbrevs	