






































Customizing Emacs with PEL

Operation	Keystroke	Function	Note
PEL: Control Emacs via Easy Customization 			


Operation	Keystroke	Function	Note
Browse PEL customize data tree	<f11> <f2> P B	(pel-customize-browse)	Open the customize tree browser for the entire PEL customization data (which is under Emacs/Convenience).
	<f12> P B		
Emacs Easy Customization	With the following command you can gain access to the Customize-mode to customize anything of interest. With the first command you open the customization buffer and then you can search or browse what you want to customize. The second command allow you to open the buffer at a specific customization group and the third one at a specific user option. These commands prompt for the information you are looking for. You can always use completion by typing <tab> at any point to get a list of available groups or variables. Several of the commands below open the PEL customization group and one or several other groups related to the same topic, when these groups are already loaded. <ul style="list-style-type: none">If you set the OTHER-WINDOW argument, the command open s the buffer in another window and also open any group related that exists. For example if you open the PEL group for grep with C-u <f11> <f2> g, this will also open the grep group, the rg and ripgrep groups if they are loaded. Each group will open inside its own bugger and the command will create the necessary windows.⚠️ Until a package is loaded its customization group is unknown to Emacs and no buffer will be opened for it. To see the customization group, first load the package via one of its command that is auto-loaded or load it explicitly.👉 Note however that the PEL commands that open customization groups attempt to identify the library where the customization group is defined and will prompt you to load the related library to enable access to the customization group. The groups accessible via the PEL commands are limited to what PEL supports.		
Customize Emacs	<f11> <f2> c	(customize)	Select a customization buffer which you can use to set user options. <ul style="list-style-type: none">User options are structured into "groups".Initially the top-level group 'Emacs' and its immediate subgroups are shown; the contents of those subgroups are initially hidden. ⚠️ Emacs is only able to show information it knows about. Customization data defined in files not loaded will not be accessible.
	<f12> c		
Customize a specific group	<f11> <f2> g	(customize-group &optional GROUP OTHER-WINDOW)	Customize GROUP, which must be a customization group. <ul style="list-style-type: none">If OTHER-WINDOW is non-nil (use C-u), display in another window.This command provides completion and you can use it to detect groups. ⚠️ Emacs is only able to show the name names of groups that are defined in files that have already been loaded. You won't be able to open a group that is not already loaded. <ul style="list-style-type: none">👉 The pel-customize-library commands available as the <f3> key of PEL key prefixes does not suffer from this problem: it will detect that the library is not loaded and will prompt you for loading it, giving you access to the customization buffer when you need it. The information is available in the various PDF pages at the top of each page.
	<f12> g		
Customize a user option	<f11> <f2> o	(customize-option SYMBOL)	Customize SYMBOL, which must be a user option. <ul style="list-style-type: none">As with groups, Emacs provides completion for user options, allowing you to detect user options. ⚠️ Emacs is only able to show the name names of user options that are defined in files that have already been loaded. You won't be able to open a group that is not already loaded. But see the notice in the above cell.
	<f12> o		
Set and store new value for user-option	<f11> <f2> v	(customize-save-variable VARIABLE VALUE &optional COMMENT)	Set the default for VARIABLE to VALUE, and save it for future sessions in the customize file. <ul style="list-style-type: none">Prompts for the user-option name, supporting tab completion.Propose values controlled by customization selections.As opposed to the commands above this does not open a customization buffer. 👉 Use this to quickly change a PEL pel-use- user-option if you know its documentation and do not want to open a customization buffer.
	<f12> v		
Activate and cleanup your packages using PEL customization user-variables	PEL provides customization-driven package management. <ul style="list-style-type: none">PEL controls download, installation and configuration of the packages supported by its pel-use- user-options controlled by the PEL customization groups. The packages missing are installed when you start Emacs or when you explicitly run the pel-init command.PEL also removes the packages that are not required by the PEL user-options when you issue the pel-cleanup command.<ul style="list-style-type: none">Use a key prefix for this command to perform a dry-run of the command and produce a report of what would be removed.PEL does not delete packages. Instead it places them into separate directories, called "attic" directories. You can then retrieve the package from the directories later.<ul style="list-style-type: none">The elpa packages are stored in the directory identified by package-user-dir or in the "elpa" directory inside the user-emacs-directory.<ul style="list-style-type: none">The elpa attic is identified by a name that appends "-attic" to the above directory name.On a Unix-like system that would normally be "~/.emacs.d/elpa" and "~/.emacs.d/elpa-attic".The non-elpa files are stored in the directory identified by the pel-utils-dirname user-options (which defaults to "utils") inside the directory identified by the user-emacs-directory. Its attic directory name is the same name with a "-attic" suffix.<ul style="list-style-type: none">By default, on Unix-like systems the directories are "~/.emacs.d/utils" and "~/.emacs.d/utils-attic".On Windows system the directories are located in your User directory, as controlled by Emacs. Also on Emacs 27.1 and later these directories can be located somewhere else.The customization file (described in a section above) should be located in the same user-emacs-directory.		
Re-initialize PEL, activate the new PEL user-option, install packages newly requested	M-x pel-init	(pel-init &optional CACHED-ABBREV-FILE-NAME)	Re-initialize PEL. Download, install and configure any package requested by the various pel-use- user-options that have not yet been installed. <ul style="list-style-type: none">Does not remove anything. Use pel-cleanup for that.The argument is not accessible interactively and exists for the initial Emacs startup only.
Show PEL user option and package info See also: ⓘ Help/Info	<f11> ? e ?	(pel-package-info &optional FULL-REPORT)	Display the following information in the echo area: <ul style="list-style-type: none">The number of PEL user-options, and the number of them that are active.The number of Elpa packages active: the count of the ones directly installed because of active PEL user-options and the count of them installed as dependencies of the first group.The number of Emacs Lisp files stored in the ~/.emacs.d/utils (or equivalent directory) as a result of PEL user options. <ul style="list-style-type: none">With optional argument, generates a full report with much more details in a "pel-user-options" report buffer. Any key prefix works. M- - <f11> ? e ? for example.
Disable all packages not requested by PEL user-options and not identified as dependency or packages that must be kept. Update the load path and the customization file content.	M-x pel-cleanup	(pel-cleanup &optional DRY-RUN)	After prompting for a confirmation, de-activates all Elpa and non-Elpa packages that are not requested by a PEL user-option. The command keeps packages that are dependencies of packages required by PEL user-options and packages that PEL always requires. It also keeps packages that you have identified as manually installed in the following user options: <ul style="list-style-type: none">pel-elpa-packages-to-keeppel-utils-packages-to-keep ⚠️ For the current version of PEL when you install an Emacs package with the Emacs package system, PEL does not automatically add the package name in the pel-elpa-packages-to-keep user-option. If you want to keep that package and configure it yourself with your own Emacs Lisp code invoked by your init.el file, add the package symbol name to the list of pel-elpa-packages-to-keep otherwise pel-cleanup will move the package to the elpa-attic.
Perform a dry-run of pel-cleanup. Generate a detailed report.	M-- M-x pel-cleanup		Runs pel-cleanup in dry-mode and produce a detailed report of what pel-pel-cleanup would remove in a "pel-cleanup" buffer.

Operation	Keystroke	Function	Note
<div>Input Completion Mode Selection</div> <div>See also:</div> <div><ul style="list-style-type: none">» Completion/Input» Menus» Navigation</div>	<div>PEL supports several input completion modes that kick in with the M-x, C-x b, C-x C-f, <f1> o and many other commands. PEL supports the following input completion modes:</div> <div><div><div>1. Emacs' default tab completion</div></div><div><div>2.  Helm mode completion</div><div>:  set pel-use-helm to t.</div></div><div><div>3. Ido mode completion</div><div>:  set pel-use-ido to t</div></div><div><div>4.  Ivy mode completion</div><div>:  set pel-use-ivy to t</div></div><div><div>5.  Ivy mode completion with Counsel mode</div><div>:  set pel-use-counsel to t</div></div><div><div>6.  Ido/Helm mode where Ido is used for dealing with Files and buffers and Helm is used everywhere else (including all Helm specific commands).</div></div></div> <div><ul style="list-style-type: none">PEL also has commands that uses the iMenu system to list symbol defined in the current or all buffers. The behaviour and user interface or these commands can be modified and extended by several external packages and customization user-options:<ul style="list-style-type: none">pel-imenu-follows-order-p user-option controls whether entries are sorted or follows the order of declaration in the file. flimenu external package  activated by pel-use-flimenu user-option, controls whether iMenu lists are flatten or hierarchical. imenu-anywhere external package  activated by pel-use-imenu-anywhere user-option is used by pel-goto-symbol-any-buffer to jump to symbol definition of any buffer using one of the following input completion method. The user-option must be set to one of the following values:<ul style="list-style-type: none">Use emacs-default: basic Emacs completion. Use tab to see possible matches.Use Ido.  pel-use-ido must be turned on.Use Ivy.  Requires Ivy mode  pel-use-ivy must be on.Use helm.  Requires Helm mode  pel-use-helm must be turned on. popup-imenu external package  activated by pel-use-popup-imenu user-option, provides one pop-up menu for the iMenu content. popup-switcher external package  activated by pel-use-popup-switcher user-option, provides the same as popup-imenu and more.<div> To customize the above, use:<ul style="list-style-type: none"><f11> M-c <f2> to customize the PEL completion group user options. It is also available via M-g <f4> <f2>.<f11> <f10> <f2> to customize the PEL iMenu user-options.</div><div>As soon as one of the extra completion mode is activated via the corresponding pel-use- user option, PEL makes the following commands available to change the completion mode and to see which one is currently active.</div></div>		
Select the completion mode	<f11> M-c <f4>	(pel-select-completion-mode)	Prompt user for completion mode to activate. The available modes depend on what is currently activated by customization. See the list above.
Show what completion mode is currently used.	<f11> M-c ?	(pel-show-active-completion-mode)	Display the completion mode currently used.
<div>Search Tools Selection</div> <div>See also:</div> <div><ul style="list-style-type: none">» Search/Replace</div>	<div>PEL supports several search tools that impact the way the C-s command operates. PEL supports the following search tools:</div> <div><div><div><ul style="list-style-type: none">Emacs' default ISearch Anzu, ISearch with match count Swiper search with overview match list</div><div><div>:  set pel-use-anzu to t.</div><div>:  set pel-use-swiper to t</div></div></div><div><div> Use <f11> s <f3> to customize the PEL completion group user options above.</div><div><ul style="list-style-type: none">Set the pel-initial-search-tool user option to select which search tool is used when Emacs starts.</div></div><div>As soon as one of the extra search tool is activated via the corresponding pel-use- user option, PEL makes the following commands available to change the currently used search tool and to see which one is currently active.</div></div>		
Show which search tool is currently used	<f1> ? s	(pel-show-active-search-tool)	Display the currently used search tool.
Select search tool to use	<f11> s s	(pel-select-search-tool)	Prompt user for search tool to use with C-s . Show new active one.
	<div><ul style="list-style-type: none">Emacs normally maps the search-forward command to C-s.PEL provides the ability to activate the following tools that can be activated for searching: The Anzu external package  activated by pel-use-anzu user option. Anzu provides a match count in the mode line when searching. The Swiper external package  activated by pel-use-swiper user option. Swiper is not using isearch-forward; it shows a list of matching lines in the mini-buffer. Use the <f11> s <f2> command to open the PEL search customize group and set the pel-initial-search-tool user option to identify which tool is used when Emacs starts.</div> <div> Being able to search using either Emacs default ISearch (see below) and Swiper helps as they are both very useful in different scenarios.</div>		
Customize PEL support	<div>The following commands opens the Emacs customization group related to a PEL topic. Most of these commands do not prompt; they open the customization buffer at the requested group.</div> <div> If you prefix the following commands with C-u PEL will also open the customization groups related to the specific feature.</div> <div>  To activate any PEL customization change in the current session, execute M-x pel-init after you saving and applying the customized variable. For motion variables that control mode hooks (eg. the flyspell automatic activation for specific major modes), you also need to restart Emacs.</div>		
All PEL	<div><f11> <f2> P !</div> <div><f12> P !</div>	(pel-cfg &optional OTHER-WINDOW)	Customize PEL support. <ul style="list-style-type: none">If OTHER-WINDOW is non-nil (use C-u), display in another window.
PEL base	<div><f11> <f2> p</div> <div><f12> p</div>	(pel-customize-pel-base-emacs-group &optional OTHER-WINDOW)	Customize basic PEL configuration: open the pel-base-emacs group. <ul style="list-style-type: none">If OTHER-WINDOW is non-nil (use C-u), display in another window.
Customize specific PEL group	<div>The following key bindings almost all use the same PEL command: (pel-customize-pel &optional OTHER-WINDOW). The command detects the key sequence that invoked it to select the customization group to open. If there are more than one it prompts for the one to open. If a group is not loaded, PEL prompts for loading it.</div> <div><ul style="list-style-type: none">All of these commands open the buffer inside another window if a prefix argument (like C-u) is typed first.</div>		
» Align	<f11> t a <f2>	Customize PEL support for text alignment.	
» Auto-Completion	<f11> , <f2>	Customize PEL auto-completion support: auto-complete, company and hippie-expand.	
» Bookmarks	<f11> ' <f2>	Customize PEL support for bookmark groups: bookmark, bm.	
» Buffers	<f11> b <f2>	Customize PEL support for buffer management: hexl.	
» Comments	<f11> ; <f2>	Customize Emacs support for comment hide control: hide-cmnt.	
» Cursor	<f11> m <f2>	Customize PEL support for cursor and multiple-cursors.	
» Filling/Justification	<div><ul style="list-style-type: none"><f11> t f <f2><f11> t j <f2></div>	Customize PEL support for:	
» Diff & Merge	<f11> d <f2>	Customize PEL support for diff: ztree.	
» Dired	<f11> f <f2> 2	Customize PEL support for dired, directory editor.	
» Drawing	<f11> D <f2>	Customize PEL drawing mode support.	
» Fast Startup	<f11> M-S <f2>	Customize PEL support for fast startup mode.	
» File-mngt	<f11> f <f2> 1	Customize PEL support for file management.	
» File-mngt - dir. tree browser	<f11> B <f2>	Customize PEL support for directory tree browsers: treemacs, ztree	

Operation	Keystroke	Function	Note
» <u>File-mngt</u> - NeoTree	<f11> B N <f2>	Customize PEL support for NeoTree directory browser	
» <u>Frames</u>	<f11> F <f2>	Customize PEL frame management support.	
» <u>Grep</u>	<f11> g <f2>	Customize PEL grep support. Groups: grep, ag, rg, ripgrep, wgrep.	
» <u>Help/Info</u>	<f11> ? <f2>	Customize PEL help support.	
» <u>Hide/Show</u>	<f11> M-/ <f2>	Customize PEL support for comments: hide-cmnt, hide-lines.	
» <u>Highlight</u>	<f11> h <f2>	Customize PEL support for buffer highlight management: fill-column-indicator, vline, rainbow-delimiters.	
» <u>Indentation</u>	<f11> <tab> <f2>	Customize PEL support for:	
» <u>Inserting Text</u>	<f11> i <f2>	Customize PEL text insertion support: lice, smart-dash, tempo, time-stamp, yasnippet	
» <u>Keyboard Macros</u>	<ul style="list-style-type: none">• <f11> k <f2>• <f11> k e <f2>• <f11> k l <f2>	Customize the PEL keyboard macro external package support: centimacro, emacros, elmacro.	
» <u>Key-Chords</u>	<f11> <f5> k <f2>	Customize PEL Key Chord support.	
Input Completion: » <u>Completion/Input</u>	<ul style="list-style-type: none">• <f11> M-c <f2>• M-g <f4> <f2>	Customize PEL Input Completion support.	
» <u>Marking</u>	<f11> . <f2>	Customize PEL Marking support.	
» <u>Menus</u> - iMenu	<f11> <f10> <f2>	Customize PEL imenu support.	
» <u>Mode Line</u>	<f11> M-d <f2>	Customize PEL mode line support	
» <u>Navigation</u>	<f11> <f2> P n	(pel-cfg-pkg-navigation &optional OTHER-WINDOW)	Customize PEL and Emacs navigation tools support. Provides access to the following customization groups: 1. PEL project management 2. avy <ul style="list-style-type: none">• If OTHER-WINDOW is non-nil (use C-u), display in another window.
» <u>Outline</u>	<f11> SPC M-l <f2>	Customize PEL outline support	
» <u>Projectile</u>	<ul style="list-style-type: none">• <f11> <f2> P <f8>	(pel-cfg-pkg-project-mng &optional OTHER-WINDOW)	Open the projectile customization group where you can modify projectiles configuration. <ul style="list-style-type: none">• The key sequence <f11> <f2> P <f8> is always available, the others are only available when the projectile mode is activated.  Available when the projectile external package is  activated by PEL with the pel-use-projectile user option is non-nil.
	<ul style="list-style-type: none">• <f11> <f8> <f2>• <f8> <f2>	(pel-customize-pel &optional OTHER-WINDOW)	
» <u>Scrolling</u>	<f11> <f2>	Customize PEL Scrolling support.	
» <u>Search/Replace</u>	<f11> s <f2>	Customize PEL basic search support.	
Regular Expression » <u>Search/Replace</u>	<f11> s x <f2>	Customize PEL regular expression tool support.	
» <u>Sessions</u>	<f11> S <f2>	Customize PEL Session support.	
» <u>Shells</u>	<f11> z <f2>	Customize PEL Shell support.	
» <u>Speedbar</u>	<f11> M-s <f2>	Customize PEL Speedbar support.	
» <u>Spell Checking</u>	<f11> \$ <f2>	Customize PEL support for: spell checking. Identify which major modes will automatically activate either flyspell-mode or flyspell-prog-mode.	
» <u>Text Modes</u>	<ul style="list-style-type: none">• <f11> t <f2>• <f11> t m <f2>	Customize PEL text management support.	
» <u>Time Tracking</u>	<f11> T <f2>	Open the PEL customize group(s) for the current context.	
» <u>Undo/Redo/Repeat/Arg</u>	<f11> u <f2>	Customize PEL undo support.	
» <u>VCS</u>	<f11> v <f2>	Customize PEL Version Control System support.	
» <u>Windows</u>	<f11> w <f2>	Customize PEL Window support.	
Yasnippet - » <u>Inserting Text</u>	<f11> y <f2>	Customize PEL Yasnippet text insertion support.	
» <u>Xref</u> - cross reference	<f11> x <f2>	Customize PEL cross-reference support: ctags/etags/gtags	

Operation	Keystroke	Function	Note
Configure PEL Programming Language support	<p>The following commands opens the Emacs configuration group to configure PEL support for the specified programming language.</p> <ul style="list-style-type: none"> You should be able to control most of the important features of the programming languages through these customizations including the activation of important packages as well as aspects of programming language styles like indentation style and width. The <f11> SPC key prefixes are available globally (for all buffers). The <f12> <f2> key is only available when point is in a buffer for one of the languages supported by PEL and open the PEL customization group for the programming language for the current buffer. <p>👉 When you use the <f11> SPC prefix, you can customize the Emacs language library support that might not even be loaded: PEL will detect if the corresponding library is loaded and will prompt you asking if you want to load it first, allowing Emacs to open the customization buffer.</p> <p>⚠️👉 To activate any PEL customization change in the current session, execute M-x pel-init after you saving and applying the customized variable. Alternatively close and re-start Emacs.</p>		
AppleScript & text audio narration	<f11> SPC a <f2>	Customize PEL Applescript support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Arc	<f11> SPC C-a <f2>	Customize PEL Arc support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - C	<f11> SPC c <f2>	Customize PEL C support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - C++	<f11> SPC C <f2>	Customize PEL C++ support: cpp.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Clojure	<f11> SPC C-j <f2>	Customize PEL Clojure support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Common Lisp	<f11> SPC L <f2>	Customize PEL Lisp support: lisp, lispy.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Chez Scheme	<f11> SPC C-s C-z <f2>	Customize PEL Chez support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Chibi Scheme	<f11> SPC C-s C-i <f2>	Customize PEL Chibi support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Chicken Scheme	<f11> SPC C-s C-k <f2>	Customize PEL Chicken support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - D	<f11> SPC D <f2>	Customize PEL D support: d-mode.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Elixir	<f11> SPC x <f2>	Customize PEL Elixir support: alchemist, alchemist-iex.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> ⌘ - Emacs Lisp	<f11> SPC l <f2>	Customize PEL Elisp support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> ⌘ - Emacs Lisp eldoc	<f11> SPC l ? <f2>	Customize PEL Elisp support: eldoc-box.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Erlang	<f11> SPC e <f2>	Customize PEL Erlang support: erlang, erldoc, edts, auto-highlight-symbol.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Forth	<f11> SPC f <f2>	Customize PEL Forth support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Go	<f11> SPC g <f2>	Customize PEL Go support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Gambit Scheme	<f11> SPC C-s C-b <f2>	Customize PEL Gambit Scheme support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - GNU Guile Scheme	<f11> SPC C-s C-g <f2>	Customize PEL Guile support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Gerbil Scheme	<f11> SPC C-s C-e <f2>	Customize PEL Gerbil Scheme support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Gleam	<f11> SPC M-g <f2>	Customize PEL Gleam support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Haskell	<f11> SPC h <f2>	Customize PEL Haskell support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Hy	<f11> SPC C-h <f2>	Customize PEL Hy support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Julia	<f11> SPC j <f2>	Customize PEL Julia support: julia, julia-mode, julia-snail.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Janet	<f11> SPC T <f2>	Customize PEL Janet support: pel-use-janet, pel-use-janet-mode, pel-use-ijanet, pel-use-inf-janet	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - LFE	<f11> SPC C-l <f2>	Customize PEL LFE support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
<u>⌘</u> - Lispy	<f11> <f2> SPC M-L	Customize support for Lisp programming languages - A group that also contains the groups for Emacs Lisp and Common Lisp: lispy.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
<u>⌘</u> - NetRexx	<f11> SPC N <f2>	Customize PEL NetRexx support. Use this to activate NetRexx support.	<ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		

Operation	Keystroke	Function	Note
<u>⌘</u> - <u>Nim</u>	<f11> SPC n <f2>	Customize PEL nim support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
<u>⌘</u> - <u>OCaml</u>	<f11> SPC o <f2>	Customize PEL OCaml support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
<u>⌘</u> - <u>Perl</u>	<f11> SPC P <f2>	Customize PEL Perl support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
<u>⌘</u> - <u>Python</u>	<f11> SPC p <f2>	Customize PEL Python support: python, python-flymake. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
<u>⌘</u> - <u>Racket</u>	<f11> SPC C–s C–r <f2>	Customize PEL Racket support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
<u>⌘</u> - <u>REXX</u>	<f11> SPC R <f2>	Customize PEL REXX support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
<u>⌘</u> - <u>Ruby</u>	<f11> SPC U <f2>	Customize PEL Ruby support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
<u>⌘</u> - <u>Rust</u>	<f11> SPC r <f2>	Customize PEL Rust support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
<u>⌘</u> - <u>UNIX Shell</u>	<f11> SPC H <f2>	Customize PEL UNIX Shell support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
<u>⌘</u> - <u>Scheme</u>	<f11> SPC C–s C–s <f2>	<f11> SPC C–s C–s <f2> <f12> <f2>	
	<f12> <f2>		
<u>⌘</u> - <u>V</u>	<f11> SPC v <f2>	Customize PEL V support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
Configure PEL Markup support	The following commands opens the Emacs customization group related to configure PEL support for the specific markup language. • The <f11> SPC key prefixes are available globally (for all buffers). • The <f12> <f2> key is only available when point is in a buffer for one of the languages supported by PEL and open the PEL customization group for the markup language for the current buffer. ⚠️👉 To activate any PEL customization change in the current session, execute M–x pel-init after you saving and applying the customized variable. ⚠️👉 To activate any PEL customization change in the current session, execute M–x pel-init after you saving and applying the customized variable. Alternatively close and re-start Emacs.		
<u>⌘</u> <u>Graphviz Dot</u>	<f11> SPC M–g <f2>	Customize PEL Graphviz-Dot support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
<u>⌘</u> <u>PlantUML</u>	• <f11> D u <f2>	Customize PEL PlantUML support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	• <f11> SPC M–u <f2>		
	<f12> <f2>		
<u>⌘</u> <u>Markdown</u>	<f11> SPC M–m <f2>	Customize PEL Markdown support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
<u>⌘</u> <u>Outline/Org-Mode</u>	<f11> SPC M–o <f2>	Customize PEL Org Mode support: open pel-pkg-for-org-mode group. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
<u>⌘</u> <u>reStructuredText</u>	<f11> SPC M–r <f2>	Customize PEL reStructuredText support. • If OTHER-WINDOW is non-nil (use C–u), display in another window.	
	<f12> <f2>		
Customize Specific Emacs Groups.	PEL provides several key bindings to open customization groups of Emacs built-in or external package. • PEL will prompt you to load their specific file if they are not loaded. • Most of the key bindings are mapped into the PEL key prefixes as the <f3> key member. For example to open auto-completion related groups you can use the <f11> , <f3> key sequence. These are not listed here. • PEL does not provide key prefixes for all Emacs concepts. It provides, however some key bindings to access the customization buffer for some of those. They are listed just below, here:		
Permanently change the cursor's color See also: <u>⌘ Cursor</u>	<f11> <f2> E C–c	(pel-customize-cursor &optional OTHER-WINDOW)	Quicks access to the customize buffer to set the cursor default color. • It sets the color permanently if the customization is saved. ⚠️ Only available in graphics mode.
locate	<f11> <f2> E l	(pel-cfge-locate &optional OTHER-WINDOW)	Customize locate. With C–u , display in another window.
man	<f11> <f2> E m	(pel-cfge-man &optional OTHER-WINDOW)	Customize man. With C–u , display in another window.
browse-url	<f11> <f2> E u	(pel-cfge-browse-url &optional OTHER-WINDOW)	Customize browse-url. With C–u , display in another window.
webjump	<f11> <f2> E j	(pel-cfge-webjump &optional OTHER-WINDOW)	Customize webjump. With C–u , display in another window.
woman	<f11> <f2> E w	(pel-cfge-woman &optional OTHER-WINDOW)	Customize woman. With C–u , display in another window.
Customize Emacs Libraries	The following key bindings almost all use the same PEL command: (pel-customize-library &optional OTHER-WINDOW). The command detects the key sequence that invoked it to select the customization group to open. If there are more than one it prompts for the one to open. If a group is not loaded, PEL prompts for loading it. If the related package is not installed PEL print a warning message. • For external packages you can use the same key sequence except for the last key: replace <f3> by <f2> : that sequence will open the PEL configuration buffer for the same topic. From that you will find the PEL option variable to activate the external package. • All of these commands open the buffer inside another window if a prefix argument (like C–u) is typed first.		
<u>⌘</u> <u>Align</u>	<f11> t a <f3>	Customize Emacs text alignment support: open the align group.	
<u>⌘</u> <u>Auto-Completion</u>	<f11> , <f3>	Customize Emacs auto-completion support: auto-complete, company and hippie-expand.	
<u>⌘</u> <u>Bookmarks</u>	<f11> ' <f3>	Customize Emacs bookmark group which includes: bookmark and bm.	
<u>⌘</u> <u>Buffers</u>	<f11> b <f3>	Customize Emacs support for buffer management: Buffer-menu, buffer, minibuffer, hexl, nhexl.	
<u>⌘</u> <u>Comments</u>	<f11> ; <f3>	Customize Emacs support for comments: comment, hideshow.	
Customization Control	<f11> <f2> <f3>	Customize Emacs customization control.	

Operation	Keystroke	Function	Note
» Hide/Show	<f11> M-/ <f3>	Customize Emacs support for comments: comment, hideshow.	
Input Completion: » Completion/Input	<f11> <f2> P M-c	(pel-cfg-pkg-completion &optional OTHER-WINDOW)	Customize Emacs Input Completion support: helm, ido, ivy, counsel.. • If OTHER-WINDOW is non-nil (use C-u) , display in other window.
» Cursor	<f11> m <f3>	Customize Emacs support for cursor and multiple-cursors.	
» Diff & Merge - ediff	<f11> d e <f3>	Customize Emacs ediff.	
» Dired	<f11> SPC M-D <f3>	Customize Emacs support for: dired, dired-git-info, dired-hide-dotfiles, ls-lisp, wdired. • The <f12> <f3> key sequence is available in the dired buffer.	
	<f12> <f3>		
» Enriched Text	<f11> t e <f3>	Customize Emacs Enriched Text support.	
» File-mngt	<f11> f <f3> 1	Customize Emacs support for file management.	
» File-mngt - auto-revert	<f11> f r <f3>	Customize Emacs support for file automatic revert management.	
» File-mngt - ffap	<f11> f a <f3>	Customize Emacs support for management of ffap (find file at point).	
» File-mngt - dir. tree browser	<f11> B <f3>	Customize directory tree browsers: treemacs, ztree	
» File-mngt - NeoTree	<f11> B N <f3>	Customize NeoTree directory browser	
» Filling/Justification	• <f11> t f <f3> • <f11> t j <f3>	Customize Emacs fill and justification control.	
» Frames	<f11> F <f3>	Customize Emacs frame management support.	
» Grep	<f11> g <f3>	Customize Emacs grep support. Groups: grep, ag, deadgrep, fzf, rg, ripgrep, wgrep.	
» Help/Info	<f11> ? <f3>	Customize Emacs help support. Groups: command-log, helpful.	
» Highlight	<f11> h <f3>	Customize Emacs support for buffer highlight management: auto-highlight, edit, rainbow-delimited, line, fill-column-indicator (for Emacs version earlier than 27.1)	
» Indentation	<f11> <tab> <f3>	Customize Emacs indentation. Opens the indent customization group.	
» Inserting Text	<f11> i <f3>	Customize Emacs text insertion support: lice, smart-dash, tempo, time-stamp, yasnippet	
» Keyboard Macros	<f11> k <f3>	Customize the Emacs keyboard macro external package support: kmacro, centimacro.	
» Keyboard Macros	<f11> k e <f3>	Customize the Emacs keyboard macro external package support: emacros.	
» Keyboard Macros	<f11> k l <f3>	Customize the Emacs keyboard macro external package support: elmacro.	
» Key-Chords	<f11> <f5> k <f3>	Customize Emacs support for: key-chord	
Line Mngt: » Display - Lines	<f11> l <f3>	Customize Emacs support for visual-line.	
» Marking	<f11> . <f3>	Customize Emacs Marking support.	
» Menus - iMenu	<f11> <f10> <f3>	Customize Emacs menu mechanisms.	
» Mode Line	<f11> M-d <f3>	Customize Emacs mode line support: mode-line	
» Navigation	<f11> <f2> P n 2	(pel-cfg-pkg-navigation &optional OTHER-WINDOW)	Customize Emacs navigation tools support: avy. • If OTHER-WINDOW is non-nil (use C-u) , display in another window.
» Outline	<f11> SPC M-l <f3>	Customize Emacs outline support	
» Projectile	• <f11> <f8> <f3> • <f8> <f3>	(pel-customize-projectile)	Open the projectile customization group where you can modify projectiles configuration.
		<ul style="list-style-type: none"> Key sequence <f11> <f8> <f3> is available if pel-use-projectile is t. Key sequence <f8> <f2> is available when the projectile mode is on. 📦 Available when projectile external package is  activated the pel-use-projectile user option.	
Regular Expression » Search/Replace	<f11> s x <f3>	Customize Emacs regular expression support: rxt, re-builder, visual-regex.	
» Scrolling	<f11> <f3>	Customize Emacs Scrolling support groups: follow, smooth-scrolling.	
» Search/Replace	<f11> s <f3>	Customize Emacs Search support: isearch, anzu, iedit, easy-escape, fzf, swiper.	
» Sessions	<f11> S <f3>	Customize Emacs Session support: desktop.	
» Shells	<f11> z <f3>	Customize Emacs Shells support groups: term, terminals, vterm.	
» Speedbar	<f11> M-s <f3>	Customize Emacs Speedbar support.	
» Spell Checking	<f11> \$ <f3>	Customize Emacs spelling support. Opens the following customization groups: ispell, flyspell.	
» Text Modes	<f11> t m <f3>	Customize Emacs text mode group: glasses	
Text » Whitespace	<f11> t w <f3>	Customize Emacs handling of whitespaces.	
» Time Tracking	<f11> T <f3>	Customize Emacs <i>time related</i> groups which includes: display-time, timeclock, timelog	
» VCS	<f11> v <f3>	Customize Emacs Version Control System support: vc, vc-hg, vc-git, magit, monky.	
» Undo/Redo/Repeat/Arg	<f11> u <f3>	Customize Emacs undo support: undo, undo-tree.	
» Windows	<f11> w <f3>	Customize Emacs Window support groups: windows, ace-window, ace-window-display, winner, windmove.	
» Xref - cross reference	<f11> x <f3>	Customize Emacs cross-reference support: ctags/etags/gtags	
Yasnippet » Inserting Text	<f11> y <f3>	Customize Yasnippet groups: yasnippet, yasnippet-snippets, yas-minor	

Operation	Keystroke	Function	Note
Configure Emacs Programming Language support	<p>The following commands opens the Emacs configuration group to configure Emacs support for the specified programming language.</p> <ul style="list-style-type: none"> The <f11> SPC key prefixes are available globally (for all buffers). The <f12> <f3> key is only available when point is in a buffer for one of the languages supported by PEL and open the Emacs customization group for the programming language for the current buffer. <p>👉 When you use the <f11> SPC prefix, you can customize the Emacs language library support that might not even be loaded: PEL will detect if the corresponding library is loaded and will prompt you asking if you want to load it first, allowing Emacs to open the customization buffer.</p>		
AppleScript & text audio narration	<f11> SPC a <f3>	Customize Emacs Applescript support. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Arc	<f11> SPC C-a <f3>	Customize Emacs Arc support: arc, lispy. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - C	<f11> SPC c <f3>	Customize Emacs C support. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - C++	<f11> SPC C <f3>	Customize Emacs C++ support: cpp. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Clojure	<f11> SPC C-j <f3>	Customize Emacs Clojure support: clojure, cider, cljr. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Common Lisp	<f11> SPC L <f3>	Customize Emacs Lisp support: lisp, lispy. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Chez Scheme	<f11> SPC C-s C-z <f3>	Customize Emacs Scheme support: scheme, geiser, quack, lispy. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Chibi Scheme	<f11> SPC C-s C-i <f3>	Customize Emacs Scheme support: scheme, geiser, quack, lispy. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Chicken Scheme	<f11> SPC C-s C-k <f3>	Customize Emacs Scheme support: scheme, geiser, quack, lispy. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - D	<f11> SPC D <f3>	Customize Emacs D support: d-mode. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Elixir	<f11> SPC x <f3>	Customize Emacs Elixir support: alchemist, alchemist-iex. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⇧</u> <u>⌘</u> - Emacs Lisp	<f11> SPC l <f3>	Customize Emacs Elisp support: checkdoc, editing-basics, elint, eldoc, eros, lisp, lispy, suggest. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⇧</u> <u>⌘</u> - Emacs Lisp eldoc	<f11> SPC l ? <f3>	Customize PEL Elisp support: eldoc, eldoc-box. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Erlang	<f11> SPC e <f3>	Customize Emacs Erlang support: erlang, erldoc, edts, auto-highlight-symbol. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Forth	<f11> SPC f <f3>	Customize Emacs Forth support. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Go	<f11> SPC g <f3>	Customize Emacs Go support. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f2>		
<u>⌘</u> - Gambit Scheme	<f11> SPC C-s C-b <f3>	Customize Emacs Scheme support: gerbil-mode, scheme, geiser, quack, lispy. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - GNU Guile Scheme	<f11> SPC C-s C-g <f3>	Customize Emacs Scheme support: scheme, geiser, quack, lispy. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Gerbil Scheme	<f11> SPC C-s C-e <f3>	Customize Emacs Scheme support: gerbil-mode, scheme, geiser, quack, lispy. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Haskell	<f11> SPC h <f3>	Customize Emacs Haskell support: haskell • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Julia	<f11> SPC j <f3>	Customize Emacs Julia support: julia, julia-mode, julia-snail. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Janet	<f11> SPC T <f3>	Customize Emacs Janet support: janet, ijanet, inf-janet • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - LFE	<f11> SPC C-l <f3>	Customize Emacs LFE support: the lfe customization group, which controls the settings of the lfe-mode. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Make	<f11> SPC M <f3>	Customize Emacs makefile support: makefile. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - NetRexx	<f11> SPC N <f3>	Customize Emacs NetRexx support: netrexx-mode • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Nim	<f11> SPC n <f3>	Customize Emacs nim support: nim • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - OCaml	<f11> SPC o <f3>	Customize Emacs OCaml support: merlin, tuareg, tuareg-opam. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Perl	<f11> SPC P <f3>	Customize Emacs Perl support: perl. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>⌘</u> - Python	<f11> SPC p <f3>	Customize Emacs Python support: python, python-flymake. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		

Operation	Keystroke	Function	Note
<u>P</u> I - Racket	<f11> SPC C-s C-r <f3>	Customize Emacs Racket support: racket, scheme, geiser, quack, lispy. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>P</u> I - REXX	<f11> SPC R <f3>	Customize Emacs REXX support. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>P</u> I - Ruby	<f11> SPC U <f3>	Customize Emacs Ruby support: ruby. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>P</u> I - Rust	<f11> SPC r <f3>	Customize Emacs Rust support: rust-mode, rustic, racer, cargo. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>P</u> I - Scheme	<f11> SPC C-s C-s <f3>	Customize PEL Scheme support. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>P</u> I - UNIX Shell	<f11> SPC H <f3>	Customize Emacs UNIX Shell support: sh, sh-script, sh-indentation. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>P</u> I - V	<f11> SPC v <f3>	Customize Emacs V support: v • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
Configure PEL Markup support	The following commands opens the Emacs customization group related to configure Emacs support for the specific markup language. • The <f11> SPC key prefixes are available globally (for all buffers). • The <f12> <f3> key is only available when point is in a buffer for one of the languages supported by PEL and open the Emacs customization group for the markup language for the current buffer. 👉 When you use the <f11> SPC prefix, you can customize the Emacs language library support that might not even be loaded: PEL will detect if the corresponding library is loaded and will prompt you asking if you want to load it first, allowing Emacs to open the customization buffer.		
<u>M</u> J Graphviz Dot	<f11> SPC M-g <f3>	Customize Emacs Graphviz-Dot support. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>M</u> J PlantUML	• <f11> D u <f3> • <f11> SPC M-u <f3>	Customize Emacs PlantUML support. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>M</u> J Markdown	<f11> SPC M-m <f3>	Customize Markdown and markdown extension package support. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		
<u>M</u> J Outline/Org-Mode	<f11> SPC M-o <f3>	Customize Org Mode external packages support: • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
<u>M</u> J reStructuredText	<f11> SPC M-r <f3>	Customize Emacs reStructuredText support. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3>		