## Emacs support for Haskell

Description	<u>Keystroke</u>	Function	Note
Haskell Editing See: Haskell Mode Manual	Emacs does not provide any built-in mode for Haskell.  The <a href="haskell-mode">haskell-mode</a> external package is required. PEL installs and activates it when the <a href="pel-use-haskell">pel-use-haskell</a> and the <a href="pel-use-haskell">pel-use-haskell</a> mode user-options are both turned on. When <a href="pel-use-haskell">pel-use-haskell</a> is turned on the <a href="pel-use-haskell">f11&gt;</a> SPC h prefix is made available.  In a Haskell buffer these commands are accessible via the <a href="pel-use-haskell">f12&gt;</a> key. It also activates the ability to activate minor modes for the haskell major mode through the PEL <a href="pel-use-haskell-activates-minor-modes">pel-use-haskell</a> and the <a href="pel-use-haskell">pel-use-haskell</a> and the <a href="pel-use-haskell">pel-use-haskell</a> and the <a href="pel-use-haskell">pel-use-haskell</a> and the <a href="pel-use-haskell">pel-use-haskell</a> major mode through the PEL <a href="pel-use-haskell">pel-use-haskell</a> activates minor modes user-option.  PEL support for Haskell is not complete. More commands should be provided and documented. Haskell support is preliminary.		
Open this PDF file. See also: <u>Nation Help/</u> Info	<f11> SPC h <f1></f1></f11>	( <b>pel-help-pdf</b> &optional OPEN-WEB-PAGE)	Open the <u>\$\mathbb{N}\tau\$ - Haskell</u> local PDF. If the prefix argument (like <b>C-u</b> or <b>M</b> ) is used, then it opens the remote GitHub hosted raw PDF instead. If the <b>pel-flip-help-pdf-arg</b> user-option is set it's the other way around.
	<f12> <f1></f1></f12>		
∑ Customize PEL   Haskell support	<f11> SPC h <f2></f2></f11>	(pel-customize-pel &optional OTHER-WINDOW)	Customize PEL Haskell support.  • If OTHER-WINDOW is non-nil (use <b>C-u</b> ), display in another window.
	<f12> <f2></f2></f12>		
∑ Customize Emacs Haskell support	<f11> SPC h <f3></f3></f11>	(pel-customize-library &optional OTHER-WINDOW)	Customize Emacs Haskell support: haskell  • If OTHER-WINDOW is non-nil (use <b>c</b> - <b>u</b> ), display in another window.
	<f12> <f3></f3></f12>		
Comments			
Toggle display of comments in buffer or active region See also: ∑ Comments	<f11> ; ;</f11>	(hide/show-comments-toggle &optional START END)	Toggle hiding/showing of comments in the active region or whole buffer.  • If the region is active then toggle in the region. Otherwise, in the whole buffer.  □ This requires the <a href="hide-comnt.el">hide-comnt.el</a> package (see <a href="package">Comments</a> ). <a href="#package">PEL activates it when the pel-use-hide-comnt user option is t.</a>

## Emacs & Haskell — References

Document	Notes