


# Perl 5

<b>See also:</b> <ul style="list-style-type: none"> <li><a href="#">Perl - Perl</a></li> <li><a href="#">Perl @ Wikipedia</a></li> <li><a href="#">perl.org</a></li> <li><a href="#">PerlMonks.org</a></li> <li><a href="#">O'Reilly Books</a></li> <li><a href="#">Perl mailing lists</a></li> </ul>	<ul style="list-style-type: none"> <li>Perl Intro - a quick introduction to Perl. <a href="#">PerlCheat</a> , <a href="#">Learn Perl in Y minutes</a>, or in 2 hours 30 minutes</li> <li>Online Perl books and <i>tutorials</i> : <a href="#">Beginning Perl</a> , <a href="#">Modern Perl (html)</a> , <a href="#">Perl Maven Tutorial</a></li> <li>Perl Cookbook <a href="#">♫</a> (PLEAC Perl: <i>list of Perl code solutions</i>)</li> <li><a href="#">Learning Perl</a> <a href="#">LP♫</a>, <a href="#">Intermediate Perl</a> <a href="#">♫</a> , <a href="#">Mastering Perl</a> <a href="#">♫</a> , <a href="#">Effective Perl Programming</a> <a href="#">♫</a></li> </ul> Other exist but are <a href="#">not recommended</a> for various reasons.	<a href="#">perl</a> , <a href="#">Perl command line options</a> , <a href="#">perlrun</a> , <a href="#">perlvp</a> , <a href="#">perldoc</a> , <a href="#">perlbug</a> / <a href="#">perthanks</a> <a href="#">perisec</a>	<ul style="list-style-type: none"> <li><a href="#">Online Perl Interpreter</a> <a href="#">perl-live-coding</a> out/in <a href="#">Emacs</a></li> <li><a href="#">Online PerlTidy</a> option info.</li> </ul>
Perl Guidelines and tools	<b>Perl Style Guide, 10 Essential Development Practices.</b> <ul style="list-style-type: none"> <li>Books: <a href="#">Perl Best Practices</a> <a href="#">♫</a>, <a href="#">Modern Perl Best Practices (course)</a> <a href="#">♫</a></li> <li><a href="#">perlcritic</a> script uses <a href="#">Perl::Critic</a> to scan Perl code. The <a href="#">pel-perl-critic</a> command invokes it to check code in buffer.</li> <li>The <a href="#">perltidy</a> application reformats Perl code. <a href="#">Older perltidy home page</a>. <a href="#">PerlTidy @ Wikipedia</a>, <a href="#">PBP recommended .perltidyrc</a></li> </ul>		
<b>perldoc browser</b> <ul style="list-style-type: none"> <li>In Emacs: <a href="#">C-c C-h F</a></li> </ul>	<ul style="list-style-type: none"> <li><a href="#">perldoc</a> : about perldoc itself</li> <li><a href="#">perltoc</a> : table of content: names of all pages</li> <li><a href="#">perlsyn</a> : Perl syntax</li> <li><a href="#">perlfunc</a> : Perl built-in functions</li> </ul>	 Use perldoc to find if a Perl module is installed, as in: <a href="#">perldoc local::lib</a> <ul style="list-style-type: none"> <li><a href="#">perldoc local::lib</a> prints the documentation of <a href="#">local::lib</a> if it is installed.</li> <li><a href="#">perl -mlocal::lib</a> is useful to get modules installed in your home directory <a href="#">♫</a></li> </ul>	
<b>CPAN (@ Wikipedia)</b> <ul style="list-style-type: none"> <li><a href="#">Search CPAN — meta::cpan</a></li> </ul>	<ul style="list-style-type: none"> <li><a href="#">The Zen of Comprehensive Archive Networks</a></li> <li><a href="#">PAUSE - Perl Authors Upload Server</a></li> <li><a href="#">Installing Local Perl Modules with CPAN</a></li> </ul>	<b>Command line tools</b> interacting with CPAN to install Perl modules <a href="#">♫</a> : (see also <a href="#">this StackOverflow Q/A</a> ): <ul style="list-style-type: none"> <li><a href="#">cpan</a>: (<a href="#">requires config</a>, but has defaults). Use <a href="#">local::lib</a>; cpan will be able to install into your ~/perl5 tree.                             <ul style="list-style-type: none"> <li>Type <a href="#">cpan</a> to open the cpan shell, then type <a href="#">install The::Module</a> to install packages.</li> </ul> </li> <li><a href="#">cpanplus</a>, or cpanminus : <a href="#">cpanm</a> :(<a href="#">no config required</a>). <a href="#">cpanm</a>: <a href="#">cpanm -S The::Module</a></li> </ul>	

## Perl scripts

Writing Perl scripts	Impose strictures in Perl files to prevent errors by adding one of the following use lines. Also see the <a href="#">strictures package</a> .		
Use the following at the beginning of Perl script files.  <a href="#">perldiag @ perldoc</a>	<pre>#!/usr/bin/env perl use strict; use warnings;  # for testing only: use diagnostics;</pre>	<pre>#!/usr/bin/perl -w use v5.12; # loads strict ... use v5.35; # &amp;loads warnings  ! use diagnostics produces more info but increases startup time.</pre> <p>Alternative: <code>perl -Mdiagnostics</code> . Emacs <a href="#">pel-perl-critic</a> command can report diagnostic.</p>	<p>Executable Perl script should have a valid <a href="#">shebang line</a> identifying the <a href="#">appropriate location</a> of the Perl interpreter. <a href="#">It may have to be modified at installation time</a> (OpenGroup/SUS).</p> <p>! It's best to: <a href="#">use warnings</a>; <a href="#">perl -w</a> generates warning for all Perl code in the program including modules used by the program. Also use the <a href="#">-c</a> option to check syntax. But most Perl code should also activate the strict Perl rules and warnings to detect warnings. See: <a href="#">Barewords in Perl</a></p>
<a href="#">use version/features</a>	<pre>use v5.36;</pre>	<p>This can be used to enable both the strict and warning pramas as well as several <a href="#">named features</a>.</p> <ul style="list-style-type: none"><li>• See the <a href="#">table listing the feature bundles per Perl versions</a>.</li></ul>	

## Perl 5 Operators

<div>Perl 5 Operators</div> <div>Note:</div>		Perl has a large number of operators, listed below with their <b>precedence and associativity</b> . <ul style="list-style-type: none"><li><a href="#">C Operators missing from Perl</a> : unary &amp;, unary * and (type)</li><li><a href="#">Quote and Quote-like operators</a> : in Perl quotes are operators and they provide various kind of interpolating and pattern matching capabilities.</li></ul>			
<div>Associativity: one of:</div> <ul style="list-style-type: none"><li>right</li><li>left</li><li>NA : not associative: cannot use more than one of these operators in sequence.</li><li>CH: chained</li></ul> <div>To get this information, use:</div> <div>perldoc perlop</div> <div>Note: ♫ The Bitwise String Operators are :</div> <div><div>~. &amp;.  . ^.</div><div>&amp;.=  .= ^.=</div></div>	left	<b><u>terms and list operators (leftward)</u></b>	( )		
	left	<b><u>Arrow Operator:</u></b>	->		
	NA	<b><u>Auto-increment and Auto-decrement:</u></b>	++ --		
	right	<b><u>Exponentiation:</u></b>	**		
	right	<b><u>Symbolic Unary Operators:</u></b>	! ~ -. \ and unary + and -		<b>Note:</b> The operator \ <a href="#">creates a reference</a> . See <a href="#">example</a> .
	left	<b><u>Binding operators:</u></b>	== !=		
	left	<b><u>Multiplicative Operators:</u></b>	* / % x		
	left	<b><u>Additive Operators:</u></b>	+ - .		
	left	<b><u>Shift Operators:</u></b>	<< >>		
	NA	<b><u>named unary operators</u></b>			
NA	<b><u>Class instance Operator:</u></b>	isa			
CH	<b><u>Relational Operators:</u></b>	as numbers: < > <= >= as strings: lt gt le ge			
CH/NA	<b><u>Equality Operators:</u></b>	as numbers: == != <=> as strings: eq ne cmp ==			
left.	<b><u>Bitwise And:</u></b>	& &.			
left	<b><u>Bitwise Or and Exclusive Or:</u></b>	. ^ ^.			
left	<b><u>C-style Logical And:</u></b>	&&			
left	<b><u>Logical Defined-Or:</u></b>	^^ //			
NA	<b><u>Range Operators:</u></b>	.. ...			
right	<b><u>Conditional Operator:</u></b>	?:			
right	<b><u>Assignment Operators:</u></b>	=			
		<div>**= += *= &amp;= &amp;.= &lt;&lt;= &amp;&amp;=</div> <div>-= /=  =  .= &gt;&gt;=   =</div> <div>.= ^= ^.= //.=</div> <div>x=</div> <div>goto last next redo dump</div>			
left	<b><u>Comma, fat-comma Operators:</u></b>	, =>			
NA	<b><u>list operators (rightward)</u></b>				
right	<b><u>Logical Not:</u></b>	not			
left	<b><u>Logical And:</u></b>	and			
left	<b><u>Logical or and Exclusive or:</u></b>	or xor			

<div>trick operators ⚠</div> <div>Do not use in production code!</div> <div>But understanding how these work does help understand Perl.</div> <div>These are not real Perl operators; they are concatenation of other operators that achieve a specific effect.</div>	<div>-+-</div> <div>0+</div>	Converts a string that starts with digits into a number.	<div>print -+- '22les poulets!';</div> <div># prints 22</div>	-+- is essentially - + - or - - but a + to allow placing them together. The 0+ does the same as -+-, but the second has higher precedence.
	<div>=()</div>	Called the 'goatse' operator. It causes the right side expression to be evaluated in array context. Used to assign the array/list size to a scalar.	<div>my \$str = "A 22 before 33 does not make 9, it is 44!";</div> <div>my \$digit_count =()= \$str =~ /\d/g;</div> <div>print "\$digit_count";</div> <div># prints '7',the number of digits in \$str</div>	
	<div>@{[]}</div>	Interpolate an array in a string: <div>@{[something]}</div> is the same as: <div>join \$", something</div>	<div>print "these people @{{get_names()}} get promoted"</div>	
	<div>--</div>	Force scalar context.	In scalar context <a href="#">localtime</a> returns human readable time, but in list context it returns a 9-tuple with date elements.	<div>\$ perl -le 'print ~~localtime'</div> <div>Mon Nov 30 09:06:13 2009</div>

<div>Truth and falsehood</div> <div>⚠ Remember that the strings '0' and " " mean false. The output of glob() may return a file named '0' !</div> <div>⚠ a bareword false has a truth value of true!!!!</div>	<div>False in a boolean context:</div> <ul style="list-style-type: none"><li>the number 0,</li><li>the strings '0' and ' ' ,</li><li>the empty list ( ) ,</li><li>"undef"</li></ul> <div>All other values are true.</div>	<div>Negation of a true value by "!" or "not" returns a special false value.</div> <div>When evaluated as a string it is treated as "", but as a number, it is treated as 0.</div>	<div>So the following scalar values are considered false:</div> <ul style="list-style-type: none"><li>undef - the undefined value</li><li>0 the number 0, even if you write it as 000 or 0.0</li><li>" the empty string.</li><li>'0', a <b>single</b> 0 in the string.</li></ul>	<div>All other scalar values, including the following are true:</div> <ul style="list-style-type: none"><li>1 any non-0 number</li><li>' ' the string with a space in it</li><li>'00' two or more 0 characters in a string</li><li>"0\n" a 0 followed by a newline</li><li>'true'</li><li>'false'. <b>Even the string 'false' evaluates to true.</b></li></ul>
	<div>💡 One way to define valid true and false constant symbols that can be used in assignments (but see ♫):</div>			<div>use constant { true =&gt; 1, false =&gt; 0 };</div>

<div>File test operators</div> <div>See <a href="#">filetest -X</a></div>	<div>File tests can be <a href="#">stacked</a> (-r -w -e \$fname) or combined as in the following example ♫:</div> <div>💡 Notice the underscore in the example: it's the <a href="#">virtual filehandle</a> _ accessing the last <a href="#">stat</a> or <a href="#">lstat</a> result :</div>			<div>if (-e \$fname &amp;&amp; -f _ &amp;&amp; -r _ ) {</div> <div>print("\$fname exists, is readable\n"); }</div>
---	---	--	--	--

<div>The operators check if the file...</div> <div>See also:</div> <ul style="list-style-type: none"><li>File Tests ♫</li><li>File test operators @ perl tutorial</li></ul> <div>See also:</div> <ul style="list-style-type: none"><li>localtime</li><li>File::stat</li><li>IO::Interactive</li></ul>	<div>-r</div> <div>-w</div> <div>-x</div> <div>-o</div> <div>-R</div> <div>-W</div> <div>-X</div> <div>-O</div> <div>-M</div>	<div>is readable by effective uid/gid</div> <div>is writable by effective uid/gid</div> <div>is executable by effective uid/gid</div> <div>is owned by effective uid</div> <div>is readable by real uid/gid</div> <div>is writable by real uid/gid</div> <div>is executable by real uid/gid</div> <div>file is owned by real uid.</div> <div>Days between start time and file modification time</div>	<div>-e</div> <div>-z</div> <div>-s</div> <div>-f</div> <div>-d</div> <div>-l</div> <div>-p</div> <div>-S</div> <div>-A</div>	<div>exists.</div> <div>is empty.</div> <div>has nonzero size (returns size in bytes).</div> <div>is a plain file.</div> <div>is a directory.</div> <div>is a symbolic link.</div> <div>is a named pipe (FIFO) or Filehandle is a pipe.</div> <div>is a socket.</div> <div>Days between start time and file access time</div>	<div>-b</div> <div>-c</div> <div>-t</div> <div>-u</div> <div>-g</div> <div>-k</div> <div>-T</div> <div>-B</div> <div>-C</div>	<div>is a block special file.</div> <div>is a character special file.</div> <div>handle is opened to a tty.</div> <div>has setuid bit set.</div> <div>has setgid bit set.</div> <div>has sticky bit set.</div> <div>is an ASCII text file (heuristic guess).</div> <div>is a “binary” file (opposite of -T).</div> <div>Days between start time and node change time (in Unix).</div>
---	---	---	---	---	---	---


Perl 5 Constants and Variables

Perl Constants					<ul style="list-style-type: none"><li>Perl pragma to declare constants. ⚠️ But be aware that these are still not read-only, that they inject sub-routines and have several limitations. Read the doc!!</li><li>CPAN modules for defining constants by Neil Bowers . Of particular interest: <b>Const::Fast</b> and <b>Attribute::Constant</b> for efficient read-only constants.</li></ul>
Perl Variables Names		Scalar Naming Conventions		Array Naming Conventions	All: underscore or letter of the first character.
Case is significant in all names. ASCII by default, <b>UTF-8</b> if the <b>utf8 pragma</b> is used.	<ul style="list-style-type: none"><li>Local variables:</li><li>Global variables:</li><li>Constants:</li><li>All variables:</li></ul>	Slowercase \$Title_Case \$UPPER_CASE words separated by underscores.	Similar conventions, except that array names should be <b>plural</b> . <ul style="list-style-type: none"><li>@locals</li><li>@Global_Arrays</li><li>@CONSTANT_ARRAYS</li></ul>	<ul style="list-style-type: none"><li>Module names are MixedCaseNoUnderscores</li><li>Constants are UPPERCASE_WITH_UNDERSCORES</li><li>Package wide vars are Mixed_Case_With_Underscores</li><li>Functions/methods are lowercase_with_underscores</li><li>Avoid ALLUPPERCASE: used by Perl special variables.</li></ul>	
Perl types	Sigil	Examples	Meaning	Extra Info	
Scalar	\$	\$foo \$days[28] \$days{'Feb'} \${days} \$Dog::days \$Dog'days #\$days \$days->[28] \$days[0][2] \$d{99}{'Feb'} \$d{99, 'Feb'}	Simple scalar value 29 <sup>th</sup> element of array @days Value associated with the <i>Feb</i> key of hash %days Same as \$days, but unambiguous before alphanumerics. Useful inside strings <a href="#">for interpolation of variables followed by other letters</a> . The \$days variable inside the Dog package. Same as above. However this is an archaic use of the single quote. Last index of array @days. 29 <sup>th</sup> element of array pointed to by reference \$days. Multi-dimensional array Multi-dimensional hash Multi-dimensional hash emulation		
list and Array <ul style="list-style-type: none"><li>0-based indexed (first index is 0).</li><li>Last index of array @name is \$#name</li></ul>	@	@days @days[3,4,5] @days[3..5]	Array containing ( <code>\$days[0]</code> , <code>\$days[1]</code> , ... <code>#days[\$#days]</code> ) . Array slice containing ( <code>\$days[3]</code> , <code>\$days[4]</code> , <code>\$days[5]</code> ) . Array slice containing ( <code>\$days[3]</code> , <code>\$days[4]</code> , <code>\$days[5]</code> ) .	<ul style="list-style-type: none"><li>A <i>list</i> is an ordered collection of scalars (of any type).</li><li>An <i>array</i> is a variable that contains a list.</li><li>Reading beyond the end of array returns <b>undef</b></li></ul>	
	<ul style="list-style-type: none"><li>Negative indices used in read access from the end: -1 is last item.</li><li>Use these negative indices to access from the end. <b>Do not compute index with \$#name -3, if the list size is 2, this will give invalid results.</b></li></ul>				
<ul style="list-style-type: none"><li><b>slices</b></li></ul>	<ul style="list-style-type: none"><li>Use a slice to select multiple elements from a list, array, or hash.</li><li>Don't use a slice when you know you need exactly one element.</li></ul>		<ul style="list-style-type: none"><li>An lvalue slice imposes list context on the righthand side.</li></ul>		
<ul style="list-style-type: none"><li><b>Anonymous arrays</b></li></ul>	<ul style="list-style-type: none"><li><a href="#">What are the advantages of anonymous array? @ StackOverflow</a></li><li><a href="#">Perlfref @ Perldoc</a>, <a href="#">Perl reference tutorial @ Perldoc</a></li></ul>		<ul style="list-style-type: none"><li>Anonymous array := a type of array reference.</li><li>Array reference allows Perl to treat the array as a single item.<ul style="list-style-type: none"><li>This can be used to build, nested data structures.</li></ul></li></ul>		
Hash/associative array	%	%days	Associative array (hash): keys-value pairs. Can be initialized as: <ul style="list-style-type: none"><li><code>%days = (Jan =&gt; 31, Feb =&gt; \$leap? 29 : 28, ...)</code></li><li><code>%days = ("Jan", 31, 'Feb', \$leap? 29 : 28, ... )</code></li></ul>	Initialize a hash slice with array context: <code>@char_to_num{'A' .. 'Z'} = 1 .. 26;</code>	
		@days{'J','F'}	Hash slice containing ( <code>\$days{'J'}</code> , <code>\$days{'F'}</code> ) .		
Subroutine	&	&foo	& is needed to create reference to subroutine.		
Typeglob	*	*foo	See: <a href="#">Advanced Perl Programming</a> , 1st Edition <a href="#">Section 3.2</a>		
7 kinds of package variables or variable-like elements in Perl:	1. scalar variables 2. array variables 3. hash variables		4. subroutine name 5. <b>format</b> names <ul style="list-style-type: none"><li><a href="#">how to format output in Perl?</a>, <a href="#">Perl-Formats</a></li><li>See <a href="#">write</a> and <a href="#">select</a></li></ul>	6. file handles 7. directory handles	
Scalar values			Numeric literals examples. Note: leading 0 work only for literals, not for string-to-number conversions.		Useful related <b>builtin functions</b>
<ul style="list-style-type: none"><li><b>numeric:</b></li></ul>	<ul style="list-style-type: none"><li>integer : using the system's native format.<ul style="list-style-type: none"><li><a href="#">bigint</a> - transparent big integer support.</li><li><a href="#">bignum</a> - transparent big number support.</li></ul></li><li>floating-point : using the system's native format.<ul style="list-style-type: none"><li><a href="#">bigrat</a> - transparent big rational number support.</li></ul></li></ul> <div>A variable holding an integer can be converted to floating-point if the operation done to it requires it (such as dividing 1 by 2).</div>		<div>my \$x = 12345;</div> <div>my \$x = 12345.67;</div> <div>my \$x = 6.02e23;</div> <div>my \$x = 0x1f.0p3;</div> <div>my \$x = 4_294_967_296;</div> <div>my \$x = 0x1234_5678;</div> <div>my \$x = 0377;</div> <div>my \$x = 0o377;</div> <div>my \$x = 0xffff;</div> <div>my \$x = 0b1100_0010;</div> <div># integer</div> <div># floating point</div> <div># scientific notation</div> <div># power<sup>2</sup> exponent: <i>Perl &gt;= v5.22</i></div> <div># underline for legibility</div> <div># underline in hex is also OK</div> <div># octal</div> <div># octal also <i>Perl &gt;= v5.34</i></div> <div># hexadecimal</div> <div># binary</div>		<ul style="list-style-type: none"><li><a href="#">oct</a> - supports binary, octal, hex</li><li><a href="#">hex</a></li><li><a href="#">POSIX::ceil</a></li><li><a href="#">POSIX::floor</a></li><li><a href="#">abs</a></li></ul>
<ul style="list-style-type: none"><li><b>string</b></li></ul>	<ul style="list-style-type: none"><li>double-quoted strings: perform backslash and variable interpolation of expression that begin with <b>\$</b> (a scalar) or <b>@</b> (an array). <b>Hashes cannot be interpolated.</b></li><li>single-quote strings: only perform <code>\'</code> and <code>\\</code> substitution (to <code>'</code> and <code>\</code> respectively), nothing else.</li><li>Single quote and double quote strings can spread multiple lines: it embeds the newline character on each new line.</li><li>But <code>\n</code> is only expanded in double quoted strings! In single quote string it is treated as two characters; no substitution is done (as explained above).</li></ul>				
<ul style="list-style-type: none"><li><a href="#">Unicode support</a></li></ul>	To use Unicode literally in a program, add the <b>utf8 pragma</b> : <code>use utf8;</code> <div>See: <a href="#">Perl Unicode Tutorial</a>, <a href="#">Perl Unicode Introduction</a>, <a href="#">Perl Unicode Support</a> @ perldoc</div>				
<ul style="list-style-type: none"><li><a href="#">Quote constructs</a></li></ul>	Customary	Generic	Meaning	Interpolates?	Notes
See: <ul style="list-style-type: none"><li><a href="#">Strings in Perl: quoted, interpolated and escaped</a></li></ul>	<code>''</code>	<code>q//</code>	Literal string	No	<ul style="list-style-type: none"><li>Not all characters can be used as the <code>/</code> separator. <code>{ }</code>, <code>( )</code> and <code>&lt; &gt;</code> can also be used.</li><li>You can use whitespace between the quote specifier and its initial bracketing character:<div><pre>my \$chuck_of_code = q {     if (\$condition) {         print "Salut!";     } };</pre></div></li></ul>
	<code>"""</code>	<code>qq//</code>	Literal string	Yes	
	<code>``</code>	<code>qx//</code>	Command execution	Yes	
	<code>()</code>	<code>qw//</code>	World list	No	
	<code>//</code>	<code>m//</code>	Pattern match	Yes	
	<code>s///</code>	<code>s///</code>	Pattern substitution	Yes	
	<code>tr///</code>	<code>y///</code>	Character translation	No	
	<code>""</code>	<code>qr//</code>	Regular expression	Yes	
<ul style="list-style-type: none"><li><b>Character escapes</b> (only inside double quoted strings)</li></ul>	<code>\a</code>	Alert (bell)	<code>\e</code>	ESC character	Any Unicode code point, by name:  <code>\N{LATIN SMALL LETTER E WITH ACUTE}</code> é <code>\N{ U+E9 }</code> é
	<code>\b</code>	Backspace	<code>\033</code>	ESC in octal	
<code>\e</code>	ESC character	<code>\o{33}</code>	ESC in octal		
<code>\f</code>	Form feed	<code>\x7f</code>	DEL in hexadecimal		
<code>\n</code>	Newline (usually LF)	<code>\x{263a}</code>	Character number 0x263A		
<code>\r</code>	Carriage return (Usually CR)	<code>\cC</code>	Control-C		
<ul style="list-style-type: none"><li><b>translation escapes</b> (inside <b>double quoted</b> strings)</li></ul>	<code>\u</code>	Force next character to titlecase	<code>\U</code>	Force all following characters to uppercase. Ends at <code>\E</code>	<code>\E</code> Ends <code>\U</code> , <code>\L</code> , <code>\F</code> or <code>\Q</code>
	<code>\l</code>	Force next character to lowercase	<code>\L</code>	Force all following characters to lowercase. Ends at <code>\E</code>	
			<code>\F</code>	Force all following characters to Unicode fold case. Ends at <code>\E</code>	
			<code>\Q</code>	Backslash all following non alphanumeric characters. Ends at <code>\E</code>	
<ul style="list-style-type: none"><li><a href="#">bareword</a></li></ul>	In Perl, a <i>bareword</i> refers to a sequence of characters suitable for an identifier. It's not quoted. By default Perl allows barewords to behave like strings. <ul style="list-style-type: none"><li>This is not allowed when any of <b>use strict</b>; or <b>use strict "subs"</b>; or <b>use v5.12</b>; is specified.</li></ul>				
<ul style="list-style-type: none"><li><a href="#">Here documents</a></li><li><a href="#">Here docs @ Perl maven</a></li><li><a href="#">Perl here doc @Wikipedia</a></li></ul>	Perl here-documents are a form of line oriented quoting. There are several forms of here documents, where the identifier (like <b>EOF</b> used below, but can be any word) must be placed at the beginning of the terminating line: <ul style="list-style-type: none"><li>Default : <code>&lt;&lt;EOF;</code> Supports variable interpolation.</li><li>Double quotes: <code>&lt;&lt;"EOF"</code>; Supports variable interpolation. Can also be written with whitespace as in <code>&lt;&lt; "EOF"</code>;</li><li>Single quotes: <code>&lt;&lt;'EOF'</code>; Does not support interpolation. Can also be written with whitespace as in <code>&lt;&lt; 'EOF'</code>;</li><li>backticks: <code>&lt;&lt;`EOF`;</code> Execute commands in a shell and return text printed on stdout. Can also be written with whitespace as in <code>&lt;&lt; `EOF`;</code></li><li>indented: <code>&lt;&lt;~EOF;</code> Allows indenting the here-doc string. Can also use the <code>~</code> with the other forms: <code>&lt;&lt;~\EOF</code>, <code>&lt;&lt;~"EOF"</code>, <code>&lt;&lt;~"EOF"</code>, <code>&lt;&lt;~`EOF`</code></li><li>They can also be stacked and text can be transformed. See the documentation.</li></ul>				
<ul style="list-style-type: none"><li><a href="#">Perl Regexp</a> info, cheatsheets &amp; regexp testers</li></ul>	<ul style="list-style-type: none"><li><a href="#">Regexp Tutorial</a></li><li><a href="#">Learn PCRE in X minutes</a></li></ul>		<ul style="list-style-type: none"><li><a href="#">PCRE cheatsheet</a></li></ul>		<ul style="list-style-type: none"><li><a href="#">Debuggex</a> regexp tester</li><li><a href="#">regex101</a></li><li><a href="#">RegEx Pal</a></li></ul>




Current value of warning switch	<ul style="list-style-type: none"><li>• \$WARNING</li><li>• \$^W</li></ul>		Current set of warning checks enabled by the use warnings pragma	\$^{^WARNING_BITS}	
<ul style="list-style-type: none"><li>• <a href="#">Variables related to the interpreter state</a></li></ul>	These variables provide information about the current interpreter state.				
Flag associated with the -c switch	<ul style="list-style-type: none"><li>• \$COMPILING</li><li>• \$^C</li></ul>		The current value of the debugging flags	<ul style="list-style-type: none"><li>• \$DEBUGGING</li><li>• \$^D</li></ul>	
Current phase of the perl interpreter	\${^GLOBAL_PHASE}		Debugging support. Internal variable.	<ul style="list-style-type: none"><li>• \$PERLDB</li><li>• \$^P</li></ul>	
Compile-time hints for the perl interpreter. Internal use only	\$^H		Values of compiled statements	%^H	
Taint mode	\${^TAINT}		Safe locale operations availability	\${^SAFE_LOCALES}	
Input/Output Layers. Internal use by PerlIO only.	\${^OPEN}		Unicode Settings of Perl	\${^UNICODE}	
Internal UTF-8 offset caching code state	\${^UTF8CACHE}		State of UTF-8 locale detected by perl at startup.	\${^UTF8LOCALE}	
<ul style="list-style-type: none"><li>• <a href="#">File handle Variables</a></li></ul>	See also: <a href="#">Perl File Handles</a> <span style="float:right">The following variables are used in the Input/Output handling as well as program arguments.</span>				
Name of current file read from <>	\$ARGV	Command line arguments of the script ← See <a href="#">diamond operator</a> <>. →	@ARGV	Number of arguments minus one	\$#ARGV
Special file handle that iterates over command-line filenames in @ARGV	ARGV	Special file handle that points to currently open output file when doing edit-in-place processing	ARGVOUT		
Output field separator for the print operator	<ul style="list-style-type: none"><li>• IO::Handle-&gt;output_field_separator( EXPR )</li><li>• \$OUTPUT_FIELD_SEPARATOR</li><li>• \$OFS</li><li>• \$,</li></ul>		Current line number for the last file handled accessed	<ul style="list-style-type: none"><li>• HANDLE-&gt;input_line_number( EXPR )</li><li>• \$INPUT_LINE_NUMBER</li><li>• \$NR</li><li>• \$.</li></ul>	
Input record separator (newline by default)	<ul style="list-style-type: none"><li>• IO::Handle-&gt;input_record_separator( EXPR )</li><li>• \$INPUT_RECORD_SEPARATOR</li><li>• \$RS</li><li>• \$/</li></ul>		Output record separator	<ul style="list-style-type: none"><li>• IO::Handle-&gt;output_record_separator( EXPR )</li><li>• \$OUTPUT_RECORD_SEPARATOR</li><li>• \$ORS</li><li>• \$\</li></ul>	
<a href="#">Auto-flush control</a> <ul style="list-style-type: none"><li>• <a href="#">order of output @ Perl Maven</a></li><li>• <a href="#">Suffering from Buffering?</a></li></ul>	<ul style="list-style-type: none"><li>• HANDLE-&gt;autoflush( EXPR )</li><li>• \$OUTPUT_AUTOFLUSH</li><li>• \$!</li></ul>	Perl activates file buffering by default. Assign 1 to <a href="#">\$!</a> to activate auto-flush.	Last read file handle	\${^LAST_FH}	

## Perl 5 Input/Output 🚧

References	<ul style="list-style-type: none"><li>• open @ perldoc browser</li><li>• Writing to files with Perl @ Perl Maven</li><li>• open file in-memory @ stackOverflow</li><li>• Stupid open() tricks @Perl.com:<ul style="list-style-type: none"><li>• No explicit filename</li><li>• create an anonymous temporary file</li></ul></li><li>• print to a string</li><li>• read lines from a string</li></ul>				
print, printf, sprintf	<a href="#">print</a> , <a href="#">printf</a> , <a href="#">sprintf</a> (which describes the format) . Note: <a href="#">print</a> is more efficient than <a href="#">printf</a> . print and printf output to stdout by default, but <a href="#">accept a file handle as the first argument if it is NOT followed by a separating comma!</a> (a <code>,</code> puts it in the list to print!)				
diamond operator <>	Both <> and <<>> operators read the content of files listed on the command line via @ARGV. Nothing or - on the command line identifies stdin. The <> operator supports shell redirection and pipe operations which <<>> does not allow (for security reasons).				
The double diamond, a more secure <> (Perl >= v5.22)	print <>;	← Simple implementation of /bin/cat	print <<>>;	← safer one	Redirection cannot be forced via file names embedding them with. the <<>> operator.
	print sort <>;	← Simple implementation of /bin/sort	print sort <<>>;	← safer one	
 In-place-editing ↔ The <> operator tries to duplicate the original file's permission and ownership.	Set \$^I to a backup file extension (such as Emacs "~" or ".bak") to change the behaviour of the <> and <<>> operators and print. In a while (<>) {...} loop, when \$^I is not undef (its default), Perl: <ul style="list-style-type: none"><li>• renames currently processed file with the specified extension added,</li><li>• opens a new file with the original name</li><li>• prints into the new file.</li><li>• Any modification goes into the new file: in-place-editing it!</li></ul>		<pre>use strict; \$I = "~"; # rename old file: add '~' to it's name (Emacs-style backup)  while (&lt;&gt;) {     s/something/Something else/; # perform any substitution     print; }</pre>		
perl -i cmdline option	It's also possible to do this on the command line!		For example:	<code>perl -p -i- -w -e 's/something/Something else/g' data*.dat</code>	
Special filehandle names	<a href="#">ARGV</a>	The special filehandle that iterates over command-line filenames in @ARGV. Usually written as the null filehandle in the angle operator <> (or <<>>)			
Also See: <ul style="list-style-type: none"><li>• <a href="#">File handle Variables</a> section above.</li></ul>	<a href="#">ARGVOUT</a>	The special filehandle that points to the currently open output file when doing edit-in-place processing with <u>i</u> . <ul style="list-style-type: none"><li>• Useful when you have to do a lot of inserting and don't want to keep modifying \$_<u></u></li></ul>			
	STDIN	<b>&lt;STDIN&gt;</b> : line input operator for the STDIN filehandle (for the <b>standard input</b> ). <ul style="list-style-type: none"><li>• Each time &lt;STDIN&gt; is used in scalar context, Perl reads 1 complete line of the standard input and uses it as the value of &lt;STDIN&gt;.<ul style="list-style-type: none"><li>• The string includes a line termination character. Use the <b>chomp()</b> built-in function to strip it off the variable.</li></ul></li><li>• If &lt;STDIN&gt; is read in list context, it returns <b>all lines inside a list!</b> For example, <b>foreach (&lt;STDIN&gt;) { ... }</b> reads the entire stdin in 1 step: \$_<u></u> holds it all!</li></ul>			
		<pre>while (&lt;STDIN&gt;) { # print all     print;      # lines of                 # stdin }</pre>	<pre>while (defined(\$_ = &lt;STDIN&gt;)) {     print \$_; }</pre>	The code in the left-most cell is the shortest form. It is equivalent to the code beside it; each line of stdin is stored in the default variable \$_ <u></u> and the loop stops on end at which time <STDIN> returns undef.	
	STDOUT	<b>standard output</b>			
	STDERR	<b>standard error</b> Note: generally STDERR is not buffered, while STDOUT is buffered by default. Text sent on STDERR may show up before STDOUT. <ul style="list-style-type: none"><li>• Print a new line on STDOUT to help flushing it or assign 1 to \$  to activate auto-flush.</li></ul>			
	DATA				
say	• <a href="#">say</a> use feature qw(say);    or    use v5.10;    (or higher). Like print, but implicitly appends a newline at the end of the list.				
open					



Perl 5 Statements ⚠️

<b>Loop control</b>	See <a href="#">perlsyn</a> for more information on Perl syntax which includes declarations, blocks, loops, labels, subroutines, etc...		
 Use the <b>last</b> and <b>redo</b> inside a naked block of code to control looping.		The <b>last</b> , <b>next</b> , and <b>redo</b> loop control keywords work in the following constructs: <ul style="list-style-type: none"><li><b>while</b> ( condition ) { ... }</li><li><b>until</b> ( condition ) { ... }</li><li><b>for</b> (init; condition; continue) { ... }</li><li><b>foreach</b> array { ... }</li><li>naked block: { ... }</li></ul>	Notes: <ul style="list-style-type: none"><li>The while and foreach loops may have a <b>continue block</b>: executed before evaluating condition again, which corresponds to the 3rd part of a for loop statement. See <a href="#">this @ stackOverflow</a>.</li><li>Blocks can be labelled <b>g</b> as targets to <b>last</b>, <b>next</b>, and <b>redo</b></li></ul>
	<b>loop control keywords:</b> <ul style="list-style-type: none"><li><b>last g</b>: exits the loop.</li><li><b>next g</b>: starts the next iteration of the loop.</li><li><b>redo g</b>: restarts the loop block without evaluating the condition again.</li></ul>		
<b>Statement modifiers</b>	<ul style="list-style-type: none"><li><b>if</b> EXPR</li><li><b>unless</b> EXPR</li><li><b>while</b> EXPR</li><li><b>until</b> EXPR</li><li><b>for</b> LIST</li><li><b>foreach</b> LIST</li><li><b>when</b> EXPR</li></ul>	The <b>for</b> and <b>foreach</b> statements <b>impose a list context</b> ; the complete list is processed. Therefore a loop like the following trying to stop on a line that has " __END__ " on it will <b>not work</b> since it reads all of STDIN: <pre>foreach (&lt;STDIN&gt;) {     last if ?__END__ /;     ...; }</pre>	The while statement <b>imposes a scalar context</b> ; it takes one line at a time from <STDIN> and the following code works properly: <pre>while (&lt;STDIN&gt;) {     last if /__END__ /;     ...; }</pre>
	<ul style="list-style-type: none"><li><b>do</b> block</li></ul>		
<b>Conditional statements</b>			

Perl 5 Subroutines ⚠️

Perl subroutines			
subroutine &	<ul style="list-style-type: none"><li>Why we teach the subroutine ampersand</li><li>Why should I use the &amp; to call a Perl subroutine? @ StackOverflow</li></ul>		Another point of view: <a href="#">Subroutines and Ampersands</a>
Subroutine Prototypes	An older Perl feature. Clashes with subroutine signatures as of Perl v5.20. In <i>Perl &gt;= v5.20</i> put the <b>:prototype</b> attribute before subroutine prototype parenthesis.		
Subroutine signatures <ul style="list-style-type: none"><li><i>Perl &gt;=5.36</i>: Stable</li><li><i>Perl &gt;= 5.20</i>: Experimental</li></ul> See: <a href="#">Use v5.20 subroutine signatures</a>	Exactly zero arguments	( )	Zero or 1 argument, no default, unnamed: (\$=)
	Zero or 1 argument, no default, named	(\$val=)	Zero or 1 argument, named, with default (\$val=1)
	exactly 1 named argument:	(\$val)	Exactly 2 arguments (\$v1, \$v2)
	2, 3 or 4 arguments no defaults:	(\$v1, \$v2, \$=, \$=)	2,3 or 4 arguments, 1 default: (\$v1, \$v2, \$v3='a', \$=)
	Two or more, any number of arguments.	(\$v1, \$v2, @)	Two or more arguments, remainders into a named array: (\$v1, \$v2, @rest)
	Two or more arguments: an even number	(\$v1, \$v2, %)	Two or more arguments, remainders into a named hash: (\$v1, \$v2, %rest)
	Class method	(\$class, ...)	Object method
Variables in subroutines	global by default		
	<a href="#">my</a>	local, lexical scope, non persistent	
	<a href="#">state</a>	Local, lexical scope, persistent <i>Perl &gt;= v5.10</i>	Restriction: in <i>Perl &lt; v5.28</i> : array and hashes state cannot be initialized in list context.
	<a href="#">our</a>	creates a lexical scoped alias to a package variable	
	<a href="#">local</a>	Localizes an existing package variable to the current scope. It's not a declaration. The variable previous value is restored when leaving the scope.	
Returned value	<ul style="list-style-type: none"><li>The result of the last evaluated expression is implicitly returned</li><li>The return operator can be used but it's not required unless used to change execution flow (return immediately from the subroutine).</li><li>The subroutine can return a scalar in scalar context or a list if called in list context.<ul style="list-style-type: none"><li>Inside the subroutine, use the <b>wantarray</b> function to determine the context of the subroutine call.</li></ul></li></ul>		

Perl 5 Built-in Functions ⚠️

Perl Functions Perl syntax	<p>👉 To get information about a Perl function from the command line use the <b>perldoc -f</b> command.</p> <ul style="list-style-type: none"><li>To get information about <b>print</b> use: <b>perldoc -f print</b></li></ul>		
⚠️ Cautionary notes			
<ul style="list-style-type: none"><li><b>each</b> keyword is broken</li><li>Use <b>Var::Pairs</b> instead.</li></ul>	<p>Do NOT use the built-in <b>each</b>. It is broken, as described by <a href="#">Damian Conway</a> in his <a href="#">Modern Perl Best Practice</a> O'Reilly course, section control structure.</p> <ul style="list-style-type: none"><li><b>each</b> is not re-entrant:<ul style="list-style-type: none"><li>nested loops of each over the same hash does not work as expected and will create infinite loop since the nested loop each juts iterates from where the first loop each left it.</li><li>Exiting the loop leaves the state of the each internal pointer at the current location.<ul style="list-style-type: none"><li>If you use each on the same hash later it will resume from where it left, it will not start form the beginning.</li></ul></li></ul></li></ul>		

Perl 5 Modules ⚠️

Perl Modules			
Perl core modules	<ul style="list-style-type: none"><li>How to detect where a module is installed : <a href="#">perldoc -l Module</a></li><li>How to check if a module is part of Perl core : <a href="#">corelist</a> Module (<i>Perl &gt;= v5.9.2</i>)</li></ul>		
Modules @perltutorial Modules Using simple modules ⚠️	<a href="#">do</a>	<p>Looks for the module file by searching the <b>@INC</b> path. Performed at run time (and therefore can be done conditionally).</p> <ul style="list-style-type: none"><li>If Perl finds the file, it places the code inside the calling program and executes it. Otherwise, Perl will skip the do statement silently.<p>👉 The "included" code does not have access to the lexical variables from the main program.</p></li><li>Skip the <b>@INC</b> path lookup if given a file path starting with <b>./</b>, <b>../</b>, or <b>/</b></li></ul>	
	<a href="#">require</a>	<p>Loads the module file once, also teaching the <b>@INC</b> path. Performed at run time (and therefore can be done conditionally).</p> <ul style="list-style-type: none"><li>If the <b>require</b> for the same file appears twice, Perl ignores it. Perl will issue an error message if it cannot find the file (as opposed to <b>do</b>)</li><li>Skip the <b>@INC</b> path lookup if given a file path starting with <b>./</b>, <b>../</b>, or <b>/</b></li></ul>	
The normal way to access Perl modules ➡	<a href="#">use</a>	<p>Similar to <b>require</b> except that Perl applies it before the program starts: it's done at compile time.</p> <ul style="list-style-type: none"><li>Therefore the <b>use</b> statement cannot be invoked inside conditional statements such as if-else. Used often to include a module in a program.</li></ul>	

Topic - Directory Operations 🚧

Directory Operations	In Books: <a href="#">LPo</a>		
Opening Files	All file open operations are relative to the <i>current working directory</i> (for relative file names)		<code>open my \$filehandle, '&lt;:utf8', 'a_relative/path.txt'</code>
Built-in Functions	Related Functions/Packages / Descriptions	Notes	
Getting file names by: <ul style="list-style-type: none"><li>Globber :<ul style="list-style-type: none"><li>with <b>glob</b></li></ul></li><li>with the glob operator <code>&lt;&gt;</code></li></ul>	<b>File::Glob</b> ( <i>Perl</i> >= <i>v5.6.0</i> ) - provides more control.	Example:	<code>my @all_files = glob '*';</code> <code>my @perl_files = glob '*.pm *.pl'; # 2 globs, space-separated</code>
	The <> operator is identifying: <ul style="list-style-type: none"><li>a <b>filehandle</b>, when: the item inside &lt;&gt; is a Perl identifier or an indirect file handle read scalar,</li><li>a <b>glob expression</b> otherwise.</li></ul>	Glob examples:	<code>my @all_files = &lt;'*&gt;;</code> <code>my @all_files = &lt;*&gt;; # 1 glob: no space, no need for string</code> <code>my @perl_files = &lt;'*.pm *.pl*&gt;; # 2 globs, space-separated</code>  <code>my \$etc_dir = '/etc';</code> <code>my @etc_dir_files = &lt;\$etc_dir/* \$etc_dir/.*&gt;;</code>  <code>my @files = &lt;LARRY/*&gt;; # a glob</code>
	See: <b>readline</b>	Filehandle examples:	<code>my @this_lines = &lt;LARRY&gt;; # a filehandle read</code>  <code>my \$name = 'LARRY';</code> <code>my @this_lines = &lt;\$name&gt;; # indirect filehandle read of LARRY handle</code> <code>my @same_lines = readline LARRY; # another way to write above</code> <code>my @same_lines = readline \$name;</code>
	<ul style="list-style-type: none"><li>with a directory handle <b>LPo</b></li></ul>	<ul style="list-style-type: none"><li><b>opendir</b> : open a directory: get a directory handle</li><li><b>readdir</b> : read the directory handle. <a href="#">But see this.</a></li><li><b>closedir</b> : close the directory handle.</li><li><b>DirHandle</b> (<i>&lt;= Perl 5.5</i>)</li><li><b>File::Spec::Functions</b> (<i>&gt;= Perl v5.5.4</i>)</li><li><b>Path::Class</b></li></ul>	Example: iterate explicitly over a list of file names extracted from the directory using these 3 functions.  <code>my \$dir = '/usr/bin';</code> <code>opendir my \$dh, \$dir or die "Failed opening \$dir: \$!";</code> <code>foreach \$file (readdir \$dh) {</code> <code>    print "File \$file is inside \$dir\n"; # ⚠ no path in name!</code> <code>}</code> <code>closedir \$dh;</code>
Removing files	<ul style="list-style-type: none"><li><b>unlink</b> a list or <code>\$_</code></li></ul>		<code>unlink 'file1.txt', 'file2.txt';</code> <code>unlink qw( file1.txt file2.txt);</code> <code>unlink glob 'file?.txt'</code>
Renaming files	<ul style="list-style-type: none"><li><b>rename</b> an old file name to a new one.<ul style="list-style-type: none"><li>The fat comma operator is sometimes used to highlight what is the old and the new name.</li></ul></li></ul>	As in here:	<code>rename 'old_name' , 'new_name';</code> <code>rename 'old_name' =&gt; 'new_name'; # using fat comma</code>
Changing permissions	<ul style="list-style-type: none"><li><b>chmod</b> changes file permissions</li></ul>		
Changing ownership	<ul style="list-style-type: none"><li><b>chown</b> changes file ownership</li></ul>		
Creating Hard link	<ul style="list-style-type: none"><li><b>link</b> to create a hard link</li></ul>		
Creating symbolic link	<ul style="list-style-type: none"><li><b>symlink</b> to create a symbolic link</li></ul>		
<b>chdir</b> Change current working directory	<ul style="list-style-type: none"><li><b>File::chdir</b></li><li><b>File::HomeDir</b></li></ul>	<ul style="list-style-type: none"><li>Change the current working directory.</li><li><b>chdir</b> without argument attempt to change to user home directory using the <code>\$ENV{HOME}</code> and <code>\$ENV{LOGDIR}</code> environment values <b>if</b> ⚠ they are set. The <b>File::HomeDir</b> module helps in setting them.</li><li>The built-in <b>chdir</b> is global ⚠ for the entire program. Use <b>File::chdir</b> facilities for localized operations.</li></ul>	
Modules	Functions <b>Legend:</b> Exported by default, exported on request, <i>Win32 specific</i>		Extra Information
<b>Cwd</b>	<ul style="list-style-type: none"><li><b>getcwd</b>, <b>cwd</b>, <b>fastcwd</b>, <b>fastgetcwd</b>, <b>getdcwd</b></li><li><b>abs_path</b>, <b>realpath</b>, <b>fast_abs_path</b></li></ul>		<code>use Cwd;</code> <code>my \$curdir = getcwd;</code> <code>print "cwd is \$curdir\n";</code>

PerlTidy formatting control 🚧

perltidy option	Option	Impact
indentation style	<ul style="list-style-type: none"><li>-bl,</li><li>--opening-brace-on-new-line</li><li>--brace-left</li></ul>	<ul style="list-style-type: none"><li>Without this option (the default) the code indentation style selected is <b>K&amp;R style</b>.</li><li>With this option, the indentation style is <b>Allman/BSD style</b>.</li></ul>