




































Dired — Directory Editor

Description	Keystroke	Function	Note
Dired (Directory Editor) <ul style="list-style-type: none"> Entering Dired Mode <ul style="list-style-type: none"> Dired Mode Commands <ul style="list-style-type: none"> Navigate in dired buffer <ul style="list-style-type: none"> Control visibility Searching for files Visit files Open info/man files Multi-Subdirectories Mark/flag files Unmark Undo, Change mark type Kill/Delete Create directory Copy, Rename files Compare files Grep & Replace Byte compile & load Compress/Uncompress Shell commands Modify file attributes Find hard/soft links OpenPGP <ul style="list-style-type: none"> WDired - editable dired Dired-narrow image-dired <p> Last updated on: 2025-03-14 </p>	<p>Dired is Emacs directory editor. You can open a Dired buffer by visiting a directory instead of a file. With it you can operate on the files of the directory and its sub-directories. See Dired manual, operating on files, other Dired features.</p> <p>See also: File mngt , Treemacs</p> <ul style="list-style-type: none"> Dired support is based on several Emacs Lisp files (called <i>libraries</i> in Emacs-speak). <ul style="list-style-type: none"> These are part of Emacs: <ul style="list-style-type: none"> <code>dired</code> : built-in, main functionality <code>dired-aux</code> : auxiliary features, less commonly used parts of dired <code>dired-x</code> : dired extra features.  PEL lazily loads it when pel-use-dired-x is set to t. <ul style="list-style-type: none"> The dired-x commands are coloured in blue in the following table. <code>epa</code> : EasyPG Assistant (GNU Privacy Guard) : built-in , but requires installed and configured OpenPGP compliant software like GNU PG. <code>ls-lisp</code>: Emacs emulation GNU Is which provides better integration with Dired.  Used when pel-use-emacs-ls-emulation is set to t. These are external: <ul style="list-style-type: none">  dired-sidebar : quick (but limited) access to dired features in side bar:  available when pel-use-dired-sidebar is set to t  dired-hide-dotfiles: controls hiding of dot-files.  Used when pel-use-dired-hide-dotfiles is set to t or to hide-dot-files-by-default.  dired-git-info control display of git log on files managed by git.  Used when pel-use-dired-git-info is set to: <ul style="list-style-type: none"> t : activate dired-git-info manually in dired by typing: <code>)</code> on-for-git-directories : dired-git-info is turned on automatically in dired for directories under Git control. <p>  Modify the ls output by changing the dired-listing-switches user option. <ul style="list-style-type: none"> For example to see the SELinux security labels and the full time stamp of every file listed, set it to the following: -alZ --full-time  Emacs can use Tramp to open directories as sudo or su : <ul style="list-style-type: none"> To open directory as sudo: C-x d /sudo::<path b="" directory<="" to=""></path> To open directory as su: C-x d /su::<path b="" directory<="" to=""></path> </p>		
Open this PDF file. See also: Help/Info	<div><f11> SPC M-D <f1></div> <div><f12> <f1></div>	<div>(pel-help-pdf &optional OPEN-WEB-PAGE)</div>	Open the File mngt Dired local PDF. If the prefix argument (like C-u or M--) is used, then it opens the remote GitHub hosted raw PDF instead. If the pel-flip-help-pdf-arg user-option is set it's the other way around.
Configure PEL Dired Support See also: Customize	<div><f11> SPC M-D <f2></div> <div><f12> <f2></div>	<div>(pel-customize-pel &optional OTHER-WINDOW)</div>	Customize PEL support for dired, directory editor. <ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u) , display in other window.
Configure Emacs Dired Support See also: Customize	<div><f11> SPC M-D <f3></div> <div><f12> <f3></div>	<div>(pel-customize-library &optional OTHER-WINDOW)</div>	Customize Emacs support for: dired, dired-git-info, dired-hide-dotfiles, ls-lisp, wdired
Entering Dired Mode	 With PEL, you can activate and dynamically select one of several input completion modes that impact these 2 commands. <ul style="list-style-type: none"> See the Completion/Input for how to activate and select the completion mode. See File mngt for more info on file management. 		
Open a directory editor	<ul style="list-style-type: none"> C-x d  %-D 	<ul style="list-style-type: none"> (dired DIRNAME &optional SWITCHES) (ido-dired) 	Opens a Dired-mode buffer on the specified directory. Prompt for the directory name.  PEL activates ido when the pel-use-ido-mode user option is set to t .
Run Dired in other window	C-x 4 d	(dired-other-window)	Opens a Dired-mode buffer on the specified directory inside another window. <ul style="list-style-type: none"> Prompt for the directory name.
List Directory See also: Completion/Input	C-x C-d	(list-directory DIRNAME &optional VERBOSE)	Display a list of files in or matching DIRNAME, a la 'ls'. <ul style="list-style-type: none"> DIRNAME is globbed by the shell if necessary. Prefix arg (C-u) means supply -l switch to 'ls'.
Jump to file entry in dired buffer ★★  Leaves point on the file jumped to, allowing immediate Dired action, eg.: C-x C-j R renames the file.	C-x C-j	(dired-jump &optional OTHER-WINDOW FILE-NAME)	Jump to Dired buffer corresponding to current buffer. <ul style="list-style-type: none"> If in a file, Dired the current directory and move to file's line. If in Dired already, pop up a level and goto old directory's line. In case the proper Dired file line cannot be found, refresh the dired buffer and try again. When OTHER-WINDOW is non-nil, jump to Dired buffer in other window. When FILE-NAME is non-nil, jump to its line in Dired. Interactively with prefix argument, read FILE-NAME.
Open (visit) a file/directory  ido-find-file can open file or URL at point when the feature is activated via customization of the ido group. With PEL you can control that behaviour for files with <f11> f M-. and for URL with <f11> f M-,	<div><f11> f f</div> <div>C-x C-f</div>	<div>(find-file FILENAME &optional WILDCARDS)</div> <div>(ido-find-file)</div>	Prompt for the file or directory name to open. Open the selected file/directory in a buffer with the appropriate mode. For directory, the buffer opens in Dired-mode. This can be replaced by the ido-mode by the ido-find-file: it provides suggestions. <ul style="list-style-type: none"> When <code>ido</code> mode is used, you can also: <ul style="list-style-type: none"> Type C-x f to change to original find-file (and stop automatic file name suggestions) Type C-j to accept the file/directory name verbatim without replacement or suggestion. Note: it is also possible to change the read-only state of a buffer with C-x C-f and then change the buffer to read-only mode. <ul style="list-style-type: none"> With PEL, the <f11> f f key binding to find-file is always available, regardless of what completion mechanism is in use. Use it as fallback when testing completion packages.
dired-sidebar	 dired-sidebar : quick (but limited) access to dired features in side bar:  available when pel-use-dired-sidebar is set to t <ul style="list-style-type: none"> A lot of dired commands are available in dired-sidebar, but the display is limited. Inside dired-sidebar, access its customization with <f12> <f3> 		
Toggle (Open/Close) a dired-sidebar window	<div><f11> C-d</div> <div><f12> C-d</div>	<div>(dired-sidebar-toggle-sidebar &optional DIR)</div>	Toggle the dired sidebar, something similar to a “ <i>project explorer</i> ”. <ul style="list-style-type: none"> PEL activates the auto-revert-mode inside the dired-sidebar to allow it to refresh when the content of the directory changes.
Entering Dired via ffp commands See also: File mngt	Emacs provides the ffp (find file at point) command set with Dired commands, These are listed below.  PEL activates the Emacs built-in ffp library when the pel-use-ffp user option is set to either t or to ffap-bindings . In both cases these activate the key bindings shown below. <ul style="list-style-type: none"> When pel-use-ffp is set to ffp-bindings, then PEL also activates the standard ffp bindings which take over the behaviour of the main file finding and dired commands. This means that Ido, Ivy or Helm are no longer available for these commands. If pel-use-ffp is only set to t then the standard ffp bindings is not activated. 		
Start Dired with file at point	<f11> f a d	(dired-at-point &optional FILENAME)	Start Dired, defaulting to file at point. See ‘ffap’.
Start Dired with file at point in other window	<f11> f a D	(ffap-dired-other-window)	Like ‘dired-at-point’, but put buffer in another window.
Start Dired with file at point in other frame	<f11> f a M-d	(ffap-dired-other-frame)	Like ‘dired-at-point’, but put buffer in another frame.
Dired Mode commands	A buffer in Dired Mode provides a large set of specialized single key commands. There's also a set of secondary/extended Dired Modes that can be activated via some of these commands. <p>As an example on what can be done, the following describes the keys to use to show only the files that have a specific file extension:</p> <ul style="list-style-type: none"> Mark all .el files: %f \.el\$ RET Toggle the marking to mark all other files: t Kill the lines that are now marked: k <p>To refresh the file list: g</p>		
Help - summary of available commands	?	(dired-summary)	Summarize basic Dired commands on the echo line and show recent Dired errors.
Help - complete help	<ul style="list-style-type: none"> h <f1> m 	(describe-mode &optional BUFFER)	Display documentation of Dired major mode and available minor modes. <ul style="list-style-type: none"> A brief summary of the minor modes comes first, followed by the major mode description. This is followed by detailed descriptions of the minor modes, each on a separate page.

Description	Keystroke	Function	Note
Navigate in Dired Buffer	The following commands select a new file line in the buffer.		
Move down one line	<ul style="list-style-type: none"> SPC n C–n 	(dired-next-line ARG)	Down one line
Move up one line	<ul style="list-style-type: none"> S–SPC p C–p 	(dired-previous-line ARG)	Up one line
Move to next marked file	<ul style="list-style-type: none"> M–} * C–n 	(dired-next-marked-file ARG &optional WRAP OPOINT)	Move to the ARGth next marked file. <ul style="list-style-type: none"> ARG is the numeric prefix argument and defaults to 1. If WRAP is non-nil, which happens interactively, wrap around to the beginning of the buffer and search from there, if no marked file is found after this line. Optional argument OPOINT specifies the buffer position to return to if no ARGth marked file is found; it defaults to the position where this command was invoked.
Move to previous marked file	<ul style="list-style-type: none"> M–{ * C–p 	(dired-prev-marked-file ARG &optional WRAP)	Move to the ARGth previous marked file. <ul style="list-style-type: none"> ARG is the numeric prefix argument and defaults to 1. If WRAP is non-nil, which happens interactively, wrap around to the end of the buffer and search backwards from there, if no ARGth marked file is found before this line.
Move to the next directory line	>	(dired-next-dirline ARG &optional OPOINT)	Goto ARGth next directory file line.
Move to previous directory line	<	(dired-prev-dirline ARG)	Goto ARGth previous directory file line.
Move to line of specified file	j	(dired-goto-file FILE)	Go to line describing file FILE in this Dired buffer. Prompts for file name.
Control Visibility	Supports: Hiding Subdirectories , Updating the Dired Buffer , show/hide dot files , show/hide git info .		
Toggle sorting lines by date	s	(dired-sort-toggle-or-edit &optional ARG)	Toggle sorting by date, and refresh the Dired buffer. With a prefix argument, edit the current listing switches instead.
Toggle visibility of details info	((dired-hide-details-mode &optional ARG)	Toggle visibility of detailed information in current Dired buffer. <ul style="list-style-type: none"> When this minor mode is enabled, details such as file ownership and permissions are hidden from view.  User options: ‘dired-hide-details-hide-symlink-targets’, ‘dired-hide-details-hide-information-lines’.
Hide/unhide current sub-directory, move to next one	\$	(dired-hide-subdir ARG)	Hide or unhide the current subdirectory and move to next directory. <ul style="list-style-type: none"> Optional prefix arg is a repeat factor.
Hide/Show all sub-directories	M–\$	(dired-hide-all &optional IGNORED)	Hide all subdirectories, leaving only their header lines. <ul style="list-style-type: none"> If there is already something hidden, make everything visible again. Use M-x dired-hide-subdir to (un)hide a particular subdirectory.
Hide/Show dot-files	/	(dired-hide-dotfiles-mode &optional ARG)	Toggle ‘dired-hide-dotfiles-mode’  Requires dired-hide-dotfiles  PEL activates when pel-use-dired-hide-dotfiles is set to t or to hide-dot-files-by-default .
Show/hide Git log info for each file)	(dired-git-info-mode &optional ARG)	Toggle git message info for each file in in current dired buffer.  May take some time to populate.  Requires dired-git-info  PEL activates when pel-use-dired-git-info is set to t or to on-for-git-directories .
Refresh	g	(revert-buffer &optional IGNORE-AUTO NOCONFIRM PRESERVE-MODES)	Refresh: read directory again.
Re-display from point <small>See subdirectory switches in Dired</small>	l	(dired-do-redisplay &optional ARG TEST-FOR-SUBDIR)	Relist the file at point or the marked files, or a subdirectory. <ul style="list-style-type: none"> Redisplay all marked (or next ARG) files. If on a subdir line, redisplay that subdirectory. In that case, a prefix arg lets you edit the ‘Is’ switches used for the new listing.
Quit Dired Window	q	(quit-window &optional KILL WINDOW)	Quit WINDOW and bury its buffer. <ul style="list-style-type: none"> WINDOW must be a live window and defaults to the selected one. With prefix argument KILL non-nil, kill the buffer instead of burying it.
Searching for Files	The following commands search for file names in the dired buffer, ignoring all other text in the buffer (but see next paragraph).  By setting dired-isearch-filenames user option to t , you can use the normal search commands (and bindings) in Dired buffer to also only search in the file names and ignoring the other text. Then the following key bindings are not needed.		
ISearch for file name	M–s f C–s	(dired-isearch-filenames)	Search for a string using Isearch only in file names in the Dired buffer.
ISearch for marked file name	M–s a C–s	(dired-do-isearch)	Search for a string through all marked files using Isearch.
Regex ISearch for file name	M–s f C–M–s	(dired-isearch-filenames-regexp)	Search for a regexp using Isearch only in file names in the Dired buffer.
Regex ISearch for marked file name	M–s a C–M–s	(dired-do-isearch-regexp)	Search for a regexp through all marked files using Isearch.
Visit Files	The following commands are used to ‘visit’ a file (i.e. open the file for editing), to ‘view’ a file (open the file in read-only mode). The last 2 commands launch an OS application to open the file: the application associated with the type of file.		
Visit file/directory on line	<ul style="list-style-type: none"> RET e f 	(dired-find-file)	Visit current line’s file or directory. For directory create new Dired buffer.
Visit parent directory	^	(dired-up-directory &optional OTHER-WINDOW)	Up one directory level (creates a new buffer)
Visit file/directory on line in current buffer	a	(dired-find-alternate-file)	Access current line’s file or directory. Kill old Dired buffer.  Use this command to avoid creating several buffers when visiting several directories.
Visit file/directory in another window	o	(dired-find-file-other-window)	Visit current line’s file or directory inside other window. <ul style="list-style-type: none"> Select that other window.
Visit file/directory in another window (keep Dired window selected)	C–o	(dired-display-file)	In Dired, display this file or directory in another window. <ul style="list-style-type: none"> Does not select the file window, keeps the Dired buffer window selected.
Visit all files marked	F	(dired-do-find-marked-files &optional NOSELECT)	Find all marked files displaying all of them simultaneously. <ul style="list-style-type: none"> With optional NOSELECT just find files but do not select them. The current window is split across all files marked, as evenly as possible. Remaining lines go to bottom-most window. The number of files that can be displayed this way is restricted by the height of the current window and ‘window-min-height’. To keep Dired buffer displayed, type C–x 2 first. To display just marked files, type C–x 1 first.
View a file	v	(dired-view-file)	In Dired, examine a file in view mode, returning to Dired when done. <ul style="list-style-type: none"> When file is a directory, show it in this buffer if it is inserted. Otherwise, display it in another (Dired) buffer.

Description	Keystroke	Function	Note
Unmark files			
Unmark file	<ul style="list-style-type: none"> • u • *u 	(dired-unmark ARG &optional INTERACTIVE)	Unmark a file or all files of inserted subdirectory
Unmark file and move up	<ul style="list-style-type: none"> • DEL • *DEL 	(dired-unmark-backward ARG)	Back up one line and unmark or unflag.
Remove all marks from all files in Dired buffer	<ul style="list-style-type: none"> • U • *! 	(dired-unmark-all-marks)	Remove all marks from all files in the Dired buffer.
Remove a specific mark from all files	<ul style="list-style-type: none"> • M-DEL • *? 	(dired-unmark-all-files MARK &optional ARG)	Remove a specific mark (or any mark) from every file. <ul style="list-style-type: none"> • After this command, type the mark character to remove, or type RET to remove all marks. • With prefix arg, query for each marked file. Type C-h at that time for help.
Toggle al marks	t	(dired-toggle-marks)	Toggle marks: marked files become unmarked, and vice versa. <ul style="list-style-type: none"> • Files marked with other flags (such as ‘D’) are not affected. • ‘.’ and ‘..’ are never toggled. • As always, hidden subdirs are not affected.
Undo Dired Buffer Changes	Changes to the Dired buffer like marking, un-marking file lines can be un-done with the dired-undo command described below.  Performing an undo after some commands may get the Dired buffer out of sync with the corresponding file system. For example if you execute dired-undo after renaming a file the old file name will be displayed back in the Dired buffer and that will not reflect the real file name. Refresh the Dired buffer in such cases.		
	<ul style="list-style-type: none"> • M-u • C-x u • C-/- 	(dired-undo)	Undo in a Dired buffer. <ul style="list-style-type: none"> • This doesn't recover lost files, it just undoes changes in the buffer itself. • You can use it to recover marks, killed lines or subdirs.
Change mark type	Dired support any character as markers. You can change the currently identified marks with others to help you manage files and directories.		
Change mark type	*c	(dired-change-marks &optional OLD NEW)	Change all OLD marks to NEW marks. Prompt for old mark and new mark. <ul style="list-style-type: none"> • OLD and NEW are both characters used to mark files.
Kill/Delete	See: Deleting files with Dired		
Delete files marked for deletion	x	(dired-do-flagged-delete &optional NOMESSAGE)	Delete (eXpunge) the files flagged ‘D’.
Delete marked files/directories	D	(dired-do-delete &optional ARG)	Delete all marked (or next ARG) files.  dired-recursive-deletes’ controls whether deletion of non-empty directories is allowed.
Kill all marked lines (not files)	k	(dired-do-kill-lines &optional ARG FMT)	Kill all marked lines (not the files). <ul style="list-style-type: none"> • With a prefix argument, kill that many lines starting with the current line. • (A negative argument kills backward.) • If you use this command with a prefix argument to kill the line for a file that is a directory, which you have inserted in the Dired buffer as a subdirectory, then it deletes that subdirectory from the buffer as well. • To kill an entire subdirectory (without killing its line in the parent directory), go to its directory header line and use this command with a prefix argument (the value does not matter).
Create			
Create directory	+	(dired-create-directory DIRECTORY)	Create a new directory. <ul style="list-style-type: none"> • Parent directories of DIRECTORY are created as needed. • If DIRECTORY already exists, signal an error.
Copy files	If copied into a directory already shown by Dired, it marks the files with a C marker. Use it as a reminder for files that were just copied. With dired-dwim-target set to t and 2 side-by-side Dired windows, the copy or move operation select the directory of the other window. • Use <f11><f2>o dired-dwim-target to open the user-option customization buffer and change its value for the session or permanently.		
See  Customize			
Copy file/directory	C	(dired-do-copy &optional ARG)	Copy all marked (or next ARG) files, or copy the current file. <ul style="list-style-type: none"> • When operating on just the current file, prompt for the new name. • When applied on a directory, prompt for recursive copy of the directory tree.
Copy files which match regexp	%C	(dired-do-copy-regexp REGEXP NEWNAME &optional ARG WHOLE-NAME)	Copy selected files whose names match REGEXP to NEWNAME. <ul style="list-style-type: none"> • With non-zero prefix argument ARG, the command operates on the next ARG files. Otherwise, it operates on all the marked files, or the current file if none are marked. • As each match is found, the user must type a character saying what to do with it. For directions, type C-h at that time. NEWNAME may contain \<n> or \& as in ‘query-replace-regexp’. REGEXP defaults to the last regexp used. • With a zero prefix arg, renaming by regexp affects the absolute file name. • Normally, only the non-directory part of the file name is used and changed.
Rename/move files	 Files can also be renamed using WDired - editable dired mode which allows you to simply change the file names in the dired buffer by doing this: <ul style="list-style-type: none"> • First type C-x C-q or <f11> b r key sequence to activate the WDired mode. • Change the name of the file by moving point over the file name and editing it. You can change the name of several files. • Type C-c C-c or C-x C-s to apply your changes and exit the WDired mode. With dired-dwim-target set to t and 2 side-by-side Dired windows, the copy or move operation select the directory of the other window. • Use <f11><f2>o dired-dwim-target to open the user-option customization buffer and change its value for the session or permanently.		
Also see Transforming File Names in Dired			
See  Customize			
Rename file/move file into other directory	R	(dired-do-rename &optional ARG)	Rename a file or move the marked files to another directory.
Rename files selected by regexp	<ul style="list-style-type: none"> • %R • %r 	(dired-do-rename-regexp REGEXP NEWNAME &optional ARG WHOLE-NAME)	Rename selected files whose names match REGEXP to NEWNAME. <ul style="list-style-type: none"> • With non-zero prefix argument ARG, the command operates on the next ARG files. Otherwise, it operates on all the marked files, or the current file if none are marked. • As each match is found, the user must type a character saying what to do with it. For directions, type C-h at that time. NEWNAME may contain \<n> or \& as in ‘query-replace-regexp’. REGEXP defaults to the last regexp used. • With a zero prefix arg, renaming by regexp affects the absolute file name. Normally, only the non-directory part of the file name is used and handed.
Rename all marked files to lowercase names	%l	(dired-downcase &optional ARG)	Rename all marked (or next ARG) files to lower case.
Rename all marked files to uppercase names	%u	(dired-upcase &optional ARG)	Rename all marked (or next ARG) files to upper case.
Compare Files			
Diff file	=	(dired-diff FILE &optional SWITCHES)	Compare file at point with FILE using ‘diff’. <ul style="list-style-type: none"> • Prompt for FILE, but : <ul style="list-style-type: none"> • If the mark is active in Transient Mark mode, use the file at the mark as the default for FILE. (That’s the mark set by C-SPC, not by Dired’s M-x dired-mark command.) • If the file at point has a backup file, use that as the default FILE. • If the file at point is a backup file, use its original, if that exists and can be found. • FILE is the first argument given to the ‘diff’ function (the “old” version). The file at point is the second argument given to ‘diff’. • With prefix arg, prompt for second argument SWITCHES, which is the string of command switches used as the third argument of ‘diff’.  Customizations of ‘backup-directory-alist’ and ‘make-backup-file-name-function’ change where this function searches for the backup file, and affect its ability to find the original of a backup file.

Description	Keystroke	Function	Note
Grep & Replace			
Grep for text in marked file(s)	A	(dired-do-find-regexp REGEXP)	Find all matches for REGEXP in all marked files. <ul style="list-style-type: none"> For any marked directory, all of its files are searched recursively. <ul style="list-style-type: none"> However, files matching ‘grep-find-ignored-files’ and subdirectories matching ‘grep-find-ignored-directories’ are skipped in the marked directories. 👉 REGEXP should use constructs supported by your local ‘grep’ command.
Replace text found in marked file(s) See also: 🔗 Search/Replace	Q	(dired-do-find-regexp-and-replace FROM TO)	Replace matches of FROM with TO, in all marked files. <ul style="list-style-type: none"> For any marked directory, matches in all of its files are replaced, recursively. However, files matching ‘grep-find-ignored-files’ and subdirectories matching ‘grep-find-ignored-directories’ are skipped in the marked directories. 👉 REGEXP should use constructs supported by your local ‘grep’ command.
Byte Compile & Load			
Byte compile marked Emacs Lisp files	B	(dired-do-byte-compile &optional ARG)	Byte compile marked (or next ARG) Emacs Lisp files.
Load Emacs Lisp files	L	(dired-do-load &optional ARG)	Load the marked (or next ARG) Emacs Lisp files.
Compress/Uncompress			
Compress/Uncompress file(s)	Z	(dired-do-compress &optional ARG)	Compress or uncompress marked (or next ARG) files. <ul style="list-style-type: none"> If invoked on a directory, compress all of the files in the directory and all of its subdirectories, recursively, into a .tar.gz archive. If invoked on a .tar.gz or a .tgz or a .zip or a .7z archive, uncompress and unpack all the files in the archive. 💡 To compress a file or directory into a ZIP file, select all files with m then press ! and type the zip command: something like: zip -r all.zip *
Shell Commands			
Execute shell command on marked files	<ul style="list-style-type: none"> ! x 	(dired-do-shell-command COMMAND &optional ARG FILE-LIST)	Execute shell command in the directory. Run a shell command COMMAND on the marked files. <ul style="list-style-type: none"> If no files are marked or a numeric prefix arg is given, the next ARG files are used. Just C-u means the current file. The prompt mentions the file(s) or the marker, as appropriate. If there is a ‘’’ in COMMAND, surrounded by whitespace, this runs COMMAND just once with the entire file list substituted there. If there is no ‘’’ , but there is a ‘?’ in COMMAND, surrounded by whitespace, or a ‘?’ this runs COMMAND on each file individually with the file name substituted for ‘?’ or ‘?’. Otherwise, this runs COMMAND on each file individually with the file name added at the end of COMMAND (separated by a space). When COMMAND runs, its working directory is the top-level directory of the Dired buffer, so output files usually are created there instead of in a subdir.
Asynchronously execute shell command on marked files	&	(dired-do-async-shell-command COMMAND &optional ARG FILE-LIST)	Like ‘dired-do-shell-command’, but adds ‘&’ at the end of COMMAND to execute it asynchronously. <ul style="list-style-type: none"> When operating on multiple files, asynchronous commands are executed in the background on each file in parallel. In shell syntax this means separating the individual commands with ‘&’. However, when COMMAND ends in ‘;’ or ‘&’ then commands are executed in the background on each file sequentially waiting for each command to terminate before running the next command. In shell syntax this means separating the individual commands with ‘;’. <p>The output appears in the buffer “*Async Shell Command”.</p>
Execute a shell command inside the current Dired directory	M-!	(dired-smart-shell-command COMMAND &optional OUTPUT-BUFFER ERROR-BUFFER)	Like function ‘shell-command’, but in the current Virtual Dired directory. <ul style="list-style-type: none"> Does not use the marked files; just uses the directory identified by Dired as the current directory for the command. For example, to execute make in the directory identified by the Dired buffer. That way you don’t need to open a shell. The disadvantage is that you’ll have to wait for the command to finish to see the output inside the “Shell Command Output” buffer.
Modify file attributes			
Change the file(s) group (chgrp)	G	(dired-do-chgrp &optional ARG)	Change the group of the marked (or next ARG) files. <ul style="list-style-type: none"> Type M-n to pull the file attributes of the file at point into the minibuffer.
Change the file(s) mode (chmod)	M	(dired-do-chmod &optional ARG)	Change the mode of the marked (or next ARG) files. <ul style="list-style-type: none"> Symbolic modes like ‘g+w’ are allowed. Type M-n to pull the file attributes of the file at point into the minibuffer.
Change the file(s) ownership (chown)	O	(dired-do-chown &optional ARG)	Change the owner of the marked (or next ARG) files. <ul style="list-style-type: none"> Type M-n to pull the file attributes of the file at point into the minibuffer.
Touch the marked file(s)	T	(dired-do-touch &optional ARG)	Change the timestamp of the marked (or next ARG) files using ‘touch’. <ul style="list-style-type: none"> Type M-n to pull the file attributes of the file at point into the minibuffer. 👉 Use this to set the timestamp of all marked files to timestamp of the current file!
File Hard/Soft Links			
Create hard link for current or all marked files.	H	(dired-do-hardlink &optional ARG)	Add names (hard links) for current file or all marked (or next ARG) files. <ul style="list-style-type: none"> When operating on just the current file, prompts and you specify the new name. When operating on multiple or marked files, you specify a directory and new hard links are made in that directory with the same names that the files currently have. The default suggested for the target directory depends on the value of ‘dired-dwim-target’.
Hardlink files selected by regexp	%H	(dired-do-hardlink-regexp REGEXP NEWNAME &optional ARG WHOLE-NAME)	Hardlink selected files whose names match REGEXP to NEWNAME. <ul style="list-style-type: none"> With non-zero prefix argument ARG, the command operates on the next ARG files. Otherwise, it operates on all the marked files, or the current file if none are marked. As each match is found, the user must type a character saying what to do with it. For directions, type C-h at that time. NEWNAME may contain \<n> or \& as in ‘query-replace-regexp’. REGEXP defaults to the last regexp used. With a zero prefix arg, renaming by regexp affects the absolute file name. Normally, only the non-directory part of the file name is used and changed.
Create symbolic links for current or all marked files	S	(dired-do-symlink &optional ARG)	Make symbolic links to current file or all marked (or next ARG) files. <ul style="list-style-type: none"> When operating on just the current file, you specify the new name. When operating on multiple or marked files, you specify a directory and new symbolic links are made in that directory with the same names that the files currently have. The default suggested for the target directory depends on the value of ‘dired-dwim-target’, which see. For relative symlinks, use M-x dired-do-relsymlink.
Symlink files selected by regexp	%S	(dired-do-symlink-regexp REGEXP NEWNAME &optional ARG WHOLE-NAME)	Symlink selected files whose names match REGEXP to NEWNAME. See function ‘dired-do-rename-regexp’ for more info.
Create relative symbolic links for current or all marked files	Y	(dired-do-relsymlink &optional ARG)	Relative symlink all marked (or next ARG) files into a directory. <ul style="list-style-type: none"> Otherwise make a relative symbolic link to the current file. This creates relative symbolic links like: <pre>foo -> ../bar/foo</pre> not absolute ones like: <pre>foo -> /ugly/file/name/that/may/change/any/day/bar/foo</pre>

Description	Keystroke	Function	Note
Create relative symbolic links for files selected by regexp	%Y	(dired-do-relsymlink-regexp REGEXP NEWNAME &optional ARG WHOLE-NAME)	RelSymlink all marked files containing REGEXP to NEWNAME. <ul style="list-style-type: none"> See functions 'dired-do-rename-regexp' and 'dired-do-relsymlink' or more info.
OpenPGP Support	The following epa Dired integration commands require OpenPGP-compliant encryption software tools (such as GNU Privacy Guard) to be available.		
Decrypt marked file(s)	: d	(epa-dired-do-decrypt)	Decrypt marked files.
Encrypt marked file(s)	: e	(epa-dired-do-encrypt)	Encrypt marked files.
Sign marked file(s)	: s	(epa-dired-do-sign)	Sign marked files.
Verify	: v	(epa-dired-do-verify)	Verify marked files.
Miscellaneous			
Print the file(s)	P	(dired-do-print &optional ARG)	Print the marked (or next ARG) files. <div>  Uses the shell command coming from variables 'lpr-command' and 'lpr-switches' as default. </div>
Visit current file as mailbox	V	(dired-do-run-mail)	Visit the current file as a mailbox, using VM or RMAIL. <ul style="list-style-type: none"> Prompt for confirmation first; if the user says yes, call 'dired-vm' if 'dired-bind-vm' is non-nil, 'dired-rmail' otherwise.
WDired: Editable Dired Buffer See also: WDired — Writable Dired	When the Wdired mode is on, the file names, symlinks and file permissions (if enabled via customization) can be modified by simply editing their names as they show in the buffer. <div>  Wdired group user options. With PEL to customize them use: <f11> <f2> g wdired to see, change them or dead more info about them. <ul style="list-style-type: none"> wdired-allow-to-change-permissions: t: allow editing the permission bits directly in the buffer to change them. Useful with multiple-cursors to change permissions of several files at the same time! t: allow editing targets of symbolic links. wdired-allow-to-redirect-links: t: request confirmation when renames overwrite files. This is the default. Otherwise it does not prompt. wdired-confirm-overwrite: t: creates parent directories automatically when renaming a file with a destination path within non-existent directory. Otherwise the rename fails. wdired-keep-marker-rename: controls whether Dired file marks are kept when a file is renamed & committed by C-c C-c or C-x C-s. wdired-use-interactive-rename: controls whether confirmation is required before renaming file. Off by default. wdired-use-dired-vertical-movement: controls the way the cursor moves. Like in normal editing (default), like in dired-mode or specialized. </div>		
Toggle read-only status of buffer	<ul style="list-style-type: none"> C-x C-q <f11> b r 	(dired-toggle-read-only)	Toggle the Editable Dired (WDired mode) on/off. When exiting, checks if there are un-committed changes and prompts to commit them.
Commit the changes	<ul style="list-style-type: none"> C-c C-c C-x C-s 	(wdired-finish-edit)	Commit the changes: actually rename files based on your editing in the Dired buffer.
Abort, does not commit changes.	<ul style="list-style-type: none"> C-c Esc C-c C-C-k 	(wdired-abort-changes)	Abort changes and return to dired mode.
Using dired-narrow Inside Dired buffer	<div>  This requires the external dired-narrow package to be installed.  PEL installs and activate when the <i>pel-use-dired-narrow</i> user option is t. With dired-narrow you can limit the number of files shown in the dired buffer by using expressions typed following one of the following commands.  To widen the list back, refresh the Dired buffer: press g. </div>		
Narrow the file list to specific filter	<f12> s	(dired-narrow)	Narrow a dired buffer to the files matching a string. (not a regexp) <ul style="list-style-type: none"> If the string contains spaces, then each word is matched against the file name separately. To succeed, all of them have to match but the order does not matter. For example "foo bar" matches filename "bar-and-foo.el".
Narrow the file list to specific regexp filter	<f12> r	(dired-narrow-regexp)	Narrow a dired buffer to the files matching a regular expression. <ul style="list-style-type: none"> For example, to list all .el files, use: .e1\$
Narrow the file list to specific fuzzy filter	<f12> f	(dired-narrow-fuzzy)	Narrow a dired buffer to the files matching a fuzzy string. <p>A fuzzy string is constructed from the filter string by inserting "." between each letter. This is then matched as regular expression against the file name.</p>
image-dired	Image manipulation within Emacs. Requires access to the external ImageMagick program which must be installed separately. To rotate JPEG files you will also need to install jpegtran if it is not already available. <div>  Although the key sequences are available in Terminal mode, these commands will only work when invoked from Emacs in graphics mode.  More commands are available in the *image-dired* and *image-dired-display-image* buffers. Type C-h m or <f1> m to list them all. </div>		
Display Image Thumbnails	C-t d	(image-dired-display-thumbs &optional ARG APPEND DO-NOT-POP)	Display thumbnails of all marked files, in 'image-dired-thumbnail-buffer'. <ul style="list-style-type: none"> If a thumbnail image does not exist for a file, it is created on the fly. With prefix argument ARG, display only thumbnail for file at point (this is useful if you have marked some files but want to show another one). <p>Recommended usage is to split the current frame horizontally so that you have the Dired buffer in the left window and the 'image-dired-thumbnail-buffer' buffer in the right window.</p>
Add Image Comment...	C-t c	(image-dired-dired-comment-files)	Add comment to current or marked files in Dired. <ul style="list-style-type: none"> The text is stored inside a local database, inside the ~/.emacs.d directory.
Add Image Tags...	C-t t	(image-dired-tag-files ARG)	Tag file(s) which are marked in a Dired buffer. <ul style="list-style-type: none"> With prefix ARG, tag the file at point.
Delete Image Tags...	C-t r	(image-dired-delete-tag ARG)	Remove tag for selected file(s). <ul style="list-style-type: none"> With prefix argument ARG, remove tag from file at point.
Edit comments and tags	C-t e	(image-dired-dired-edit-comment-and-tags)	Edit comment and tags for current or all marked image files in an easy-to-use form.

Dired — References

Description & link	Notes
Dired @ wikipedia	An overview.
Dired in Emacs Manual	Dired table of Content in the emacs manual.
GNU Dired Extra Manual	
GNU Easy PG User Assistant User's Manual	
Mike Sperber's dired page	Page of Dired current maintainer
Emacs: techniques to narrow Dired - Youtube video	A quick video on how to use straight dired-mode to list a sub-set of all files. It also describes the dired-narrow package though.
Integrating OS X and Emacs Dired	Jason Blevins describes how to launch macOS registered application for a specific file in Dired mode.
WDired: Editable Dired Buffers	Mickey Petersen quickly describes the power of WDired mode to manage file names.
Dired: Rename Multiple Files @ Pragmatic Emacs	A quick animated Gif demo showing how to rename files using wdired-mode (Editable Dired Mode)

Description & link	Notes
<u>Batch-Edit File Permissions In Dired @ Pragmatic Emacs</u>	<p>A quick animated Gif demo using wdired-mode, dired-narrow and multiple-cursors to set permissions of several files.</p> <p>Note: instead of setting wdired-allow-to-change-permissions in your init.el file, PEL proposes to change it in the customization system. It's easy to change and you don't have to write any Emacs Lisp code. You can also read the full description and see alternatives.</p>