




⚠ Emacs support for the Schen Programming Language ⚠

Description	Keystroke	Function	Note
Schen Editing Last updated on: 2026-01-21	<div> <div>  PEL supports Schen via schen-mode when pel-use-schen is t. PEL does not support a tree-sitter mode for Schen. ⚠UPCOMING! Not yet implemented! </div> <div> PEL also provides: <ul style="list-style-type: none"> ⌘ Speedbar support for Schen files listing functions and some types. ⌘iMenu is supported by schen-mode ⚠ </div> </div> <div> ⚠ PEL supports for the Schen programming language is an early implementation not yet fully documented. </div>		
Open this PDF file. See also: ⌘ Help/Info	<f11> SPC 8 <f1>	(pel-help-pdf &optional OPEN-WEB-PAGE)	Open the ⌘I - Schen local PDF. If the prefix argument (like C-u or M--) is used, then it opens the remote GitHub hosted raw PDF instead. If the pel-flip-help-pdf-arg user-option is set it's the other way around.
	<f12> <f1>		
⌘ Customize PEL Schen support	<f11> SPC 8 <f2>	(pel-customize-pel &optional OTHER-WINDOW)	Customize PEL Schen support. <ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f2>		
⌘ Customize Emacs Schen support	<f11> SPC 8 <f3>	(pel-customize-library &optional OTHER-WINDOW)	Customize Emacs Schen support. <ul style="list-style-type: none"> If OTHER-WINDOW is non-nil (use C-u), display in another window.
	<f12> <f3>		
Show PEL setup for Schen68 buffer	<f11> ? /	(pel-mode-setup-info &optional APPEND)	Display Schen setup information inside a "pel-mode-info" buffer with buttons providing quick access to the customization buffer of each variable shown. <ul style="list-style-type: none"> To append information in the buffer instead of clearing the previous content type any prefix argument (such as C-u) before the command keystroke.
Comments			
Toggle display of comments in buffer or active region See also: ⌘ Comments	<f11> ; ;	(hide/show-comments-toggle &optional START END)	Toggle hiding/showing of comments in the active region or whole buffer. <ul style="list-style-type: none"> If the region is active then toggle in the region. Otherwise, in the whole buffer. <div>  This requires the hide-comnt.el package (see ⌘ Comments).  PEL activates it when the pel-use-hide-comnt user option is t. </div>

Emacs & Schen— References

Document	Notes	
The Schen Programming Language	<ul style="list-style-type: none"> About Schen The Shen Group Shen News Group 	<ul style="list-style-type: none"> Schen Learning: <ul style="list-style-type: none"> Schen in 15 minutes with topic table of content. The Schen OS Manual The Book of Schen, 4th edition - online The Book of Schen. 5th edition - hardcopy
Emacs support:	schen-mode @ Github	
Schen port systems	schen-scheme @ GitHub	
Information about Schen		
Discussions about Schen		