





## 🚧 Emacs support for Perl 🚧

Description	Keystroke	Function	Note
<b>Perl Editing</b>	Emacs provides the built-in perl-mode to support Perl programming. PEL activates Perl support with the  <b>pel-use-perl</b> user-options. When it is turned on the <b>&lt;f11&gt; SPC U</b> prefix is made available. In a perl buffer these commands are accessible via the <b>&lt;f12&gt;</b> key. It also activates the ability to activate minor modes for the perl major mode through the PEL <b>pel-perl-activates-minor-modes</b> user-option.   PEL support for Perl is not complete. More commands should be provided and documented. Perl support is preliminary.		
<b>Open this PDF file.</b> See also: <a href="#">📖 Help/Info</a>	<b>&lt;f11&gt; SPC P &lt;f1&gt;</b>	<b>(pel-help-pdf</b> &optional OPEN-WEB-PAGE)	Open the <b>📖 - Perl</b> local PDF. If the prefix argument (like <b>C-u</b> or <b>M--</b> ) is used, then it opens the remote GitHub hosted raw PDF instead. If the <b>pel-flip-help-pdf-arg</b> user-option is set it's the other way around.
	<b>&lt;f12&gt; &lt;f1&gt;</b>		
<a href="#">📖 Customize</a> PEL Perl support	<b>&lt;f11&gt; SPC P &lt;f2&gt;</b>	<b>(pel-customize-pel</b> &optional OTHER-WINDOW)	Customize PEL Perl support. <ul style="list-style-type: none"><li>If OTHER-WINDOW is non-nil (use <b>C-u</b>), display in another window.</li></ul>
	<b>&lt;f12&gt; &lt;f2&gt;</b>		
<a href="#">📖 Customize</a> Emacs Perl support	<b>&lt;f11&gt; SPC P &lt;f3&gt;</b>	<b>(pel-customize-library</b> &optional OTHER-WINDOW)	Customize Emacs Perl support: perl. <ul style="list-style-type: none"><li>If OTHER-WINDOW is non-nil (use <b>C-u</b>), display in another window.</li></ul>
	<b>&lt;f12&gt; &lt;f3&gt;</b>		
<b>Comments</b>			
<b>Toggle display of comments in buffer or active region</b> See also: <a href="#">📖 Comments</a>	<b>&lt;f11&gt; ; ;</b>	<b>(hide/show-comments-toggle</b> &optional START END)	Toggle hiding/showing of comments in the active region or whole buffer. <ul style="list-style-type: none"><li>If the region is active then toggle in the region. Otherwise, in the whole buffer.</li></ul>  This requires the <a href="#">hide-comnt.el</a> package (see <a href="#">📖 Comments</a> ).  PEL activates it when the <b>pel-use-hide-comnt</b> user option is t.

### Emacs & Perl — References

Document	Notes