






Emacs support for editing Changelog files

Description	Keystroke	Function	Note
<div> Changelog Files </div> <div> <div> <div>  PEL enhance Emacs' support when <code>pel-use-changelog</code> user-option is set, providing some extra key bindings and providing access to this PDF. </div> <div> <div> <div>Last updated on:</div> <div>2025-05-07</div> </div> <div> <div>See</div> <div>Emacs Change Log Commands</div> </div> </div> <div> This mode is related to VCS and CVS version control systems.  The documentation here does not include information about those and might have to be updated.  </div> </div> </div>			
<div> <div>Open this PDF file.</div> <div>See also:  Help/Info</div> </div>	<div><f12> <f1></div>	<div>(pel-changelog-help &optional OPEN-WEB-PAGE)</div>	<div> Open the  Changelog File local PDF. If the prefix argument (like <code>C-u</code> or <code>M--</code>) is used, then it opens the remote GitHub hosted raw PDF instead. If the <code>pel-flip-help-pdf-arg</code> user-option is set it's the other way around. </div>
<div> <div>ChangeLog</div> <div>Control</div> </div>			
<div>Use change-log-mode</div>	<div>M-x <code>change-log-mode</code></div>	<div>(change-log-mode)</div>	<div> Major mode for editing change logs; like Indented Text mode. <ul style="list-style-type: none"> Prevents numeric backups and sets 'left-margin' to 8 and 'fill-column' to 74. New log entries are usually made with <code>M-x add-change-log-entry</code> or <code>C-x 4 a</code>. Each entry behaves as a paragraph, and the entries for one day as a page. </div>
<div>Add new entry in the change-log</div>	<div>C-x 4 a</div>	<div>(add-change-log-entry &optional WHOAMI CHANGELOG-FILE-NAME OTHER-WINDOW NEW-ENTRY PUT-NEW-ENTRY-ON-NEW-LINE)</div>	<div> Find ChangeLog buffer, add an entry for today and an item for this file. <ul style="list-style-type: none"> With an optional prefix WHOAMI (such as <code>C-u</code>) prompt for user name and email (the default values are stored in 'add-log-full-name' and 'add-log-mailing-address' user-options). </div> <div> <ul style="list-style-type: none"> The CHANGELOG-FILE-NAME is the file name of the change log. <ul style="list-style-type: none"> Interactively, it's nil; so the function uses the value of 'change-log-default-name' user-option. If the file thus named exists, it is used for the new entry. If it doesn't exist, it is created, unless 'add-log-dont-create-changelog-file' is t, in which case a suitably named buffer that doesn't visit any file is used for keeping entries pertaining to CHANGELOG-FILE-NAME's directory. Third arg OTHER-WINDOW non-nil means visit in other window. Interactively it's nil and therefore uses the current window. Fourth arg NEW-ENTRY non-nil means always create a new entry at the front; never append to an existing entry. Option 'add-log-keep-changes-together' otherwise affects whether a new entry is created. Interactively it's nil so it creates a new entry at the front (the top) of the file. Fifth arg PUT-NEW-ENTRY-ON-NEW-LINE non-nil means that if a new entry is created, put it on a new line by itself, do not put it after a comma on an existing line. Option 'add-log-always-start-new-record' non-nil means always create a new record, even when the last record was made on the same date and by the same person. The change log file can start with a copyright notice and a copying permission notice. The first blank line indicates the end of these notices. Today's date is calculated according to 'add-log-time-zone-rule' if non-nil, otherwise in local time. </div>
<div>Go to source location of change log tag</div>	<div>C-c C-c</div>	<div>(change-log-goto-source)</div>	<div> Go to source location of "change log tag" near 'point'. <ul style="list-style-type: none"> A change log tag is a symbol within a parenthesized, comma-separated list. If no suitable tag can be found nearby, try to visit the file for the change under 'point' instead. </div>
<div>Visit changed file</div>	<div>C-c C-f</div>	<div>(change-log-find-file)</div>	<div> Visit the file for the change under point. </div>
<div>Move to next note</div>	<div>C-c C-n</div>	<div>(add-log-edit-next-comment ARG)</div>	<div> Cycle forward through Log-Edit mode comment history. <ul style="list-style-type: none"> With a numeric prefix ARG, go forward ARG comments. </div>
<div>Move to previous note</div>	<div>C-c C-p</div>	<div>(add-log-edit-prev-comment ARG)</div>	<div> Cycle backward through Log-Edit mode comment history. <ul style="list-style-type: none"> With a numeric prefix ARG, go back ARG comments. </div>