



















Writing Tools

| Operation | Keystroke | Function | Note | |
|--|---|--|--|--|
| Writing Tools ○ Help & Customize • artbollocks-mode • writegood-mode • wc-mode (counts & goals) • writeroom-mode ○ my-whisper | Several external packages provide supplemental writing tools to what Emacs already provides. See also: 🔗 Spell Checking PEL installs the following external packages when their corresponding pel-use- customizable user-option is turned on (set to t): <div> <div>  artbollocks-mode  pel-use-artbollocks-mode </div> <div>  gt  pel-use-go-translate </div> <div>  harper-ls  pel-use-harper-ls </div> <div>  my-whisper  pel-use-my-whisper </div> <div>  wc-mode  pel-use-wc-mode </div> <div>  writegood-mode  pel-use-writegood-mode </div> <div>  writeroom-mode  pel-use-writeroom-mode </div> </div> <div> <div>Last updated on:</div> <div>2025-11-27</div> <div>To activate above package in PEL access the pel-pkg-for-writing customization group. Access it with: <f11> W <f2></div> </div> | | | |
| Open this PDF file. See also: 🔗 Help/Info | <f11> W <f1> | (pel-help-pdf &optional OPEN-WEB-PAGE) | Open the Writing Tools local PDF. If the prefix argument (like C-u or M--) is used, then it opens the remote GitHub hosted raw PDF instead. If the pel-flip-help-pdf-arg user-option is set it's the other way around. | |
| 🔗 Customize PEL Writing Tools support | <f11> W <f2> | (pel-customize-pel &optional OTHER-WINDOW) | Customize PEL Writing Tools support: open pel-pkg-for-writing-mode group giving access to all pel-use- user options listed above. • If OTHER-WINDOW is non-nil (use C-u), display in another window. | |
| 🔗 Customize Emacs Writing Tools support | <f11> W <f3> | (pel-customize-library &optional OTHER-WINDOW) | Customize Writing Tools external packages support: artbollocks-mode, wc, writegood, writeroom. • If OTHER-WINDOW is non-nil (use C-u), display in another window. | |
| | | | | |
| Toggle artbollocks-mode to highlight various English prose issues | <f11> W a | (artbollocks-mode &optional ARG) | Highlight passive voice, weasel words and artbollocks jargon in text, and provide useful text metrics.  Requires artbollocks-mode  activated by pel-use-artbollocks-mode . 👉 In some cases you might need to force re-fontification win the buffer, by executing: M-x font-lock-fontify-buffer | |
| Count words in the marked area | C-c [| (artbollocks-word-count &optional START END) | Count the number of words in the marked area or complete buffer and print it in the echo area. | |
| Count sentences in the marked area | C-c] | (artbollocks-sentence-count &optional START END) | Count the number of sentences in the marked area or complete buffer and print it in the echo area. | |
| Evaluate the readability index of marked section. | C-c \ | (artbollocks-readability-index &optional START END) | Determine the automated readability index of the text or complete buffer in the marked area. | |
| Evaluate the Flesch reading ease of text in marked section. | C-c / | (artbollocks-reading-ease &optional START END) | Determine the Flesch reading ease of text in the marked area or complete buffer, print the rating in the echo area. • Higher scores indicate material that is easier to read. | |
| Evaluate and print Flesch-Kinkaid grade level of text in the marked | C-c = | (artbollocks-grade-level &optional START END) | Determine the Flesch-Kinkaid grade level of text in the marked area and print it in the echo area. | |
| | | | | |
| Toggle writegood-mode to highlight various English prose issues | <f11> W g g | (writegood-mode &optional ARG) | Colorize issues with the writing in the buffer.  Requires writegood-mode  activated by pel-use-writegood-mode | |
| Print writegood-mode version | <f11> W g v | (writegood-version) | Print the version of write good-mode.el | |
| Evaluate the Flesch reading ease of text in marked section. | <f11> W g r | (writegood-reading-ease &optional START END) | Print Flesch reading ease and Flesch-Kinkaid grade level of text in the marked area or complete buffer. Scores roughly between 0 and 100. | |
| Evaluate and print Flesch-Kinkaid grade level of text in the marked | <f11> W g l | (writegood-grade-level &optional START END) | Flesch-Kincaid grade level test. Converts reading ease score to a grade level (Score ~ years of school needed to read passage). | |
| | | | | |
| Toggle wc-mode (Word Count Mode) | <f11> W c | (wc-mode &optional ARG) | Toggle wc mode (Word Count mode). • When wc-mode is enabled on a buffer, it counts the current words in the buffer and keeps track of a differential of added or subtracted words. • A goal of number of words added/subtracted can be set while using this mode. Upon completion of the goal, the modeline text will highlight indicating that the goal has been reached. | |
| Set word goal | C-c C-w w | (wc-set-word-goal GOAL) | Set a goal for adding or removing words in the buffer. | |
| Set line goal | C-c C-w l | (wc-set-line-goal GOAL) | Set a goal for adding or removing lines in the buffer. | |
| Set character goal | C-c C-w a | (wc-set-char-goal GOAL) | Set a goal for adding or removing chars in the buffer. | |
| Count words | C-c C-w c | (wc-count &optional RSTART REND FIELD) | Count the words, lines and characters present in the region following point. This function follows most of the rules present in the ‘how-many’ function. If INTERACTIVE is omitted or nil, just return the word count, do not print it. Otherwise, if INTERACTIVE is t, the function behaves according to interactive behavior. • START and END specify the region to operate on. • When called interactively, this function first checks to see if it is in Transient Mark mode. If that is the case, then the function operates over the marked region. Otherwise, it will operate over the entire buffer. | |
| | | | | |
| Toggle writeroom-mode | <f11> W r r | (writeroom-mode &optional ARG) | Minor mode for distraction-free writing.  Requires writeroom-mode  activated by pel-use-writeroom-mode | |
| Increase width | <f11> W r + | (writeroom-increase-width) | Increase the width of the writing area by 2 characters. | |
| Decrease width | <f11> W r - | (writeroom-decrease-width) | Decrease the width of the writing area by 2 characters. | |
| Adjust width | <f11> W r 0 | (writeroom-adjust-width AMOUNT) | Adjust the width of the writing area on the fly by AMOUNT. • A numeric prefix argument can be used to specify the adjustment. • When called without a prefix, this will reset the width to the default value | |
| Toggle display of mode line | <f11> W r m | (writeroom-toggle-mode-line) | Toggle display of the mode line (shows modeline at the top of buffer). 👉 Since this command is allowed while the writeroom-mode is off, you can use it to add a modeline bar at the top of the current window. That window will then have 2 mode lines: one at the top and one at the bottom. | |
| | | | | |

| Operation | Keystroke | Function | Note | |
|---|-------------|---|---|--|
| my-whisper Transcribe speech to text All processing is local. | <f11> W w t | (my-whisper-transcribe & optional FAST-MODE-P) | Record audio and transcribe text in current buffer. <ul style="list-style-type: none"> By default, or when FAST-MODE-P is nil, use the model selected by the ‘my-whisper-model’ user-option. When FAST-MODE-P is non-nil use the fast mode, the model specified by ‘my-whisper-model-fast’. Record audio until you press C-g, then transcribes it and insert the text at point.  Requires my-whisper  activated by pel-use-my-whisper | |
| | | | | |