

ERT — Emacs Lisp Regression Testing

Description	Keystroke		Function	Note
<div>Using ERT</div> <div><div><div>○ Help & Customization</div><div>• Run tests interactively</div><div>• Byte Compile & run tests</div><div>• *ert* buffer commands</div><div>○ command line tests</div><div>• Emacs Lisp test code facilities</div><div>• ERT Reference</div></div></div>	<div>If you write Emacs Lisp code, writing unit test code normally helps increase code quality and maintainability. For 🔗🔗🔗 - Emacs Lisp</div> <div>ERT is a simple, yet powerful, environment to write test you can run from the command line and interactively inside Emacs with the ability to debug failing code.</div> <div><div><div>• ERT is part of Emacs standard distribution since Emacs 24.</div><div>• ERT provides a command to run tests that have been written using the ERT macros.</div><div>• Tests are normally written inside separate .el files, with names using the same prefix as the file being tested and also often placed inside a test directory.</div></div></div> <div>To run the test:</div> <div><div><div>1. Load the Emacs Lisp file that defines the tests. You can also visit and byte compile the file (with PEL: <f12> c b).</div><div><div>• With PEL you can use the <f12> 1 f or <f12> 1 v key bindings to load-file and pel-load-visited-file commands.</div><div>• See 🔗🔗🔗 - Emacs Lisp for more info.</div></div></div><div><div>2. Type M-x ert RET t RET.</div><div><div>• That executes the ert command described below and provides the selector t which means running every test.</div><div>• You can also use other regular expression that identify the names of the test functions to run:</div><div>• for example use “^foo-“ to run all tests that have a name that begins with foo-.</div></div></div><div>You can extend ERT testing capabilities with several external packages and libraries. PEL support the automatic installation and setup of the following ones. Just turn on the corresponding PEL user-option to install and activate them.</div><div><div><div>• Emacs Lisp language extension.</div><div>• Mocking Libraries</div><div>• Test coverage highlighting</div><div>• ERT test runner</div><div>• Alternative test frameworks</div></div></div><div><div>Last updated on:</div><div>2026-01-13</div><div><f12> ERT commands key bindings refer to kets typed inside an Emacs Lisp buffer. See more info in 🔗🔗🔗 - Emacs Lisp.</div></div></div>			
<div>Open this PDF file. See also: 🔗 Help/Info</div>	<f12> C-t <f1>	(pel-help-pdf &optional OPEN-WEB-PAGE)	Open the 🔗🔗 - ERT local PDF. If the prefix argument (like C-u or M--) is used, then it opens the remote GitHub hosted raw PDF instead. If the pel-flip-help-pdf-arg user-option is set it's the other way around.	
	<f11> SPC 1 C-t <f1>			
	<f12> <f2>	(pel-customize-pel &optional OTHER-WINDOW)	Customize PEL ERT support.	
<div>🔗 Customize PEL ERT support</div>	<f11> SPC 1 C-t <f2>		• If OTHER-WINDOW is non-nil (use C-u), display in another window.	
<div>🔗 Customize Emacs ERT support</div>	<f12> <f3>	(pel-customize-library &optional OTHER-WINDOW)	Customize Emacs ERT support: overlay, testcover, testcover-mark-line	
	<f11> SPC 1 C-t <f3>		• If OTHER-WINDOW is non-nil (use C-u), display in another window.	
<div>Run test interactively</div> <div>Extra 2 args, only available in Emacs < 29</div>	M-x ert	(ert SELECTOR &optional OUTPUT-BUFFER-NAME MESSAGE-FN)	Run the tests specified by SELECTOR and display the results in a buffer.	
			• SELECTOR works as described in 'ert-select-tests'. (Use t to run all tests, or name the test to execute.	
			• By default, the results are stored inside the *ert* buffer, opened in ERT-Results mode. ⚠️ ert does not save and byte compile the buffer before attempting to run the test. It must be done before. With PEL, use pel-run-test . See below.	
			The OUTPUT-BUFFER-NAME and MESSAGE-FN optional arguments were available until Emacs 29 . Starting at Emacs 29 they are no longer available. OUTPUT-BUFFER-NAME and MESSAGE-FN should normally be nil; they are used for automated self-tests and specify which buffer to use and how to display message.	
<div>Byte Compile and run Emacs Lisp tests</div>	<f12> C-t C-t	(pel-run-ert)	Byte compile and run ERT test on current 🔗🔗🔗 - Emacs Lisp buffer.	
			• Prompts if the buffer needs to be saved first.	
<div>*ert* buffer commands</div> <div>(Available from the *ert* buffer opened once art runs a test.)</div>	<div>In the *ert* buffer, the result of each test appears as a coloured character button:</div> <div><div><div>• A period . if the test passed. Coloured in green.</div><div>• A red upper case F if the test failed.</div><div>• A green lower case f if the test failed, but was expected to fail (the ert-deftest has a :expected-result :failed). Used to identify bugs not yet fixed.</div><div>• A red upper case P indicating a test passed but was expected to fail.</div><div>• While at a button you can issue other commands. The following single key commands are available when point is inside the buffer's window:</div></div></div>			
<div>Move to test</div>	TAB	(forward-button N &optional WRAP DISPLAY-MESSAGE)	Move point to the next test result button.	
<div>Re-run test</div>	r	(ert-results-rerun-test-at-point)	Re-run the same test	
<div>Jump to test source</div>	.	(ert-results-find-test-at-point-other-window)	Jump to the source code of the test (in another window)	
<div>List <i>should</i> forms</div>	l	(ert-results-pop-to-should-forms-for-test-at-point)	Shows the list of all <i>should</i> forms executed during the test before it failed	
<div>View backtrace</div>	b	(ert-results-pop-to-backtrace-for-test-at-point)	View the backtrace for the failed test at point	
<div>Re-run test with debugging</div>	d	(ert-results-rerun-test-at-point-debugging-errors)	Re-run the same test with debugging enabled	
<div>Show messages</div>	m	(ert-results-pop-to-messages-for-test-at-point)	Show what messages were printed before the test failed	
<div>Toggle condition printing</div>	L	(ert-results-toggle-printer-limits-for-test-at-point)	Toggle how much of the condition to print for the test at point.	
<div>Delete obsolete tests</div>	D	(ert-delete-test TEST-NAME)	Delete obsolete tests (test whose code might have changed)	
<div>Re-run all tests</div>	R	(ert-results-rerun-all-tests)	Re-run all tests, using the same selector	
<div>Move to the next test result</div>	n	(ert-results-next-test)	Move to the next test results.	
<div>Move to previous test result</div>	p	(ert-results-previous-test)	Move to the previous test results.	
<div>Jump between summary and result</div>	j	(ert-results-jump-between-summary-and-result)	Jump between test result and summary.	
			By positioning point on the test result character (., F or f) and then typing j point will move to the test summary (and will create one if the test passed). From the summary you can easily press RET to move point to the source code of the test (in another window).	
<div>Show help for test</div>	h	(ert-results-describe-test-at-point)	Get help for the test corresponding to the test result character (or test summary) at point.	
<div>Describe available commands</div>	?	(describe-mode &optional BUFFER)	Describe mode (and these commands)	
<div>Quit - close window</div>	q	(quit-window &optional KILL WINDOW)	Quit window - dismiss the *ert* popup buffer window.	

Description	Keystroke	Function	Note
Run Tests in Batch Mode	To execute tests from the command line, use Emacs in batch mode to load the specific tests and run them using one of the following ERT functions. <ul style="list-style-type: none">For example: <code>emacs -batch -l ert -l my-tests.el -f ert-run-tests-batch-and-exit</code>		
Run batch test	(ert-run-tests-batch &optional SELECTOR)	<ul style="list-style-type: none">Run the tests specified by SELECTOR, printing results to the terminal.	
	<ul style="list-style-type: none">SELECTOR works as described in 'ert-select-tests', except if SELECTOR is nil, in which case all tests rather than none will be run; this makes the command line "emacs -batch -l my-tests.el -f ert-run-tests-batch-and-exit" useful. Returns the stats object.		
Run batch tests and exit	(ert-run-tests-batch-and-exit &optional SELECTOR)	Like 'ert-run-tests-batch', but exits Emacs when done.	
	<ul style="list-style-type: none">The exit status will be 0 if all test results were as expected, 1 on unexpected results, or 2 if the tool detected an error outside of the tests (e.g. invalid SELECTOR or bug in the code that runs the tests).		
Emacs Lisp Test Code	Test code is written using forms that use the ert-deftest macro. See the following macro descriptions		
Define a test	(ert-deftest NAME () [DOCSTRING] [:expected-result RESULT-TYPE] [:tags '(TAG...)] BODY...)	Define NAME (a symbol) as a test. <ul style="list-style-type: none">BODY is evaluated as a 'progn' when the test is run. It should signal a condition on failure or just return if the test passes.'should', 'should-not', 'should-error' and 'skip-unless' are useful for assertions in BODY.Use 'ert' to run tests interactively.Tests that are expected to fail can be marked as such using :expected-result. See 'ert-test-result-type-p' for a description of valid values for RESULT-TYPE.	
The should macro	(should FORM)	Evaluate FORM. If it returns nil, abort the current test as failed. <ul style="list-style-type: none">Returns the value of FORM.	
The should-not macro	(should-not FORM)	Evaluate FORM. If it returns non-nil, abort the current test as failed. <ul style="list-style-type: none">Returns nil.	
The should-error macro	(should-error FORM &rest KEYS &key TYPE EXCLUDE-SUBTYPES)	Evaluate FORM and check that it signals an error.	
	<ul style="list-style-type: none">The error signaled needs to match TYPE. TYPE should be a list of condition names. (It can also be a non-nil symbol, which is equivalent to a singleton list containing that symbol.) If EXCLUDE-SUBTYPES is nil, the error matches TYPE if one of its condition names is an element of TYPE. If EXCLUDE-SUBTYPES is non-nil, the error matches TYPE if it is an element of TYPE.If the error matches, returns (ERROR-SYMBOL . DATA) from the error. If not, or if no error was signaled, abort the test as failed.		
The skip-unless macro	(skip-unless CONDITION)	Skip the current ert-deftest defined test unless CONDITION is non-nil. <ul style="list-style-type: none">Normally used to skip tests when the environment does not provide the necessary conditions for a valid test.	
The :expected-result tag	:expected-result <ul style="list-style-type: none">:failed:passed	Tag tests of lesser importances that are expected to fail potentially under some conditions. It can also be used to silence the report of a bug while leaving in the test. <ul style="list-style-type: none">See the documentation.	

Emacs Lisp Testing — References

Topic & Link	Description
ERT Manuals	
ERT : Emacs Lisp Regression Testing	ERT Manual, part of Emacs.
Test Coverage — Emacs Lisp	Test coverage section of the GNU Emacs Lisp manual
ERT Tools Repositories and Files	
pel-ert.el	pel-ert.el defines a set of equality predicates that accept extra arguments for the sole purpose of having them shown in the ERT report of a failed test. To see a set of <i>test environment</i> variables in the test report just pass them as extra arguments to these equality predicates.
testcover.el source	Source of the test coverage support
overseer.el @ GitHub	
ert-runner @ GitHub	
Emacs Lisp Mock @ EmacsWiki	The original location of that mock library that can be used with ert.
El mock @ GitHub	The new location for el-mock.el
emacs-noflet @ GitHub	External package that provides the noflet macro which can be used to re-define functions locally. Can be used in ERT testing. I created my own fork of this and integrated most long standing pull requests. See pierre-rouleau / emacs-noflet .
Articles/Blogs on ERT	Interesting articles to read before writing Emacs Lisp ERT testing code.
Quick intro to ert testing	A quick overview of ERT based Emacs Lisp testing.
Elisp Unit Testing with ERT	Quick overview of ERT in an August 2012 blog written by Chris Wellons. <ul style="list-style-type: none"> Since then the cl.el library was replaced by the cl-lib.el and the flet function was deprecated to cl-flet, but aside from these small items the description is still valid.
Make Flet Great Again	Another great post from Chris Wellons. <ul style="list-style-type: none"> Describes the new cl-flet and cl-letf, and how to use cl-letf to create Ert test that modify the behaviour of called functions.
ERT: Emacs Lisp Regression Testing	A nice description of the ERT features and techniques given at the NYC meetup. Describes: <ul style="list-style-type: none"> How to write a simple test, how to run the test and use the "ert" buffer commands. How to test expected errors with should-error
Continuous integration and code coverage for Emacs packages with Travis and Coveralls	An overview of automated Emacs Lisp unit testing with coverage measurement from Sacha Chua blog.
Reddit discussion: Testing in Emacs	Interesting discussion on testing under Emacs. Leads to several interesting projects: <ul style="list-style-type: none"> test-cockpit for testing code written in several programming languages under Emacs dape : Debug Adapter Protocol for Emacs stan-mode which uses buttercup for testing.
Other Unit Testing Support	Other packages and libraries for testing are not listed at the top of this page and currently not explicitly supported by PEL. Some are listed here.
• Unit Testing on EmacsWiki	Provides a list of alternatives to ERT with other testing-related information.
• emacs-test-simple @ GitHub	An Alternative to ERT developed by debugger expert R.Bernstein (see also here).
• undercover.el	A test coverage library for Emacs. Does not support byte-compilation nor circular objects. Meant to be used with Cask , Eask or Eldev .
Shell based unit test tools	
cram	A simple test system to test shell commands. cram is a command line tool that takes cram scripts stored in .t files. <ul style="list-style-type: none"> PEL supports the cram-mode when pel-use-cram-mode is turned on.
Emacs Lisp Concepts	Several Emacs Lisp concepts are useful when writing ERT test and mock ups.
Scoping Rules for Variable Bindings	When writing Emacs Lisp code and test with mockup in particular its important to fully understand the concepts of dynamic and lexical binding in Emacs Lisp. <p>⚠ Be aware that starting with version 27 of Emacs Lisp lexical binding is the default while dynamic binding was the default in previous versions.</p>

Topic & Link	Description
Github Continuous Integration	
• With Github Actions	<ul style="list-style-type: none">• Workflow syntax for GitHub Actions• Github Actions Runner Images : select the os environment• Setup Emacs for Github Actions : select the Emacs version