


















# Auto-Completion Support

| Description   | Keystroke  | Function   | Note  |
|---|--|--|---|
| <b>Auto Completion</b><br><ul style="list-style-type: none"> <li>Help @ Customization</li> <li>Display auto-completion info</li> <li>Select auto-completion mode</li> <li><b>Built-in completion</b></li> <li>completion-preview-mode</li> <li><b>External completion modes</b> <ul style="list-style-type: none"> <li>auto-complete</li> <li>company-mode</li> <li>corfu</li> </ul> </li> <li>Auto-completion Reference</li> </ul> <div>  Automatic activation of completion modes in specified major modes with PEL: <div>  </div> </div> | Emacs provides support for text completion, called <b>auto-completion</b> . <ul style="list-style-type: none"><li>Emacs provides a built-in auto-completion system, accessible via the (<b>completion-at-point</b>) command bound to <b>C-M-i</b> .</li><li>PEL supports the following external packages that provide alternative completion at point with pop-up menu:</li></ul>  |  |   |
|   |  <a href="#">auto-complete</a>  |  <a href="#">pel-use-auto-complete</a>  | The oldest external completion engine.  |
|   |  <a href="#">company-mode</a>   |  <a href="#">pel-use-company</a>  | A powerful completion engine.   |
|   |  <a href="#">corfu</a>  |  <a href="#">pel-use-corfu</a>  | Use <b>CO</b> mpletion in <b>Re</b> gion <b>FU</b> nction. A very powerful and popular auto-completion engine. Available for <b>Emacs</b> >= 29.1 only.   |
|   |  <a href="#">corfu-terminal</a>   |  <a href="#">pel-use-corfu-terminal</a>   | Use corfu popup in terminal <b>Emacs</b> < 31. PEL activates it when pel-use-corfu is on, but Emacs < 31 and runs in terminal mode.   |
|   | For these PEL supported modes, you can access the customization buffer quickly with the <f11> c <f2> key sequence.   |  |   |
|   | To activate an automatic completion mode for a major mode add one of the following special PEL functions to the list of minor modes listed in the major mode specific instance of:   |  |   |
|   |  <a href="#">pel-MODE-activates-minor-modes</a>   |  | Add one of the following special PEL functions that activate the corresponding engines: <ul style="list-style-type: none"><li>pel-auto-complete-mode, pel-company-mode, pel-corfu-mode</li></ul>  |
|   | <ul style="list-style-type: none"> <li>For example, add <a href="#">completion-preview-mode</a> and <a href="#">pel-company-mode</a> to  <a href="#">pel-elisp-activates-minor-modes</a> to automatically activate these in all Emacs Lisp buffers.</li> <li><b>Emacs</b> &gt;= 30 provides the <a href="#">completion-preview-mode</a> which provides an easy-to-use in-buffer completion help that complements the above.</li> </ul> <div>  More on abbreviation completion is available in the <a href="#">Abbreviations</a> table. <div> Both abbreviation completion and one auto-completion mechanism can be used at the same time (using different keys if any), in some case the abbreviation choices can also be available via auto-completion. </div> </div> <div>  More dynamic completion modes based on <a href="#">Eglot</a> or LSP are supported by Emacs but not yet documented in PEL. </div> |  |   |
|   | Last updated on: 2025-12-19  |  |   |
| <b>Open this PDF file.</b><br>See also: <a href="#">ℹ Help/Info</a>   | <f11> c <f1>   | ( <a href="#">pel-help-pdf</a> &optional OPEN-WEB-PAGE)  | Open the <a href="#">ℹ Auto-Completion</a> local PDF. If the prefix argument (like <b>C-u</b> or <b>M--</b> ) is used, then it opens the remote GitHub hosted raw PDF instead. If the <a href="#">pel-flip-help-pdf-arg</a> user-option is set it's the other way around.   |
| <b>Customize PEL auto-completion support.</b><br>See also: <a href="#">ℹ Customize</a>  | <f11> c <f2>   | ( <a href="#">pel-customize-pel</a> &optional OTHER-WINDOW)  | Open the PEL customize group(s) for the current context: auto-completion support. Use this to open to change PEL user option variables the activate and control the various Apple script features such as the name of the narrator voice. <ul style="list-style-type: none"><li>When a prefix argument (like <b>C-u</b>) opens the buffer inside another window.</li></ul>  |
| <b>Customize Emacs built-in auto-completion support</b><br>See also: <a href="#">ℹ Customize</a>  | <f11> c <f3>   | ( <a href="#">pel-customize-library</a> &optional OTHER-WINDOW)  | Customize Emacs auto-completion group which includes: auto-complete, company, hippie-expand. When prefix arg. (like <b>C-u</b> ) opens the buffer inside another window.  |
|   |  Group belonging to files that have not yet been loaded are normally not accessible in Emacs and via the customize-group command. PEL, however, attempts to locate the file that defines a non-loaded customization group and will prompt you for loading the file if it finds it.  |  |   |
| <b>Display Auto-completion info: status and configuration</b><br><br><div>  Provides quick access buttons to change customizable user-options. </div>  | <f11> c ?  | ( <a href="#">pel-completion-info</a> &optional APPEND)  | Print information about available auto-completion info in a "pel-autocomplete-info" <a href="#">help-mode</a> buffer. Clear previous buffer content unless a prefix arg (like <b>C-u</b> ) is used.   |
|   | <ul style="list-style-type: none"> <li>Prints current state and values of relevant user-options as buttons you can use to get more info and change their customized values.</li> <li>Shows which one is enabled via customization and their current activation state.</li> <li> Underlines links are buttons that open the customization buffer where you can change the customized value.</li> </ul>   |  |   |
| <b>Select auto-completion mode</b>  | <f11> c =  | ( <a href="#">pel-select-auto-complete-tool</a> &GLOBALLY)   | Prompt user to select auto-completetion mode to use in current buffer. <ul style="list-style-type: none"><li>With prefix arg (such as <b>C-u</b>) select for all buffers.</li></ul> Select: Emacs built-in auto-completion, <a href="#">auto-complete</a> , <a href="#">company-mode</a> , <a href="#">corfu</a> .  |
| <b>Emacs Built-in Completion</b>  | Emacs built-in completion is provided by the <a href="#">completion-at-point</a> command, described below. <ul style="list-style-type: none"><li>This automatic text completion is always available but can be extended or overridden by mechanisms used by the external auto-completion packages.</li><li>The <a href="#">pel-completion-info</a> command prints the values of the various variables and user-options controlling its behaviour.</li></ul>  |  |   |
| <b>Symbol Completion at point</b><br>See also: <a href="#">ℹ Xref</a>   | <ul style="list-style-type: none"> <li><b>C-M-i</b></li> <li><b>&lt;Esc&gt; &lt;tab&gt;</b></li> <li><b>M-&lt;tab&gt;</b></li> </ul>   | ( <a href="#">completion-at-point</a> )  | Perform completion on the text around point. <ul style="list-style-type: none"><li>The completion method is determined by '<a href="#">completion-at-point-functions</a>'.</li><li>The tags-completion-at-point-function is used for Emacs Lisp code by default.<ul style="list-style-type: none"><li>It provides a list of possible values in the "Completions" buffer.</li><li>The key bindings to select from "completions" buffer are shown below.</li></ul></li></ul>  |
|   |  <b>C-M-i</b> is also used for Flyspell, which can be used to spell check only moments and strings.   |  |   |
| <b>Symbol Completion at point and language specific completion</b>  | <f6> c   | ( <a href="#">complete-symbol</a> ARG)   | Perform completion of the text around point, using the method identified by the variable <b>completion-at-point-functions</b> , acting as the <b>completion-at-point</b> command above. <ul style="list-style-type: none"><li>With prefix argument, such as <b>C-u</b>, this does completion within the collection of symbols listed in the index of the manual for the language you are using.</li></ul>   |
| <b>Complete language specific symbol at point</b>   | <f6> C   | ( <a href="#">info-complete-symbol</a> &optional MODE)   | Perform completion of symbol at point using mode-specific language items. <ul style="list-style-type: none"><li>For example, inside a Emacs-Lisp buffer it finds the Emacs-Lisp functions, variables names.</li></ul>   |
| <b>Completion function - using tags</b><br>Candidate for: completion-at-point-functions   |  | ( <a href="#">tags-completion-at-point-function</a> )  | Using tags, return a completion table for the text around point. If no tags table is loaded, do nothing and return nil. This uses the tag facility.   |
| <b>Toggle Completion Preview mode</b><br><b>Emacs</b> >= 30   | The completion preview mode is a minor mode available since Emacs 30. It completes the current symbol with overlay when possible.  |  |   |
| <div> A minor mode that shows possible completion in a light face. Can be available while another completion major-mode is used. </div> <div>  The following keys are available whenever the "Completions" buffer shows a list of potential completions. The keys are typed at point, there's no need to switch to the window of the "Completion" buffer. </div> <div>  These are available for <a href="#">completion preview</a> but also for <a href="#">completion-at-point</a>. </div>   | <f11> c p  | ( <a href="#">completion-preview-mode</a> &optional ARG)   | Toggle completion-preview-mode in current buffer. <ul style="list-style-type: none"><li>Activate it with positive prefix argument, disable it with negative prefix argument.</li></ul>  |
|   | <f11> c P  | ( <a href="#">global-completion-preview-mode</a> &optional ARG)  | Toggle Completion-Preview mode in all buffers. <ul style="list-style-type: none"><li>Activate it with positive prefix argument, disable it with negative prefix argument.</li></ul>   |
|   | <tab>  | Expand suggested completion in buffer. Type more characters to further refine the search.  |   |
|   | <b>M-i</b>   | Open a "Completion" buffer listing all possible completion candidates. Does not move point. <ul style="list-style-type: none"><li>Select other candidate show in the "Completion" buffer with <b>M-&lt;up&gt;</b> and <b>M-&lt;down&gt;</b>. Then chose one with <b>M-RET</b>.</li></ul> |   |
|   | <b>M-&lt;down&gt;</b>  | ( <a href="#">minibuffer-next-completion</a> &optional N VERTICAL)   | Selects and show next completion candidate. <ul style="list-style-type: none"><li>Move by N positions with <a href="#">numeric prefix</a> N</li></ul>   |
|   | <b>M-&lt;up&gt;</b>  | ( <a href="#">minibuffer-previous-completion</a> &optional N)  | Selects and show previous completion candidate. <ul style="list-style-type: none"><li>Move by N positions with <a href="#">numeric prefix</a> N</li></ul>   |
|   | <b>M-RET</b>   | ( <a href="#">minibuffer-choose-completion</a> &optional NO-EXIT NO-QUIT)  | Select candidate.<br>Run 'choose-completion' from the minibuffer in its completions window. <ul style="list-style-type: none"><li>With prefix argument NO-EXIT, insert the completion candidate at point to the minibuffer, but don't exit the minibuffer. When the prefix argument is not provided, then whether to exit the minibuffer depends on the value of 'completion-no-auto-exit'.</li><li>If NO-QUIT is non-nil, insert the completion candidate at point to the minibuffer, but don't quit the completions window.</li></ul> |

| Description  | Keystroke  | Function       | Note   |
|--|--|----------------|--|
| <b>Other completion at point engines</b> <div>  </div>  | PEL dynamically activate either <code>auto-complete-mode</code> , <code>company-mode</code> and <code>corfu</code> for one or all buffers through commands accessible via the <code>&lt;f11&gt;c</code> prefix. <ul style="list-style-type: none"> <li> You must first select witch one should be available via PEL customization:               <ul style="list-style-type: none"> <li>Set <b>pel-use-auto-complete</b> to <code>t</code> to enable the ability to use <code>auto-complete-mode</code>.</li> <li>Set <b>pel-use-company</b> user option to <code>t</code> to enable the ability to use <code>company-mode</code>.</li> </ul> </li> <li>When <b>pel-init</b> is executed, the commands made available depend on the section made by customization of PEL but also of the two modes. Then the corresponding commands listed in the sections below are available.</li> </ul> PEL's auto-completion support implementation is not yet completed. For now just standard hooks are setup, but not for all programming languages. Support for each programming language is described in the language specific page.   |                |  |
| <b>Explicitly List Completion Candidates with the currently active auto completion system</b> <ul style="list-style-type: none"> <li>Use <code>auto-complete</code> or <code>company-mode</code>, whichever that is currently active globally or in the buffer.</li> </ul>     | <ul style="list-style-type: none"> <li><code>&lt;f11&gt; c c</code></li> <li><code>M-l</code></li> </ul>   | (pel-complete) | List completion candidates. There must be at least 1 character preceding point. <ul style="list-style-type: none"> <li>Force auto-completion of text at point, don't wait for timeout, using the currently active auto-completion system (either <code>auto-complete-mode</code> or <code>company-mode</code>).</li> </ul> |
|  | <ul style="list-style-type: none"> <li>If no auto completion system is active in the current buffer, the command issues an error.</li> <li> <code>M-l</code> default binding is to downcase-word. PEL rebinds this key <code>company-mode</code> is activated via customization and <code>company-mode</code> is active.</li> <li> With PEL, the <code>M-l</code> key is close to the <code>M-/</code> key, bound to the command used for abbreviation expansions. It becomes easy to use either.</li> </ul>   |                |  |
| <b>Completion Menu keys</b> <ul style="list-style-type: none"> <li><b>Auto-completion Menu Operations</b></li> <li><b>Company-Mode Menu Operations</b></li> </ul> See also:  <b>Scrolling</b> | When an completion pop-up menu generated <b>either</b> by <code>auto-complete</code> or <code>company-mode</code> is shown, you can use the following keys for operating on that menu: <ul style="list-style-type: none"> <li><code>M-n</code> : next candidate (or <code>&lt;down&gt;</code> cursor)</li> <li><code>M-p</code> : previous candidate (or <code>&lt;up&gt;</code> cursor)</li> <li><code>M-1</code>, <code>M-2</code>, <code>M-3</code>, etc...: select candidate by line number</li> <li><code>&lt;tab&gt;</code> : complete using 1 candidate (if 1 choice), using the prefix part among many candidates, or cycle through all candidates.</li> <li><code>&lt;DEL&gt;</code> : Delete 1 char of the current candidate prefix</li> <li><code>&lt;RET&gt;</code> : Select current candidate, execute action for candidate if any (eg. when template selection used)</li> <li><code>C-?</code> : Show candidate help in separate buffer</li> <li><code>&lt;f1&gt;</code> : Show candidate help in separate buffer.  This is <b>very</b> handy to quickly review documentation of several symbols!</li> <li><code>C-M-v</code> : Scroll help buffer forward (note: see the  <b>Scrolling</b> table for more info on scrolling)</li> <li><code>Esc &lt;PgDown&gt;</code> : Scroll help buffer forward</li> <li><code>C-M-S-v</code> : Scroll help buffer backward</li> <li><code>Esc &lt;Pg-up&gt;</code> : Scroll help buffer backward</li> <li><code>C-g</code> : Stop completion</li> </ul> |                |  |
| <b>auto-complete</b> <ul style="list-style-type: none"> <li>For Emacs &gt;= 25.1</li> </ul> <div>  A bug affects auto-complete on Emacs 30: <a href="#">bug 76430</a> </div>                  | Auto-Complete is the oldest of the 3 external auto-completion supported by PEL. <div>  Requires the <a href="#">auto-complete</a> package  that PEL supports if the <b>pel-use-auto-complete</b> customization variable is set to <code>t</code>.         </div> <div>           Completion done by <a href="#">auto-complete</a> pops a drop-down menu when invoked by:           <ul style="list-style-type: none"> <li><code>&lt;f11&gt; c c</code></li> <li><code>M-l</code></li> </ul>           The other key bindings are still bound to the built-in completion-at-point command which brings up the "Completions" buffer:           <ul style="list-style-type: none"> <li><code>C-M-i</code></li> <li><code>&lt;Esc&gt; &lt;tab&gt;</code></li> <li><code>M-&lt;tab&gt;</code></li> </ul> </div> <div>  </div>   |                |  |
| <b>company-mode</b> <ul style="list-style-type: none"> <li>For Emacs &gt;= 26.1</li> </ul>   | Company-Mode is the other auto completion package supported by PEL. <div>  Requires the <a href="#">company-mode</a> external package  that PEL activates when the <b>pel-use-company</b> customization variable is set to <code>t</code>.         </div> <ul style="list-style-type: none"> <li>Available for Emacs &gt;= 26.1 only.</li> </ul> <div>           The completion done by <a href="#">company-mode</a> pops a drop-down menu with categorized entries (<b>f</b>: function, <b>k</b>: macro, <b>v</b>: variable) and entry index.           <div>  </div> </div> <div>           The menu pops up on:           <ul style="list-style-type: none"> <li>automatic, by timeout</li> <li>manual by typing:               <ul style="list-style-type: none"> <li><code>C-M-i</code></li> <li><code>&lt;Esc&gt; &lt;tab&gt;</code></li> <li><code>M-&lt;tab&gt;</code></li> <li><code>&lt;f11&gt; c c</code></li> <li><code>M-l</code></li> </ul> </li> </ul> </div>  |                |  |
| <b>corfu</b><br><b>CO</b> mpletion in <b>Re</b> gion <b>FU</b> nction. <ul style="list-style-type: none"> <li>For Emacs &gt;= 29.1</li> </ul>  | <div>  Requires the <a href="#">corfu</a> external package  activated by <b>pel-use-corfu</b>. A very powerful, popular and extensible auto-completion engine.         </div> <ul style="list-style-type: none"> <li>Available for Emacs &gt;= 29.1 only.</li> </ul> <div>           The completion done by <a href="#">corfu</a> pops a drop-down menu as shown at right.           <div>  </div> </div> <div>           The menu pop up on:           <ul style="list-style-type: none"> <li>automatic, by timeout</li> <li>manual by typing:               <ul style="list-style-type: none"> <li><code>C-M-i</code></li> <li><code>&lt;Esc&gt; &lt;tab&gt;</code></li> <li><code>M-&lt;tab&gt;</code></li> <li><code>&lt;f11&gt; c c</code></li> <li><code>M-l</code></li> </ul> </li> </ul> </div>   |                |  |

Auto-completion — References

| Document   | Note   |
|--|--|
| Basic Auto Completion  | GNU Emacs Manual - Completion for Symbol Names   |
| Auto Completion with Auto-Complete                                     |  |
| Auto Complete @ MELPA  | You can get auto-complete from MELPA. An interesting point of this page lists the other packages that need auto-complete. There's over 45 packages that use it for various programming languages and environments. |
| Auto Complete @ GitHub   | Auto complete source code  |
| Auto Complete Manual @ Github  | Covers installation, check, features, concepts, configuration, advanced usage. Reading required for users.   |
| Using Emacs: 8 - Auto-complete @ Youtube                               | Mike Zamansky video that covers abbreviation and auto-complete. Duration: 5 minutes.   |
| Using Emacs: 45- Company or Autocomplete @ Youtube                     | Another video from Mike Zamansky that covers both auto-complete and company-mode. Duration: 13 minutes.  |
| Auto Completion with Company-mode                                      |  |
| company-mode ; Modular in-buffer completion framework for Emacs        | Text completion framework for emacs  |
| Using digits to select company-mode candidates @ (or emacs irrelevant) |  |