

Tramp - Emacs Remote File Editing

Operation	Keystroke	Function	Note
Tramp <ul style="list-style-type: none"> Tramp @ wikiEmacs tramp-mode @ Emacs Wiki Tramp FAQ 	Emacs can open file located on a remote computer. Use a command to visit (open) a file and provide a file name that uses the Tramp-specific format (explained below) to identify the network protocol, user name, hostname and the file name of the remote computer.		
Troubleshooting Tramp <p>See also:</p> <ul style="list-style-type: none"> Remote shell setup hints 	<ul style="list-style-type: none"> If the shell prompt of the remote shell is complex, Tramp might not be able to connect and will timeout. There are 2 potential solutions to this problem: <ul style="list-style-type: none"> Update the regular expression specified by the tramp-shell-prompt-pattern user-option. Configure the shell to use a simple prompt that has no escape sequence. The simpler the better. <ul style="list-style-type: none"> Tramp set the TERM environment variable to "dumb", therefore you can modify your shell configuration code (in ~/.bashrc, ~/.zshrc or whatever your shell uses) to select a simple prompt when TERM is dumb as in the following: <pre>if ["\$TERM" == "dumb"]; then PS1='\$ ' else ...</pre> <p>On zshrc you may want to add the following line:</p> <pre>[["\$TERM" == "dumb"]] && unsetopt zle && PS1='\$ ' && return</pre>		
<ul style="list-style-type: none"> Activate Tramp Trace buffer 	If the above fails, you will need to debug Tramp and look into the Tramp tracing: <ul style="list-style-type: none"> Set tramp-verbose user option to 10 to activate the tramp debug buffer. <ul style="list-style-type: none"> See ELisp evaluation in Part 1 - Emacs Lisp for various ways of setting Emacs Lisp variables. Look at the Tramp debug trace to identify the problem. <ul style="list-style-type: none"> Locate the ssh command issued by Tramp and try it manually to see what it does. If that fails, try the above with. a clean Emacs started with emacs -Q 		
<ul style="list-style-type: none"> Remote File format <ul style="list-style-type: none"> Quoted file names 	/method:host:filename /method:user@host:filename /method:user@host#port:filename	method is: ftp , scp , ssh or - . If it is -, the tramp selects the method as follows: <ul style="list-style-type: none"> If the host name starts with 'ftp.' (with dot), Emacs uses FTP. If the user name is 'ftp' or 'anonymous', Emacs uses FTP. If the variable tramp-default-method is set to 'ftp', Emacs uses FTP. If ssh-agent is running, Emacs uses scp. Otherwise, Emacs uses ssh. 	If you want to access a <i>local</i> file that has the syntax corresponding to the remote file name syntax, then you need to quote the file name by adding /: at the beginning of the file name.
Open this PDF file. See also: 🔗 Help/Info	<f11> p tramp	(pel-help-pdf-select &optional OPEN-GITHUB-PAGE-P)	Open the 🔗 Tramp local PDF. If the prefix argument (like C-u or M--) is used, then open remote GitHub hosted raw PDF instead. If pel-flip-help-pdf-arg user-option is set it's the other way around.
🔗 Customize Tramp	<f11> <f2> g	(customize-group &optional GROUP OTHER-WINDOW)	Open the tramp customization group.
Open a file on remote computer See: 🔗 File-mngt	<ul style="list-style-type: none"> <f11> f f M-<f11> M-f M-f C-x C-f 	(find-file FILENAME &optional WILDCARDS) (ido-find-file)	Prompt for the file name. <ul style="list-style-type: none"> Enter a file name that corresponds to the remote file name syntax, as described above. Completion is available, as usual. <ul style="list-style-type: none"> Type / first and then the <i>method</i> followed by :

Tramp— References

Topic & Link	Notes
Tramp Quick Start Guide	Short Introduction how to use TRAMP from the Emacs User Manual
Tramp User Manual	Tramp User Manual.
Tramp Mode @ Emacs Wiki	
Tramp @ Stack Overflow	There's several Q&A about tramp.
Tramp @ Emacs StackExchange	And on Emacs Stack Exchange too.
Reddit Emacs has some discussion on Tramp	<ul style="list-style-type: none"> Has TRAMP ever work for you flawlessly? Tramp another "waiting for prompts from remote shell...failed"