


Closing/Suspending and the Emacs Server

Operation	Keystroke	Function	Note
Close emacs	C-x C-c	(save-buffers-kill-terminal &optional ARG)	Offer to save each modified buffer, then kill the current connection, run all final hooks and close Emacs.
Close emacs	⌘-q	(save-buffer-kill-emacs &optional ARG)	<div>  On macOS in graphics mode only: offer to save each modified buffer, then kill the Emacs graphics application. </div>
Suspend Emacs	<ul style="list-style-type: none"> C-x C-z C-z 	(suspend-frame)	<p>Normally C-z is mapped for this operation, however, in cua-mode, C-z is mapped to (undo) , which is useful.</p> <p>To use the cua-mode using C-x C-z is a good alternative.</p> <p>▀ This command is useful when Emacs is running in terminal (tty) mode to quickly go to the shell from outside Emacs. In graphics mode it just hides the frame.</p>

Emacs Server Emacs Client Client Options	<ul style="list-style-type: none"> Start an Emacs daemon (server) with: <code>emacs --daemon</code> Connect a terminal to the server with: <code>emacsclient -t</code> Connect a graphical client to the server with: <code>emacsclient -c</code> 		
Stop Emacs Server	M-x pel-shutdown-server	(pel-shutdown-server)	Prompt to save buffers then stop/kill Emacs server. <ul style="list-style-type: none"> If the current Emacs session is not using an Emacs server the command issues an error and does not stop Emacs. If the current session is a client attached to an Emacs server it prompts further static that this will close all current clients, giving you the chance to cancel before it's too late.

Enable/Disable Commands

Disabling/Enabling Commands	Some Emacs commands (like C-x n n for narrowing) are disabled by default because they might be confusing for new Emacs users. Its possible to enable or disable commands using the following commands.		
Enable a command	M-x enable-command	(enable-command COMMAND)	Allow COMMAND to be executed without special confirmation from now on. COMMAND must be a symbol. <ul style="list-style-type: none"> This command alters the user's .emacs file so that this will apply to future sessions. <ul style="list-style-type: none"> It adds a (<i>put 'COMMAND 'disabled t</i>) inside the emacs init file.
Disable a command	M-x disable-command	(disable-command COMMAND)	Require special confirmation to execute COMMAND from now on. COMMAND must be a symbol. <ul style="list-style-type: none"> This command alters your init file so that this choice applies to future sessions. <ul style="list-style-type: none"> It adds a (put 'COMMAND 'disabled nil) inside the emacs init file.