










Abbreviations/Expansions

Operation	Keystroke	Function	Note
Abbreviations	Emacs supports several text abbreviation expansion mechanisms. <ul style="list-style-type: none"> There's manual and dynamic abbreviation expansion modes: <ul style="list-style-type: none"> In the dynamic expansion modes, the abbreviations and expansions are determined automatically from the content of the current buffer (for DAbbrev) and from various, configurable sources (for Hippie). The manual mode is the Abbrev minor mode. In this mode you have to define the abbreviations and the matching expansion either explicitly or via a special spell checking command. It's possible to use a dynamic expansion mode as well as a manual expansion. They use different commands (and key bindings). Emacs also support template expansion packages, not covered here. See 🔗 Inserting Text for mechanisms like yasnippet.		
Open this PDF file. See also: 🔗 Help/Info	<f11> a <f1>	(pel-help-pdf &optional OPEN-WEB-PAGE)	Open the 🔗 Abbreviations local PDF. If the prefix argument (like C-u or M--) is used, then it opens the remote GitHub hosted raw PDF instead. If the pel-flip-help-pdf-arg user-option is set it's the other way around.
Open PEL abbreviation customization group. See also: 🔗 Customize	<f11> a <f2>	(pel-customize-pel &optional OTHER-WINDOW)	Open the PEL customize group(s) for the current context. Use this to open to change PEL user option variables the activate and control the various abbreviations features. <ul style="list-style-type: none"> When a prefix argument (like C-u) opens the buffer inside another window.
Customize Emacs built-in abbreviation support See also: 🔗 Customize	<f11> a <f3>	(pel-customize-library &optional OTHER-WINDOW)	Customize Emacs abbrev group which includes: abbrev-mode, dynamic-abbreviations, expand, hippie-expand, quickurl. <ul style="list-style-type: none"> When a prefix argument (like C-u) opens the buffer inside another window. Group belonging to files that have not yet been loaded are normally not accessible in Emacs and via the customize-group command. PEL, however, attempts to locate the file that defines a non-loaded customization group and will prompt you for loading the file if it finds it.
Dynamic Text Expansion: <ul style="list-style-type: none"> dabbrev-expand hippie-expand 	The <i>dynamic</i> expansion mode refers to the dynamic identification of the fully expanded text for partial text. <ul style="list-style-type: none"> Emacs supports two built-in dynamic expansion commands: dabbrev-expand and hippie-expand. The hippie-expand provides the same functionality as dabbrev-expand but it also includes more selectable sources of abbreviation/expansions. <div>  The M-/ key is bound to dabbrev-expand by default. PEL remaps it to hippie-expand when pel-use-hippie-expand user-option is set to t. </div> <p>The following commands are available to explicitly request expansion of an abbreviation.</p>		
Expand Abbreviation	M-/	(dabbrev-expand ARG)	Expand previous word “dynamically”. Used in DAbbrev mode. <div>  PEL activates this when the pel-use-hippie-expand user option is set to nil </div> <ul style="list-style-type: none"> Expands to the most recent, preceding word for which this is a prefix. If no suitable preceding word is found, words following point are considered. If still no suitable word is found, then look in the buffers accepted by the function pointed out by variable ‘dabbrev-friend-buffer-function’, if ‘dabbrev-check-other-buffers’ says so. Then, if ‘dabbrev-check-all-buffers’ is non-nil, look in all the other buffers, subject to constraints specified by ‘dabbrev-ignored-buffer-names’ and ‘dabbrev-ignored-regexps’. A positive prefix argument, N, says to take the Nth backward “distinct” possibility. A negative argument says search forward. If the cursor has not moved from the end of the previous expansion and no argument is given, replace the previously-made expansion with the next possible expansion not yet tried. The variable ‘dabbrev-backward-only’ may be used to limit the direction of search to backward if set non-nil.
	M-/ <div>See also: 🔗 Hide/Show</div> M-/ M-/	(hippie-expand ARG)	Try to expand text before point, using multiple methods. The expansion functions in ‘ <i>hippie-expand-try-functions-list</i> ’ are tried in order, until a possible expansion is found. Repeated application of ‘hippie-expand’ inserts successively possible expansions. With a positive numeric argument, jumps directly to the ARG next function in this list. With a negative argument or just C-u , undoes the expansion. <div>  PEL activates this when the pel-use-hippie-expand user option is set to t. </div> <div> When the origami-mode is active, hippie-expand is re-mapped to this key binding. The origami-mode is a code folder mode. See 🔗 Hide/Show </div>
Find all possible expansions	C-M-/	(dabbrev-completion &optional ARG)	Completion on current word. <ul style="list-style-type: none"> Like M-/ but finds all expansions in the current buffer and presents suggestions for completion. With a prefix argument ARG, it searches all buffers accepted by the function pointed out by ‘dabbrev-friend-buffer-function’ to find the completions. If the prefix argument is 16 (which comes from C-u C-u), then it searches “all” buffers.
Manual Abbreviation: Abbrev Mode	Emacs abbreviation system performs abbreviation expansions when the abbrev minor mode is active in the current buffer. <ul style="list-style-type: none"> Association of abbreviation to the fully expanded text must be defined explicitly with commands identified in the section “Creating Abbreviations” below. <div>  The abbreviations are stored in a file identified by the <i>abbrev-file-name</i> user option, which is “~/emacs.d/abbrev_defs” by default. <ul style="list-style-type: none"> When Emacs terminates, it will prompt for saving the new abbreviations. You can change that by setting the <i>save-abbrevs</i> user option to silently instead of t. </div> <div>  Emacs load the abbreviation file at init time. As its size grows, the load time increases and that slows down Emacs startup time. <div>   PEL delays the loading of the abbreviation file by temporary changing the value of abbrev-file-name, loading it silently after initialization. <ul style="list-style-type: none"> PEL installation instructions describe the required code; see the PEL Manual section Delay Loading of Abbreviation Definition File. </div> </div> <div>  To automatically activate abbrev-mode for some major modes, add the name of these major modes to the pel-modes-activating-abbrev-mode user-option. Access the appropriate customize buffer with the <f11> a <f2> key sequence. </div>		
Toggle Abbrev mode	<f11> a a	(abbrev-mode &optional ARG)	Toggle the Abbrev mode in current buffer. <ul style="list-style-type: none"> Once the Abbrev mode is activated in a buffer, you can type the abbreviation then a space or punctuation (comma, period, return, etc...) will automatically expand the abbreviation to its complete expansion.
Creating Abbreviations	To define an abbreviation , position point after the word(s) that define the target expansion and use: <ul style="list-style-type: none"> C-x a g to define the abbreviation globally or C-x a l to define the abbreviation for the current mode only. In both cases Emacs prompts for the corresponding abbreviation. <p>The inverse method is to position the cursor after the abbreviation text in the buffer and</p> <ul style="list-style-type: none"> use C-x a i g to define the target expansion globally or use C-x a i l to define it for the current mode only (local). <p>The explicit commands prompt for the abbreviation and its expansion. The define-global-abbrev defines abbreviations that are accessible from all buffers while the define-mode-abbrev defines abbreviations that are only active in the buffer using the current major mode.</p> <div>  Take advantage of the spell check mechanism to identify <i>abbreviations</i> that really are spell checking fixes by using the command pel-ispell-word-then-abbrev when you detect a spelling error either manually, or through flyspell with flyspell-auto-correct-word. </div>		
Define an abbreviation	<ul style="list-style-type: none"> C-x a g <f11> a g 	(add-global-abbrev ARG)	Define global (all modes) abbrev for last word(s) before point. <ul style="list-style-type: none"> Prompts for the abbreviation that will be used when the abbrev-mode is used. The prefix argument specifies the number of words before point that form the expansion; or zero means the region is the expansion. A negative argument means to undefine the specified abbrev. This command uses the minibuffer to read the abbreviation.

Operation	Keystroke	Function	Note
Define an abbreviation for the current mode only	<ul style="list-style-type: none"> C-x a 1 C-x a + C-x a C-a <f11> a 1 	(add-mode-abbrev ARG)	Define mode-specific abbrev for last word(s) before point. <ul style="list-style-type: none"> Argument is how many words before point form the expansion; or zero means the region is the expansion. A negative argument means to undefine the specified abbrev. Reads the abbreviation in the minibuffer.
Define expansion	<ul style="list-style-type: none"> C-x a i g C-x a - 	(inverse-add-global-abbrev N)	Define last word before point as a global (mode-independent) abbrev. <ul style="list-style-type: none"> With prefix argument N, defines the Nth word before point. This command uses the minibuffer to read the expansion. Expands the abbreviation after defining it.
Define expansion for the current mode only	C-x a i 1	(inverse-add-mode-abbrev N)	Define last word before point as a mode-specific abbrev. <ul style="list-style-type: none"> With prefix argument N, defines the Nth word before point. This command uses the minibuffer to read the expansion. Expands the abbreviation after defining it.
Explicitly define global abbreviation/expansion	<f11> a G	(define-global-abbrev ABBREV EXPANSION)	Define ABBREV as a global abbreviation for EXPANSION. Prompts for both. <ul style="list-style-type: none"> The characters in ABBREV must all be word constituents in the standard syntax table.
Explicitly define local abbreviation/expansion	<f11> a L	(define-mode-abbrev ABBREV EXPANSION)	Define ABBREV as a mode-specific abbreviation for EXPANSION. Prompts for both. <ul style="list-style-type: none"> The characters in ABBREV must all be word-constituents in the current mode.
Fix spelling mistake before point <ul style="list-style-type: none"> Add old->new in the abbreviation table See also: ☞ Spell Checking	<ul style="list-style-type: none"> <f11> a \$ <f11> M-\$ 	(pel-ispell-word-then-abbrev &optional LOCALLY)	Fix spelling mistake in text before point. 👉 A similar operation is possible with flyspell. See flyspell-auto-correct-word .
	<ul style="list-style-type: none"> Create an 'abbrev' abbreviation for it. Store the abbreviation globally unless the LOCALLY argument is non-nil, in which case store it in the local abbreviation list. If there's nothing wrong with the word at point, keep looking for a typo until the beginning of buffer. You can skip typos you don't want to fix with 'SPC', and you can abort completely with 'C-g'. 		
Deleting Abbreviations	To remove all global and local abbreviations, type M-x kill-all-abbrevs		
Delete all abbreviations		(kill-all-abbrevs)	Undefine all defined abbrevs. Deletes both globals and locals (current mode specific) ones.
Manual Expansion of Abbreviations	The following commands expand the abbreviations created manually.		
Expand abbreviation with prefix	M- '	(abbrev-prefix-mark &optional ARG)	Mark current point as the beginning of an abbrev. <ul style="list-style-type: none"> Abbrev to be expanded starts here rather than at beginning of word. 👉 See the EmacWiki Abbrev Prefixes for very nice example on how to use this.
	<ul style="list-style-type: none"> This way, you can expand an abbrev with a prefix: insert the prefix, use this command, then insert the abbrev. This command inserts a temporary hyphen after the prefix (until the intended abbrev expansion occurs). If the prefix is itself an abbrev, this command expands it, unless ARG is non-nil. Interactively, ARG is the prefix argument. If you just want to expand an abbreviation, type the abbreviation and then type M- ' . The command will expand and append a '- character that you can then delete if you don't need it. If you want expand a word with a prefix type the prefix, type M- ' , then type the abbreviation and type M- ' again.		
Expand abbreviation	<ul style="list-style-type: none"> C-x a e <f11> a e <f11> / 	(expand-abbrev)	Expand the abbrev before point, if there is an abbrev there. 👉 This can be used to expand skeleton abbreviations.
Expand abbreviations in region	<f11> a E	(expand-region-abbrevs START END &optional NOQUERY)	<ul style="list-style-type: none"> For abbrev occurrence in the region, offer to expand it. The user is asked to type 'y' or 'n' for each occurrence. A prefix argument means don't query; expand all abbrevs.
Undo last expansion	<f11> a u	(unexpand-abbrev)	Undo the expansion of the last abbrev that expanded. <ul style="list-style-type: none"> This differs from ordinary undo in that other editing done since then is not undone.
Editing Abbreviations	Use the following commands to list all existing abbreviations and modify them inside the *Abbrevs* buffer. <ul style="list-style-type: none"> The abbrevs editing buffer contains a header line for each abbrev table, which is the abbrev table name in parentheses. This is followed by one line per abbrev in that table: <div>NAME USECOUNT EXPANSION HOOK</div> where NAME and EXPANSION are strings with quotes, USECOUNT is an integer, and HOOK is any valid function or may be omitted <ul style="list-style-type: none"> (it is usually omitted). 		
List & Edit all abbreviation definitions	<f11> a M-1	(list-abbrevs &optional LOCAL)	Display a list of defined abbreviations inside the *Abbrevs* buffer, that operates in edit-abbrevs-mode. <ul style="list-style-type: none"> If LOCAL is non-nil, interactively when invoked with a prefix arg (C-u), display only local, i.e. mode-specific, abbrevs. Otherwise display all abbrevs. Edit the text in the opened *Abbrev* buffer to modify the abbreviations. <ul style="list-style-type: none"> Complete by typing C-c C-c.
Edit abbreviations in *Abbrev* buffer	<ul style="list-style-type: none"> <f11> a M-e ⌘-E 	(edit-abbrevs)	Alter abbrev definitions by editing the current mode list in the *Abbrevs* buffer, that operates in edit-abbrevs-mode. <ul style="list-style-type: none"> Selects a buffer containing a list of abbrev definitions with point located in the abbrev table for the current buffer, and turns on 'edit-abbrevs-mode' in that buffer. You can edit them and type C-c C-c to redefine abbrevs according to your editing.
Abbrevs buffer commands	Inside the *Abbrevs* buffer the following commands can be used:		
Use specified abbreviations	C-c C-c	(edit-abbrevs-redefine)	Redefine abbrevs according to current buffer contents.
Save abbreviations	C-x C-s	(abbrev-edit-save-buffer)	Save all user-level abbrev definitions in current buffer. <ul style="list-style-type: none"> The saved abbrevs are written to the file specified by 'abbrev-file-name'.
Save abbreviations to specified file	C-x C-w	(abbrev-edit-save-to-file FILE)	Save all user-level abbrev definitions in current buffer to FILE.
Saving Abbreviations	Use the following commands to store abbreviations in a file or buffer, restore abbreviations from a file or a buffer.		
Write abbreviations in a file	<f11> a s	(write-abbrev-file &optional FILE VERBOSE)	Write all user-level abbrev definitions to a file of Lisp code. <ul style="list-style-type: none"> This does not include system abbrevs; it includes only the abbrev tables listed in 'abbrev-table-name-list'.
Read abbreviations from a file	<f11> a r	(read-abbrev-file &optional FILE QUIETLY)	Read abbrev definitions from file written with 'write-abbrev-file'. <ul style="list-style-type: none"> Optional argument FILE is the name of the file to read; it defaults to the value of 'abbrev-file-name'.
Write abbreviations inside current buffer after point	<f11> a i	(insert-abbrevs)	Insert after point a description of all defined abbrevs. <ul style="list-style-type: none"> Mark is set after the inserted text.
Define abbreviations by reading them from the current buffer	<f11> a x	(pel-extract-abbrev-definitions)	Read abbreviation/expansion data from the current abbrev definition buffer. <ul style="list-style-type: none"> Prompt user before proceeding. See documentation of 'edit-abbrevs' for info on the format of the text you must have in the buffer. With argument, eliminate all abbrev definitions except the ones defined from the buffer now. 🐧 pel-define-abbrevs calls define-abbrevs after a positive response to the prompt.