Emacs support for the V Programming Language

Description	<u>Keystroke</u>	Function	Note	
<u>V</u> Editing	Emacs does not provide	any built-in mode for the V Programming	Language. PEL support for V is not complete.	
	To activate support for V on PEL, the pel-use-v user-option must be turned on (set to t). • When pel-use-v is turned on the <f11> SPC</f11> v prefix is made available.			
	PEL provides the following user-options to download and activate V supporting Emacs packages.			
	The <u>v-mode</u> external package is required. PEL installs and activates it when the <u>pel-use-v</u> user-options is set to <u>v-mode</u> . • You can also set it to <u>vlang-mode</u> to use the <u>vlang-mode</u> package, an experimental and incomplete implementation.			
	 ↑ The V programming language uses the .▼ file extension. The Verilog hardware description language uses the same file extension! • Emacs supports Verilog natively. The v-mode external package code does not take that into account and prevents opening Verilog .v files in verilog-mode. • PEL solves the issue: the activation of the V programming language, done via the pel-use-v user-option schedules logic to cleanup cleans up the file association in auto-mode-alist and provides logic that inspects the content of the .v file to determine what major mode to use allowing simultaneous opening of Verilog and V files that both use the .v file extension. 			
Last updated on:	2025-09-11			
Open this PDF file. See also: <u>Nelp/</u> Info	<f11> SPC v <f1></f1></f11>	(pel-help-pdf &optional OPEN-WEB-PAGE)	Open the $\mathfrak{PL}-V$ local PDF. If the prefix argument (like $C-u$ or M) is used, then it opens the remote GitHub hosted raw PDF instead. If the pel-flip-help-pdf-arg user-option is set it's the other way around.	
	<f12> <f1></f1></f12>			
© Customize PEL V support	<f11> SPC v <f2></f2></f11>	(pel-customize-pel &optional OTHER-WINDOW)	Customize PEL V support. • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f2></f2></f12>			
∑ Customize Emacs V support	<f11> SPC v <f3></f3></f11>	(pel-customize-library &optional OTHER-WINDOW)	Customize Emacs V support: v • If OTHER-WINDOW is non-nil (use C-u), display in another window.	
	<f12> <f3></f3></f12>	OTHER-WINDOW)		
Comments				
Toggle display of comments in buffer or active region See also: ∑ Comments	<f11> ; ;</f11>	(hide/show-comments-toggle &optional START END)	Toggle hiding/showing of comments in the active region or whole buffer. • If the region is active then toggle in the region. Otherwise, in the whole buffer. • This requires the hide-comnt.el package (see ∑ Comments). • PEL activates it when the pel-use-hide-comnt user option is t.	

Emacs & V — References

Document	Notes
The V Programming Language	V@ Wikipedia Vhome page V@ GitHub
V is under development and quality/functionality/validity is disputed	V is still under development. It seems to be an interesting project with impressive goals. It will be interesting to see where this project goes, as it has.several.detractors (but is there any one language/implementation everyone loves?). Also see: