






graphviz-dot—mode: Graphviz Dot Mode

Description	Keystroke	Function	Note
Graphviz Dot	 This table is in early stage of development		
	 PEL uses the graphviz-dot-mode package instead of the default undo.		
	 Under PEL activate the undo-tree package by setting the pel-use-graphviz-dot customize variable to t .		
Customize PEL Graphviz Dot Support (See also: Σ Customize)	<ul style="list-style-type: none">• <f11> <f1>• SPC g• <f12> <f1>	(pel-cfg-pkg-graphviz-dot &optional OTHER-WINDOW)	Customize PEL Graphviz Dot support. <ul style="list-style-type: none">• If OTHER-WINDOW is non-nil (use C–u), display in another window and open the graphviz customization group.• The <f12> <f1> binding is available when point is in a buffer visiting a Graphviz Dot file.
Activate Graphviz Dot mode	<f11> M–g	(graphviz-dot-mode)	Toggle use of the graviz-dot-mode to edit Graphviz Dot files.
Editing Dot syntax	The following commands help writing Graphviz DOT code. See the following reference documents: <ul style="list-style-type: none">• Documentation, which contains the following and much more:<ul style="list-style-type: none">• The DOT Language• Node, Edge and Graph Attributes• Node Shapes• Arrow Shapes• Colors		
Indent current line (See also: Σ Indentation)	<tab>	(indent-for-tab-command &optional ARG)	Indent current line of dot code (regardless of point position within the line)
		(graphviz-dot-indent-line)	
Indent the graph statement at point	<ul style="list-style-type: none">• C–M–q• <f12> <tab>	(graphviz-dot-indent-graph)	Indent the graph/digraph/subgraph where point is at. <ul style="list-style-type: none">• This will first reach the beginning of the graph were point is at, and then indent this and each subgraph in it.
Break line and indent	M–j	(indent-new-comment-line &optional SOFT)	Break line at point and indent, continuing comment if within one. <ul style="list-style-type: none">• This indents the body of the continued comment under the previous comment line.• This command is intended for styles where you write a comment per line, starting a new comment (and terminating it if necessary) on each line.• If a fill column is specified, it overrides the use of the comment column or comment indentation.• The inserted newline is marked hard if variable ‘use-hard-newlines’ is true, unless optional argument SOFT is non-nil.
Compiling			
Compile the graph	<ul style="list-style-type: none">• C–c C–c• <f12> c	(compile COMMAND &optional COMINT)	Compile the graph using the program identified by graphviz-dot-dot-program to the output format identified by graphviz-dot-preview-extension. The command is shown in the mini buffer, allowing modification before execution.
Jump to next match	<ul style="list-style-type: none">• C–x `• M–g n• M–g M–n	(next-error &optional ARG RESET)	A prefix ARG specifies how many error messages to move; negative means move back to previous error messages. Just C-u as a prefix means reparse the error message buffer and start at the first error.
Jump to previous match	<ul style="list-style-type: none">• M–g p• M–g M–p	(previous-error &optional N)	Prefix arg N says how many error messages to move backwards (or forwards, if negative).
Viewing			
Preview image in Emacs buffer	<ul style="list-style-type: none">• C–C C–p• <f12> p	(graphviz-dot-preview)	Compile the graph and preview it in an other buffer.   Only works in graphics mode.
View image using external program	C–c C–v	(graphviz-dot-view)	Run an external viewer. <ul style="list-style-type: none">• This creates an external process every time it is executed. If ‘graphviz-dot-save-before-view’ is set, the current buffer is saved before the command is executed.
Graphviz Dot Variables			
		graphviz-dot-dot-program	Program used to compile the graphs. Default := ‘dot’.
		graphviz-dot-preview-extension	File type to use for output. Default := ‘png’.
		graphviz-dot-view-command	Command to run when ‘graphviz-dot-view’ is executed. Default:= ‘dotty %s’
		graphviz-dot-view-edit-command	If the user should be asked to edit the view command. Default:= nil
		graphviz-dot-save-before-view	Automatically save current buffer berore ‘graphviz-dot-view’.
		graphviz-dot-mode-hook	Hook variable for initialization of the mode.

Graphviz Dot Mode — References

Description & URL	Notes
Graphviz Dot	
GraphViz @ Wikipedia	Overview description with various links.
GraphViz.org - Graphviz Graph Visualization Software	Graphviz home page. Includes: <ul style="list-style-type: none">• Gallery• Documentation, which contains the following and much more:<ul style="list-style-type: none">• The DOT Language• Command-line Usage• Output formats• Node, Edge and Graph Attributes• Node Shapes• Arrow Shapes• Colors• Resources
Graphviz Dot Mode for Emacs	
graphviz-dot-mode @ GitHub	