

Perl 5

See also: Perl - Perl <ul style="list-style-type: none"> Perl @ Wikipedia perl.org 	Perl Tools Learning Perl	Perl Style Guide. perlcritic script uses Perl::Critic to scan Perl code. The perltidy application reformats Perl code. <ul style="list-style-type: none"> Perl Intro - a quick introduction to Perl Online Perl books <ul style="list-style-type: none"> Beginning Perl
---	---	--

Perl 5 Syntax

File test operators	It is possible to combine the file test operator with the AND operator as in the following example:			<pre>if (-e \$filename && -f _ && -r _){ print("\$filename exists and is readable\n"); }</pre>
The most important operators are shown here. They check if the file...	-r is readable	-e exists.	-b is a block special file.	
	-w is writable	-z is empty.	-c is a character special file.	
	-x is executable	-s has nonzero size (returns size in bytes).	-t handle is opened to a tty.	
	-o is owned by effective uid.	-f is a plain file.	-u has setuid bit set.	
	-R is readable	-d is a directory.	-g has setgid bit set.	
	-W is writable	-l is a symbolic link.	-k has sticky bit set.	
	-X is executable	-p is a named pipe (FIFO) or Filehandle is a pipe.	-T is an ASCII text file (heuristic guess).	
	-O file is owned by real uid.	-S is a socket.	-B is a “binary” file (opposite of -T).	