




Getting Help / Apropos / Descriptions / Info Manuals / Queries

Description	Keystroke	Function	Notes / Example description
Prefix Keys	Note on prefix: In the following rows, the description uses C-h as the prefix. For each of this you can also use the <f1> prefix instead.		
List all keys that belong to a prefix	<prefix> C-h		Type C-h after the prefix keystroke. For example to list all C-x r keys, type C-x r C-h
Describe Help	The following commands display a description of the item the command requests. The information is displayed in a read-only *Help* buffer.		
Show all key commands for this buffer	C-h b	(describe-bindings &optional PREFIX BUFFER)	Display a buffer showing a list of all defined keys, and their definitions. The keys are displayed in order of precedence.
Help on key binding	C-h k <keystroke>	(describe-key &optional KEY UNTRANSLATED UP-EVENT)	Display documentation of the function invoked by KEY. KEY can be any kind of a key sequence; it can include keyboard events, mouse events, and/or menu events. Get binding for the typed <keystroke> in the current context. Displays the name of the command function, it's description, it's bindings. 👉 The PEL system comes with an extensive key binding system entered around a set of function keys like <F11> , some of these are bindings for commands that already have standard Emacs bindings and sometimes the standard Emacs bindings are easier to type. Using C-h k (or the equivalent <f1> k) binding to get help on a specific binding may help you discover other, more efficient key bindings for the same command.
Print name of function invoked by key	C-h c <keystroke>	(describe-key-briefly &optional KEY INSERT UNTRANSLATED)	Print the name of the function KEY invokes. KEY is a string.
Describe active major/minor(s) modes and the key bindings	• C-h m • <f11> ? k m	(describe-mode &optional BUFFER)	Lists the active major mode, all active minor modes and the bound keystrokes.
Show top level bindings in the map of the current major mode	<f11> ? k k	(which-key-show-major-mode)	Show top-level bindings in the map of the current major mode. This function will also detect evil bindings made using 'evil-define-key' in this map. These bindings will depend on the current evil state. 📦 This requires the which-key package. 🔗 Under PEL set the pel-use-which-key customize variable to t to enable this. When this is set to t which-key-mode is turned on by pel-init .
Describe a package	C-h p	(describe-package PACKAGE)	Display the full documentation of PACKAGE (a symbol). Shows whether it is installed or not, its version, the features it implements and some extra notes.
Describe a function	C-h f	(describe-function FUNCTION)	Display the full documentation of FUNCTION (a symbol). - For example: C-h f *-mode : Get a completion list of all emacs modes - The buffer shown contains link to the file where the function is implemented. Following the link will open the file in a buffer, even if the file is compressed.
Describe symbol	C-h o	(describe-symbol SYMBOL &optional BUFFER FRAME)	Display the full documentation of SYMBOL. Will show the info of SYMBOL as a function, variable, and/or face.
Describe variable	C-h v	(describe-variable VARIABLE &optional BUFFER FRAME)	- For example: C-h v load-path : shows the emacs lisp path. - Reference: https://www.gnu.org/software/emacs/manual/html_node/eintr/See-variable-current-value.html
Help on Input Method	• C-h i • C-h C-\	(describe-input-method INPUT-METHOD)	Provide information about the <u>input method</u> . Prompts for the name of an input method. See Input Method section for more info.
Getting Help with Emacs Help, Apropos, and Info.	The following commands search, gather and open information in buffers using the info reader format. The info reader mode commands are shown after the command list. As with everything in Emacs you can always get help on the current mode, that applies to the info reader mode as well.		
Show information available about specified pattern	<f11> ? a a	(apropos PATTERN &optional DO-ALL)	Show all meaningful Lisp symbols whose names match PATTERN. Symbols are shown if they are defined as functions, variables, or faces, or if they have nonempty property lists. PATTERN can be a word, a list of words (separated by spaces), or a regexp (using some regexp special characters). If it is a word, search for matches for that word as a substring. If it is a list of words, search for matches for any two (or more) of those words.
Get a-propos info on command	• C-h a • <f11> ? a c	(apropos-command PATTERN &optional DO-ALL VAR-PREDICATE)	Show commands (interactively callable functions) that match PATTERN. • PATTERN can be a word, a list of words (separated by spaces), or a regexp (using some regexp special characters). If it is a word, search for matches for that word as a substring. If it is a list of words, search for matches for any two (or more) of those words. • With C-u prefix, or if 'apropos-do-all' is non-nil, also show non interactive functions. • Examples: • <f1> a mode : list all modes available in the Emacs session, showing their key bindings and a quick description. 📦 Old Emacs command name was: command-apropos .
Look for topic in all info documents	<f11> ? i a	(info-apropos STRING)	Prompts for a string and looks up for that string in all the indices of all the Info documents installed in the system. Opens an Apropos index menu with the links to the found topics. Use this to find the manual section(s) that describe a specific function or variable .
Open the Info Reader on specific topic	• C-h i • <f11> ? i i • %-?	(info &optional FILE-OR-NODE BUFFER)	Open the *info* buffer if already opened. If not, open the info reader for the top node. • A non-numeric prefix argument (C-u) directs this command to read a file name from the minibuffer. It is possible to open a compressed .info.gz file directly! Emacs will uncompress it and open it. • A numeric prefix argument of N selects an Info buffer named ""info*<N>". Called from a program, or from M-: , FILE-OR-NODE may specify an Info node of the form "(FILENAME)NODENAME". See the Info Reader Mode Keys table below for the following actions available once emacs is in the Info Reader Mode.
Search for text in function and variables doc strings	• C-h d • <f11> ? a d	(apropos-documentation PATTERN &optional DO-ALL)	Search for functions and variables whose documentation strings match the specified pattern and display the appropriate info pages.
List variables and functions defined in Emacs Lisp file.	<f11> ? a L	(apropos-library FILE)	List the variables and functions defined by library FILE. FILE should be one of the libraries currently loaded and should thus be found in 'load-history'.
Show buffer-local variables	<f11> ? a l	(apropos-local-variable PATTERN &optional BUFFER)	Show buffer-local variables that match PATTERN. Optional arg BUFFER (default: current buffer) is the buffer to check.

Description	Keystroke	Function	Notes / Example description
Show user option	<f11> ? a o	(apropos-user-option PATTERN &optional DO-ALL)	Show user options that match PATTERN. PATTERN can be a word, a list of words (separated by spaces), or a regexp (using some regexp special characters). If it is a word, search for matches for that word as a substring. If it is a list of words, search for matches for any two (or more) of those words. With C-u prefix, also show variables, not just user options.
Show all symbols that have a specific value	<f11> ? a u	(apropos-value PATTERN &optional DO-ALL)	Show all symbols whose value's printed representation matches PATTERN. PATTERN can be a word, a list of words (separated by spaces), or a regexp (using some regexp special characters). If it is a word, search for matches for that word as a substring. If it is a list of words, search for matches for any two (or more) of those words. With C-u prefix, or if 'apropos-do-all' is non-nil, also looks at function definitions (arguments, documentation and body) and at the names and values of properties.
Show variables that match a specific name pattern	<f11> ? a v	(apropos-variable PATTERN &optional DO-NOT-ALL)	Show variables that match PATTERN. With the optional argument DO-NOT-ALL non-nil (or when called interactively with the prefix C-u), show user options only, i.e. behave like 'apropos-user-option'.
Open specified info manual	<f11> ? i m	(info-display-manual MANUAL)	Prompt for a specific Info manual to open in a buffer. Example: "eintr" := Introduction to Emacs Lisp.
Open Emacs Manual describing a specified command function	C-h F	(Info-goto-emacs-command-node COMMAND)	Go to the Info node in the Emacs manual for command COMMAND. The command is found by looking up in Emacs manual's indices or in another manual found via COMMAND's 'info-file' property or the variable 'Info-file-list-for-emacs'. COMMAND must be a symbol or string.
Find specified function function or variable in info	C-h S	(info-lookup-symbol SYMBOL &optional MODE)	Display the definition of SYMBOL, as found in the relevant info manual. When this command is called interactively, it reads SYMBOL from the minibuffer. In the minibuffer, use M-n to yank the default argument value into the minibuffer so you can edit it. The default symbol is the one found at point. With prefix arg MODE a query for the symbol help mode is offered.
Info reader mode keys	<p>The keys that can be typed in the *Info* buffers and their meanings include the following:</p> <p>? : Get Info help</p> <p>SPC : Page down into the node text, move to following text/node if already at end</p> <p><Page Down> : Page Down inside the node text (Does not move to other node)</p> <p> : Page up into the node text, move to previous text/node if already at top</p> <p><Page Up> : Page up into the node text. (Does not move to other node)</p> <p>t : Move to the top of the Info document</p> <p>n : Next node in the current level</p> <p>p : Previous node in the current level</p> <p>] : Next Node (any level)</p> <p>[: Previous Node (any level)</p> <p>u : Move to the Upper node (in the menu tree)</p> <p>l : Info History: visit last (lowercase 'L')</p> <p>r : Info History: visit history forward</p> <p>L : Info History: Create Virtual Node of all last visited</p> <p>m : Menu - Open a node's sub-menu entry. Emacs prompts for the menu text. Abbreviation is supported. Tab completion also supported.</p> <p><RET> : Menu - enter nodes' sub-menu (at cursor position)</p> <p>1-9 : Menu - enter nodes' sub-menu (at cursor position)</p> <p>- Type a number between 1 to 9 to select the corresponding menu entry. 1 := first.</p> <p>- Menu asterisk for menu entry 3, 6 and 9 are coloured in red to help identify them.</p> <p>f crossref-text : Cross Reference - follow node's cross reference. - To get all cross references, type: f?</p> <p><tab> : Menu/Cross-Reference - Move cursor to nodes' next sub-menu/cross-reference link</p> <p>M-<tab> : Menu/Cross-Reference - Move cursor to nodes' previous sub-menu/cross-reference link</p> <p>s : Search Info - search entire info file for a string. After typing 's' type the string to search and <RET> To repeat search type 's' followed by <RET></p> <p>i : Search Info - search index. Search the index for a specific topic. Prompts for the topic. Tab shows list of indices. If several are found, the ',' character can be used to display each one in turn. Access any section of any manual with the Info Reader by doing this:</p> <ol style="list-style-type: none"> C-h i to open the Info Reader at the top m to open the menu prompt in the menu buffer type topic name and RET <p>I : (Search Info - construct a virtual info node displaying results of an index search. Runs the command (Info-virtual-index TOPIC)</p> <p>g : Goto a node by name. Topic is a node name: abbreviation is not supported, but completion with TAB is supported. Also allows going into another file using the syntax: 'g(filename)Topic<RET>' Topic may be '*' : means: open the whole file in the buffer.</p> <p><f11> ? i a : M-x info-apropos : Search Info - search in all Info files installed in the computer</p> <p>M-n : Create New Independent Info Buffer</p> <ul style="list-style-type: none"> M-n opens a new, independent, Info buffer, that at first contains the same Info, but can be managed independently from the original. This can also be done using: C-u m : Move to menu entry into new Info buffer C-u g : Go to topic in new Info buffer C-u number C-h i : Open an info topic into a 'Info<#>' buffer (for the identified number) creating it if necessary. 		
Extra Descriptions			
Show available colours	<f11> ? d c	(list-colors-display &optional LIST BUFFER-NAME CALLBACK	Display names of defined colors, and show what they look like.
List all available faces	<f11> ? d F	(list-faces-display &optional REGEXP)	List all faces, using the same sample text in each.
Show buffer and file name	<f11> ? d f	(pel-show-window-filename-or-buffer-name)	Show the (full path) name of the file or buffer of current window.
Show information about an input method	<f11> ? d i	(list-input-methods)	Display information about all input methods.
Display content of kill ring	<f11> ? d k	(pel-show-kill-ring)	Display content of 'kill-ring' in *Help* buffer.
Print current buffer line # (and narrowed line #)	<f11> ? d l	(what-line)	Print the current buffer line number and narrowed line number of point.
Query info about point	<ul style="list-style-type: none"> C-x = <f11> ? d p 	(what-cursor-position &optional DETAIL)	Displays information about point oil the echo area: - position, character, encoding
Show syntax of char at point	<f11> ? d s	(pel-show-char-syntax)	Display a message showing the character syntax of character at point.
Show window dimension	<f11> ? d w	(pel-show-window-sizes)	Show the height & width of the current window.
Show state of PEL numlock	<f11> ? k #	(pel-show-mac-numlock)	🔵 Display state of ' pel-mac-keypad-numlocked ' used to control the numeric keypad.
Show personal key bindings	<f11> ? k b	(describe-personal-keybindings)	Display all the personal keybindings defined by 'bind-key'.

Description	Keystroke	Function	Notes / Example description
Display free keys	<f11> ? k f	(free-keys &optional PREFIX BUFFER)	Display free keys in current buffer. <ul style="list-style-type: none"> A free key is a key that has no associated key-binding as determined by function 'key-binding'. By default, keys on 'free-keys-keys' list with no prefix sequence are considered, possibly together with modifier keys from 'free-keys-modifiers'. You can change the prefix sequence by hitting 'p' in the "Free keys" buffer. Prefix is supplied in format recognized by 'kbd', for example "C-x".  Requires the package free-keys.  PEL activates this when the pel-use-free-keys customize variable is set to t.
More Help			
Open Emacs Tutorial	C-h t	(help-with-tutorial &optional ARG DONT-ASK-FOR-REVERT)	Open an Emacs Tutorial. Restore location if used before (after prompt).
Help on Elisp Packages on this computer	C-h p	(finder-by-keyword)	Find packages matching a given keyword. Useful to search for packages supporting a specific concept.
Open Emacs FAQ	C-h C-f	(view-emacs-FAQ)	Display the Emacs Frequently Asked Questions (FAQ) file.
Emacs news	C-h n	(view-emacs-news &optional VERSION)	Display info on recent changes to Emacs. With argument, display info only for the selected version. Includes code modifications of each version of Emacs.
About Emacs	Information about Emacs, its environment and configuration is available through a set of commands listed below		
Show loaded files & features	<f11> ? e l	(pel-emacs-load-stats)	Display the number of loaded files (the length of <i>load-history</i>) and the number of features currently loaded.
Check/display list of shadowed Emacs Lisp files	<f11> ? e s	(list-load-path-shadows &optional STRINGP)	Display a list of Emacs Lisp files that shadow other files <ul style="list-style-type: none"> Shows any shadows in a "Shadows" buffer
Display Emacs initialization duration	<f11> ? e t	(emacs-init-time)	Display the duration of the Emacs initialization.
Display Emacs version	<f11> ? e v	(emacs-version)	Display Emacs version
Using Man	Emacs provide 2 main commands to display man pages inside buffers. These are much more powerful than the usual man reader available on the shell.		
Open a man page inside an Emacs buffer	<ul style="list-style-type: none"> <f11> ? m  -M 	(man MAN-ARGS)	Using man pages inside emacs is even better than using it from the shell because: <ul style="list-style-type: none"> the links are active and can be followed. When the man page describes a directory or file, emacs will open the file or the directory (in direct mode) when pressing <RET> over the link. You can navigate easily between sections (n/p will move to the next/previous section) You can use any of the searches. You can use any of the options to the man command at the prompt, like the -a option to access all man pages of the same name. Then use M-n and M-p to move from one to the other page, inside the same buffer. See all keys available in mode description (Use '<f1> m' or '<f11> ? k m') to do so.
Open a man page without external man process: woman	<f11> ? w	(woman &optional TOPIC RE-CACHE)	Open a man page file in Emacs using the woman mode, completely implemented in Emacs Lisp (and therefore without using the external 'man' process). That can be very useful under environments where man is not available (such as basic Windows).

Help — References

Topic & Link	Description	Comment
Emacs Help		
GNU Emacs Manuals Online	The page with the list of all available online GNU Emacs manuals.	
GNU Emacs Manual - Help	Emacs manual - Help chapter	
Gnu Emacs Manual - Help Mode	Describes the command and key bindings that can be used in the Help-mode buffer window, which shows the help information.	
Emacs Manuals		Note that all Emacs manuals are available <i>inside of Emacs</i> . <i>It's better to test, investigate code, etc..</i>
GNU Emacs Manuals Online		Lists all GNU Emacs manuals, reference cards, etc...
GNU Emacs Manual		Points to different formats of the manual. The format where all is inside one HTML file is useful to search. There's also the PDF formats.
GNU Reference Cards		This is accessible via the first link.
Emacs Papers		
EMACS: The Extensible, Customizable Display Editor	This paper was written by Richard Stallman in 1981 and delivered in the ACM Conference on Text Processing.	
Emacs Tutorials		
A Guided Tour of Emacs	The official Emacs Tutorial. Part of Emacs. Best used <i>inside</i> Emacs.	A good starting point. Use the others to get different point of views.
Absolute Beginner's Guide to Emacs		
A Tutorial Introduction to GNU Emacs		
Practical Emacs Tutorial @ ErgoEmacs		
Emacs Cheat Sheet / Keystroke Lists		
Emacs Cheat Sheet		
List of Emacs Keystrokes		
Emacs Videos		

Topic & Link	Description	Comment
<u>Emacs Rocks - home</u>	A collection of Youtube homed videos about various Emacs features.	Well documented with keystrokes showing on the screen cast. Worth watching slowly to catch what is being done.