



Emacs Support for GNU Guile

Description	Keystroke	Function	Note
GNU Guile Programming Language Support See also: <ul style="list-style-type: none">• Guile Reference Manual• File/Directory Variables	<div> PEL support for Guile Scheme is preliminary. More work is required to identify Guile specific support.</div> <div> PEL activates Guile Scheme support when the pel-use-guile user-option is turned on (t). PEL provide extra support for the Guile programming language. Most support is provided by Emacs support for pel - Scheme.</div> <ul style="list-style-type: none">• The Guile programming language is a Scheme implementation. The Guile Scheme files use the same extension as Scheme: .ss.		
Open this PDF file. See also: Help/Info	<div><f11> SPC C-s C-g <f1></div> <div><f12> <f1></div>	(pel-help-pdf &optional OPEN-WEB-PAGE)	Open the pel - GNU Guile local PDF. If the prefix argument (like C-u or M--) is used, then it opens the remote GitHub hosted raw PDF instead. If the pel-flip-help-pdf-arg user-option is set it's the other way around.
Customize PEL Guile support	<div><f11> SPC C-s C-g <f2></div> <div><f12> <f2></div>	(pel-customize-pel &optional OTHER-WINDOW)	Customize PEL Guile support. <ul style="list-style-type: none">• If OTHER-WINDOW is non-nil (use C-u), display in another window.
Customize Emacs Guile support	<div><f11> SPC C-s C-g <f3></div> <div><f12> <f3></div>	(pel-customize-library &optional OTHER-WINDOW)	Customize Emacs Scheme support: scheme, geiser, quack, lispy. <ul style="list-style-type: none">• If OTHER-WINDOW is non-nil (use C-u), display in another window.
Use the following commands to interact with the gsi Scheme Guile REPL			
Open the Guile REPL	<div><f11> z r C-g</div> <div><f12> z</div>	(pel-guile-repl &optional N)	Run the Guile REPL in window specified by N. <ul style="list-style-type: none">• By default use the other window. If a numeric argument is specified, its value correspond to the direction of a numeric keypad:<div>8 4 6 2 That is:<ul style="list-style-type: none">• 8: up• 4: left• 6: right• 2: down• 0 and 5 identify the current window.</div>
Erase the content of REPL	<f12> C-l	(pel-clear-scheme-repl-buffer)	Erase content of the Guile REPL running under Emacs.