

Frames

Operation	Keystroke	Function	Notes
Emacs Frames	<ul style="list-style-type: none">Emacs calls frames what model graphical Operating Systems call “windows”, or more specifically “OS windows”.Emacs supports multiple frames, both when Emacs works in graphical mode but also when it is used in text terminal mode.		
Move directly to another graphical frame	The following commands move point to another frame existing in the direction selected by the cursor key. These commands only work in graphics mode .		
Move to window above	<f11> S-<up>	(fm-up-frame)	Move point to frame above current frame (if one exists and is located there).
Move to window below	<f11> S-<down>	(fm-down-frame)	Move point to frame below current frame (if one exists and is located there).
Move to window at right	<f11> S-<right>	(fm-right-frame)	Move point to frame at right of the current frame (if one exists and is located there).
Move to window at left	<f11> S-<left>	(fm-left-frame)	Move point to frame at left of the current frame (if one exists and is located there).
Manage Frames	Emacs frame operations work in both modes: graphics and text terminal. In graphics mode a new frame is creating a separate OS frame. Although surprising, in text terminal mode a new frame is inside the same OS frame: it simply hides the other(s) existing frame(s) as the text terminal can only display one Emacs frame at any given time. When Emacs runs in text terminal mode, each mode line identifies the currently active frame number with “F1”, “F2”, etc... The windows numbers are all part of the space number-space.		
Show frame count	<f11> F ?	(pel-show-frame-count)	Display the number of Emacs active frames in the mini-buffer.
Delete this frame	<ul style="list-style-type: none">C-x 5 0<f11> F 0⌘-w	(delete-frame &optional FRAME FORCE)	Delete FRAME, permanently eliminating it from use. FRAME must be a live frame and defaults to the selected one.
Delete all other frames	<ul style="list-style-type: none">C-x 5 1<f11> F 1	(delete-other-frames &optional FRAME)	Delete all frames on FRAME’s terminal, except FRAME.
New Frame below	<ul style="list-style-type: none">C-x 5 2<f11> F 2⌘-n	<ul style="list-style-type: none">(make-frame-command)(make-frame &optional PARAMETERS)	Make a new frame, on the same terminal as the selected frame. 🍏 On macOS in graphics mode only: make-frame is called for ⌘-n, it has the same effect as make-frame-command.
Display buffer in other (next) frame	<ul style="list-style-type: none">C-x 5 C-o<f11> F b	(display-buffer-other-frame BUFFER)	Display a buffer preferably in another frame.
Run Dired in other (next) frame	<ul style="list-style-type: none">C-x 5 d<f11> F d	(dired-other-frame DIRNAME &optional SWITCHES)	"Edit" a directory. Like ‘dired’ but makes a new frame.
Find file in other (next) frame	<ul style="list-style-type: none">C-x 5 fC-x 5 C-f<f11> F f	(find-file-other-frame FILENAME &optional WILDCARDS)	Switch to/open another file and show it in another frame.
Select next frame	<ul style="list-style-type: none"><f11> F n⌘-`	(pel-next-frame ARG)	Make next frame visible. <ul style="list-style-type: none">In text terminal mode: iterate through all frames.In graphics mode:<ul style="list-style-type: none">with no/nil argument (the default): iterate through visible frames,with ARG non nil: iterate through all frames (included iconified frames). 🔑The ⌘-` key is a macOS command that moves to the next frame of the same application: no Emacs code is invoked but the effect is the same.
Move cursor to other (next) frame	<ul style="list-style-type: none">C-x 5 o<f11> F o	(other-frame ARG)	Activate the other frame. Numeric argument identifies frame in Z order.
Select buffer in other frame	<ul style="list-style-type: none">C-x 5 0<f11> F 0	(switch-to-buffer-other-frame BUFFER-OR-NAME &optional NORECORD)	Prompt for buffer and open in other frame.
Select previous frame	<ul style="list-style-type: none"><f11> F p⌘--	<ul style="list-style-type: none">(pel-previous-frame ARG)(ns-prev-frame)	Make previous frame visible. <ul style="list-style-type: none">In text terminal mode: iterate through all frames.In graphics mode:<ul style="list-style-type: none">with no/nil argument (the default): iterate through visible frames,with ARG non nil: iterate through all frames (included iconified frames).
Find file in other (next) frame in read-only	<ul style="list-style-type: none">C-x 5 r<f11> F r	(find-file-read-only-other-frame FILENAME &optional WILDCARDS)	Edit file read-only in other frame with name obtained via minibuffer.
Hide Emacs frame	⌘-h	(ns-do-hide-emacs)	🍏 On macOS in graphics mode only: hide Emacs frame. Retrieve it via the ⌘-<tab> key.
Hide all other applications	⌘-H	(ns-do-hide-others)	🍏 On macOS in graphics mode only: hide all other applications, except Emacs. Retrieve them via the ⌘-<tab> key.
Iconify frame	⌘-m	(iconify-frame &optional FRAME)	🍏 On macOS in graphics mode only: iconify the frame.