↖ Topic Index

Emacs support for Pascal 🚧

Description	Keystroke	Function	Note
Pascal Editing Last updated on:	Emacs has built-in Pascal support. • PEL adds extra support when the **pel-use-pascal** user-option is set to t. Type **<f1> o pel-use-pascal <RET>** to change it. • PEL support is partial 🚧. If you need extra features implemented please request them via bug in the PEL Github project. 2026-09-19		
Open this PDF file. See also: **Help/Info**	**<f11> SPC M-p <f1>** **<f12> <f1>**	(**pel-help-pdf** &optional OPEN-WEB-PAGE)	Open the **PEL - Pascal** local PDF. With **C-u** , **M--**, **M- -1** or **C- -1** prefix: open the remote GitHub hosted PDF instead. If the **pel-flip-help-pdf-arg** user-option is set it's the other way around.
Customize PEL Pascal support	**<f11> SPC M-p <f2>** **<f12> <f2>**	(**pel-customize-pel** &optional OTHER-WINDOW)	Customize PEL Pascal support. • If OTHER-WINDOW is non-nil (use **C-u**), display in another window.
Customize Emacs Pascal support	**<f11> SPC M-p <f3>** **<f12> <f3>**	(**pel-customize-library** &optional OTHER-WINDOW)	Customize Emacs Pascal support: pascal • If OTHER-WINDOW is non-nil (use **C-u**), display in another window.
Comments			
Toggle display of comments in buffer or active region See also: **Comments**	**<f11> ; ;**	(**hide/show-comments-toggle** &optional START END)	Toggle hiding/showing of comments in the active region or whole buffer. • If the region is active then toggle in the region. Otherwise, in the whole buffer. 📦 This requires the **hide-comnt.el** package (see **Comments**). PEL activates it when the **pel-use-hide-comnt** user option is **t**.

Emacs & Pascal — References

Document	Notes