

Description	Keystroke	Function	Note	
	 Several Linux distros map C-M-<left> to desktop workspace operation. In that case you can either use another key binding or change Linux key binding in Systems->settings->keyboard->shortcuts to prevent it from using that key sequence.			
block forward   	• C-M-<right>	(forward-sexp &optional ARG)	Move forward across one balanced expression (sexp). • With ARG, do it that many times. Negative arg -N means move backward across N balanced expressions. This command assumes point is not in a string or comment. •  With PEL: if you want to use Esc C-<right> binding you must ensure that pel-windmove-on-esc-cursor user option is set to nil. ❖ C-M-<right> does not work on Windows, but H-<right> does.	
	• Esc C-<right> 			
	• C-M-f • C-[C-f • Esc C-f			
	 Several Linux distros map C-M-<right> to desktop workspace operation. In that case you can either use another key binding or change Linux key binding in Systems->settings->keyboard->shortcuts to prevent it from using that key sequence.			
Up/inside sexp hierarchy   	• C-M-<up>	(backward-up-list &optional ARG ESCAPE-STRINGS NO-SYNTAX-CROSSING)	Move backward out of one level of parentheses. • This command will also work on other parentheses-like expressions defined by the current language mode. With ARG, do this that many times. • A negative argument means move forward but still to a less deep spot. •  With PEL: if you want to use Esc C-<up> binding you must ensure that pel-windmove-on-esc-cursor user option is set to nil. ❖ C-M-<up> does not work on Windows, but H-<up> does.	
	• Esc C-<up>			
	• C-M-u • C-[C-u • Esc C-u			
Down/inside sexp/block   	• C-M-<down>	(down-list &optional ARG)	Move forward down one level of parentheses. • This command will also work on other parentheses-like expressions defined by the current language mode. • With ARG, do this that many times. A negative argument means move backward but still go down a level. • This command assumes point is not in a string or comment. •  With PEL: To use Esc C-<down> binding you must ensure that pel-windmove-on-esc-cursor user option is set to nil. ❖ C-M-<down> does not work on Windows, but H-<down> does.	
	• Esc C-<down>			
	• C-M-d • C-[C-d • Esc C-d			
<u>🔗</u> Marking				
mark function See also: <u>🔗</u> Marking	C-M-h	(mark-defun &optional ALLOW-EXTEND)	Put mark at end of current definition, point at beginning. • With positive ARG, mark this and that many next definitions; with negative ARG, change the direction of marking. • If the mark is active, it marks the next or previous definition(s) after the one(s) already marked.	
Compilation				
Compile C3 file See <u>🔗</u> Compilation Mode	<f12> c	(pel-c3-compile)	Compile C3 file, show rrors in compilation-mode buffer.	

Emacs & C3— References

Document	Notes		
The C3 Programming Language	• C3 home • c3c: C3 Compiler @ Github	Github repos: • Awesome C3 Projects @ Github • c3 vendor libraries @ Github	
Learning C3	• What is C3?		
C3 blogs	• C evolved: The C3 programming Language, by Cristopher Lernö		
C3 LSP servers	• c3-lsp: LSP-server for the C3 language. This must be installed manually. See the installation instructions.		
Emacs support	• c3-ts-mode @ Github : tree-sitter-based major-mode for C3. • tree-sitter-c3 @ Github : tree-sitter language grammar for C3.		