

Action	Key binding	Command	Note
Kill comments			
Kill comment on current line	<f11> ; k	(comment-kill ARG)	Kill the complete comment text on the line (whether it is at the beginning of the line or after some code) and remember in kill ring. - With numeric argument, kill comment on as many lines staring with the current one. - For one line this can also be executed with C–u M– ;
Delete all comments in buffer or marked region See also: • ⌘ Cut & Paste	<f11> ; ⌘	(pel-delete-all-comments)	Delete all comments in current (possibly narrowed) buffer or marked region. 👉 To delete all comments inside a region mark the region first. You can also narrow a region and then use this command to remove all comments from that narrowed region, without affecting anything else. See the ⌘ Narrowing table for information on narrowing.
Kill all comments in buffer or marked region (& retain them in kill ring) See also: • ⌘ Cut & Paste	<f11> ; - <f11> - ;	(pel-kill-all-comments)	Kill all comments in current (possibly narrowed) buffer or marked region and retain them in kill ring. 👉 To kill all comments inside a region mark the region first. You can also narrow a region and then use this command to remove all comments from that narrowed region, without affecting anything else. See the ⌘ Narrowing table for information on narrowing.
Hide/Show Comments	The hide-cmnt file, written by Drew Adams, provides the following commands to quickly hide/show the comments in a buffer. - PEL provides binding for these 2 commands, but the file must be installed manually copied in a directory the is in your Emacs load path. - You can download the file from the hide-comnt.el EmacsWiki link or from the hide-count EmacsMirror. They should contain the exact same code. 👉 Very useful to see a list of methods without all comments when you also use the Hide/Show Mode commands (see ⌘ Hide/Show Code table). 📦 Both of these commands require the hide-comnt.el package (see above). 🔗 PEL activates it when the pel-use-hide-comnt user option is t.		
Toggle display of comments in buffer or active region	<f11> ; ;	(hide/show-comments-toggle &optional START END)	Toggle hiding/showing of comments in the active region or whole buffer. If the region is active then toggle in the region. Otherwise, in the whole buffer.
Show (or hide) comments in buffer or marked region	<f11> ; :	(hide/show-comments &optional HIDE/SHOW START END)	Hide or show comments in buffer or active region. - Hide if no argument. To show, use any prefix argument (any of the C–u, M– –, M–0 to M–9 will do). - If a region is active the command applies to the active region, otherwise it applies to the entire or narrowed buffer. - Uses ‘save-excursion’, restoring point. - Option ‘show-invisible-comments-shows-all’: - If non-nil then using this command to show invisible text shows *ALL* such text, regardless of how it was hidden. IOW, it does not just show invisible text that you previously hid using this command. - If nil (the default value) then using this command to show invisible text makes visible only such text that was previously hidden by this command. (More precisely, it makes visible only text whose ‘invisible’ property has value ‘hide-comment’.)
Insert Commented Lines	The following commands help insert commented lines or just underlines the current line of text using the character corresponding to one of the adornment level used for reStructuredText sections. The strings are commented according to the major mode of the current buffer. If the buffer has no identified comment strings, the command prompts for them the first time it is used in that type of buffer. The following commands are also listed in the ⌘ Inserting Text table.		
Insert generic file module header block — Language agnostic	<f6> h	(pel-generic-file-header)	Insert a file header block at the top of the file. - Works only for buffer visiting a file. - Supports all programming and markup language files that have a dedicated major mode. It is also available in buffers for major modes explicitly supported by the <f12> <f12> key prefix. This way, those modes can use two different commands to insert file header blocks, each having its own different format. - It supports several programming and markup language and uses the comment style identified by the file extension. If the comment style is unknown the command prompts for one. - The layout of the entered text is controlled by user options. It is possible to create a user-specified skeleton this command will used instead of the one provided by PEL. ⚠️ This command is available only 2 seconds after Emacs has started.
Insert commented line See also: ⌘ Inserting Text	• <f11> i 1 • <f6> 1	(pel-insert-line &optional LINELEN)	Insert a (commented) line before/at current line. - If point is at the beginning of the line insert it there. - If point is in the middle of a line, move point at beginning of line before inserting it. - The number of dash characters of the line is specified by LINELEN: - If LINELEN is not specified the buffer’s fill-column value is used. - It supports several programming and markup language and uses the comment style identified by the file extension. If the comment style is unknown the command prompts for one. ▀ fill-column is customizable and can be used as a file or directory variable.
Comment-underline current line with level 1 adornment	<f11> _ 1	(pel-commented-adorn-1)	Insert a commented level-1 reST line adornment at point.
Comment-underline current line with level 2 adornment	<f11> _ 2	(pel-commented-adorn-2)	Insert a commented level-2 reST line adornment at point.
Comment-underline current line with level 3 adornment	<f11> _ 3	(pel-commented-adorn-3)	Insert a commented level-3 reST line adornment at point.
Comment-underline current line with level 4 adornment	<f11> _ 4	(pel-commented-adorn-4)	Insert a commented level-4 reST line adornment at point.
Comment-underline current line with level 5 adornment	<f11> _ 5	(pel-commented-adorn-5)	Insert a commented level-5 reST line adornment at point.
Comment-underline current line with level 6 adornment	<f11> _ 6	(pel-commented-adorn-6)	Insert a commented level-6 reST line adornment at point.
Comment-underline current line with level 7 adornment	<f11> _ 7	(pel-commented-adorn-7)	Insert a commented level-7 reST line adornment at point.
Comment-underline current line with level 8 adornment	<f11> _ 8	(pel-commented-adorn-8)	Insert a commented level-8 reST line adornment at point.
Comment-underline current line with level 9 adornment	<f11> _ 9	(pel-commented-adorn-9)	Insert a commented level-9 reST line adornment at point.
Comment-underline current line with level 10 adornment	<f11> _ 0	(pel-commented-adorn-10)	Insert a commented level-10 reST line adornment at point.

Comments — References

GNU Emacs Manual - Manipulating Comments	
GNU Emacs Lisp — Tips on Writing Comments	Emacs Lisp comments conventions/guidelines.
Drew Adams hide-cmnt @ EmacsWiki	Drew Adams wrote this nice utility to quickly hide all comments in buffer that is under a mode that understands comments. En passant, merci Drew pour ce code (entre autres librairies) et la page en français . Il faudrait bien que je m’y mette et traduise tout mon document un jour...