

Emacs Calendar

Description	Keystroke	Function	Note
Calendar/Diary See also: M Org-Mode Last updated on: 2026-08-31	Emacs provides a useful calendar view with a diary of planned or past events, facilities for managing appointments and keeping track of how much time you work on various projects.		
Open this PDF file. See also: Z Help/Info	<f11> SPC SPC c <f1> <f12> <f1>	(pel-help-pdf &optional OPEN-WEB-PAGE)	Open the Z Calendar local PDF. With prefix argument (like C-u or M--) open the remote GitHub hosted raw PDF instead. If the pel-flip-help-pdf-arg user-option is set it's the other way around.
Z Customize Emacs calendar support	<f11> SPC SPC c <f3> <f12> <f3>	(pel-customize-library &optional OTHER-WINDOW)	Customize Emacs calendar support. When a prefix argument (like C-u) opens the buffer inside another window.
Open calendar view	<f11> M-C	(calendar &optional ARG)	Display a three-month Gregorian calendar. - If optional prefix argument ARG is non-nil, prompts for the central month and year. - The three months appear side by side, with the current month in the middle surrounded by the previous and next months. The cursor is put on today's date. - Once in the calendar window, future or past months can be moved into view. Arbitrary months can be displayed, or the calendar can be scrolled forward or backward. The cursor can be moved forward or backward by one day, one week, one month, or one year. - All of these commands take prefix arguments which, when negative, cause movement in the opposite direction. For convenience, the digit keys and the minus sign are automatically prefixes. Use C-h m for details of the key bindings in the calendar window. - Displays the calendar in a separate window, or optionally in a separate frame, depending on the value of 'calendar-setup'. - If 'calendar-view-diary-initially-flag' is non-nil, also displays the diary entries for the current date (or however many days 'diary-number-of-entries' specifies). This variable can be overridden by 'calendar-setup'. As well as being displayed, diary entries can also be marked on the calendar (see 'calendar-mark-diary-entries-flag').
Calendar-mode Commands			
	C-@	(calendar-set-mark ARG &optional EVENT)	Mark the date under the cursor, or jump to marked date. - With no prefix argument, push current date onto marked date ring. - With argument ARG, jump to mark, pop it, and put point at end of ring.
	C-a	(calendar-beginning-of-week ARG)	Move the cursor back ARG calendar-week-start-day's.
	C-b	(calendar-backward-day ARG)	Move the cursor back ARG days. Moves forward if ARG is negative.
	C-e	(calendar-end-of-week ARG)	Move the cursor forward ARG calendar-week-start-day+6's.
	C-f	(calendar-forward-day ARG)	Move the cursor forward ARG days. Moves backward if ARG is negative.
	C-n	(calendar-forward-week ARG)	Move the cursor forward ARG weeks. Moves backward if ARG is negative.
	C-p	(calendar-backward-week ARG)	Move the cursor back ARG weeks. Moves forward if ARG is negative.
	C-v	(calendar-scroll-left-three-months ARG &optional EVENT)	Scroll the displayed calendar window left by 3*ARG months. - If ARG is negative the calendar is scrolled right. - Maintains the relative position of the cursor with respect to the calendar as well as possible. - EVENT is an event like 'last-nonmenu-event'.
	SPC	(scroll-other-window &optional LINES)	Scroll next window upward LINES lines; or near full screen if no ARG. See 'scroll-up-command' for details.
	.	(calendar-goto-today)	Reposition the calendar window so the current date is visible.
	<	(calendar-scroll-right &optional ARG EVENT)	Scroll the displayed calendar window right by ARG months. - If ARG is negative the calendar is scrolled left. Maintains the relative position of the cursor with respect to the calendar as well as possible. - EVENT is an event like 'last-nonmenu-event'.
	>	(calendar-scroll-left &optional ARG EVENT)	Scroll the displayed calendar left by ARG months. - If ARG is negative the calendar is scrolled right. Maintains the relative position of the cursor with respect to the calendar as well as possible. - EVENT is an event like 'last-nonmenu-event'.
	?	(calendar-goto-info-node)	Go to the info node for the calendar.
	D	(diary-view-other-diary-entries ARG DFILE)	Prepare and display buffer of diary entries from an alternative diary file. - Searches for entries that match ARG days, starting with the date indicated by the cursor position in the displayed three-month calendar. - DFILE specifies the file to use as the diary file.
	M	(calendar-lunar-phases &optional EVENT)	Create a buffer with the lunar phases for the current calendar window. If EVENT is non-nil, it's an event indicating the buffer position to use instead of point.
(Emacs ≥ 28.1)	S	(calendar-sunrise-sunset &optional EVENT)	Local time of sunrise and sunset for date under cursor. Accurate to a few seconds.
	a	(calendar-list-holidays &optional EVENT)	Create a buffer containing the holidays for the current calendar window. The holidays are those in the list 'calendar-notable-days' .
	c	(org-calendar-goto-agenda)	Compute the Org agenda for the calendar date displayed at the cursor. Command is available once the oRg Agenda view was opened once.
	d	(diary-view-entries &optional ARG)	Prepare and display a buffer with diary entries. Searches the file named in 'diary-file' for entries that match ARG days starting with the date indicated by the cursor position in the displayed three-month calendar.
	h	(calendar-cursor-holidays &optional DATE EVENT)	Find holidays for the date specified by the cursor in the calendar window. Optional DATE is a list (month day year) to use instead of the cursor position. EVENT specifies a buffer position to use for a date.
	m	(diary-mark-entries &optional REDRAW)	Mark days in the calendar window that have diary entries.
	- Marks each entry in the diary that is visible in the calendar window. - After marking the entries, runs 'diary-nongregorian-marking-hook' for the main diary file, and each included file. For example, this is the appropriate hook to process Islamic entries in all diary files. Next 'diary-mark-entries-hook' runs, for the main diary file only. If not using include files, there is no difference between these two hooks. - If the optional argument REDRAW is non-nil (which is the case interactively, for example) then this first removes any existing diary marks. This is intended to deal with deleted diary entries.		
	o	(calendar-other-month MONTH YEAR &optional EVENT)	Display a three-month calendar centered around MONTH and YEAR. EVENT is an event like 'last-nonmenu-event'.
	q	(calendar-exit &optional KILL)	Get out of the calendar window and hide it and related buffers. If KILL (interactively, the prefix), kill the buffers instead of hiding them.
	s	(diary-show-all-entries)	Show all of the diary entries in the diary file. - Gets rid of the selective display of the diary file so that all entries, not just some, are visible. - If there is no diary buffer, one is created.
	u	(calendar-unmark)	Delete all diary/holiday marks/highlighting from the calendar.

Description	Keystroke	Function	Note
	x	(calendar-mark-holidays &optional EVENT)	Mark notable days in the calendar window. If EVENT is non-nil, it's an event indicating the buffer position to use instead of point.
	DEL S-SPC	(scroll-other-window-down &optional LINES)	Scroll next window downward LINES lines; or near full screen if no ARG. See 'scroll-down-command' for details.
	C-SPC	(calendar-set-mark ARG &optional EVENT)	Mark the date under the cursor, or jump to marked date. - With no prefix argument, push current date onto marked date ring. - With argument ARG, jump to mark, pop it, and put point at end of ring.
	<down>	(calendar-forward-week ARG)	Move the cursor forward ARG weeks. Moves backward if ARG is negative.
	<left>	(calendar-backward-day ARG)	Move the cursor back ARG days. Moves forward if ARG is negative.
	<next> <Pg Down>	(calendar-scroll-left-three-months ARG &optional EVENT)	Scroll the displayed calendar window left by 3*ARG months. - If ARG is negative the calendar is scrolled right. Maintains the relative position of the cursor with respect to the calendar as well as possible. - EVENT is an event like 'last-nonmenu-event'.
	<prior> <Pg up>	(calendar-scroll-right-three-months ARG &optional EVENT)	Scroll the displayed calendar window right by 3*ARG months. - If ARG is negative the calendar is scrolled left. Maintains the relative position of the cursor with respect to the calendar as well as possible. - EVENT is an event like 'last-nonmenu-event'.
	<right>	(calendar-forward-day ARG)	Move the cursor forward ARG days. Moves backward if ARG is negative.
	<up>	(calendar-backward-week ARG)	Move the cursor back ARG weeks. Moves forward if ARG is negative.
	C-c C-l	(calendar-redraw)	Redraw the calendar display, if 'calendar-buffer' is live.
	C-x C-x	(calendar-exchange-point-and-mark)	Exchange the current cursor position with the marked date.
	C-x <	(calendar-scroll-right &optional ARG EVENT)	Scroll the displayed calendar window right by ARG months. - If ARG is negative the calendar is scrolled left. - Maintains the relative position of the cursor with respect to the calendar as well as possible. - EVENT is an event like 'last-nonmenu-event'.
	C-x >	(calendar-scroll-left &optional ARG EVENT)	Scroll the displayed calendar left by ARG months. - If ARG is negative the calendar is scrolled right. - Maintains the relative position of the cursor with respect to the calendar as well as possible. - EVENT is an event like 'last-nonmenu-event'.
	C-x [	(calendar-backward-year ARG)	Move the cursor backward ARG years. Movement is forward is ARG is negative.
	C-x]	(calendar-forward-year ARG)	Move the cursor forward by ARG years. Movement is backward if ARG is negative.
	M-<	(calendar-beginning-of-year ARG)	Move the cursor backward ARG year beginnings.
	M-=	(calendar-count-days-region)	Count the number of days (inclusive) between point and the mark.
	M->	(calendar-end-of-year ARG)	Move the cursor forward ARG year beginnings.
	M-a	(calendar-beginning-of-month ARG)	Move the cursor backward ARG month beginnings.
	M-e	(calendar-end-of-month ARG)	Move the cursor forward ARG month ends.
	M-v	(calendar-scroll-right-three-months ARG &optional EVENT)	Scroll the displayed calendar window right by 3*ARG months. - If ARG is negative the calendar is scrolled left. - Maintains the relative position of the cursor with respect to the calendar as well as possible. - EVENT is an event like 'last-nonmenu-event'.
	M-{	(calendar-backward-month ARG)	Move the cursor backward by ARG months. Movement is forward if ARG is negative.
	M-}	(calendar-forward-month ARG)	Move the cursor forward ARG months. Movement is backward if ARG is negative.
	A a	(appt-add TIME MSG &optional WARNTIME)	Add an appointment for today at TIME with message MSG. - The time should be in either 24 hour format or am/pm format. - Optional argument WARNTIME is an integer (or string) giving the number of minutes before the appointment at which to start warning. The default is 'appt-message-warning-time'
	A d	(appt-delete)	Delete an appointment from the list of appointments.
	g D	(calendar-goto-day-of-year YEAR DAY &optional NOECHO)	Move cursor to YEAR, DAY number; echo DAY/YEAR unless NOECHO is non-nil. - Negative DAY counts backward from end of year. - Interactively, prompt for YEAR and DAY number.
	g a	(calendar-astro-goto-day-number DAYNUMBER &optional NOECHO)	Move cursor to astronomical (Julian) DAYNUMBER. Echo astronomical (Julian) day number unless NOECHO is non-nil.
	g c	(calendar-iso-goto-date DATE &optional NOECHO)	Move cursor to ISO DATE; echo ISO date unless NOECHO is non-nil.
	g d	(calendar-goto-date DATE)	Move cursor to DATE.
	g w	(calendar-iso-goto-week DATE &optional NOECHO)	Move cursor to ISO DATE; echo ISO date unless NOECHO is non-nil. Interactively, goes to the first day of the specified week.
	i a	(diary-insert-anniversary-entry ARG)	Insert an anniversary diary entry for the date given by point. Prefix argument ARG makes the entry nonmarking.
	i b	(diary-insert-block-entry ARG)	Insert a block diary entry for the days between the point and marked date. Prefix argument ARG makes the entry nonmarking.
	i c	(diary-insert-cyclic-entry ARG)	Insert a cyclic diary entry starting at the date given by point. Prefix argument ARG makes the entry nonmarking.
	i d	(diary-insert-entry ARG &optional EVENT)	Insert a diary entry for the date indicated by point. Prefix argument ARG makes the entry nonmarking.
	i m	(diary-insert-monthly-entry ARG)	Insert a monthly diary entry for the day of the month indicated by point. Prefix argument ARG makes the entry nonmarking.
	i w	(diary-insert-weekly-entry ARG)	Insert a weekly diary entry for the day of the week indicated by point. Prefix argument ARG makes the entry nonmarking.
	i y	(diary-insert-yearly-entry ARG)	Insert an annual diary entry for the day of the year indicated by point. Prefix argument ARG makes the entry nonmarking.
	p d	(calendar-print-day-of-year)	Show day number in year/days remaining in year for date under the cursor.
Print Calendar in HTML			
	H m	(cal-html-cursor-month MONTH YEAR DIR &optional EVENT)	Write an HTML calendar file for numeric MONTH of four-digit YEAR. - The output directory DIR is created if necessary. - Interactively, MONTH and YEAR are taken from the calendar cursor position. - Note that any existing output files are overwritten.
	H y	(cal-html-cursor-year YEAR DIR &optional EVENT)	Write HTML calendar files (index and monthly pages) for four-digit YEAR. - The output directory DIR is created if necessary. - Interactively, YEAR is taken from the calendar cursor position. - Note that any existing output files are overwritten.

Description	Keystroke	Function	Note
Print Calendars in LaTeX			
	t M	(cal-tex-cursor-month-landscape &optional N EVENT)	Make a LaTeX calendar buffer for the month the cursor is on. - Optional prefix argument N specifies number of months to be produced (default 1). The output is in landscape format, one month to a page. It shows holiday and diary entries if 'cal-tex-holidays' and 'cal-tex-diary', respectively, are non-nil. - Optional EVENT indicates a buffer position to use instead of point.
	t Y	(cal-tex-cursor-year-landscape &optional N EVENT)	Make a buffer with LaTeX commands for the year cursor is on. - Optional prefix argument N specifies number of years. - Optional EVENT indicates a buffer position to use instead of point.
	t d	(cal-tex-cursor-day &optional N EVENT)	Make a buffer with LaTeX commands for the day cursor is on. - Optional prefix argument N specifies number of days. The calendar shows the hours between 'cal-tex-daily-start' and 'cal-tex-daily-end', using the 24-hour clock if 'cal-tex-24' is non-nil. - Optional EVENT indicates a buffer position to use instead of point.
	t m	(cal-tex-cursor-month &optional N EVENT)	Make a LaTeX calendar buffer for the month the cursor is on. - Optional prefix argument N specifies number of months to be produced (default 1). The calendar is condensed onto one page. - It shows holiday and diary entries if 'cal-tex-holidays' and 'cal-tex-diary', respectively, are non-nil. Optional EVENT indicates a buffer position to use instead of point.
	t y	(cal-tex-cursor-year &optional N EVENT)	Make a buffer with LaTeX commands for the year cursor is on. - Optional prefix argument N specifies number of years. - Optional EVENT indicates a buffer position to use instead of point.
	t f W	(cal-tex-cursor-filofax-week &optional N EVENT)	One-week-at-a-glance <i>Filofax</i> style calendar for week indicated by cursor. - Optional prefix argument N specifies number of weeks (default 1), starting on Mondays. The calendar shows holiday and diary entries if 'cal-tex-holidays' and 'cal-tex-diary', respectively, are non-nil. - Optional EVENT indicates a buffer position to use instead of point.
	t f d	(cal-tex-cursor-filofax-daily &optional N EVENT)	Day-per-page <i>Filofax</i> style calendar for week indicated by cursor. - Optional prefix argument N specifies number of weeks (default 1), starting on Mondays. The calendar shows holiday and diary entries if 'cal-tex-holidays' and 'cal-tex-diary', respectively, are non-nil. Pages are ruled if 'cal-tex-rules' is non-nil. - Optional EVENT indicates a buffer position to use instead of point.
	t f w	(cal-tex-cursor-filofax-2week &optional N EVENT)	Two-weeks-at-a-glance <i>Filofax</i> style calendar for week cursor is in. - Optional prefix argument N specifies number of weeks (default 1). - The calendar shows holiday and diary entries if 'cal-tex-holidays' and 'cal-tex-diary', respectively, are non-nil. - Optional EVENT indicates a buffer position to use instead of point.
	t f y	(cal-tex-cursor-filofax-year &optional N EVENT)	Make a <i>Filofax</i> one page yearly calendar of year indicated by cursor. - Optional prefix argument N specifies number of years. - Optional EVENT indicates a buffer position to use instead of point.
	t w 1	(cal-tex-cursor-week &optional N EVENT)	Make a one page LaTeX calendar for one week, showing hours of the day. - There are two columns; with 8-12am in the first and 1-5pm in the second. - It shows holidays if 'cal-tex-holidays' is non-nil. - It does not show diary entries. - The optional prefix argument N specifies a number of weeks (default 1). - By default, the calendar is for the week at point; the optional argument EVENT specifies a different buffer position.
	t w 2	(cal-tex-cursor-week2 &optional N EVENT)	Make a two page LaTeX calendar for one week, showing hours of the day. - There are two columns; with 8-12am in the first and 1-5pm in the second. - It shows holidays if 'cal-tex-holidays' is non-nil. - It does not show diary entries. - The optional prefix argument N specifies a number of weeks (default 1). - By default, the calendar is for the week at point; the optional argument EVENT specifies a different buffer position.
	t w 3	(cal-tex-cursor-week-iso &optional N EVENT)	Make a one page LaTeX calendar for one week, in the ISO-style. - It does not show hours of the day. - It shows holidays if 'cal-tex-holidays' is non-nil. - It shows diary entries if 'cal-tex-diary' is non-nil. - The optional prefix argument N specifies a number of weeks (default 1). - By default, the calendar is for the week at point; the optional argument EVENT specifies a different buffer position.
	t w 4	(cal-tex-cursor-week-monday &optional N EVENT)	Make a one page LaTeX calendar for one week, showing hours of the day. - There are two columns; with M-W in the first and T-S in the second. - It shows the hours 8-12am and 1-5pm. - It shows holidays if 'cal-tex-holidays' is non-nil. - It does not show diary entries. - The optional prefix argument N specifies a number of weeks (default 1). - By default, the calendar is for the week at point; the optional argument EVENT specifies a different buffer position.
	t w W	(cal-tex-cursor-week2-summary &optional N EVENT)	Make a two page LaTeX calendar for one week, with optional diary entries. - It does not show hours of the day. - It shows holidays if 'cal-tex-holidays' is non-nil. - It shows diary entries if 'cal-tex-diary' is non-nil. - The optional prefix argument N specifies a number of weeks (default 1). - By default, the calendar is for the week at point; the optional argument EVENT specifies a different buffer position.
Other Calendars			
	p o	(calendar-print-other-dates &optional EVENT)	Show dates on other calendars for date under the cursor. If called by a mouse-event, pops up a menu with the result.
	p a	(calendar-astro-print-day-number)	Show astronomical (Julian) day number after noon UTC on cursor date.
	p c	(calendar-iso-print-date)	Show equivalent ISO date for the date under the cursor.
Bahai Calendar			
	p b	(calendar-bahai-print-date)	Show the Bahá'í calendar equivalent of the selected date.
	g b	(calendar-bahai-goto-date DATE &optional NOECHO)	Move cursor to Bahá'í date DATE; echo Bahá'í date unless NOECHO is non-nil.
	i B d	(diary-bahai-insert-entry ARG)	Insert a diary entry. - For the Bahá'í date corresponding to the date indicated by point. - Prefix argument ARG makes the entry nonmarking.
	i B m	(diary-bahai-insert-monthly-entry ARG)	Insert a monthly diary entry. - For the day of the Bahá'í month corresponding to the date indicated by point. - Prefix argument ARG makes the entry nonmarking.
	i B y	(diary-bahai-insert-yearly-entry ARG)	Insert an annual diary entry. - For the day of the Bahá'í year corresponding to the date indicated by point. - Prefix argument ARG will make the entry nonmarking.
Chinese Calendar			

Description	Keystroke	Function	Note
	p c	(calendar-chinese-print-date)	Show the Chinese date equivalents of date.
	g c	(calendar-chinese-goto-date DATE &optional NOECHO)	Move cursor to Chinese date DATE. • Echo Chinese date unless NOECHO is non-nil.
	i c a	(diary-chinese-insert-anniversary-entry &optional ARG)	Insert an anniversary diary entry for the Chinese date at point. • Prefix argument ARG makes the entry nonmarking.
	i c d	(diary-chinese-insert-entry &optional ARG)	Insert a diary entry for the Chinese date at point.
	i c m	(diary-chinese-insert-monthly-entry &optional ARG)	Insert a monthly diary entry for the Chinese date at point.
	i c y	(diary-chinese-insert-yearly-entry &optional ARG)	Insert a yearly diary entry for the Chinese date at point.
Coptic Calendar			
	p k	(calendar-coptic-print-date)	Show the Coptic calendar equivalent of the selected date.
	g k	(calendar-coptic-goto-date DATE &optional NOECHO)	Move cursor to Coptic date DATE. • Echo Coptic date unless NOECHO is t.
Ethiopian Calendar			
	p e	(calendar-ethiopic-print-date)	Show the Ethiopic calendar equivalent of the selected date.
	g e	(calendar-ethiopic-goto-date THEDATE &optional NOECHO)	Move cursor to Ethiopic date THEDATE. • Echo Ethiopic date unless NOECHO is t.
French Revolutionary Calendar			
	p f	(calendar-french-print-date)	Show the French Revolutionary calendar equivalent of the selected date.
	g f	(calendar-french-goto-date DATE &optional NOECHO)	Move cursor to French Revolutionary date DATE. • Echo French Revolutionary date unless NOECHO is non-nil.
Hebrew Calendar			
	p h	(calendar-hebrew-print-date)	Show the Hebrew calendar equivalent of the date under the cursor.
	g h	(calendar-hebrew-goto-date DATE &optional NOECHO)	Move cursor to Hebrew DATE; echo Hebrew date unless NOECHO is non-nil.
	i h d	(diary-hebrew-insert-entry ARG)	Insert a diary entry for the Hebrew date at point. • Prefix argument ARG makes the entry nonmarking.
	i h m	(diary-hebrew-insert-monthly-entry ARG)	Insert a monthly diary entry. • For the day of the Hebrew month corresponding to the date indicated by point. • Prefix argument ARG makes the entry nonmarking.
	i h y	(diary-hebrew-insert-yearly-entry ARG)	Insert an annual diary entry. • For the day of the Hebrew year corresponding to the date indicated by point. • Prefix argument ARG makes the entry nonmarking.
Islamic Calendar			
	p i	(calendar-islamic-print-date)	Show the Islamic calendar equivalent of the date under the cursor.
	g i	(calendar-islamic-goto-date DATE &optional NOECHO)	Move cursor to Islamic DATE; echo Islamic date unless NOECHO is non-nil.
	i i d	(diary-islamic-insert-entry ARG)	Insert a diary entry. • For the Islamic date corresponding to the date indicated by point. • Prefix argument ARG makes the entry nonmarking.
	i i m	(diary-islamic-insert-monthly-entry ARG)	Insert a monthly diary entry. • For the day of the Islamic month corresponding to the date indicated by point. • Prefix argument ARG makes the entry nonmarking.
	i i y	(diary-islamic-insert-yearly-entry ARG)	Insert an annual diary entry. • For the day of the Islamic year corresponding to the date indicated by point. • Prefix argument ARG makes the entry nonmarking.
Julian Calendar			
	p j	(calendar-julian-print-date)	Show the Julian calendar equivalent of the date under the cursor.
	g j	(calendar-julian-goto-date DATE &optional NOECHO)	Move cursor to Julian DATE; echo Julian date unless NOECHO is non-nil.
Maya Calendar			
	p m	(calendar-mayan-print-date)	Show the Mayan long count, tzolkin, and haab equivalents of date.
	g m l	(calendar-mayan-goto-long-count-date DATE &optional NOECHO)	Move cursor to Mayan long count DATE. • Echo Mayan date unless NOECHO is non-nil.
	g m n c	(calendar-mayan-next-round-date TZOLKIN-DATE HAAB-DATE &optional NOECHO)	Move cursor to next instance of Mayan TZOLKIN-DATE HAAB-DATE combination. • Echo Mayan date unless NOECHO is non-nil.
	g m n h	(calendar-mayan-next-haab-date HAAB-DATE &optional NOECHO)	Move cursor to next instance of Mayan HAAB-DATE. • Echo Mayan date unless NOECHO is non-nil.
	g m n t	(calendar-mayan-next-tzolkin-date TZOLKIN-DATE &optional NOECHO)	Move cursor to next instance of Mayan TZOLKIN-DATE. • Echo Mayan date unless NOECHO is non-nil.
	g m p c	(calendar-mayan-previous-round-date TZOLKIN-DATE HAAB-DATE &optional NOECHO)	Move to previous instance of Mayan TZOLKIN-DATE HAAB-DATE combination. • Echo Mayan date unless NOECHO is non-nil.
	g m p h	(calendar-mayan-previous-haab-date HAAB-DATE &optional NOECHO)	Move cursor to previous instance of Mayan HAAB-DATE. • Echo Mayan date unless NOECHO is non-nil.
	g m p t	(calendar-mayan-previous-tzolkin-date TZOLKIN-DATE &optional NOECHO)	Move cursor to previous instance of Mayan TZOLKIN-DATE. • Echo Mayan date unless NOECHO is non-nil.
Persian Calendar			
	p p	(calendar-persian-print-date)	Show the Persian calendar equivalent of the selected date
	g p	(calendar-persian-goto-date DATE &optional NOECHO)	Move cursor to Persian date DATE. • Echo Persian date unless NOECHO is non-nil.