

Exercice Lab: Content-based Recommendation Systems

<https://www.coursera.org/learn/machine-learning-with-python/ungradedLti/x4ipC/lab-content-based-recommendation-systems>

Recommendation systems are a collection of algorithms used to recommend items to users based on information taken from the user. These systems have become ubiquitous and can be commonly seen in online stores, movies databases and job finders. In this notebook, we will explore Content-based recommendation systems and implement a simple version of one using Python and the Pandas library.

Please notice that the practice labs (except the last week assignment) are optional and are provided for you to practice and understand the topic. Therefore, you do not need to submit those, as they are not graded, and won't be updated as complete. Just run the codes to see the results, and feel free to change it.

Ce cours utilise l'outil d'un tiers, Lab: Content-based Recommendation Systems, pour améliorer votre expérience d'apprentissage. L'outil référence des informations de base comme votre nom, votre adresse e-mail et votre ID Coursera.



CONTENT-BASED FILTERING

Recommendation systems are a collection of algorithms used to recommend items to users based on information taken from the user. These systems have become ubiquitous, and can be commonly seen in online stores, movies databases and job finders. In this notebook, we will explore Content-based recommendation systems and implement a simple version of one using Python and the Pandas library.

Table of contents

1. Acquiring the Data
2. Preprocessing
3. Content-Based Filtering

Acquiring the Data

To acquire and extract the data, simply run the following Bash scripts:

Dataset acquired from [GroupLens](#). Let's download the dataset. To download the data, we will use `!wget` to download it from IBM Object Storage.

Did you know? When it comes to Machine Learning, you will likely be working with large datasets. As a business, where can you host your data? IBM is offering a unique opportunity for businesses, with 10 Tb of IBM Cloud Object Storage: [Sign up now for free](#)

```
[ ]: !wget -O moviedataset.zip https://s3-api.us-geo.objectstorage.softlayer.net/cf-courses-data/Cog
print('unzipping ...')
!unzip -o -j moviedataset.zip
```

Code

```
!wget -O moviedataset.zip https://s3-api.us-géo.objectstorage.softlayer.net/cf-courses-
data/CognitiveClass/ML0101ENV3/labs/moviedataset.zip
print('unzipping ...')
!unzip -o -j moviedataset.zip
```

Now you're ready to start working with the data!

Preprocessing

First, let's get all of the imports out of the way:

```
[ ]: #Dataframe manipulation library
import pandas as pd
#Math functions, we'll only need the sqrt function so let's import only that
from math import sqrt
import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline
```

Code

```
#Dataframe manipulation library
import pandas as pd
#Math functions, we'll only need the sqrt function so let's import only that
from math import sqrt
import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline
```

Now let's read each file into their Dataframes:

```
[ ]: #Storing the movie information into a pandas dataframe
movies_df = pd.read_csv('movies.csv')
#Storing the user information into a pandas dataframe
ratings_df = pd.read_csv('ratings.csv')
#Head is a function that gets the first N rows of a dataframe. N's default is 5.
movies_df.head()
```

```
[3]:
```

	movieId	title	genres
0	1	Toy Story (1995)	Adventure Animation Children Comedy Fantasy
1	2	Jumanji (1995)	Adventure Children Fantasy
2	3	Grumpier Old Men (1995)	Comedy Romance
3	4	Waiting to Exhale (1995)	Comedy Drama Romance
4	5	Father of the Bride Part II (1995)	Comedy

ode

```
#Storing the movie information into a pandas dataframe
movies_df = pd.read_csv('movies.csv')
#Storing the user information into a pandas dataframe
ratings_df = pd.read_csv('ratings.csv')
```

#Head is a function that gets the first N rows of a dataframe. N's default is 5.

movies_df.head()

Let's also remove the year from the **title** column by using pandas' replace function and store in a new **year** column.

```
[ ]: #Using regular expressions to find a year stored between parentheses
#We specify the parantheses so we don't conflict with movies that have years in their titles
movies_df['year'] = movies_df.title.str.extract('(\d\d\d\d)',expand=False)
#Removing the parentheses
movies_df['year'] = movies_df.year.str.extract('(\d\d\d\d)',expand=False)
#Removing the years from the 'title' column
movies_df['title'] = movies_df.title.str.replace('(\d\d\d\d)', '')
#Applying the strip function to get rid of any ending whitespace characters that may have appeared
movies_df['title'] = movies_df['title'].apply(lambda x: x.strip())
movies_df.head()
```

```
[4]:
```

	movielfid	title	genres	year
0	1	Toy Story	Adventure Animation Children Comedy Fantasy	1995
1	2	Jumanji	Adventure Children Fantasy	1995
2	3	Grumpier Old Men	Comedy Romance	1995
3	4	Waiting to Exhale	Comedy Drama Romance	1995
4	5	Father of the Bride Part II	Comedy	1995

Code

#Using regular expressions to find a year stored between parentheses

#We specify the parantheses so we don't conflict with movies that have years in their titles

movies_df['year'] = movies_df.title.str.extract('(\d\d\d\d)',expand=False)

#Removing the parentheses

movies_df['year'] = movies_df.year.str.extract('(\d\d\d\d)',expand=False)

#Removing the years from the 'title' column

movies_df['title'] = movies_df.title.str.replace('(\d\d\d\d)', '')

#Applying the strip function to get rid of any ending whitespace characters that may have appeared

movies_df['title'] = movies_df['title'].apply(lambda x: x.strip())

movies_df.head()

With that, let's also split the values in the **Genres** column into a **list of Genres** to simplify future use. This can be achieved by applying Python's split string function on the correct column.

```
[ ]: #Every genre is separated by a | so we simply have to call the split function on /
movies_df['genres'] = movies_df.genres.str.split('|')
movies_df.head()
```

```
[5]:
```

	movielfid	title	genres	year
0	1	Toy Story	[Adventure, Animation, Children, Comedy, Fantasy]	1995
1	2	Jumanji	[Adventure, Children, Fantasy]	1995
2	3	Grumpier Old Men	[Comedy, Romance]	1995
3	4	Waiting to Exhale	[Comedy, Drama, Romance]	1995
4	5	Father of the Bride Part II	[Comedy]	1995

Code

```
#Every genre is separated by a | so we simply have to call the split function on |
movies_df['genres'] = movies_df.genres.str.split('|')
movies_df.head()
```

Since keeping genres in a list format isn't optimal for the content-based recommendation system technique, we will use the One Hot Encoding technique to convert the list of genres to a vector where each column corresponds to one possible value of the feature. This encoding is needed for feeding categorical data. In this case, we store every different genre in columns that contain either 1 or 0. 1 shows that a movie has that genre and 0 shows that it doesn't. Let's also store this dataframe in another variable since genres won't be important for our first recommendation system.

```
[ ]: #Copying the movie dataframe into a new one since we won't need to use the genre information in
      moviesWithGenres_df = movies_df.copy()

      #For every row in the dataframe, iterate through the list of genres and place a 1 into the corr
      for index, row in movies_df.iterrows():
          for genre in row['genres']:
              moviesWithGenres_df.at[index, genre] = 1
      #Filling in the NaN values with 0 to show that a movie doesn't have that column's genre
      moviesWithGenres_df = moviesWithGenres_df.fillna(0)
      moviesWithGenres_df.head()
```

	movieId	title	genres	year	Adventure	Animation	Children	Comedy	Fantasy	Romance	...	Horr
0	1	Toy Story	[Adventure, Animation, Children, Comedy, Fantasy]	1995	1.0	1.0	1.0	1.0	1.0	0.0	...	(
1	2	Jumanji	[Adventure, Children, Fantasy]	1995	1.0	0.0	1.0	0.0	1.0	0.0	...	(
2	3	Grumpier Old Men	[Comedy, Romance]	1995	0.0	0.0	0.0	1.0	0.0	1.0	...	(
3	4	Waiting to Exhale	[Comedy, Drama, Romance]	1995	0.0	0.0	0.0	1.0	0.0	1.0	...	(

Code

```
#Copying the movie dataframe into a new one since we won't need to use the genre information in our first case.
moviesWithGenres_df = movies_df.copy()
```

```
#For every row in the dataframe, iterate through the list of genres and place a 1 into the corresponding column
for index, row in movies_df.iterrows():
    for genre in row['genres']:
        moviesWithGenres_df.at[index, genre] = 1
#Filling in the NaN values with 0 to show that a movie doesn't have that column's genre
moviesWithGenres_df = moviesWithGenres_df.fillna(0)
moviesWithGenres_df.head()
```


Next, let's look at the ratings dataframe.

```
[ ]: ratings_df.head()
```

```
[7]:
```

	userId	movieId	rating	timestamp
0	1	169	2.5	1204927694
1	1	2471	3.0	1204927438
2	1	48516	5.0	1204927435
3	2	2571	3.5	1436165433
4	2	109487	4.0	1436165496

ode
ratings_df.head()

Every row in the ratings dataframe has a user id associated with at least one movie, a rating and a timestamp showing when they reviewed it. We won't be needing the timestamp column, so let's drop it to save on memory.

```
[ ]: #Drop removes a specified row or column from a dataframe  
ratings_df = ratings_df.drop('timestamp', 1)  
ratings_df.head()
```

```
[8]:
```

	userId	movieId	rating
0	1	169	2.5
1	1	2471	3.0
2	1	48516	5.0
3	2	2571	3.5
4	2	109487	4.0

Code

```
#Drop removes a specified row or column from a dataframe  
ratings_df = ratings_df.drop('timestamp', 1)  
ratings_df.head()
```

Content-Based recommendation system

Now, let's take a look at how to implement **Content-Based** or **Item-Item recommendation systems**. This technique attempts to figure out what a user's favourite aspects of an item is, and then recommends items that present those aspects. In our case, we're going to try to figure out the input's favorite genres from the movies and ratings given.

Let's begin by creating an input user to recommend movies to:

Notice: To add more movies, simply increase the amount of elements in the **userInput**. Feel free to add more in! Just be sure to write it in with capital letters and if a movie starts with a "The", like "The Matrix" then write it in like this: 'Matrix, The' .

```
[ ]: userInput = [
    {'title':'Breakfast Club, The', 'rating':5},
    {'title':'Toy Story', 'rating':3.5},
    {'title':'Jumanji', 'rating':2},
    {'title':"Pulp Fiction", 'rating':5},
    {'title':'Akira', 'rating':4.5}
]
inputMovies = pd.DataFrame(userInput)
inputMovies
```

```
[9]:
```

	title	rating
0	Breakfast Club, The	5.0
1	Toy Story	3.5
2	Jumanji	2.0
3	Pulp Fiction	5.0
4	Akira	4.5

Code

```
userInput = [
    {'title':'Breakfast Club, The', 'rating':5},
    {'title':'Toy Story', 'rating':3.5},
    {'title':'Jumanji', 'rating':2},
    {'title':"Pulp Fiction", 'rating':5},
    {'title':'Akira', 'rating':4.5}
]
inputMovies = pd.DataFrame(userInput)
inputMovies
```

Add movieId to input user

With the input complete, let's extract the input movie's ID's from the movies dataframe and add them into it.

We can achieve this by first filtering out the rows that contain the input movie's title and then merging this subset with the input dataframe. We also drop unnecessary columns for the input to save memory space.

```
[ ]: #Filtering out the movies by title
inputId = movies_df[movies_df['title'].isin(inputMovies['title'].tolist())]
#Then merging it so we can get the movieId. It's implicitly merging it by title.
inputMovies = pd.merge(inputId, inputMovies)
#Dropping information we won't use from the input dataframe
inputMovies = inputMovies.drop('genres', 1).drop('year', 1)
#Final input dataframe
#If a movie you added in above isn't here, then it might not be in the original
#dataframe or it might spelled differently, please check capitalisation.
inputMovies
```

```
[10]:
```

	movieId	title	rating
0	1	Toy Story	3.5
1	2	Jumanji	2.0
2	296	Pulp Fiction	5.0
3	1274	Akira	4.5
4	1968	Breakfast Club, The	5.0

Co

de

#Filtering out the movies by title

inputId = movies_df[movies_df['title'].isin(inputMovies['title'].tolist())]

#Then merging it so we can get the movieId. It's implicitly merging it by title.

inputMovies = pd.merge(inputId, inputMovies)

#Dropping information we won't use from the input dataframe

inputMovies = inputMovies.drop('genres', 1).drop('year', 1)

#Final input dataframe

#If a movie you added in above isn't here, then it might not be in the original

#dataframe or it might spelled differently, please check capitalisation.

inputMovies

We're going to start by learning the input's preferences, so let's get the subset of movies that the input has watched from the Dataframe containing genres defined with binary values.

```
[ ]: #Filtering out the movies from the input
userMovies = moviesWithGenres_df[moviesWithGenres_df['movieId'].isin(inputMovies['movieId'].tolist())]
userMovies
```

```
++ ]:
```

	movieId	title	genres	year	Adventure	Animation	Children	Comedy	Fantasy	Romance	...	H
0	1	Toy Story	[Adventure, Animation, Children, Comedy, Fantasy]	1995	1.0	1.0	1.0	1.0	1.0	0.0	...	
1	2	Jumanji	[Adventure, Children, Fantasy]	1995	1.0	0.0	1.0	0.0	1.0	0.0	...	
293	296	Pulp Fiction	[Comedy, Crime, Drama, Thriller]	1994	0.0	0.0	0.0	1.0	0.0	0.0	...	
1246	1274	Akira	[Action, Adventure, Animation]	1988	1.0	1.0	0.0	0.0	0.0	0.0	...	
1885	1968	Breakfast Club, The	[Comedy, Drama]	1985	0.0	0.0	0.0	1.0	0.0	0.0	...	

5 rows × 24 columns

Code

#Filtering out the movies from the input

```
userMovies = moviesWithGenres_df[moviesWithGenres_df['movieId'].isin(inputMovies['movieId'].tolist())]
userMovies
```

We'll only need the actual genre table, so let's clean this up a bit by resetting the index and dropping the movieId, title, genres and year columns.

```
[ ]: #Resetting the index to avoid future issues
userMovies = userMovies.reset_index(drop=True)
#Dropping unnecessary issues due to save memory and to avoid issues
userGenreTable = userMovies.drop('movieId', 1).drop('title', 1).drop('genres', 1).drop('year', 1)
userGenreTable
```

```
[12]:
```

	Adventure	Animation	Children	Comedy	Fantasy	Romance	Drama	Action	Crime	Thriller	Horror	Mystery
0	1.0	1.0	1.0	1.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
1	1.0	0.0	1.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
2	0.0	0.0	0.0	1.0	0.0	0.0	1.0	0.0	1.0	1.0	0.0	0.0
3	1.0	1.0	0.0	0.0	0.0	0.0	0.0	1.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	1.0	0.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0

Code

```
#Resetting the index to avoid future issues
userMovies = userMovies.reset_index(drop=True)
#Dropping unnecessary issues due to save memory and to avoid issues
userGenreTable = userMovies.drop('movieId', 1).drop('title', 1).drop('genres', 1).drop('year', 1)
userGenreTable
```

Now we're ready to start learning the input's preferences!

To do this, we're going to turn each genre into weights. We can do this by using the input's reviews and multiplying them into the input's genre table and then summing up the resulting table by column. This operation is actually a dot product between a matrix and a vector, so we can simply accomplish by calling Pandas's "dot" function.

```
[ ]: inputMovies['rating']
```

```
[13]: 0    3.5
      1    2.0
      2    5.0
      3    4.5
      4    5.0
      Name: rating, dtype: float64
```

ode

```
inputMovies['rating']
```



```
[ ]: #Dot produt to get weights
userProfile = userGenreTable.transpose().dot(inputMovies['rating'])
#The user profile
userProfile
```

```
[14]: Adventure          10.0
      Animation          8.0
      Children           5.5
      Comedy            13.5
      Fantasy            5.5
      Romance            0.0
      Drama             10.0
      Action             4.5
      Crime              5.0
      Thriller           5.0
      Horror             0.0
      Mystery            0.0
      Sci-Fi             4.5
      IMAX               0.0
      Documentary        0.0
      War                0.0
      Musical            0.0
      Western            0.0
      Film-Noir          0.0
      (no genres listed) 0.0
      dtype: float64
```

C

ode

```
#Dot produt to get weights
userProfile = userGenreTable.transpose().dot(inputMovies['rating'])
#The user profile
userProfile
```

Now, we have the weights for every of the user's preferences. This is known as the User Profile. Using this, we can recommend movies that satisfy the user's preferences.

Let's start by extracting the genre table from the original dataframe:

```
[ ]: #Now Let's get the genres of every movie in our original dataframe
genreTable = moviesWithGenres_df.set_index(moviesWithGenres_df['movieId'])
#And drop the unnecessary information
genreTable = genreTable.drop('movieId', 1).drop('title', 1).drop('genres', 1).drop('year', 1)
genreTable.head()
```

Adventure Animation Children Comedy Fantasy Romance Drama Action Crime Thriller Horror

movieId												
1	1.0	1.0	1.0	1.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
2	1.0	0.0	1.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
3	0.0	0.0	0.0	1.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	1.0	0.0	1.0	1.0	0.0	0.0	0.0	0.0	0.0
5	0.0	0.0	0.0	1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C

ode

#Now let's get the genres of every movie in our original dataframe

```
genreTable = moviesWithGenres_df.set_index(moviesWithGenres_df['movieId'])
```

#And drop the unnecessary information

```
genreTable = genreTable.drop('movieId', 1).drop('title', 1).drop('genres', 1).drop('year', 1)
```

```
genreTable.head()
```

```
[ ]: genreTable.shape
```

```
[16]: (34208, 20)
```

Code

```
genreTable.shape
```

With the input's profile and the complete list of movies and their genres in hand, we're going to take the weighted average of every movie based on the input profile and recommend the top twenty movies that most satisfy it.

```
[ ]: #Multiply the genres by the weights and then take the weighted average
recommendationTable_df = ((genreTable*userProfile).sum(axis=1))/(userProfile.sum())
recommendationTable_df.head()
```

```
[17]: movieId
1      0.594406
2      0.293706
3      0.188811
4      0.328671
5      0.188811
dtype: float64
```

Code

#Multiply the genres by the weights and then take the weighted average

```
recommendationTable_df = ((genreTable*userProfile).sum(axis=1))/(userProfile.sum())
```

```
recommendationTable_df.head()
```

```
[ ]: #Sort our recommendations in descending order
recommendationTable_df = recommendationTable_df.sort_values(ascending=False)
#Just a peek at the values
recommendationTable_df.head()
```

```
[18]: movieId
      5018      0.748252
      26093     0.734266
      27344     0.720280
      148775    0.685315
      6902      0.678322
      dtype: float64
```

Code

#Sort our recommendations in descending order

```
recommendationTable_df = recommendationTable_df.sort_values(ascending=False)
```

#Just a peek at the values

```
recommendationTable_df.head()
```

Now here's the recommendation table!

```
[ ]: #The final recommendation table
      movies_df.loc[movies_df['movieId'].isin(recommendationTable_df.head(20).keys())]
```

[19]:	movieId		title	genres	year
	664	673	Space Jam	[Adventure, Animation, Children, Comedy, Fanta...	1996
	1824	1907	Mulan	[Adventure, Animation, Children, Comedy, Drama...	1998
	2902	2987	Who Framed Roger Rabbit?	[Adventure, Animation, Children, Comedy, Crime...	1988
	4923	5018	Motorama	[Adventure, Comedy, Crime, Drama, Fantasy, Mvs...	1991
	4923	5018	Motorama	[Adventure, Comedy, Crime, Drama, Fantasy, Mys...	1991
	6793	6902	Interstate 60	[Adventure, Comedy, Drama, Fantasy, Mystery, S...	2002
	8605	26093	Wonderful World of the Brothers Grimm, The	[Adventure, Animation, Children, Comedy, Drama...	1962
	8783	26340	Twelve Tasks of Asterix, The (Les douze travaux...	[Action, Adventure, Animation, Children, Comed...	1976
	9296	27344	Revolutionary Girl Utena: Adolescence of Utena...	[Action, Adventure, Animation, Comedy, Drama, ...	1999
	9825	32031	Robots	[Adventure, Animation, Children, Comedy, Fanta...	2005
	11716	51632	Atlantis: Milo's Return	[Action, Adventure, Animation, Children, Comed...	2003
	11751	51939	TMNT (Teenage Mutant Ninja Turtles)	[Action, Adventure, Animation, Children, Comed...	2007

13250	64645	The Wrecking Crew	[Action, Adventure, Comedy, Crime, Drama, Thri...	1968
16055	81132	Rubber	[Action, Adventure, Comedy, Crime, Drama, Film...	2010
18312	91335	Gruffalo, The	[Adventure, Animation, Children, Comedy, Drama]	2009
22778	108540	Ernest & Célestine (Ernest et Célestine)	[Adventure, Animation, Children, Comedy, Drama...	2012
22881	108932	The Lego Movie	[Action, Adventure, Animation, Children, Comed...	2014
25218	117646	Dragonheart 2: A New Beginning	[Action, Adventure, Comedy, Drama, Fantasy, Th...	2000
26442	122787	The 39 Steps	[Action, Adventure, Comedy, Crime, Drama, Thri...	1959
32854	146305	Princes and Princesses	[Animation, Children, Comedy, Drama, Fantasy, ...	2000
33509	148775	Wizards of Waverly Place: The Movie	[Adventure, Children, Comedy, Drama, Fantasy, ...	2009

e

```
#The final recommendation table
movies_df.loc[movies_df['movieId'].isin(recommendationTable_df.head(20).keys())]
```


Advantages and Disadvantages of Content-Based Filtering

Advantages

- Learns user's preferences
- Highly personalized for the user

Disadvantages

- Doesn't take into account what others think of the item, so low quality item recommendations might happen
- Extracting data is not always intuitive
- Determining what characteristics of the item the user dislikes or likes is not always obvious

Want to learn more?

IBM SPSS Modeler is a comprehensive analytics platform that has many machine learning algorithms. It has been designed to bring predictive intelligence to decisions made by individuals, by groups, by systems – by your enterprise as a whole. A free trial is available through this course, available here: [SPSS Modeler](#)

Also, you can use Watson Studio to run these notebooks faster with bigger datasets. Watson Studio is IBM's leading cloud solution for data scientists, built by data scientists. With Jupyter notebooks, RStudio, Apache Spark and popular libraries pre-packaged in the cloud, Watson Studio enables data scientists to collaborate on their projects without having to install anything. Join the fast-growing community of Watson Studio users today with a free account at [Watson Studio](#)

Thanks for completing this lesson!