

Continuous_Control

January 23, 2021

1 Continuous Control

In this notebook, you will learn how to use the Unity ML-Agents environment for the second project of the [Deep Reinforcement Learning Nanodegree](#) program.

1.0.1 1. Start the Environment

We begin by importing the necessary packages. If the code cell below returns an error, please revisit the project instructions to double-check that you have installed [Unity ML-Agents](#) and [NumPy](#).

```
[1]: from unityagents import UnityEnvironment
import numpy as np
```

Next, we will start the environment! *Before running the code cell below*, change the `file_name` parameter to match the location of the Unity environment that you downloaded.

- **Mac**: "path/to/Reacher.app"
- **Windows (x86)**: "path/to/Reacher_Windows_x86/Reacher.exe"
- **Windows (x86_64)**: "path/to/Reacher_Windows_x86_64/Reacher.exe"
- **Linux (x86)**: "path/to/Reacher_Linux/Reacher.x86"
- **Linux (x86_64)**: "path/to/Reacher_Linux/Reacher.x86_64"
- **Linux (x86, headless)**: "path/to/Reacher_Linux_NoVis/Reacher.x86"
- **Linux (x86_64, headless)**: "path/to/Reacher_Linux_NoVis/Reacher.x86_64"

For instance, if you are using a Mac, then you downloaded `Reacher.app`. If this file is in the same folder as the notebook, then the line below should appear as follows:

```
env = UnityEnvironment(file_name="Reacher.app")
```

```
[2]: env = UnityEnvironment(file_name='Reacher_20.app')
```

```
INFO:unityagents:
'Academy' started successfully!
Unity Academy name: Academy
  Number of Brains: 1
  Number of External Brains : 1
  Lesson number : 0
  Reset Parameters :
    goal_speed -> 1.0
```

```

        goal_size -> 5.0
Unity brain name: ReacherBrain
    Number of Visual Observations (per agent): 0
    Vector Observation space type: continuous
    Vector Observation space size (per agent): 33
    Number of stacked Vector Observation: 1
    Vector Action space type: continuous
    Vector Action space size (per agent): 4
    Vector Action descriptions: , , ,

```

Environments contain *brains* which are responsible for deciding the actions of their associated agents. Here we check for the first brain available, and set it as the default brain we will be controlling from Python.

```

[3]: # get the default brain
brain_name = env.brain_names[0]
brain = env.brains[brain_name]

```

1.0.2 2. Examine the State and Action Spaces

In this environment, a double-jointed arm can move to target locations. A reward of +0.1 is provided for each step that the agent's hand is in the goal location. Thus, the goal of your agent is to maintain its position at the target location for as many time steps as possible.

The observation space consists of 33 variables corresponding to position, rotation, velocity, and angular velocities of the arm. Each action is a vector with four numbers, corresponding to torque applicable to two joints. Every entry in the action vector must be a number between -1 and 1.

Run the code cell below to print some information about the environment.

```

[4]: # reset the environment
env_info = env.reset(train_mode=True)[brain_name]

# number of agents
num_agents = len(env_info.agents)
print('Number of agents:', num_agents)

# size of each action
action_size = brain.vector_action_space_size
print('Size of each action:', action_size)

# examine the state space
states = env_info.vector_observations
state_size = states.shape[1]
print('There are {} agents. Each observes a state with length: {}'.
      ↪format(states.shape[0], state_size))
print('The state for the first agent looks like:', states[0])

```

```

Number of agents: 1
Size of each action: 4

```

There are 1 agents. Each observes a state with length: 33
The state for the first agent looks like: [0.00000000e+00 -4.00000000e+00
0.00000000e+00 1.00000000e+00
-0.00000000e+00 -0.00000000e+00 -4.37113883e-08 0.00000000e+00
0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
0.00000000e+00 0.00000000e+00 -1.00000000e+01 0.00000000e+00
1.00000000e+00 -0.00000000e+00 -0.00000000e+00 -4.37113883e-08
0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
0.00000000e+00 0.00000000e+00 5.75471878e+00 -1.00000000e+00
5.55726671e+00 0.00000000e+00 1.00000000e+00 0.00000000e+00
-1.68164849e-01]

1.0.3 3. Take Random Actions in the Environment

In the next code cell, you will learn how to use the Python API to control the agent and receive feedback from the environment.

Once this cell is executed, you will watch the agent's performance, if it selects an action at random with each time step. A window should pop up that allows you to observe the agent, as it moves through the environment.

Of course, as part of the project, you'll have to change the code so that the agent is able to use its experience to gradually choose better actions when interacting with the environment!

```
[5]: env_info = env.reset(train_mode=False)[brain_name]      # reset the environment
    ↪
    states = env_info.vector_observations                    # get the current state
    ↪ (for each agent)
    scores = np.zeros(num_agents)                          # initialize the score
    ↪ (for each agent)
    while True:
        actions = np.random.randn(num_agents, action_size) # select an action (for
    ↪ each agent)
        actions = np.clip(actions, -1, 1)                  # all actions between -1
    ↪ and 1
        env_info = env.step(actions)[brain_name]           # send all actions to
    ↪ the environment
        next_states = env_info.vector_observations          # get next state (for
    ↪ each agent)
        rewards = env_info.rewards                         # get reward (for each
    ↪ agent)
        dones = env_info.local_done                        # see if episode finished
        scores += env_info.rewards                          # update the score (for
    ↪ each agent)
        states = next_states                                # roll over states to
    ↪ next time step
        if np.any(dones):                                  # exit loop if episode
    ↪ finished
```

```

        break
    print('Total score (averaged over agents) this episode: {}'.format(np.
        ↳mean(scores)))

```

Total score (averaged over agents) this episode: 0.0

When finished, you can close the environment.

```
[6]: env.close()
```

1.0.4 4. It's Your Turn!

Now it's your turn to train your own agent to solve the environment! When training the environment, set `train_mode=True`, so that the line for resetting the environment looks like the following:

```
env_info = env.reset(train_mode=True)[brain_name]
```

```
[1]: from unityagents import UnityEnvironment
import numpy as np

env = UnityEnvironment(file_name='Reacher_single.app')
```

```

INFO:unityagents:
'Academy' started successfully!
Unity Academy name: Academy
    Number of Brains: 1
    Number of External Brains : 1
    Lesson number : 0
    Reset Parameters :
        goal_speed -> 1.0
        goal_size -> 5.0
Unity brain name: ReacherBrain
    Number of Visual Observations (per agent): 0
    Vector Observation space type: continuous
    Vector Observation space size (per agent): 33
    Number of stacked Vector Observation: 1
    Vector Action space type: continuous
    Vector Action space size (per agent): 4
    Vector Action descriptions: , , ,

```

```
[2]: # get the default brain
brain_name = env.brain_names[0]
brain = env.brains[brain_name]
```

```
[3]: import os.path

def restore_agent(actor_name, filepath_local_actor, filepath_local_critic,
    ↳filepath_target_actor, filepath_target_critic):
    # function to read and load saved weights into agent networks

```

```

checkpoint_local_actor = torch.load(filepath_local_actor)
checkpoint_local_critic = torch.load(filepath_local_critic)
checkpoint_target_actor = torch.load(filepath_target_actor)
checkpoint_target_critic = torch.load(filepath_target_critic)

if actor_name == 'ddpg':
    loaded_agent = Agent(state_size, action_size, random_seed=33)
elif actor_name == 'td3':
    loaded_agent = Agent(state_size, action_size, random_seed=33,
→policy_noise=0.2)

loaded_agent.actor_local.load_state_dict(checkpoint_local_actor)
loaded_agent.actor_target.load_state_dict(checkpoint_target_actor)
loaded_agent.critic_local.load_state_dict(checkpoint_local_critic)
loaded_agent.critic_target.load_state_dict(checkpoint_target_critic)

return loaded_agent

```

```

[4]: from collections import deque
import torch

def run_experiment(agent, n_episodes=2000, max_t=10000,
→agent_ckpt_prefix='agent', critic_ckpt_prefix='critic'):

    scores_deque = deque(maxlen=100)
    rolling_average_score = []
    scores = []

    for i_episode in range(1, n_episodes+1):
        env_info = env.reset(train_mode=True)[brain_name]      # reset the
→environment                                                  #
        states = env_info.vector_observations                  # get the current
→state                                                         #
        score = np.zeros(num_agents)
        agent.reset()                                          # reset the agent
        for t in range(max_t):
            actions = agent.act(states, add_noise=True)

            env_info = env.step(actions)[brain_name]          # send all
→actions to the environment                                    #
            next_states = env_info.vector_observations         # get next
→state (for each agent)                                       #
            rewards = env_info.rewards                        # get reward
→(for each agent)

```

```

        dones = env_info.local_done # see if
→episode finished

        for state, action, reward, next_state, done in zip(states, actions,
→rewards, next_states, dones):
            agent.step(state, action, reward, next_state, done, t)

            states = next_states
            score += rewards

            if np.any(dones):
                break

        score = np.mean(score)
        scores_deque.append(score)
        rolling_average_score.append(np.mean(scores_deque))
        scores.append(score)

        print('\rEpisode {} \tAverage Score: {:.2f} \tScore: {:.2f}'.
→format(i_episode,
                                                    np.
→mean(scores_deque),
                                                   
→score), end='')

        if i_episode % 10 == 0:
            print('\rSave_agent\r')
            torch.save(agent.actor_local.state_dict(),
→agent_ckp_prefix+'_ckpt_local.pth') # save local actor
            torch.save(agent.actor_target.state_dict(),
→agent_ckp_prefix+'_ckpt_target.pth') # save target actor
            torch.save(agent.critic_local.state_dict(),
→critic_ckp_prefix+'_ckpt_local.pth') # save local critic
            torch.save(agent.critic_target.state_dict(),
→critic_ckp_prefix+'_ckpt_target.pth') # target critic
            if i_episode % 100 == 0:
                print('\rEpisode {} \tAverage Score: {:.2f}'.format(i_episode, np.
→mean(scores_deque)))
                if np.mean(scores_deque) >= 30.0:
                    torch.save(agent.actor_local.state_dict(),
→agent_ckp_prefix+'_ckpt_local.pth') # save local actor
                    torch.save(agent.actor_target.state_dict(),
→agent_ckp_prefix+'_ckpt_target.pth') # save target actor
                    torch.save(agent.critic_local.state_dict(),
→critic_ckp_prefix+'_ckpt_local.pth') # save local critic

```

```

        torch.save(agent.critic_target.state_dict(),
        ↪critic_ckpt_prefix+'_ckpt_target.pth')
        print('\rEnvironment solved Episode {} \tAverage Score: {:.2f}'.
        ↪format(i_episode, np.mean(scores_deque)))
        break
    return scores, rolling_average_score

```

```

[5]: # reset the environment
env_info = env.reset(train_mode=True)[brain_name]

# number of agents
num_agents = len(env_info.agents)
print('Number of agents:', num_agents)

# size of each action
action_size = brain.vector_action_space_size
print('Size of each action:', action_size)

# examine the state space
states = env_info.vector_observations
state_size = states.shape[1]
print('There are {} agents. Each observes a state with length: {}'.
    ↪format(states.shape[0], state_size))
print('The state for the first agent looks like:', states[0])

```

```

Number of agents: 1
Size of each action: 4
There are 1 agents. Each observes a state with length: 33
The state for the first agent looks like: [ 0.00000000e+00 -4.00000000e+00
 0.00000000e+00  1.00000000e+00
 -0.00000000e+00 -0.00000000e+00 -4.37113883e-08  0.00000000e+00
  0.00000000e+00  0.00000000e+00  0.00000000e+00  0.00000000e+00
  0.00000000e+00  0.00000000e+00 -1.00000000e+01  0.00000000e+00
  1.00000000e+00 -0.00000000e+00 -0.00000000e+00 -4.37113883e-08
  0.00000000e+00  0.00000000e+00  0.00000000e+00  0.00000000e+00
  0.00000000e+00  0.00000000e+00  5.75471878e+00 -1.00000000e+00
  5.55726671e+00  0.00000000e+00  1.00000000e+00  0.00000000e+00
 -1.68164849e-01]

```

1.1 DDPG

The first algorithm will be a standard DDPG as found in the examples from the Udacity Deep Learning NanoDegree: <https://github.com/udacity/deep-reinforcement-learning/tree/master/ddpg-bipedal>

It will be adapted to solve the Reacher environment

```
[6]: from actors.ddpg_actor import Agent

agent_name = 'checkpoints/agent_ddpg_noise_reduction_single'
critic_name = 'checkpoints/critic_ddpg_noise_reduction_single'

local_actor_path = agent_name+'_ckpt_local.pth'
target_actor_path = agent_name+'_ckpt_target.pth'
local_critic_path = critic_name+'_ckpt_local.pth'
target_critic_path = critic_name+'_ckpt_target.pth'

# if checkpoint exists we load the agent
if os.path.isfile(local_actor_path):
    agent = restore_agent('ddpg', local_actor_path, local_critic_path,
        ↪target_actor_path, target_critic_path)
    print("Agent loaded.")
else:
    agent = Agent(state_size, action_size, random_seed = 33)
    print("Agent created.")
```

Agent created.

```
[ ]: scores, rolling_average = run_experiment(agent, agent_ckp_prefix=agent_name,
    ↪critic_ckp_prefix=critic_name)
```

```
[ ]: import matplotlib.pyplot as plt
    %matplotlib inline

# plot scores across episodes
fig = plt.figure()
ax = fig.add_subplot(111)
plt.plot(np.arange(len(scores)), scores, label='DDPG')
plt.plot(np.arange(len(scores)), rolling_average, c='r', label='Rolling AVG')
plt.ylabel('Score')
plt.xlabel('Episode #')
plt.legend(loc='upper left');
plt.show()
```

```
[ ]: env.close()
```

1.2 TD3

The first improvement tried is the TD3 algorithm which essentially make 3 improvements to the DDPG. 1. Twin network for the critic 2. Add noise to actions used to compute targets 3. Delayed updates of the policy

Please restart the environment before running the cells below


```
[6]: from actors.td3_actor import Agent

agent_name = 'checkpoints/agent_td3_single_noise'
critic_name = 'checkpoints/critic_td3_single_noise'

local_actor_path = agent_name+'_ckpt_local.pth'
target_actor_path = agent_name+'_ckpt_target.pth'
local_critic_path = critic_name+'_ckpt_local.pth'
target_critic_path = critic_name+'_ckpt_target.pth'

# if checkpoint exists we load the agent
if os.path.isfile(local_actor_path):
    agent = restore_agent('td3', local_actor_path, local_critic_path,
        ↪target_actor_path, target_critic_path)
    print("Agent loaded.")
else:
    agent = Agent(state_size, action_size, random_seed=33, policy_noise=0.2)
    print("Agent created.")
```

Agent created.

```
[7]: # run
scores, rolling_average = run_experiment(agent, agent_ckpt_prefix=agent_name,
    ↪critic_ckpt_prefix=critic_name)
```

Save_agent	Average Score: 0.80	Score: 1.48
Save_agent	Average Score: 1.04	Score: 0.44
Save_agent	Average Score: 1.05	Score: 0.95
Save_agent	Average Score: 1.16	Score: 2.38
Save_agent	Average Score: 1.36	Score: 3.98
Save_agent	Average Score: 1.41	Score: 2.10
Save_agent	Average Score: 1.51	Score: 2.46
Save_agent	Average Score: 1.52	Score: 0.53
Save_agent	Average Score: 1.52	Score: 1.51
Save_agent0	Average Score: 1.59	Score: 1.36
Episode 100	Average Score: 1.59	
Save_agent0	Average Score: 1.81	Score: 4.14
Save_agent0	Average Score: 1.86	Score: 1.30
Save_agent0	Average Score: 2.00	Score: 1.21
Save_agent0	Average Score: 2.03	Score: 1.14
Save_agent0	Average Score: 1.85	Score: 0.00
Save_agent0	Average Score: 1.70	Score: 0.02
Save_agent0	Average Score: 1.53	Score: 0.31
Save_agent0	Average Score: 1.44	Score: 1.62
Save_agent0	Average Score: 1.45	Score: 2.43
Save_agent0	Average Score: 1.41	Score: 2.67


Episode 200	Average Score: 1.41	
Save_agent0	Average Score: 1.29	Score: 2.55
Save_agent0	Average Score: 1.28	Score: 2.49
Save_agent0	Average Score: 1.10	Score: 0.47
Save_agent0	Average Score: 1.03	Score: 0.00
Save_agent0	Average Score: 1.05	Score: 0.00
Save_agent0	Average Score: 1.06	Score: 0.62
Save_agent0	Average Score: 1.13	Score: 3.38
Save_agent0	Average Score: 1.22	Score: 1.74
Save_agent0	Average Score: 1.36	Score: 0.41
Save_agent0	Average Score: 1.34	Score: 3.67
Episode 300	Average Score: 1.34	
Save_agent0	Average Score: 1.36	Score: 3.82
Save_agent0	Average Score: 1.60	Score: 4.71
Save_agent0	Average Score: 1.85	Score: 1.676
Save_agent0	Average Score: 1.84	Score: 0.74
Save_agent0	Average Score: 1.82	Score: 0.32
Save_agent0	Average Score: 1.90	Score: 0.00
Save_agent0	Average Score: 2.09	Score: 5.16
Save_agent0	Average Score: 2.51	Score: 5.406
Save_agent0	Average Score: 2.44	Score: 0.98
Save_agent0	Average Score: 2.58	Score: 0.00
Episode 400	Average Score: 2.58	
Save_agent0	Average Score: 2.43	Score: 1.98
Save_agent0	Average Score: 2.12	Score: 0.00
Save_agent0	Average Score: 1.99	Score: 6.11
Save_agent0	Average Score: 2.39	Score: 3.74
Save_agent0	Average Score: 2.86	Score: 1.800
Save_agent0	Average Score: 3.39	Score: 4.186
Save_agent0	Average Score: 3.62	Score: 5.70
Save_agent0	Average Score: 3.49	Score: 7.33
Save_agent0	Average Score: 3.55	Score: 4.96
Save_agent0	Average Score: 4.04	Score: 3.529
Episode 500	Average Score: 4.04	
Save_agent0	Average Score: 4.71	Score: 9.175
Save_agent0	Average Score: 5.41	Score: 3.770
Save_agent0	Average Score: 6.13	Score: 9.315
Save_agent0	Average Score: 6.38	Score: 13.37
Save_agent0	Average Score: 7.03	Score: 12.60
Save_agent0	Average Score: 7.32	Score: 7.931
Save_agent0	Average Score: 7.91	Score: 14.47
Save_agent0	Average Score: 8.58	Score: 8.289
Save_agent0	Average Score: 9.28	Score: 14.41
Save_agent0	Average Score: 9.48	Score: 7.493
Episode 600	Average Score: 9.48	
Save_agent0	Average Score: 10.02	Score: 17.42
Save_agent0	Average Score: 10.33	Score: 6.140
Save_agent0	Average Score: 10.75	Score: 10.19

Save_agent0	Average Score: 11.24	Score: 13.23
Save_agent0	Average Score: 11.70	Score: 11.40
Save_agent0	Average Score: 12.36	Score: 19.34
Save_agent0	Average Score: 13.10	Score: 26.94
Save_agent0	Average Score: 13.32	Score: 12.65
Save_agent0	Average Score: 13.96	Score: 17.27
Save_agent0	Average Score: 14.45	Score: 21.71
Episode 700	Average Score: 14.45	
Save_agent0	Average Score: 14.92	Score: 17.44
Save_agent0	Average Score: 15.33	Score: 12.71
Save_agent0	Average Score: 15.44	Score: 18.26
Save_agent0	Average Score: 15.88	Score: 18.21
Save_agent0	Average Score: 15.74	Score: 17.90
Save_agent0	Average Score: 15.66	Score: 19.01
Save_agent0	Average Score: 15.41	Score: 15.74
Save_agent0	Average Score: 15.90	Score: 15.41
Save_agent0	Average Score: 16.27	Score: 18.64
Save_agent0	Average Score: 16.60	Score: 20.37
Episode 800	Average Score: 16.60	
Save_agent0	Average Score: 16.69	Score: 17.82
Save_agent0	Average Score: 17.32	Score: 23.99
Save_agent0	Average Score: 18.09	Score: 24.66
Save_agent0	Average Score: 18.12	Score: 16.90
Save_agent0	Average Score: 18.79	Score: 22.00
Save_agent0	Average Score: 19.48	Score: 23.51
Save_agent0	Average Score: 19.84	Score: 16.31
Save_agent0	Average Score: 19.85	Score: 17.45
Save_agent0	Average Score: 19.83	Score: 19.63
Save_agent0	Average Score: 19.99	Score: 18.82
Episode 900	Average Score: 19.99	
Save_agent0	Average Score: 20.41	Score: 18.16
Save_agent0	Average Score: 20.30	Score: 21.96
Save_agent0	Average Score: 20.16	Score: 21.92
Save_agent0	Average Score: 20.69	Score: 24.19
Save_agent0	Average Score: 20.60	Score: 21.02
Save_agent0	Average Score: 20.54	Score: 18.88
Save_agent0	Average Score: 20.84	Score: 19.23
Save_agent0	Average Score: 21.31	Score: 21.37
Save_agent0	Average Score: 21.41	Score: 17.10
Save_agent00	Average Score: 21.61	Score: 22.26
Episode 1000	Average Score: 21.61	
Save_agent10	Average Score: 21.69	Score: 23.08
Save_agent20	Average Score: 21.88	Score: 23.97
Save_agent30	Average Score: 21.95	Score: 17.31
Save_agent40	Average Score: 21.79	Score: 25.19
Save_agent50	Average Score: 22.12	Score: 26.86
Save_agent60	Average Score: 22.51	Score: 23.07
Save_agent70	Average Score: 22.49	Score: 22.08

Save_agent80	Average Score: 22.40	Score: 26.63
Save_agent90	Average Score: 22.70	Score: 25.29
Save_agent00	Average Score: 23.08	Score: 25.85
Episode 1100	Average Score: 23.08	
Save_agent10	Average Score: 23.11	Score: 26.13
Save_agent20	Average Score: 23.55	Score: 22.68
Save_agent30	Average Score: 23.90	Score: 26.96
Save_agent40	Average Score: 24.05	Score: 15.33
Save_agent50	Average Score: 24.22	Score: 24.61
Save_agent60	Average Score: 24.06	Score: 21.44
Save_agent70	Average Score: 24.29	Score: 25.76
Save_agent80	Average Score: 24.60	Score: 27.05
Save_agent90	Average Score: 24.62	Score: 24.14
Save_agent00	Average Score: 24.86	Score: 28.81
Episode 1200	Average Score: 24.86	
Save_agent10	Average Score: 25.07	Score: 28.07
Save_agent20	Average Score: 24.83	Score: 29.00
Save_agent30	Average Score: 24.90	Score: 27.08
Save_agent40	Average Score: 25.53	Score: 25.68
Save_agent50	Average Score: 25.67	Score: 29.59
Save_agent60	Average Score: 25.76	Score: 24.52
Save_agent70	Average Score: 26.04	Score: 24.82
Save_agent80	Average Score: 26.23	Score: 26.96
Save_agent90	Average Score: 26.86	Score: 28.31
Save_agent00	Average Score: 27.04	Score: 39.48
Episode 1300	Average Score: 27.04	
Save_agent10	Average Score: 27.93	Score: 33.93
Save_agent20	Average Score: 28.50	Score: 27.82
Save_agent30	Average Score: 29.00	Score: 25.88
Save_agent40	Average Score: 29.13	Score: 32.54
Save_agent50	Average Score: 29.49	Score: 36.44
Environment solved Episode 1357 Average Score: 30.03		

```
[8]: import matplotlib.pyplot as plt
      %matplotlib inline

      # plot scores across episodes
      fig = plt.figure()
      ax = fig.add_subplot(111)
      plt.plot(np.arange(len(scores)), scores, label='TD3')
      plt.plot(np.arange(len(scores)), rolling_average, c='r', label='Rolling AVG')
      plt.ylabel('Score')
      plt.xlabel('Episode #')
      plt.legend(loc='upper left');
      plt.show()
```



```
[9]: env.close()
```

```
[ ]:
```