DRILLMEC HH SERIES

HYDRAULIC DRILLING RIGS | TECHNICAL SPECIFICATIONS

HH102

Rated hook load	100 metric tonnes (220,000 lb)
Hoisting system	Hydraulic hoisting with 16 m stroke; 20 t pull-down
Hydraulic power unit	Caterpillar 3412 DITA diesel engine; 560 hp (418 kW)
Top drive	Hydraulic; 200 hp continuous; 0–160 rpm
Top drive torque	26,000 ft-lb at 45 rpm
Rig floor height	4.88 m (16 ft)
Pipe handling	Hydraulic torque wrench, automatic power tongs and power slips
Rotary table	20½ in opening; 60 rpm maximum

HH220 EC

Rated hook load	200 metric tonnes (440,000 lb)
Nominal drilling capacity	10,000 ft with 5 in drill pipe
Power generation	4 × Caterpillar 3412 diesel generator sets; 980 hp each
Top drive	Hydraulic HTD 220; 200 rpm maximum
Top drive torque	26,000 ft-lb continuous at 60 rpm
Rig floor height	7.62 m (25 ft)
Mud pumps	2 × Drillmec 9T1000 triplex; 1,000 hp each
Pipe handling	Hydraulic torque wrench and mechanised handling equipment

HH300

Rated hook load	600,000 lb (approximately 272 metric tonnes)

Nominal drilling capacity	13,000 ft with 3½ in drill pipe
Power architecture	Diesel-electric SCR supply with hydraulic hoisting and rotation
Hydraulic power pack	1,150 kW stated installed power
Top drive	Hydraulic; 375 kW maximum; 0–200 rpm
Top drive torque	36,140 ft-lb at 70 rpm
Rig floor height	6.71 m (22 ft)
Pipe handling	Automatic hydraulic power tongs and pipe-handling systems
Rotary table	27½ in opening; 60 rpm maximum

CYBER / AUTOMATED CONFIGURATIONS

Automation features, control interfaces and mechanised pipe handling depend on the individual rig configuration. The HH102, HH220 EC and HH300 specifications above should not be interpreted as certified Cyber-package specifications.

Specifications describe representative documented equipment configurations; actual installed equipment and operating limits may vary by rig.