


Boosting: a jump into the realm of slow learning

Filippo Biscarini (CNR, Milan, Italy)

filippo.biscarini@cnr.it



Combining predictors



Ensemble methods


- Like bagging and random forest, boosting is an **ensemble method**
- Multiple (**many!**) **models** are fitted to (many) **different versions of the data**
- Predictors (classifiers) are then **combined by averaging/voting** (majority vote)
- **Combining** predictors **improves accuracy** (usually at the expense of interpretability)



Ensemble methods


- Like bagging and random forest, boosting is an **ensemble method**
- Multiple (**many!**) **models** are fitted to (many) **different versions of the data**
- Predictors (classifiers) are then **combined by averaging/voting** (majority vote)
- **Combining** predictors **improves accuracy** (usually at the cost of interpretability)

Ensemble methods (deep learning, gradient boosting) dominate Kaggle competitions!



Boosting

- Bagging and Random Forest work on **bootstrapped copies** of the original data (and reduced samples of the features for RF)
- Bagging and RF work by building **many parallel** and independent **models**
- **Boosting** creates many **sequential models**; each model is built on information from the previous model




Boosting - intuition

- case/controls: **5** completely **independent classifiers**, each with **70% accuracy**
- **majority vote**: if ≥ 3 out of 5 classifiers say “case”, we conclude it’s a case
- **combined accuracy = 83.7%** (from the binomial CDF)
- with 101 (independent) classifiers \rightarrow accuracy = 99.9%
- (if 101 models seems a lot, the Netflix Prize in 2009 was won by a combination of 107 predictors)




Simple (weak) learners

- e.g. multiple linear regression, logistic regression (with simple features)
- Tend to be very good (**high accuracy**)
- **Low variance** → **fast learning**
- But **bias is high** ...




Simple (weak) learners

Training Vs. Test Set Error



1. Add more features, depth, complexity to the “weak” learner
2. **Combine multiple weak learners**




The boosting way

- Can a set of weak learners be combined to create a stronger learner? [[Kearns and Valiant, 1988](#)]
- Yes! ([Schapire, 1990](#)) → **boosting**!
- Boosting can be used for both regression and classification problems




The boosting way



4 classification trees

- D1: first split makes three mistakes → errors will have a higher weight in the next model
- D2: makes three mistakes - higher weight in D3
- D3: classifies correctly the three mistakes from D2, no more mistakes
- D4: all models combined, perfect classification

The boosting way




4 classification trees

- D1: first split makes three mistakes → errors will have a higher weight in the next model
- D2: makes three mistakes - higher weight in D3
- D3: classifies correctly the three mistakes from D2, no more mistakes
- D4: all models combined, perfect classification

There is one obvious risk: can you guess which?

Boosting algorithm - a regression tree example



1. Initialize: $\hat{f}(x) = 0$ $r_i = y_i$

2. b in 1, 2, ... B

a. Fit a regression tree with d (few) splits to the training data (X, r): $\rightarrow \hat{f}^b(x)$

b. Update the classifier by a shrunk version of the new model:

$$\hat{f}(x) \leftarrow \hat{f}(x) + \lambda \hat{f}^b(x)$$

c. Update residuals: $r_i \leftarrow r_i - \lambda \hat{f}^b(x_i)$

3. Final boosted model:

$$\hat{f}(x) = \sum_{b=1}^B \lambda \hat{f}^b(x)$$



Boosting learns slowly

- in the classification example, we saw that sequential boosting models started from the **classification results of the previous model(s)**
- in the regression example, we saw that sequential boosting models started from **residuals from the previous model(s)**
- in both cases, individual sequential models are rather “shallow” (weak)
- rather than fitting a single large and complicated model to the data, multiple simpler models are fitted sequentially → **slow learning**



Boosting - hyperparameters


- number of trees, **B**: unlike bagging and RF, boosting can overfit (again, slowly!) if B is too large (**trees are sequential, not parallel!**)
- shrinkage parameter **lambda**: small positive number, if too slow many trees are needed
- model depth, **d**: e.g. n. of splits in trees (small d usually works well)



Boosting

- demonstration 10.boosting

→ 10.boosting.ipynb



Recap messages from day 4

- Moving from “regressions” to “equation-free” methods (trees)
- The power of ensemble methods:
 - averaging \rightarrow **< variance**
 - “shrinkage” (fewer variables/splits \rightarrow simpler models) \rightarrow **< overfitting**
 - **> accuracy** (at the expense of interpretability)
- Extract interpretation from ensembles \rightarrow variable importance
 - model frequency (Lasso)
 - RSS/entropy reduction
 - permuted accuracy

