

CSCI-1200 Data Structures — Fall 2016

Lab 13 — Priority Queues and Binary Heaps

In this lab, you will use `binary heaps to implement the priority queue container`, as discussed in Lectures 21 & 22. Having these notes available while you are working on this lab will make it substantially easier. Start by downloading the files, and then turn off all network connections:

http://www.cs.rpi.edu/academics/courses/fall16/csci1200/labs/13_priority_queues/priority_queue.h

http://www.cs.rpi.edu/academics/courses/fall16/csci1200/labs/13_priority_queues/test_pq.cpp

The code provided in these files is straightforward. `test_pq.cpp` is a driver and test program, while `priority_queue.h` is a skeleton implementation. Please take a careful look. You will complete the implementation and add to the main program in lab. In your implementation, be careful when subtracting 1 from an unsigned int whose value is 0; it is not -1!

Checkpoint 1

Implement and test the `push` (a.k.a. `insert`) and the `check_heap` functions. Recall that `push` depends on `the percolate_up functionality`. `check_heap`, which works either with the heap member variable or with a vector provided from the outside, `determines if the vector is properly a heap, meaning that each value is less than or equal to the values of both of its children` (if they exist).

To complete this checkpoint: Show a TA your debugged implementation and discuss the running time of both `insert` and `check_heap`.

Checkpoint 2

Implement and test the `pop` (a.k.a. `delete_min`) function and `the constructor that builds a valid heap from a vector of values that is in no particular order`. Both of these depend on proper implementation of the `percolate_down` function.

To complete this checkpoint: Show a TA these additions and the test output.