

**EXPERIMENT NO 01**  
\*\*\*\*\*

```
=====
Author   : Atharva Paliwal
Roll No  : 40 [5B]
Date     : 11-August-2020
=====
```

```
*****
AIM :   Write a program to find Minimum and Maximum element in the given array using
         Min-Max Algorithm based on Divide and Conquer Strategy.
*****
```

**CODES**

```
*****
INF = float('inf')
import time
import random
def findMinAndMax1(numbers,n):
    max= numbers[0]
    min= numbers[0]
    for i in range(0,n):
        if numbers[i] > max:
            max= numbers[i]
        if numbers[i] < min:
            min= numbers[i]
    return (min,max)

def findMinAndMax2(A, left, right, min, max):
    if left == right:
        if min > A[right]:
            min = A[right]
        if max < A[left]:
            max = A[left]

        return min, max
    if right - left == 1:

        if A[left] < A[right]:
            if min > A[left]:
                min = A[left]

            if max < A[right]:
                max = A[right]

        else:
            if min > A[right]:
                min = A[right]
```

```

        if max < A[left]:
            max = A[left]
        return min, max
    mid = (left + right) // 2
    min, max = findMinAndMax2(A, left, mid, min, max)
    min, max = findMinAndMax2(A, mid + 1, right, min, max)
    return min, max

```

```

def minmax(A):
    (min2, max2) = (INF, -INF)

    #naive
    start_time1 = time.time()
    (min1, max1) = findMinAndMax1(A, len(A))
    end_time1 = time.time()
    print("The minimum element in the "+str(len(A))+" list is with naive", min1)
    print("The maximum element in the "+str(len(A))+" list is with naive", max1)
    print("time taken was for naive:=", end_time1-start_time1)
    print("")
    print("")
    #d and c
    start_time2 = time.time()
    (min2, max2) = findMinAndMax2(A, 0, len(A) - 1, min2, max2)
    end_time2 = time.time()
    print("The minimum element in the "+str(len(A))+" list is with divide and
conquer", min2)
    print("The maximum element in the "+str(len(A))+" list is with divide and
conquer", max2)
    print("time taken was for naive:=", end_time2-start_time2)
    print("")
    print("")
    return(len(A), start_time1-end_time1, start_time2-end_time2)

#for 100 elements
A = random.sample(range(1, 100000), 100)
n1, time11, time12 = minmax(A)

#for 1000 elements
A = random.sample(range(1, 10000000), 1000)
n2, time21, time22 = minmax(A)

#for 10000 elements
A = random.sample(range(1, 10000000), 10000)
n3, time31, time32 = minmax(A)

```

```
#for 100000
A =random.sample(range(1,10000000),100000)
n3,time41,time42=minmax(A)
*****

*****
```


## TABULAR ANALYSIS

\*\*\*\*\*

NUMBER OF INPUTS	MIN-MAX TIME (SIMPLE LINEAR STRATEGY)	MIN-MAX (DAC) TIME
100	3.2901763916015625e-05	0.00016951560974121094
1000	0.0003266334533691406	0.0010440349578857422
10000	0.0034902095794677734	0.04285717010498047
100000	0.07744646072387695	0.2432863712310791

\*\*\*\*\*

## GRAPH



\*\*\*\*\*INFERENCE\*\*\*\*\*

We have learnt about divide and conquer programming. We have seen that DAC takes less time to execute a particular array than normal min-max algo. In DAC we have used recursive approach/top down approach.

\*\*\*\*\*

\*\*\*\*\*END\*\*\*\*\*