



LINEA B

STR-DL

Overview

This is a surface-mounted spotlight designed with a **distinctive arm structure** and **graduated adjustability** that allows smooth **0°–360° horizontal rotation** and **precise vertical aiming**. Its robust design and high-performance COB LED make it ideal for accent, display, or task lighting in sophisticated interiors.




Family Range


Code	Power	Dimension
STR-203-24-3	3W	Φ37x74mm
STR-203-24-7	7W	Φ50x83mm
STR-203-24-12	12W	Φ60x105mm
STR-203-24-18	18W	Φ70x140mm
STR-203-24-24	24W	Φ97x175mm
STR-203-24-30	30W	Φ116x119mm

Parameters

Efficiency	85 lm/w
CRI	90
Adjustable	Yes
Power Factor	0.9
Input Voltage	AC220-240V 50/60Hz
Operating Temperature	-20° to 60°
Working Hours	50,000 Hrs.
IP RATING	IP40



Specification

LED CHIP	OSRAM
FINISH	WH BK
MATERIAL DESCRIPTION	HOUSING: DIE CAST ALUMINIUM
BEAM ANGLE	60°
DIMMING OPTION	  
PHOTOMETRIC	

Application

Modern Workspaces, Institutions, Small Format Retail Outlets
Hotels, High End Villas