



LINEA C

STR-DL

Overview

This is a compact, surface-mounted spotlight built for spaces that demand both **flexibility and precision in lighting control**. Designed with a smooth **graduated adjustment mechanism**, it offers full **0°–360° horizontal rotation** and precise vertical tilting, making it perfect for accent, task, or ambient lighting in modern interiors.




Family Range


Code	Power	Dimension
STR-203-24T-7	7W	Φ50x83mm
STR-203-24T-12	12W	Φ60x105mm
STR-203-24T-18	18W	Φ70x140mm
STR-203-24T-24	24W	Φ97x175mm
STR-203-24T-30	30W	Φ116x119mm

Parameters

Efficiency	85 lm/w
CRI	90
Adjustable	Yes
Power Factor	0.9
Input Voltage	AC220-240V 50/60Hz
Operating Temperature	-20° to 60°
Working Hours	50,000 Hrs.
IP RATING	IP40



Specification

LED CHIP	OSRAM
FINISH	WH BK
MATERIAL DESCRIPTION	HOUSING: DIE CAST ALUMINIUM
BEAM ANGLE	60°
DIMMING OPTION	  
PHOTOMETRIC	

Application

Modern Workspaces, Institutions, Small Format Retail Outlets
Hotels, High End Villas