



# SPLENDORE-R

STM-MCL

## Overview

High-quality fixture with die-cast aluminum body, efficient LED module, and anti-glare design. Available in various wattages, beam angles, and color temperatures for versatile applications.




## Family Range


| Code          | Power | Dimension  |
|---------------|-------|------------|
| SLM-104812-CL | 12W   | Ø52*H150mm |

## Parameters

|                       |                    |
|-----------------------|--------------------|
| Efficiency            | 110lm/W            |
| CRI                   | 95                 |
| Adjustable            | No                 |
| Power Factor          | 0.5                |
| Input Voltage         | AC220-240V 50/60Hz |
| Operating Temperature | -20° to 60°        |
| Working Hours         | 50,000 Hrs.        |
| IP RATING             | IP20               |



Specification

|                      |                                                                                                                                                                                                                                                                   |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LED CHIP             | BRIDGELUX                                                                                                                                                                                                                                                         |
| FINISH               | WH, BK                                                                                                                                                                                                                                                            |
| MATERIAL DESCRIPTION | HOUSING: DIE CAST ALUMINIUM<br>DIFFUSER: PMMA OPAL LENS                                                                                                                                                                                                           |
| BEAM ANGLE           | 15°,24°,36°                                                                                                                                                                                                                                                       |
| DIMMING OPTION       |    |
| PHOTOMETRIC          |                                                                                                                                                                              |

Application

Modern Workplaces, institutions, retail Outlets, Hotels, Hight End Villas

Drawing

Unit: MM

