



TONO

STR-DL


Overview

Our Adjustable LED Spotlights are designed to deliver high-performance lighting solutions across a variety of applications. With a wide range of sizes and power options, these spotlights combine flexibility, durability, and efficiency, making them ideal for both indoor and outdoor environments.



Family Range


Code	Power	Dimension
STR-200-37-3	3W	Φ65x43mm
STR-200-37-7	7W	Φ85x60mm
STR-200-37-12	12W	Φ85x68mm
STR-200-37-18	18W	Φ108x70mm
STR-200-37-24	24W	Φ128x75mm
STR-200-37-30	30W	Φ138x120mm
STR-200-37-30	30W	Φ160x113mm
STR-200-37-50	50W	Φ160x115mm
STR-200-37-50	50W	Φ 170*115mm
STR-200-37-80	80W	Φ195*125mm



Parameters

Efficiency	85lm/w
CRI	90
Adjustable	Yes
Power Factor	0.9
Input Voltage	AC220-240V 50/60Hz
Operating Temperature	-20° to 60°
Working Hours	50,000 Hrs.
IP RATING	IP40

Specification

LED CHIP	OSRAM
FINISH	WH BK
MATERIAL DESCRIPTION	HOUSING: Aviation Aluminum
BEAM ANGLE	36°,60°
DIMMING OPTION	
PHOTOMETRIC	

Application

Modern Workspaces, Institutions, Small Format Retail Outlets
Hotels, High End Villas